

TECHNICAL INFORMATION

FOR PROFESSIONAL USE ONLY

**BRAYT
POLISHING FOAM
HARD
yellow**



PRODUCT DESCRIPTION

Polishing foam made of innovative open-cell polyurethane foam, decreasing effect of overheating the surface, designed for work with rotary and orbital machines. Can be used with first and second step polishing compounds (from cut to polishing type), wet and dry. Recommended speed range 600 – 1600 rpm. Product shows resistance to aqueous environment, organic solvents, and prolonged exposure to high temperatures (up to 110°C).

TECHNICAL INFORMATION

- Color: yellow
- Dimensions: diameter: 80mm, 150 mm, thickness: 25 mm
- Velcro: diameter: 75 mm, 125 mm
- Density: 41 – 45 kg / m³
- Compression hardness 40%: 5,5 – 7,5 kPa
- Elongation on break: >110
- Tensile strength: >450 kPa
- Cellcount: 18-22 [C/cm]

STORAGE

Store at temperatures between -3°C to + 40°C and a humidity of 25% to 65%.

TROTON Sp. z.o.o

Address: Ząbrowo 14A, 78-120 Gościno, Poland, Tel: +48 94 35 123 94
Tel/Fax: +48 94 35 126 22 Website: www.troton.com.pl Email: troton@troton.com.pl