


TECHNICAL INFORMATION

FOR PROFESSIONAL USE ONLY

| | |
|--|---|
| <h3>R1 REGENERATION</h3> |  |
| Art. No. | |
| 300007597 (250 ml) | |
| COLOUR: amber | |
| SPECIFIC GRAVITY: approx. 0,875 g/cm ³ | |

| PRODUCT DESCRIPTION | |
|--|---------------------------------|
| Product intended to restore and refresh plastic surfaces. Suitable also to use on metal (chrome, brass, stainless steel, aluminium) and painted or varnished surfaces. Agent has a strong penetrating ability and thanks to it he restore lost color and luster. After drying creates flexible and resistant finishing coating. | |
| <ul style="list-style-type: none"> Base: alkad resin Consistency: liquid Efficiency: 18 m²/l (efficiency may vary depending on the type of surface) Drying time: 24 h (depending on the temperature and air humidity) | |
| USAGE | |
| <ul style="list-style-type: none"> Surface to be treated should be clean and dry. All layers of waxes and silicone should be removed. Plastic should be cleaned with warm water with soap, rinse thoroughly and wait at least 12 hours to dry completely. It's not recommended to use on white lacquers. Using the clean cloth or brush apply product evenly on the surface. Recommended application temperature is 5 – 35°C. Do not apply on hot surface. Leave for 10 – 20 min (it's recommended to work on the surface of which can be completed within max. 20 min). Remove product residue with clean cloth.. Leave until dry and then polish by dry microfiber cloth to obtain better gloss. | |
| STORAGE | |
| Store the product in tightly closed container at 0 - 45°C. Keep away from heat, fire and direct sunlight. Close the containers immediately after each use. Protect from frost. Keep away from children. | |
| EXPIRY DATE | |
| R1 REGENERATION | 24 months from production date. |

| LIMITATION OF LIABILITY | |
|---|--|
| <p>The information contained in this TDS sheet is up-to-date and correct on the day the information is released</p> <p>Because TROTON cannot control or predict the conditions under which a product will be used, each user should review the information in the specific context of the intended usage. To the maximum extent permitted by applicable law, TROTON shall not be liable for damages of any kind arising from the use or reliance on information contained in this TDS. Given the variety of factors that can affect the usage and application of the TROTON product, some of which are only within the user's knowledge and control range, it is essential that the user evaluate the TROTON product to determine if the product is fit for a particular purpose and whether the product is suitable for the user's usage.</p> <p>Under no circumstances shall TROTON be liable to the user or any third party for any indirect, derivative, incidental, special or punitive damages, including loss of profits resulting from the use of products manufactured by TROTON and / or TROTON's services.</p> <p>All information is based on meticulous laboratory tests and many years of experience. An established position on the market does not release us from continuous quality control of our products. However, we are not responsible for the final effects of improper storage or use of our products and for work that is not in line with good craftsmanship. .</p> <p style="text-align: right;">TROTON Sp. z o.o. Ząbrowo, Poland.</p> | |