


TECHNICAL INFORMATION

FOR PROFESSIONAL USE ONLY

T1 STRONG POLISHING COMPOUND	
Art. No.	
10090 (250 g) 10091 (1 kg) 10103 (4,6 kg) 10330 (100 g x 12/display)	
COLOUR: white	
DENSITY: 1,23 g/cm ³	

PRODUCT DESCRIPTION

BRAYT T1 STRONG is a polishing compound suitable to use on every kind of varnish used in industry and automotive sector, including hard scratch resistant lacquers (also ceramic lacquers). Product recommended for fresh and old paint coatings. Easily removes scratches and traces after P1500 sanding paper. Silicone free, no filler.

- Cut level: 8/10
- Gloss level: 8/10
- Processing: manual work, mechanical work (rotary machine)

RECOMMENDED APPLICATORS

- BRAYT POLISHING FOAM HARD yellow
- BRAYT LAMBSWOOL „D” yellow
- BRAYT LAMBSWOOL „MM” white
- BRAYT ORANGE PEEL REMOVAL PAD „JEANS”

USAGE

- For hard and scratch resistant varnish use with lambswool or yellow polishing sponge.
- Apply a small amount of polishing compound on the surface to be polished.
- In case of new polishing pad is recommended to apply compound on pad also and make pre polishing.
- Polish using rotary polisher in the optimum speed range 1200 – 1600 RPM (max. 2000 RPM) with slight or medium pressure.
- Polish until all imperfection are removed.
- Remove all residue using microfiber cloth.
- In case of polishing on big surfaces work a small area at time.

STORAGE

Store the product in tightly closed container at 0 - 45°C. Keep away from heat, fire and direct sunlight. Close the containers immediately after each use. Protect from frost. Keep away from children.

EXPIRY DATE

T1 STRONG

24 months from production date

LIMITATION OF LIABILITY

The information contained in this TDS sheet is up-to-date and correct on the day the information is released. Because TROTON cannot control or predict the conditions under which a product will be used, each user should review the information in the specific context of the intended usage. To the maximum extent permitted by applicable law, TROTON shall not be liable for damages of any kind arising from the use or reliance on information contained in this TDS. Given the variety of factors that can affect the usage and application of the TROTON product, some of which are only within the user's knowledge and control range, it is essential that the user evaluate the TROTON product to determine if the product is fit for a particular purpose and whether the product is suitable for the user's usage. Under no circumstances shall TROTON be liable to the user or any third party for any indirect, derivative, incidental, special or punitive damages, including loss of profits resulting from the use of products manufactured by TROTON and / or TROTON's services.

All information is based on meticulous laboratory tests and many years of experience. An established position on the market does not release us from continuous quality control of our products. However, we are not responsible for the final effects of improper storage or use of our products and for work that is not in line with good craftsmanship. .

TROTON Sp. z o.o.
Ząbrowo, Poland..