



TECHNICAL INFORMATION

FOR PROFESSIONAL USE ONLY

BRAYT i01 HIGH GLOSS POLISHING COMPOUND

>silicone free<



PRODUCT DESCRIPTION

BRAYT i01 HIGH GLOSS it's polishing compound recommended to use on any kind of painted coatings, including hard and scratch resistant lacquers as ceramic lacquers ect. Suitable to use on fresh (polymerized) and also old coatings. Easily remove scratches and P2000 sanding paper marks. Perfectly works with most commercial available polishing pads (foam, wool, microfiber). Product doesn't contains fillers or silicone.

PHYSICAL AND CHEMICAL PROPERTIES

Capacity: 1 kg

• Density: ok. 1,09 g/cm³

Color: biały
 Cut level: 6 / 10
 Gloss level: 9 / 10

Application: manual work, mechanical work

(rotary machine, orbital machine)





USAGE

- In case of hard, scratch resistant lacquers it is recommended to use polishing wool or hard polishing sponge.
- Apply small amount of the i01 HIGH GLOSS on the surafce to be treated. For new polishing pad it is recommended to apply product also on pad and make prepolishing.
- Polish using polisher with optimal speed 800 1600 RPM and medium pressure (depending on the surface).
- Polish until all imperfection have been removed.
- After polishing remove any residue by clean microfiber cloth.
- In case of polishing on big surfaces work a small area at time.

ZALECANE APLIKATORY

BRAYT polishing foam "PROFI" white BRAYT polishing wool TYPE "D" yellow BRAYT polishing wool TYPE "MM" white

STORAGE

Product works best when its temperature is $15 - 25^{\circ}$ C.

Storage in sealed container at $0 - 45^{\circ}$ C.

WARRANTY PERIOD

24 months from production date.

All information are based upon the precise laboratory studies and many years of experience. The good market position does not release us from the constant supervision of our products quality. However we are not responsible for the final effects of the improper storage or application of our products, as well as for work inconsistent with the good craft practice.

TROTON Sp. z o.o. Ząbrowo, Poland