



TECHNICAL INFORMATION

FOR PROFESSIONAL USE ONLY

BRAYT i1 LIQUID POLISHING COMPOUND

>silone free<



PRODUCT DESCRIPTION

BRAYT i1 LIQUID it is a highly effective, silicone free polishing compound. Contains high quality polishing minerals which guarantees quick elimination of sanding marks and high gloss in one-step process. Quickly eliminates grit 1200 sanding marks and sign of wear. Because of optimized bonding does not warm-up surface during polishing.

PHYSICAL AND CHEMICAL PROPERTIES

Density: 1,23 kg/l Consystence: liquid Color: turquoise

Capacity: 500 g, 1 kg, 4,6 kg

Cut level: 6/10 Gloss level: 8/10

Application: manual work, mechanical work (rotary machine),

automatic polishing machine (depending on the specification of the

device)





USAGE

- Apply compound on the surface to be treated (use hard sponge or lambswool).
- Possible manual work or mechanical polishing using rotary machine with adjustable rotation.
- Spread compound on the surface by machine with minimum RPM.
- Slowly increase the speed to max. 1800 2000 RPM and polish surface with medium pressure or without any pressure (depending on polished surface).
- Polish surfaces until the scratches have been removed.
- Change applicator to a soft sponge and polish to reach perfect gloss.

POLISHING PADS

BRAYT polishing foam "PROFI" white BRAYT polishing lambswool "D" yellow BRAYT polishing lambswool "MM" white

STORAGE

Product works best when its temperature is $15 - 25^{\circ}$ C.

Storage in sealed container at $0 - 45^{\circ}$ C.

EXPIRY DATE

24 months from production date.

All information are based upon the precise laboratory studies and many years of experience. The good market position does not release us from the constant supervision of our products quality. However we are not responsible for the final effects of the improper storage or application of our products, as well as for work inconsistent with the good craft practice.

TROTON Sp. z o.o. Ząbrowo, Poland