TROTON

# ZINC-ALUMINIUM NEW FORMULA

ECT	TION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING
.1	Product identifier: ZINC-ALUMINIUM NEW FORMULA
	Other means of identification:
	<b>UFI:</b> 1UTS-8F1G-3S21-13YC
.2	Relevant identified uses of the substance or mixture and uses advised against:
	Relevant uses: Car repair; spray paint. For professional users/industrial user only.
	Uses advised against: All uses not specified in this section or in section 7.3
.3	Details of the supplier of the safety data sheet:
	Troton Sp. z o.o. Ząbrowo 14A 78-120 Gościno - Zachodniopomorskie - Polska Phone: +48 94 35 123 94 - Fax: +48 94 35 126 22 troton@troton.com.pl www.troton.pl / www.troton.eu
1.4	Emergency telephone number: (8am-4pm)+48 094 35 123 94; 112
SEC.	TION 2: HAZARDS IDENTIFICATION **
2.1	Classification of the substance or mixture:
	CLP Regulation (EC) No 1272/2008:
	Classification of this product has been carried out in accordance with CLP Regulation (EC) No 1272/2008.
	Aerosol 1: Pressurised container: May burst if heated., H229 Aerosol 1: Flammable aerosols, Category 1, H222 Aquatic Chronic 3: Hazardous to the aquatic environment, long-term hazard, Category 3, H412 Eye Irrit. 2: Eye irritation, Category 2, H319 STOT SE 3: Specific toxicity causing drowsiness and dizziness, single exposure, Category 3, H336
2.2	Label elements:
	CLP Regulation (EC) No 1272/2008:
	Danger
	Hazard statements:
	Aerosol 1: H229 - Pressurised container: May burst if heated. Aerosol 1: H222 - Extremely flammable aerosol. Aquatic Chronic 3: H412 - Harmful to aquatic life with long lasting effects. Eye Irrit. 2: H319 - Causes serious eye irritation. STOT SE 3: H336 - May cause drowsiness or dizziness.
	Precautionary statements:
	<ul> <li>P210: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.</li> <li>P211: Do not spray on an open flame or other ignition source.</li> <li>P251: Do not pierce or burn, even after use.</li> <li>P280: Wear protective gloves/protective clothing/respiratory protection/eye protection/protective footwear.</li> <li>P304+P340: IF INHALED: Remove person to fresh air and keep comfortable for breathing.</li> <li>P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.</li> <li>P410+P412: Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122°F</li> <li>P501: Dispose of contents/container in accordance with regulations on hazardous waste or packaging and packaging waste</li> </ul>
	respectively.
	Supplementary information: EUH066: Repeated exposure may cause skin dryness or cracking.
	Substances that contribute to the classification
	Substances that contribute to the classification
	acetone; Hydrocarbons, C9, aromatics



 Printing: 09/01/2023
 Date of compilation: 11/09/2015
 Revised: 14/12/2022
 Version: 6 (Replaced 5)

 SECTION 2: HAZARDS IDENTIFICATION \*\* (continued)

 **2.3 Other hazards:** 

 Product fails to meet PBT/vPvB criteria

 Endocrine-disrupting properties: The product fails to meet the criteria.

\*\* Changes with regards to the previous version

## SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS \*\*

#### 3.1 Substance:

Non-applicable

#### 3.2 Mixture:

#### Chemical description: Mixture composed of chemical products

#### Components:

In accordance with Annex II of Regulation (EC) No 1907/2006 (point 3), the product contains:

	Identification		Chemical name/Classification				
	67-64-1	acetone <sup>(1)</sup> ATP CLP00					
REACH:	200-662-2 606-001-00-8 01-2119471330-49- XXXX	Regulation 1272/2008	Eye Irrit. 2: H319; Flam. Liq. 2: H225; STOT SE 3: H336; EUH066 - Danger	25 - <50 %			
	74-98-6	Propane <sup>(2)</sup>	ATP CLP00				
REACH:	200-827-9 601-003-00-5 01-2119486944-21- XXXX	Regulation 1272/2008	Flam. Gas 1A: H220; Press. Gas: H280 - Danger	10 - <25 %			
	106-97-8 203-448-7	Butane <sup>(2)</sup>	ATP CLP00				
REACH:	203-448-7 601-004-00-0 01-2119474691-32- XXXX	Regulation 1272/2008	Flam. Gas 1A: H220; Press. Gas: H280 - Danger	10 - <25 %			
	75-28-5	Isobutane <sup>(2)</sup> ATP CLP00					
REACH:	200-857-2 601-004-00-0 01-2119485395-27- XXXX	Regulation 1272/2008	Flam. Gas 1A: H220; Press. Gas: H280 - Danger	10 - <25 %			
	1330-20-7 215-535-7 601-022-00-9 01-2119488216-32- XXXX	Xylene <sup>(1)</sup>	Self-classified				
REACH:		Regulation 1272/2008	Acute Tox. 4: H312+H332; Aquatic Chronic 3: H412; Asp. Tox. 1: H304; Eye Irrit. 2: H319; Flam. Liq. 3: H226; Skin Irrit. 2: H315; STOT RE 2: H373; STOT SE 3: H335 - Danger	5 - <10 %			
	128601-23-0	Hydrocarbons, C9, a	romatics <sup>(1)</sup> Self-classified				
REACH:	918-668-5 Non-applicable 01-2119455851-35- XXXX	Regulation 1272/2008	Aquatic Chronic 2: H411; Asp. Tox. 1: H304; Flam. Liq. 3: H226; STOT SE 3: () 🔅 🏵 🏠 H335; STOT SE 3: H336; EUH066 - Danger	2,5 - <5 %			
CAS: EC:	100-41-4 202-849-4	Ethylbenzene <sup>(1)</sup>	Self-classified				
Index: REACH:	202-849-4 601-023-00-4 01-2119489370-35- XXXX	Regulation 1272/2008	Acute Tox. 4: H332; Aquatic Chronic 3: H412; Asp. Tox. 1: H304; Flam. Liq. 2: H225; STOT RE 2: H373 - Danger	2,5 - <5 %			

<sup>(1)</sup> Substances presenting a health or environmental hazard which meet criteria laid down in Regulation (EU) No. 2020/878 <sup>(2)</sup> Voluntarily-listed substance failing to meet any of the criteria set out in Regulation (EU) No. 2020/878

To obtain more information on the hazards of the substances consult sections 11, 12 and 16.

\*\* Changes with regards to the previous version

#### SECTION 4: FIRST AID MEASURES

#### 4.1 Description of first aid measures:

The symptoms resulting from intoxication can appear after exposure, therefore, in case of doubt, seek medical attention for direct exposure to the chemical product or persistent discomfort, showing the SDS of this product. **By inhalation:** 

rinting:	: 09/01/2023	Date of compilation: 11/09/2015	Revised: 14/12/2022	Version: 6 (Replaced 5)
SECT	FION 4: FIRST AI	D MEASURES (continued)		
	cardiorespiratory f	c.) requiring immediate medical assista	es will be necessary (mouth t	ep at rest. In serious cases such as o mouth resuscitation, cardiac massage,
	and neutral soap.	In serious cases see a doctor. If the p injury caused if it is stuck to the skin.	roduct causes burns or freezi	d if appropriate with plenty of cold water ng, clothing should not be removed as this hese should never be burst as this will
	If the injured pers cause further dam product.	on uses contact lenses, these should age. In all cases, after cleaning, a do	be removed unless they are s	person affected to rub or close their eyes. tuck to the eyes, in which case this could uickly as possible with the SDS of the
	By ingestion/as	piration:		
4.2	out the mouth and	hiting, but if it does happen keep the throat, as they may have been affec symptoms and effects, both acut	ted during ingestion.	n. Keep the person affected at rest. Rinse
	Acute and delayed	l effects are indicated in sections 2 an	d 11.	
4.3		y immediate medical attention ar		ed:
	Non-applicable	,		
SECT	FION 5: FIREFIGH	ITING MEASURES		
5.1	Extinguishing m	edia:		
	Suitable extingu	ishing media:		
	-	-	C powder), alternatively use for	oam or carbon dioxide extinguishers (CO2).
	Unsuitable extin			
		DED NOT to use full jet water as an ex	tinguishing agent.	
5.2		arising from the substance or mix		
5.3	As a result of comb	pustion or thermal decomposition read present a serious health risk.		I that can become highly toxic and,
0.0				

Depending on the magnitude of the fire it may be necessary to use full protective clothing and self-contained breathing apparatus (SCBA). Minimum emergency facilities and equipment should be available (fire blankets, portable first aid kit,...) in accordance with Directive 89/654/EC.

#### Additional provisions:

Act in accordance with the Internal Emergency Plan and the Information Sheets on actions to take after an accident or other emergencies. Eliminate all sources of ignition. In case of fire, cool the storage containers and tanks for products susceptible to combustion, explosion or BLEVE as a result of high temperatures. Avoid spillage of the products used to extinguish the fire into an aqueous medium.

#### SECTION 6: ACCIDENTAL RELEASE MEASURES

#### 6.1 Personal precautions, protective equipment and emergency procedures:

#### For non-emergency personnel:

Isolate leaks provided that there is no additional risk for the people performing this task. Evacuate the area and keep out those without protection. Personal protection equipment must be used against potential contact with the spilt product (See section 8). Above all prevent the formation of any vapour-air flammable mixtures, through either ventilation or the use of an inert medium. Remove any source of ignition. Eliminate electrostatic charges by interconnecting all the conductive surfaces on which static electricity could form, and also ensuring that all surfaces are connected to the ground.

#### For emergency responders:

Wear protective equipment. Keep unprotected persons away. See section 8.

#### 6.2 Environmental precautions:

Printing	: 09/01/2023	Date of compilation: 11/09/2015	Revised: 14/12/2022	Version: 6 (Replaced 5)						
SEC	SECTION 6: ACCIDENTAL RELEASE MEASURES (continued)									
<ul> <li>Avoid at all cost any type of spillage into an aqueous medium. Contain the product absorbed appropriately in hermetically sealed containers. Notify the relevant authority in case of exposure to the general public or the environment.</li> <li>6.3 Methods and material for containment and cleaning up:</li> </ul>										
It is recommended:										
Absorb the spillage using sand or inert absorbent and move it to a safe place. Do not absorb in sawdust or other com absorbents. For any concern related to disposal consult section 13.										

#### 6.4 Reference to other sections:

See sections 8 and 13.

#### SECTION 7: HANDLING AND STORAGE

#### 7.1 Precautions for safe handling:

#### A.- General precautions for safe use

Comply with the current legislation concerning the prevention of industrial risks. Keep containers hermetically sealed. Control spills and residues, destroying them with safe methods (section 6). Avoid leakages from the container. Maintain order and cleanliness where dangerous products are used.

B.- Technical recommendations for the prevention of fires and explosions

Avoid the evaporation of the product as it contains flammable substances, which could form flammable vapour/air mixtures in the presence of sources of ignition. Control sources of ignition (mobile phones, sparks,...) and transfer at slow speeds to avoid the creation of electrostatic charges. Consult section 10 for conditions and materials that should be avoided.

C.- Technical recommendations on general occupational hygiene

Do not eat or drink during the process, washing hands afterwards with suitable cleaning products.

D.- Technical recommendations to prevent environmental risks

Due to the danger of this product for the environment it is recommended to use it within an area containing contamination control barriers in case of spillage, as well as having absorbent material in close proximity.

#### 7.2 Conditions for safe storage, including any incompatibilities:

25 °C

A.- Technical measures for storage

- Maximum Temp.:
- B.- General conditions for storage

Avoid sources of heat, radiation, static electricity and contact with food. For additional information see subsection 10.5

#### 7.3 Specific end use(s):

Except for the instructions already specified it is not necessary to provide any special recommendation regarding the uses of this product.

#### SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

#### 8.1 Control parameters:

Substances whose occupational exposure limits have to be monitored in the workplace (European OEL, not country-specific legislation):

Directive (EU) 2000/39, Directive 2004/37/EC, Directive (EU) 2006/15, Directive (EU) 2009/161, Directive (EU) 2017/164, Directive (EU) 2019/1831:

Identification	Occupational exposure limits			
acetone	IOELV (8h)	500 ppm	1210 mg/m <sup>3</sup>	
CAS: 67-64-1 EC: 200-662-2	IOELV (STEL)			
Xylene	IOELV (8h)	50 ppm	221 mg/m <sup>3</sup>	
CAS: 1330-20-7 EC: 215-535-7	IOELV (STEL)	100 ppm	442 mg/m <sup>3</sup>	
Ethylbenzene	IOELV (8h)	100 ppm	442 mg/m <sup>3</sup>	
CAS: 100-41-4 EC: 202-849-4	IOELV (STEL)	200 ppm	884 mg/m <sup>3</sup>	

#### DNEL (Workers):

#### Printing: 09/01/2023

Date of compilation: 11/09/2015

Revised: 14/12/2022

Version: 6 (Replaced 5)

## SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION (continued)

			Short exposure		Long exposure	
Identification		Systemic	Local	Systemic	Local	
acetone	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable	
CAS: 67-64-1	Dermal	Non-applicable	Non-applicable	186 mg/kg	Non-applicable	
EC: 200-662-2	Inhalation	Non-applicable	2420 mg/m <sup>3</sup>	1210 mg/m <sup>3</sup>	Non-applicable	
Xylene	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable	
CAS: 1330-20-7	Dermal	Non-applicable	Non-applicable	212 mg/kg	Non-applicable	
EC: 215-535-7	Inhalation	442 mg/m <sup>3</sup>	442 mg/m <sup>3</sup>	221 mg/m <sup>3</sup>	221 mg/m <sup>3</sup>	
Hydrocarbons, C9, aromatics	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable	
CAS: 128601-23-0	Dermal	Non-applicable	Non-applicable	25 mg/kg	Non-applicable	
EC: 918-668-5	Inhalation	Non-applicable	Non-applicable	150 mg/m <sup>3</sup>	Non-applicable	
Ethylbenzene	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable	
CAS: 100-41-4	Dermal	Non-applicable	Non-applicable	180 mg/kg	Non-applicable	
EC: 202-849-4	Inhalation	Non-applicable	293 mg/m <sup>3</sup>	77 mg/m <sup>3</sup>	Non-applicable	

#### **DNEL (General population):**

		Short exposure		Long exposure	
Identification		Systemic	Local	Systemic	Local
acetone	Oral	Non-applicable	Non-applicable	62 mg/kg	Non-applicable
CAS: 67-64-1	Dermal	Non-applicable	Non-applicable	62 mg/kg	Non-applicable
EC: 200-662-2	Inhalation	Non-applicable	Non-applicable	200 mg/m <sup>3</sup>	Non-applicable
Xylene	Oral	Non-applicable	Non-applicable	12,5 mg/kg	Non-applicable
CAS: 1330-20-7	Dermal	Non-applicable	Non-applicable	125 mg/kg	Non-applicable
EC: 215-535-7	Inhalation	260 mg/m <sup>3</sup>	260 mg/m <sup>3</sup>	65,3 mg/m <sup>3</sup>	65,3 mg/m <sup>3</sup>
Hydrocarbons, C9, aromatics	Oral	Non-applicable	Non-applicable	11 mg/kg	Non-applicable
CAS: 128601-23-0	Dermal	Non-applicable	Non-applicable	11 mg/kg	Non-applicable
EC: 918-668-5	Inhalation	Non-applicable	Non-applicable	32 mg/m <sup>3</sup>	Non-applicable
Ethylbenzene	Oral	Non-applicable	Non-applicable	1,6 mg/kg	Non-applicable
CAS: 100-41-4	Dermal	Non-applicable	Non-applicable	Non-applicable	Non-applicable
EC: 202-849-4	Inhalation	Non-applicable	Non-applicable	15 mg/m <sup>3</sup>	Non-applicable

#### PNEC:

Identification				
acetone	STP	100 mg/L	Fresh water	10,6 mg/L
CAS: 67-64-1	Soil	29,5 mg/kg	Marine water	1,06 mg/L
EC: 200-662-2	Intermittent	21 mg/L	Sediment (Fresh water)	30,4 mg/kg
	Oral	Non-applicable	Sediment (Marine water)	3,04 mg/kg
Xylene	STP	6,58 mg/L	Fresh water	0,327 mg/L
CAS: 1330-20-7	Soil	2,31 mg/kg	Marine water	0,327 mg/L
EC: 215-535-7	Intermittent	0,327 mg/L	Sediment (Fresh water)	12,46 mg/kg
	Oral	Non-applicable	Sediment (Marine water)	12,46 mg/kg
Ethylbenzene	STP	9,6 mg/L	Fresh water	0,1 mg/L
CAS: 100-41-4	Soil	2,68 mg/kg	Marine water	0,01 mg/L
EC: 202-849-4	Intermittent	0,1 mg/L	Sediment (Fresh water)	13,7 mg/kg
	Oral	0,02 g/kg	Sediment (Marine water)	1,37 mg/kg

#### 8.2 Exposure controls:

A.- Individual protection measures, such as personal protective equipment

As a preventative measure it is recommended to use basic Personal Protective Equipment, with the corresponding <<CE marking>> in accordance with Regulation (EU) 2016/425. For more information on Personal Protective Equipment (storage, use, cleaning, maintenance, class of protection,...) consult the information leaflet provided by the manufacturer. For more information see subsection 7.1. All information contained herein is a recommendation which needs some specification from the labour risk prevention services as it is not known whether the company has additional measures at its disposal.

B.- Respiratory protection

Pictog	jram 🛛	PPE	Labelling	CEN Standard		Remarks
Manda respirato protect	atory ry tract	lter mask for gases and apours (Filter type: A)		EN 405:2002+A1:2010	cc c	lace when there is a taste or smell of the ontaminant inside the face mask. If the contaminant comes with warnings it is commended to use isolation equipment.
C Specific p	rotection fo	r the hands				
Pictog	jram	PPE	Labelling	CEN Standard		Remarks
Mandato	pro Nitr y hand 480	DN-disposable chemical tective gloves (Material: ile, Breakthrough time: > min, Thickness: 0.4 mm)		EN ISO 374-1:2016+A1:2018 EN 16523-1:2015+A1:2018 EN ISO 21420:2020	manufa the pr	he Breakthrough Time indicated by the locturer must exceed the period during whi oduct is being used. Do not use protective hs after the product has come into contact with skin.
	bility and ha	s therefore to be che			rial can	not be calculated in advance with
Pictog	jram	PPE	Labelling	CEN Standard		Remarks
Mandato	ry face	noramic glasses against splash/projections.		EN 166:2002 EN ISO 4007:2018		daily and disinfect periodically according t anufacturer 's instructions. Use if there is risk of splashing.
E Body prot	ection					
Pictog	jram	PPE	Labelling	CEN Standard		Remarks
Mandatory body pro	complete ri	Disposable clothing for tection against chemical sks, with antistatic and fireproof properties		EN 1149-1,2,3 EN 13034:2005+A1:2009 EN ISO 13982- 1:2004/A1:2010 EN ISO 6529:2013 EN ISO 6530:2005 EN ISO 13688:2013 EN 464:1994		professional use only. Clean periodically rding to the manufacturer 's instructions.
Mandato	risk ry foot	Safety footwear for tection against chemical , with antistatic and heat resistant properties		EN ISO 13287:2020 EN ISO 20345:2011 EN 13832-1:2019	Re	place boots at any sign of deterioration.
F Additiona	l emergency	measures				
Emerg	gency measure	Sta	andards	Emergency measu	re	Standards
Eme	rgency shower		I Z358-1 11, ISO 3864-4:20	11 Eyewash stations	5	DIN 12 899 ISO 3864-1:2011, ISO 3864-4:2011
In accordance	e with the c			on of the environment it is not see subsection		nmended to avoid environmental

96,4 % weight
670,1 kg/m <sup>3</sup> (670,1 g/L)
4,5
72,83 g/mol

Printing:	09/01/2023	Date of compilation: 11/09/2015	Revised: 14/12/2022	Version: 6 (Replaced 5)				
SECT	TION 9: PHYSIC	AL AND CHEMICAL PROPERTIE	S					
9.1	Information on	basic physical and chemical pro	perties:					
	For complete information see the product datasheet.							
	Appearance:							
	Physical state at 2	20 °C:	Aerosol					
	, Appearance:		Volatile					
	Colour:		Silver					
	Odour:		Characteristic					
	Odour threshold:		Non-applicable *					
	Volatility:							
	Boiling point at al	tmospheric pressure:	-42 °C (Propellant)					
	Vapour pressure	at 20 ºC:	350000 Pa					
	Vapour pressure	at 50 °C:	<300000 Pa (300 kPa)					
	Evaporation rate	at 20 ºC:	Non-applicable *					
	Product descrip	otion:						
	Density at 20 °C:		695 kg/m³					
	Relative density a	at 20 °C:	Non-applicable *					
	Dynamic viscosity	/ at 20 °C:	Non-applicable *					
	Kinematic viscosit	ty at 20 °C:	Non-applicable *					
	Kinematic viscosit	ty at 40 °C:	Non-applicable *					
	Concentration:		Non-applicable *					
	pH:		Non-applicable *					
	Vapour density at	t 20 °C:	Non-applicable *					
	Partition coefficie	nt n-octanol/water 20 °C:	Non-applicable *					
	Solubility in water	r at 20 °C:	Non-applicable *					
	Solubility properti	ies:	Non-applicable *					
	Decomposition te	mperature:	Non-applicable *					
	Melting point/free	ezing point:	Non-applicable *					
	Recipient pressur	e:	Non-applicable *					
	Flammability:							
	Flash Point:		Non-applicable					
	Flammability (soli	id, gas):	Non-applicable *					
	Autoignition temp		410 °C (Propellant)					
	Lower flammabilit		1,5 % Volume					
	Upper flammabilit		13 % Volume					
	Particle charact							
	Median equivalen		Non-applicable					
9.2	Other information							
		th regard to physical hazard clas						
	Explosive propert		Non-applicable *					
	Oxidising propert		Non-applicable *					
	Corrosive to meta		Non-applicable *					
	Heat of combusti		Non-applicable *					
1	Aerosols-total per components:	centage (by mass) of flammable	Non-applicable *					
1	Other safety ch	aracteristics:						
	*Not relevant due to	the nature of the product, not providing info	rmation property of its hazards.					

Safety data sheet This SDS is an English translation of COMMISSION REGULATION (EU) 2020/878, without any country-specific legislation

## ZINC-ALUMINIUM NEW FORMULA

Printing:	09/01/2023	Date of compilation: 11/09/2015	Revised: 14/12/20	22 Version: 6 (Re	placed 5)				
SECT	ION 9: PHYSICAI	_ AND CHEMICAL PROPERTIES	(continued)						
	Surface tension at 20 °C: Non-applicable *								
	Refraction index:		Non-applicable *						
	*Not relevant due to th	e nature of the product, not providing inform	nation property of its hazards						
SECT	ION 10: STABILI	TY AND REACTIVITY							
10.1	Reactivity:								
	No hazardous read	tions are expected because the prod	uct is stable under recor	nmended storage condition	ons. See section 7.				
10.2	Chemical stabilit	y:							
	Chemically stable u	Inder the indicated conditions of stor	rage, handling and use.						
10.3	Possibility of haz	ardous reactions:							
	Under the specified	l conditions, hazardous reactions tha	at lead to excessive temp	peratures or pressure are	not expected.				
10.4	Conditions to ave	bid:							
	Applicable for hand	lling and storage at room temperatu	re:						
	Shock and friction	on Contact with air	Increase in temperature	Sunlight	Humidity				
	Not applicable	e Not applicable	Risk of combustion	Avoid direct impact	Not applicable				
10.5	Incompatible ma	iterials:							
	Acids	Water	Oxidising materials	Combustible materials	Others				
	Avoid strong ac	ids Not applicable	Avoid direct impact	Not applicable	Avoid alkalis or strong bases				
10.6	Hazardous decor	mposition products:							
	See subsection 10.3, 10.4 and 10.5 to find out the specific decomposition products. Depending on the decomposition conditions,								

complex mixtures of chemical substances can be released: carbon dioxide (CO<sub>2</sub>), carbon monoxide and other organic compounds.

#### SECTION 11: TOXICOLOGICAL INFORMATION \*\*

#### 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008:

The experimental information related to the toxicological properties of the product itself is not available

#### **Dangerous health implications:**

In case of exposure that is repetitive, prolonged or at concentrations higher than the recommended occupational exposure limits, adverse effects on health may result, depending on the means of exposure:

- A- Ingestion (acute effect):
  - Acute toxicity : Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for consumption. For more information see section 3
  - Corrosivity/Irritability: Based on available data, the classification criteria are not met. However, it does contain substances classified as hazardous for this effect. For more information see section 3.
- B- Inhalation (acute effect):
  - Acute toxicity : Based on available data, the classification criteria are not met. However, it contains substances classified as hazardous for inhalation. For more information see section 3.
  - Corrosivity/Irritability: Based on available data, the classification criteria are not met. However, it contains substances classified as hazardous for inhalation. For more information see section 3.
- C- Contact with the skin and the eyes (acute effect):
  - Contact with the skin: Based on available data, the classification criteria are not met. However, it contains substances classified as hazardous for skin contact. For more information see section 3.
  - Contact with the eyes: Produces eye damage after contact.
- D- CMR effects (carcinogenicity, mutagenicity and toxicity to reproduction):

	Date of compilation: 11/09/2015		Version: 6 (Replaced 5)	
ON 11: TOX	COLOGICAL INFORMATION ** (cor	ntinued)		
as hazardo IARC: Xy - Mutager hazardous - Reprodu	enicity: Based on available data, the class us for the effects mentioned. For more info lene (3); Ethylbenzene (2B); Hydrocarbons nicity: Based on available data, the classific for this effect. For more information see se ctive toxicity: Based on available data, the s hazardous for this effect. For more inform effects:	ormation see section 3. s, C9, aromatics (3) cation criteria are not met, as it de ection 3. e classification criteria are not met	oes not contain substan	ces classifi
- Respirat hazardous - Skin: Ba hazardous	ory: Based on available data, the classifica with sensitising effects. For more informati sed on available data, the classification cri for this effect. For more information see se get organ toxicity (STOT) - single exposure	ion see section 3. teria are not met, as it does not c ection 3.		
Exposure ir vomiting, c	high concentration can interfere with the onfusion, and in serious cases, loss of cons get organ toxicity (STOT)-repeated exposu	central nervous system causing h sciousness.	neadache, dizziness, ver	tigo, naus
- Specific However, it	target organ toxicity (STOT)-repeated exp does contain substances classified as haza peated exposure may cause skin dryness o	osure: Based on available data, th ardous for this effect. For more in		
Other inform Non-applicable			in substances classified	as hazardo
Other inform Non-applicable	ation: ology information on the substances:	:		
Other inform Non-applicable	ation:	: 	Acute toxicity	as hazardo Gen
Other inform Non-applicable Specific toxic acetone	ation: ology information on the substances:	LD50 oral	Acute toxicity 5800 mg/kg	Gen
Other inform Non-applicable Specific toxic	ation: ology information on the substances:	: 	Acute toxicity 5800 mg/kg 7426 mg/kg	Gen
Other inform Non-applicable Specific toxic acetone	ation: ology information on the substances:	LD50 oral	Acute toxicity 5800 mg/kg	Gen Ra Rab
Other inform Non-applicable Specific toxic acetone CAS: 67-64-1	ation: ology information on the substances:	LD50 oral LD50 dermal	Acute toxicity 5800 mg/kg 7426 mg/kg	
Other inform Non-applicable Specific toxic acetone CAS: 67-64-1 EC: 200-662-2	ation: ology information on the substances:	LD50 oral LD50 dermal LC50 inhalation	Acute toxicity 5800 mg/kg 7426 mg/kg 76 mg/L (4 h)	Gen Ra Rabi
Other inform Non-applicable Specific toxic acetone CAS: 67-64-1 EC: 200-662-2 Propane	ation: ology information on the substances:	LD50 oral LD50 dermal LC50 inhalation LD50 oral	Acute toxicity 5800 mg/kg 7426 mg/kg 76 mg/L (4 h) >2000 mg/kg	Gen Ra Rab
Other inform Non-applicable Specific toxic acetone CAS: 67-64-1 EC: 200-662-2 Propane CAS: 74-98-6	ation: ology information on the substances:	LD50 oral LD50 dermal LC50 inhalation LD50 oral LD50 dermal	Acute toxicity 5800 mg/kg 7426 mg/kg 76 mg/L (4 h) >2000 mg/kg >2000 mg/kg	Gen Ra Rab
Other inform Non-applicable Specific toxic acetone CAS: 67-64-1 EC: 200-662-2 Propane CAS: 74-98-6 EC: 200-827-9	ation: ology information on the substances:	LD50 oral LD50 dermal LC50 inhalation LD50 dermal LD50 dermal LD50 dermal LC50 inhalation	Acute toxicity 5800 mg/kg 7426 mg/kg 76 mg/L (4 h) >2000 mg/kg >2000 mg/kg >5 mg/L	Gen Ra Rab
Other inform Non-applicable Specific toxic acetone CAS: 67-64-1 EC: 200-662-2 Propane CAS: 74-98-6 EC: 200-827-9 Butane	ation: ology information on the substances:	LD50 oral LD50 dermal LC50 inhalation LD50 dermal LD50 dermal LD50 dermal LC50 inhalation LC50 inhalation	Acute toxicity           5800 mg/kg           7426 mg/kg           76 mg/L (4 h)           >2000 mg/kg           >2000 mg/kg           >5 mg/L           >2000 mg/kg	Gen Ra Rab Rab
Other inform Non-applicable Specific toxic acetone CAS: 67-64-1 EC: 200-662-2 Propane CAS: 74-98-6 EC: 200-827-9 Butane CAS: 106-97-8	ation: ology information on the substances:	LD50 oral LD50 dermal LC50 inhalation LD50 dermal LD50 dermal LC50 inhalation LD50 oral LC50 oral LD50 dermal	Acute toxicity           5800 mg/kg           7426 mg/kg           76 mg/L (4 h)           >2000 mg/kg           >2000 mg/kg           >5 mg/L           >2000 mg/kg           >2000 mg/kg           >2000 mg/kg           >2000 mg/kg	Gen Ra Rab Rab
Other inform Non-applicable Specific toxic acetone CAS: 67-64-1 EC: 200-662-2 Propane CAS: 74-98-6 EC: 200-827-9 Butane CAS: 106-97-8 EC: 203-448-7	ation: ology information on the substances:	LD50 oral LD50 dermal LC50 inhalation LD50 dermal LD50 oral LD50 dermal LC50 inhalation LD50 oral LD50 oral LD50 oral LD50 dermal	Acute toxicity         5800 mg/kg         7426 mg/kg         76 mg/L (4 h)         >2000 mg/kg         >2000 mg/kg         >5 mg/L         >2000 mg/kg	Gen Ra Rab Rab
Other inform Non-applicable Specific toxic acetone CAS: 67-64-1 EC: 200-662-2 Propane CAS: 74-98-6 EC: 200-827-9 Butane CAS: 106-97-8 EC: 203-448-7 Isobutane	ation: ology information on the substances:	LD50 oral LD50 dermal LD50 dermal LC50 inhalation LD50 oral LD50 dermal LC50 inhalation LD50 dermal LD50 dermal LD50 dermal LD50 oral LD50 oral	Acute toxicity         5800 mg/kg         7426 mg/kg         76 mg/L (4 h)         >2000 mg/kg         >2000 mg/kg         >5 mg/L         >2000 mg/kg         >2000 mg/kg         >5 mg/L         >2000 mg/kg         >2000 mg/kg         >2000 mg/kg         >2000 mg/kg         >2000 mg/kg         >2000 mg/kg	Ger Ra Rab Rab
Other inform Non-applicable Specific toxic acetone CAS: 67-64-1 EC: 200-662-2 Propane CAS: 74-98-6 EC: 200-827-9 Butane CAS: 106-97-8 EC: 203-448-7 Isobutane CAS: 75-28-5	ation: ology information on the substances:	LD50 oral LD50 dermal LD50 dermal LC50 inhalation LD50 dermal LC50 inhalation LD50 oral LD50 oral LD50 dermal LD50 oral LD50 oral LD50 oral LD50 oral	Acute toxicity         5800 mg/kg         7426 mg/kg         76 mg/L (4 h)         >2000 mg/kg	Gen Ra Rab Rab Ra Ra Ra Ra
Other inform Non-applicable Specific toxic acetone CAS: 67-64-1 EC: 200-662-2 Propane CAS: 74-98-6 EC: 200-827-9 Butane CAS: 106-97-8 EC: 203-448-7 Isobutane CAS: 75-28-5 EC: 200-857-2	ation: ology information on the substances:	LD50 oral LD50 dermal LC50 inhalation LD50 dermal LD50 dermal LD50 dermal LD50 oral LD50 oral LD50 dermal LC50 inhalation LD50 oral LD50 dermal LD50 dermal LD50 dermal	Acute toxicity           5800 mg/kg           7426 mg/kg           76 mg/L (4 h)           >2000 mg/kg	Gen Rab Rab Rab Rab Ra Ra Ra Ra
Other inform Non-applicable Specific toxic acetone CAS: 67-64-1 EC: 200-662-2 Propane CAS: 74-98-6 EC: 200-827-9 Butane CAS: 106-97-8 EC: 203-448-7 Isobutane CAS: 75-28-5 EC: 200-857-2 Xylene	ation: ology information on the substances:	LD50 oral LD50 dermal LD50 dermal LD50 dermal LD50 oral LD50 dermal LD50 dermal LD50 dermal LD50 dermal LD50 dermal LD50 dermal LD50 dermal LD50 dermal LD50 dermal LD50 dermal	Acute toxicity           5800 mg/kg           7426 mg/kg           7426 mg/kg           76 mg/L (4 h)           >2000 mg/kg	Gen Rab Rab Rab Rab Ra Ra Ra Ra
Other inform Non-applicable Specific toxic acetone CAS: 67-64-1 EC: 200-662-2 Propane CAS: 74-98-6 EC: 200-827-9 Butane CAS: 106-97-8 EC: 203-448-7 Isobutane CAS: 75-28-5 EC: 200-857-2 Xylene CAS: 1330-20-7 EC: 215-535-7	ation: ology information on the substances:	LD50 oral LD50 dermal LD50 dermal LD50 dermal LD50 dermal LD50 dermal LD50 oral LD50 dermal LD50 dermal LD50 dermal LD50 dermal LD50 dermal LD50 dermal LD50 dermal	Acute toxicity           5800 mg/kg           7426 mg/kg           7426 mg/kg           76 mg/L (4 h)           >2000 mg/kg           >100 mg/kg           11 mg/L (ATEi)	Gen Rab Rab Rab Rab Ra Ra Ra Ra Ra
Other inform Non-applicable Specific toxic acetone CAS: 67-64-1 EC: 200-662-2 Propane CAS: 74-98-6 EC: 200-827-9 Butane CAS: 106-97-8 EC: 203-448-7 Isobutane CAS: 75-28-5 EC: 200-857-2 Xylene CAS: 1330-20-7	ation: ology information on the substances:	LD50 oral LD50 dermal LD50 dermal LD50 dermal LD50 oral LD50 oral LD50 dermal LD50 dermal	Acute toxicity         5800 mg/kg         7426 mg/kg         76 mg/L (4 h)         >2000 mg/kg	Gen Ra Rab Rab Ra Ra Ra Ra Ra Ra Ra Ra
Other inform Non-applicable Specific toxic acetone CAS: 67-64-1 EC: 200-662-2 Propane CAS: 74-98-6 EC: 200-827-9 Butane CAS: 106-97-8 EC: 203-448-7 Isobutane CAS: 75-28-5 EC: 200-857-2 Xylene CAS: 1330-20-7 EC: 215-535-7 Ethylbenzene CAS: 100-41-4	ation: ology information on the substances:	LD50 oral LD50 dermal LD50 dermal LD50 dermal LD50 oral LD50 dermal LD50 dermal	Acute toxicity         5800 mg/kg         7426 mg/kg         7426 mg/kg         76 mg/L (4 h)         >2000 mg/kg         >2000 mg/kg         >5 mg/L         >2000 mg/kg         >100 mg/kg         11 mg/L (ATEi)         3500 mg/kg         15354 mg/kg	Gen Rab Rab Rab Ra Ra Ra Ra Ra Ra Rab
Other inform Non-applicable Specific toxic acetone CAS: 67-64-1 EC: 200-662-2 Propane CAS: 74-98-6 EC: 200-827-9 Butane CAS: 106-97-8 EC: 203-448-7 Isobutane CAS: 75-28-5 EC: 200-857-2 Xylene CAS: 1330-20-7 EC: 215-535-7 Ethylbenzene CAS: 100-41-4 EC: 202-849-4	ation: ology information on the substances: Identification	LD50 oral LD50 dermal LD50 dermal	Acute toxicity         5800 mg/kg         7426 mg/kg         76 mg/L (4 h)         >2000 mg/kg         100 mg/kg         1100 mg/kg         11 mg/L (ATEi)         3500 mg/kg         15354 mg/kg         17,2 mg/L (4 h)	Gen Rab Rab Rab Ra Ra Ra Ra Ra Ra Rab
Other inform Non-applicable Specific toxic acetone CAS: 67-64-1 EC: 200-662-2 Propane CAS: 74-98-6 EC: 200-827-9 Butane CAS: 106-97-8 EC: 203-448-7 Isobutane CAS: 75-28-5 EC: 200-857-2 Xylene CAS: 1330-20-7 EC: 215-535-7 Ethylbenzene CAS: 100-41-4	ation: ology information on the substances: Identification	LD50 oral LD50 dermal LD50 dermal LD50 dermal LD50 oral LD50 dermal LD50 dermal	Acute toxicity         5800 mg/kg         7426 mg/kg         7426 mg/kg         76 mg/L (4 h)         >2000 mg/kg         >2000 mg/kg         >5 mg/L         >2000 mg/kg         >100 mg/kg         11 mg/L (ATEi)         3500 mg/kg         15354 mg/kg	Gen Ra Rabi

### Acute Toxicity Estimate (ATE mix):

ATE mix		Ingredient(s) of unknown toxicity
Oral	>2000 mg/kg (Calculation method)	Non-applicable
Dermal	12649,93 mg/kg (Calculation method)	0 %
Inhalation	95,85 mg/L (4 h) (Calculation method)	0 %

\*\* Changes with regards to the previous version

NOTOEL

## ZINC-ALUMINIUM NEW FORMULA

 Printing: 09/01/2023
 Date of compilation: 11/09/2015
 Revised: 14/12/2022
 Version: 6 (Replaced 5)

# SECTION 11: TOXICOLOGICAL INFORMATION \*\* (continued)

## **11.2** Information on other hazards:

## Endocrine disrupting properties

Endocrine-disrupting properties: The product fails to meet the criteria.

#### **Other information**

Non-applicable

\*\* Changes with regards to the previous version

#### SECTION 12: ECOLOGICAL INFORMATION \*\*

The experimental information related to the eco-toxicological properties of the product itself is not available

#### 12.1 Toxicity:

#### Acute toxicity:

Identification		Concentration	Species	Genus	
acetone	LC50	5540 mg/L (96 h)	Oncorhynchus mykiss	Fish	
CAS: 67-64-1	EC50	8800 mg/L (48 h)	Daphnia pulex	Crustacean	
EC: 200-662-2	EC50	3400 mg/L (48 h)	Chlorella pyrenoidosa	Algae	
Xylene	LC50	>10 - 100 mg/L (96 h)		Fish	
CAS: 1330-20-7	EC50	>10 - 100 mg/L (48 h)		Crustacean	
EC: 215-535-7	EC50	>10 - 100 mg/L (72 h)		Algae	
Hydrocarbons, C9, aromatics	LC50	>1 - 10 mg/L (96 h)		Fish	
CAS: 128601-23-0	EC50	>1 - 10 mg/L (48 h)		Crustacean	
EC: 918-668-5	EC50	>1 - 10 mg/L (72 h)		Algae	
Ethylbenzene	LC50	42,3 mg/L (96 h)	Pimephales promelas	Fish	
CAS: 100-41-4	EC50	75 mg/L (48 h)	Daphnia magna	Crustacean	
EC: 202-849-4	EC50	63 mg/L (3 h)	Chlorella vulgaris	Algae	

#### Chronic toxicity:

Identification		Concentration	Species	Genus
acetone	NOEC	Non-applicable		
CAS: 67-64-1 EC: 200-662-2	NOEC	2212 mg/L	Daphnia magna	Crustacean
Xylene	NOEC	1,3 mg/L	Oncorhynchus mykiss	Fish
CAS: 1330-20-7 EC: 215-535-7	NOEC	1,17 mg/L	Ceriodaphnia dubia	Crustacean
Ethylbenzene	NOEC	Non-applicable		
CAS: 100-41-4 EC: 202-849-4	NOEC	0,96 mg/L	Ceriodaphnia dubia	Crustacean

## 12.2 Persistence and degradability:

#### Substance-specific information:

Identification	Degradability		Biodegradability	
acetone	BOD5	Non-applicable	Concentration	100 mg/L
CAS: 67-64-1	COD	Non-applicable	Period	28 days
EC: 200-662-2	BOD5/COD	Non-applicable	% Biodegradable	96 %
Xylene	BOD5	Non-applicable	Concentration	Non-applicable
CAS: 1330-20-7	COD	Non-applicable	Period	28 days
EC: 215-535-7	BOD5/COD	Non-applicable	% Biodegradable	88 %
Ethylbenzene	BOD5	Non-applicable	Concentration	100 mg/L
CAS: 100-41-4	COD	Non-applicable	Period	14 days
EC: 202-849-4	BOD5/COD	Non-applicable	% Biodegradable	90 %

## 12.3 Bioaccumulative potential:

Substance-specific information:

\*\* Changes with regards to the previous version

Printing: 09/01/2023 Date of compilation: 11/09/2015 Revised: 14/12/2022 Version: 6 (Replaced 5) SECTION 12: ECOLOGICAL INFORMATION \*\* (continued) Identification **Bioaccumulation potential** BCF acetone Pow Log -0.24 CAS: 67-64-1 EC: 200-662-2 Potential Low BCF 13 Propane Pow Log 2.86 CAS: 74-98-6 EC: 200-827-9 Potential Low Butane BCF 33 CAS: 106-97-8 Pow Log 2.89 Potential Moderate EC: 203-448-7 BCF Isobutane 27 CAS: 75-28-5 Pow Log 2.76 EC: 200-857-2 Potential Low BCF Xvlene g CAS: 1330-20-7 Pow Log 2.77 EC: 215-535-7 Potential low BCF Ethylbenzene CAS: 100-41-4 Pow Log 3.15 EC: 202-849-4 Potential Low 12.4 Mobility in soil: Absorption/desorption Volatility Identification acetone Koc Henry 2,93 Pa·m³/mol CAS: 67-64-1 Conclusion Very High Dry soi Yes EC: 200-662-2 Surface tension 2,304E-2 N/m (25 °C) Moist soil Yes 71636,78 Pa·m<sup>3</sup>/mol 460 Henry Кос Propane Moderate CAS: 74-98-6 Conclusion Dry soil Yes EC: 200-827-9 Surface tension 7,02E-3 N/m (25 °C) Moist soil Yes Butane Кос 900 Henry 96258,75 Pa·m<sup>3</sup>/mol CAS: 106-97-8 Conclusion Dry soil Yes Low 1,187E-2 N/m (25 °C) EC: 203-448-7 Surface tension Moist soil Yes Кос Henry 120576,75 Pa·m<sup>3</sup>/mol Isobutane 35 Conclusion Very High Dry soil CAS: 75-28-5 Yes EC: 200-857-2 Surface tension 9,84E-3 N/m (25 °C) Yes Moist soil 524,86 Pa·m<sup>3</sup>/mol 202 Henry Xvlene Кос Dry soil Conclusion Moderate CAS: 1330-20-7 Yes EC: 215-535-7 Surface tension Non-applicable Moist soil Yes 520 Henry 798,44 Pa·m<sup>3</sup>/mol Ethylbenzene Koc Moderate CAS: 100-41-4 Conclusion Dry soil Yes EC: 202-849-4 Surface tension 2,859E-2 N/m (25 °C) Moist soil Yes 12.5 Results of PBT and vPvB assessment: Product fails to meet PBT/vPvB criteria 12.6 Endocrine disrupting properties: Endocrine-disrupting properties: The product fails to meet the criteria. 12.7 Other adverse effects: Not described

\*\* Changes with regards to the previous version

## SECTION 13: DISPOSAL CONSIDERATIONS

### **13.1** Waste treatment methods:

Safety data sheet This SDS is an English translation of COMMISSION REGULATION (EU) 2020/878, without any country-specific legislation

## ZINC-ALUMINIUM NEW FORMULA

Code		Descripti	on	Waste class (Regulation (El 1357/2014)
16 05 04* ga	ses in pre	ssure containers (including halons) contai	ning hazardous substances	Dangerous
Type of waste	(Regula	tion (EU) No 1357/2014):		
	P3 Flam	mable, HP5 Specific Target Organ	Toxicity (STOT)/Aspiration To	xicity, HP4 Irritant — skin irritation
eye damage	mont (	lisposal and evaluation):		
-	-		sement and disposal operation	is in accordance with Annex 1 and
2 (Directive 2008	/98/EC).	As under 15 01 (2014/955/EC) o	f the code and in case the co	ntainer has been in direct contact w
		cessed the same way as the actua osed of to drains. See paragraph		e processed as non-dangerous resi
	•	waste management:	0.2.	
-		-	006 (REACH) the community	or state provisions related to waste
management are	stated	-	. , , ,	
Community legisl	ation: D	irective 2008/98/EC, 2014/955/EU	J, Regulation (EU) No 135//20	)14
TION 14: TRANS	PORT 1	INFORMATION		
Transport of d	angero	us goods by land:		
With regard to A		1 and RID 2021:		
		UN number or ID number:	UN1950	
yhe.		UN proper shipping name: Transport hazard class(es):	AEROSOLS 2	
	110	Labels:	2.1	
	14.4	Packing group:	N/A	
2		Environmental hazards:	No	
	14.6	<b>Special precautions for user</b> Special regulations:	190, 327, 344, 625	
		Tunnel restriction code:	D	
		Physico-Chemical properties:	see section 9	
		Limited quantities:	1 L	
	14.7	Maritime transport in bulk according to IMO	Non-applicable	
		instruments:		
Transport of d	angero	us goods by sea:		
With regard to I	MDG 40	-20:		
	14.1	UN number or ID number:	UN1950	
		UN proper shipping name:	AEROSOLS	
she	14.3	Transport hazard class(es): Labels:	2 2.1	
$\langle \underline{\mathbf{e}} \rangle$	14.4	Packing group:	N/A	
2		Marine pollutant:	No	
	14.6	Special precautions for user		
		Special regulations:	63, 959, 190, 277, 327, 344	
		EmS Codes:	F-D, S-U	
		Physico-Chemical properties: Limited quantities:	see section 9 1 L	
		Segregation group:	Non-applicable	
	14.7	Maritime transport in bulk	Non-applicable	
		according to IMO		
	angero	instruments: us goods by air:		
Transport of d				

Printing: 09/01/2023	Date	of compilation: 11/09/2015	Revised: 14/12/2022	Version: 6 (Replaced 5)
SECTION 14: TRANSI	PORT	INFORMATION (continued)		
2	14.2 14.3 14.4 14.5	UN number or ID number: UN proper shipping name: Transport hazard class(es): Labels: Packing group: Environmental hazards: Special precautions for user	UN1950 AEROSOLS 2 2.1 N/A No	
	14.7	Physico-Chemical properties: Maritime transport in bulk according to IMO instruments:	see section 9 Non-applicable	

#### SECTION 15: REGULATORY INFORMATION

#### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture:

Candidate substances for authorisation under the Regulation (EC) No 1907/2006 (REACH): Non-applicable

Substances included in Annex XIV of REACH ("Authorisation List") and sunset date: Non-applicable

Regulation (EC) No 1005/2009, about substances that deplete the ozone layer: Non-applicable

Article 95, REGULATION (EU) No 528/2012: Non-applicable

REGULATION (EU) No 649/2012, in relation to the import and export of hazardous chemical products: Non-applicable

#### Seveso III:

Section	Description	Lower-tier requirements	Upper-tier requirements
P3a	FLAMMABLE AEROSOLS	150	500

Limitations to commercialisation and the use of certain dangerous substances and mixtures (Annex XVII REACH, etc ....):

Regulation (EU) 2019/1148 on the marketing and use of explosives precursors: Contains acetone. Product under the provisions of Article 9. However, products that contain explosives precursors only to such a small extent and in such complex mixtures that the extraction of the explosives precursors is technically extremely difficult should be excluded from the scope of this Regulation. Shall not be used in:

—ornamental articles intended to produce light or colour effects by means of different phases, for example in ornamental lamps and ashtrays,

-tricks and jokes,

-games for one or more participants, or any article intended to be used as such, even with ornamental aspects.

#### Specific provisions in terms of protecting people or the environment:

It is recommended to use the information included in this safety data sheet as a basis for conducting workplace-specific risk assessments in order to establish the necessary risk prevention measures for the handling, use, storage and disposal of this product.

#### Other legislation:

The product could be affected by sectorial legislation

Council Directive 75/324/EEC of 20 May 1975 on the approximation of the laws of the Member States relating to aerosol dispensers

Commission Directive 94/1/EC of 6 January 1994 adapting some technicalities of Council Directive 75/324/EEC on the approximation of the laws of the relating Member States to aerosol dispensers

Commission Directive 2008/47/EC of 8 April 2008 amending, for the purposes of adapting to technical progress, Council Directive 75/324/EEC on the approximation of the laws of the Member States relating to aerosol dispensers

Commission Directive 2013/10/EU of 19 March 2013 amending Council Directive 75/324/EEC on the approximation of the laws of the Member States relating to aerosol dispensers in order to adapt its labelling provisions to Regulation (EC) No 1272/2008 of the European Parliament and of the Council on classification, labelling and packaging of substances and mixtures

COMMISSION DIRECTIVE (EU) 2016/2037 of 21 November 2016 amending Council Directive 75/324/EEC as regards the maximum allowable pressure of aerosol dispensers and to adapt its labelling provisions to Regulation (EC) No 1272/2008 of the European Parliament and of the Council on classification, labelling and packaging of substances and mixtures

#### 15.2 Chemical safety assessment:

The supplier has not carried out evaluation of chemical safety.

ting: 09/01/2023	Date of compilation: 11/09/2015	Revised: 14/12/2022	Version: 6 (Replaced 5)
SECTION 16: OTHE	R INFORMATION **		
Legislation rel The SDS shall be has been design (COMMISSION F Modifications COMPOSITION/ • New declare Propane ( Butane (1 Isobutane Hydrocarb • Removed sul Solvent na Substances that • New declare Hydrocarb • Removed sul Solvent na Solvent na	ated to safety data sheets: e supplied in an official language of the c ed in accordance with ANNEX II-Guide to REGULATION (EU) 2020/878). related to the previous Safety Data INFORMATION ON INGREDIENTS (SECT: d substances 74-98-6) 06-97-8) (75-28-5) ions, C9, aromatics (128601-23-0) ostances aphtha (petroleum), light arom., < 0.1 % contribute to the classification (SECTION d substances ions, C9, aromatics (128601-23-0) ostances aphtha (petroleum), light arom., < 0.1 %	b the compilation of safety da         Sheet which concerns the         ION 3, SECTION 11, SECTION         b EC 200-753-7 (64742-95-6)         > 2):         b EC 200-753-7 (64742-95-6)	
· Hazard state		N 16):	
	ry information gislative phrases mentioned in sect	ion Ju	
H319: Causes se H336: May caus H412: Harmful t H229: Pressurise	erious eye irritation. e drowsiness or dizziness. o aquatic life with long lasting effects. ed container: May burst if heated. r flammable aerosol.	ION 2.	
Texts of the le	gislative phrases mentioned in sect	ion 3:	
	cated do not refer to the product itself; to nents which appear in section 3	they are present merely for ir	formative purposes and refer to the
CLP Regulation	n (EC) No 1272/2008:		
Acute Tox. 4: H3 Acute Tox. 4: H3	812+H332 - Harmful in contact with skin 832 - Harmful if inhaled. 2: H411 - Toxic to aquatic life with long		
Aquatic Chronic Asp. Tox. 1: H30	3: H412 - Harmful to aquatic life with lo A - May be fatal if swallowed and enters	ng lasting effects.	
Flam. Gas 1A: H	9 - Causes serious eye irritation. 220 - Extremely flammable gas. 25 - Highly flammable liquid and vapour.		
Press. Gas: H28 Skin Irrit. 2: H3	26 - Flammable liquid and vapour. 0 - Contains gas under pressure, may ex 15 - Causes skin irritation. 3 - May cause damage to organs throug		ocura (Inhalation)
STOT RE 2: H37 STOT SE 3: H33	<ol> <li>May cause damage to organs throug</li> <li>May cause damage to organs throug</li> <li>May cause respiratory irritation.</li> <li>May cause drowsiness or dizziness.</li> </ol>		
Classification			
Eye Irrit. 2: Calc STOT SE 3: Calc Aquatic Chronic Aerosol 1: Calcu Aerosol 1: Calcu	ulation method 3: Calculation method lation method		
Advice related			
Training is recon	-		t and to facilitate their comprehension and
•	pgraphical sources: pa.eu		

Safety data sheet This SDS is an English translation of COMMISSION REGULATION (EU) 2020/878, without any country-specific legislation

## ZINC-ALUMINIUM NEW FORMULA

Printing: 09/01/2023	Date of compilation: 11/09/2015	Revised: 14/12/2022	Version: 6 (Replaced 5)	
SECTION 16: OTH	ER INFORMATION ** (continued)			
IMDG: Internati IATA: Internati ICAO: Internati COD: Chemical BOD5: 5day bio BCF: Bioconcer LD50: Lethal D LC50: Lethal C EC50: Effective LogPOW: Octal Koc: Partition c UFI: unique for		carriage of dangerous goods	by road	

\*\* Changes with regards to the previous version

The information contained in this safety data sheet is based on sources, technical knowledge and current legislation at European and state level, without being able to guarantee its accuracy. This information cannot be considered a guarantee of the properties of the product, it is simply a description of the security requirements. The occupational methodology and conditions for users of this product are not within our awareness or control, and it is ultimately the responsibility of the user to take the necessary measures to obtain the legal requirements concerning the manipulation, storage, use and disposal of chemical products. The information on this safety data sheet only refers to this product, which should not be used for needs other than those specified.