

TECHNICAL INFORMATION

FOR PROFESSIONAL USE ONLY

SPEC ALUMINUM – ZINC PAINT

PRODUCT DESCRIPTION

Anticorrosive one-component vinyl paint pigmented with zinc and aluminum dusts, designed for decorative and anti-corrosion painting of clean or rusted surface. Specially selected binder provides very good adhesion to the surfaces such as zinc steel, galvanized steel, aluminum and plaster. After drying creates elastic coating fully resistant against weather condition.

PHYSICAL AND CHEMICAL PROPERTIES

Color:	silver-grey
Gloss grade:	semigloss
Capacity:	1 liter
Density:	approx. 1,1 kg/dm ³
Film thickness recommended:	approx. 55 µm
Dry time (w 20 ⁰ C)	
- tack free :	1 h.
- dry to touch:	3 h.
Number of coatings recommended:	1 – 2
Coverage (theoretical):	0,16 dm ³ /m ² (for 55 µm film thickness)
Solid content:	approx. 45% of volume
Solvents content:	approx. 50% of volume
V.O.C.	500 g/l

USAGE

- Surface: high degree of surface to be treated, helps to extend paint durability. Rust remove manually or mechanically.
 - aluminium surfaces, un-weathered galvanized steel – clean, tarnish and dry.
 - weathered galvanized steel – remove the product of corrosion (white rust) and Rother contaminations.
 - acrylic coatings, vinyl coatings, chloro-rubber – clean, degreased and dry. It's recommended to make notching net to verify adhesion.
- Before use stir paint thoroughly.
- To omitting condensation it is recommended to work on the surface temperature above the dew point.
- Application method : brush, roller, airless sprayer (Ø0,38-0,53 mm; min. 10 MPa),
- Re-coat ater min. 5 hours.

Caution: To maintain safety, always follow the instructions given in the Safety Data Sheet for the given product.

STORAGE

Product should be stored in dry, cool and ventilated place, away from sources of ignition, heat and direct sunlight.

EXPIRY DATE

12 months from production date in unopened packaging.

Important Information:

The information contained in this document corresponds to our present knowledge and is a guide to our products and their uses.

Read all directions and warnings prior to using Troton products - Safety Data Sheets can be found online at www.troton.com.pl or will be sent according to your request: troton@troton.com.pl

Technical Information: The technical information, recommendations and other statements contained in this document are based upon tests or experience that Troton believes are reliable, but the accuracy or completeness of such information is not guaranteed.

Many factors beyond Troton's control and uniquely within user's knowledge and control can affect the use and performance of a Troton product in a particular application. Given the variety of factors that can affect the use and performance of a Troton product, user is solely responsible for evaluating the Troton product and determining whether it is fit for a particular purpose and suitable for user's method of application.

Limitation of Liability: Except where prohibited by law, Troton will not be liable for any loss or damage arising from the Troton product, whether direct, indirect, special, incidental or consequential, regardless of the legal theory asserted, including warranty, contract, negligence or strict liability. If used as instructed, this product is designed to comply with the European Volatile Organic Compound (VOC) Emission Standard for Automotive Refinish Coatings. Confirm compliance with your country, state and local air quality rules before use. The data on this sheet represent typical values. Since application variables are a major factor in product performance, this information should serve only as a general guide. Troton assumes no obligation or liability for use of this information.

TROTON Sp. z o.o.
Ząbrowo, Poland