

BUMPER PAINT 1K NO STRUCTURE GLOSS

Printing: 20/12/2022

Date of compilation: 13/10/2020

Revised: 19/07/2022

Version: 2 (Replaced 1)

SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1 Product identifier: BUMPER PAINT 1K NO STRUCTURE GLOSS

Other means of identification:

UFI: H3T4-91CH-400Y-VPRS

1.2 Relevant identified uses of the substance or mixture and uses advised against:

Relevant uses: Car repair. For professional users only.

Uses advised against: All uses not specified in this section or in section 7.3

1.3 Details of the supplier of the safety data sheet:

Troton Sp. z o.o.
 Ząbrowo 14A
 78-120 Gościno - Zachodniopomorskie - Polska
 Phone: +48 94 35 123 94 - Fax: +48 94 35 126 22
 troton@troton.com.pl
 www.troton.pl / www.troton.eu

1.4 Emergency telephone number: (8am-4pm)+48 094 35 123 94; 112

SECTION 2: HAZARDS IDENTIFICATION

2.1 Classification of the substance or mixture:

CLP Regulation (EC) No 1272/2008:

Classification of this product has been carried out in accordance with CLP Regulation (EC) No 1272/2008.

Aquatic Chronic 3: Hazardous to the aquatic environment, long-term hazard, Category 3, H412

Eye Irrit. 2: Eye irritation, Category 2, H319

Flam. Liq. 3: Flammable liquids, Category 3, H226

Skin Irrit. 2: Skin irritation, Category 2, H315

STOT RE 2: Specific target organ toxicity — Repeated exposure, Hazard Category 2 (Oral), H373

STOT SE 3: Specific toxicity causing drowsiness and dizziness, single exposure, Category 3, H336

2.2 Label elements:

CLP Regulation (EC) No 1272/2008:

Warning



Hazard statements:

Aquatic Chronic 3: H412 - Harmful to aquatic life with long lasting effects.

Eye Irrit. 2: H319 - Causes serious eye irritation.

Flam. Liq. 3: H226 - Flammable liquid and vapour.

Skin Irrit. 2: H315 - Causes skin irritation.

STOT RE 2: H373 - May cause damage to organs through prolonged or repeated exposure (Oral).

STOT SE 3: H336 - May cause drowsiness or dizziness.

Precautionary statements:

P210: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P280: Wear protective gloves/protective clothing/respiratory protection/eye protection/protective footwear.

P302+P352: IF ON SKIN: Wash with plenty of water.

P304+P340: IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P403+P233: Store in a well-ventilated place. Keep container tightly closed.

P501: Dispose of contents/container in accordance with regulations on hazardous waste or packaging and packaging waste respectively.

Substances that contribute to the classification

N-butyl acetate; Xylene; Solvent naphtha (petroleum), light arom., < 0.1 % EC 200-753-7

2.3 Other hazards:

BUMPER PAINT 1K NO STRUCTURE GLOSS

Printing: 20/12/2022

Date of compilation: 13/10/2020

Revised: 19/07/2022

Version: 2 (Replaced 1)

SECTION 2: HAZARDS IDENTIFICATION (continued)

Product fails to meet PBT/vPvB criteria
Endocrine-disrupting properties: The product fails to meet the criteria.

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

3.1 Substance:






Non-applicable

3.2 Mixture:

Chemical description: Mixture composed of chemical products

Components:

In accordance with Annex II of Regulation (EC) No 1907/2006 (point 3), the product contains:

Identification	Chemical name/Classification		Concentration
CAS: 123-86-4 EC: 204-658-1 Index: 607-025-00-1 REACH: 01-2119485493-29-XXXX	N-butyl acetate⁽¹⁾ ATP CLP00		25 - <50 %
	Regulation 1272/2008	Flam. Liq. 3: H226; STOT SE 3: H336; EUH066 - Warning 	
CAS: 1330-20-7 EC: 215-535-7 Index: 601-022-00-9 REACH: 01-2119488216-32-XXXX	Xylene⁽¹⁾ Self-classified		10 - <25 %
	Regulation 1272/2008	Acute Tox. 4: H312+H332; Aquatic Chronic 3: H412; Asp. Tox. 1: H304; Eye Irrit. 2: H319; Flam. Liq. 3: H226; Skin Irrit. 2: H315; STOT RE 2: H373; STOT SE 3: H335 - Danger 	
CAS: 100-41-4 EC: 202-849-4 Index: 601-023-00-4 REACH: 01-2119489370-35-XXXX	Ethylbenzene⁽¹⁾ ATP ATP06		2,5 - <5 %
	Regulation 1272/2008	Acute Tox. 4: H332; Asp. Tox. 1: H304; Flam. Liq. 2: H225; STOT RE 2: H373 - Danger 	
CAS: 64742-95-6 EC: 265-199-0 Index: 649-356-00-4 REACH: 01-2119486773-24-XXXX	Solvent naphtha (petroleum), light arom., < 0.1 % EC 200-753-7⁽¹⁾ ATP ATP01		2,5 - <5 %
	Regulation 1272/2008	Aquatic Chronic 2: H411; Asp. Tox. 1: H304; Flam. Liq. 3: H226; Skin Irrit. 2: H315; STOT SE 3: H336; EUH066 - Danger 	
CAS: 108-65-6 EC: 203-603-9 Index: 607-195-00-7 REACH: 01-2119475791-29-XXXX	2-methoxy-1-methylethyl acetate⁽²⁾ ATP ATP01		2,5 - <5 %
	Regulation 1272/2008	Flam. Liq. 3: H226 - Warning 	

⁽¹⁾ Substances presenting a health or environmental hazard which meet criteria laid down in Regulation (EU) No. 2020/878

⁽²⁾ Substance with a Union workplace exposure limit

To obtain more information on the hazards of the substances consult sections 11, 12 and 16.

SECTION 4: FIRST AID MEASURES

4.1 Description of first aid measures:

The symptoms resulting from intoxication can appear after exposure, therefore, in case of doubt, seek medical attention for direct exposure to the chemical product or persistent discomfort, showing the SDS of this product.

By inhalation:

Remove the person affected from the area of exposure, provide with fresh air and keep at rest. In serious cases such as cardiorespiratory failure, artificial resuscitation techniques will be necessary (mouth to mouth resuscitation, cardiac massage, oxygen supply, etc.) requiring immediate medical assistance.

By skin contact:

Remove contaminated clothing and footwear, rinse skin or shower the person affected if appropriate with plenty of cold water and neutral soap. In serious cases see a doctor. If the product causes burns or freezing, clothing should not be removed as this could worsen the injury caused if it is stuck to the skin. If blisters form on the skin, these should never be burst as this will increase the risk of infection.

By eye contact:

Rinse eyes thoroughly with water for at least 15 minutes. If the injured person uses contact lenses, these should be removed unless they are stuck to the eyes, in which case removal could cause further damage. In all cases, after cleaning, a doctor should be consulted as quickly as possible with the SDS for the product.

By ingestion/aspiration:

BUMPER PAINT 1K NO STRUCTURE GLOSS

Printing: 20/12/2022

Date of compilation: 13/10/2020

Revised: 19/07/2022

Version: 2 (Replaced 1)

SECTION 4: FIRST AID MEASURES (continued)

Do not induce vomiting, but if it does happen keep the head down to avoid aspiration. Keep the person affected at rest. Rinse out the mouth and throat, as they may have been affected during ingestion.

4.2 Most important symptoms and effects, both acute and delayed:

Acute and delayed effects are indicated in sections 2 and 11.

4.3 Indication of any immediate medical attention and special treatment needed:

Non-applicable

SECTION 5: FIREFIGHTING MEASURES

5.1 Extinguishing media:

Suitable extinguishing media:

If possible use polyvalent powder fire extinguishers (ABC powder), alternatively use foam or carbon dioxide extinguishers (CO₂).

Unsuitable extinguishing media:

IT IS RECOMMENDED NOT to use full jet water as an extinguishing agent.

5.2 Special hazards arising from the substance or mixture:

As a result of combustion or thermal decomposition reactive sub-products are created that can become highly toxic and, consequently, can present a serious health risk.

5.3 Advice for firefighters:

Depending on the magnitude of the fire it may be necessary to use full protective clothing and self-contained breathing apparatus (SCBA). Minimum emergency facilities and equipment should be available (fire blankets, portable first aid kit,...) in accordance with Directive 89/654/EC.

Additional provisions:

Act in accordance with the Internal Emergency Plan and the Information Sheets on actions to take after an accident or other emergencies. Eliminate all sources of ignition. In case of fire, cool the storage containers and tanks for products susceptible to combustion, explosion or BLEVE as a result of high temperatures. Avoid spillage of the products used to extinguish the fire into an aqueous medium.

SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1 Personal precautions, protective equipment and emergency procedures:

For non-emergency personnel:

Isolate leaks provided that there is no additional risk for the people performing this task. Evacuate the area and keep out those without protection. Personal protection equipment must be used against potential contact with the spilt product (See section 8). Above all prevent the formation of any vapour-air flammable mixtures, through either ventilation or the use of an inert medium. Remove any source of ignition. Eliminate electrostatic charges by interconnecting all the conductive surfaces on which static electricity could form, and also ensuring that all surfaces are connected to the ground.

For emergency responders:

Wear protective equipment. Keep unprotected persons away. See section 8.

6.2 Environmental precautions:

Avoid at all cost any type of spillage into an aqueous medium. Contain the product absorbed appropriately in hermetically sealed containers. Notify the relevant authority in case of exposure to the general public or the environment.

6.3 Methods and material for containment and cleaning up:

It is recommended:

Absorb the spillage using sand or inert absorbent and move it to a safe place. Do not absorb in sawdust or other combustible absorbents. For any concern related to disposal consult section 13.

6.4 Reference to other sections:

See sections 8 and 13.

SECTION 7: HANDLING AND STORAGE

7.1 Precautions for safe handling:

BUMPER PAINT 1K NO STRUCTURE GLOSS

Printing: 20/12/2022

Date of compilation: 13/10/2020

Revised: 19/07/2022

Version: 2 (Replaced 1)

SECTION 7: HANDLING AND STORAGE (continued)

A.- General precautions for safe use

Comply with the current legislation concerning the prevention of industrial risks. Keep containers hermetically sealed. Control spills and residues, destroying them with safe methods (section 6). Avoid leakages from the container. Maintain order and cleanliness where dangerous products are used.

B.- Technical recommendations for the prevention of fires and explosions

Transfer in well ventilated areas, preferably through localized extraction. Fully control sources of ignition (mobile phones, sparks,...) and ventilate during cleaning operations. Avoid the existence of dangerous atmospheres inside containers, applying inertization systems where possible. Transfer at a slow speed to avoid the creation of electrostatic charges. Against the possibility of electrostatic charges: ensure a perfect equipotential connection, always use groundings, do not wear work clothes made of acrylic fibres, preferably wearing cotton clothing and conductive footwear. Comply with the essential security requirements for equipment and systems defined in Directive 2014/34/EC (ATEX 100) and with the minimum requirements for protecting the security and health of workers under the selection criteria of Directive 1999/92/EC (ATEX 137). Consult section 10 for conditions and materials that should be avoided.

C.- Technical recommendations on general occupational hygiene

Do not eat or drink during the process, washing hands afterwards with suitable cleaning products.

D.- Technical recommendations to prevent environmental risks

Due to the danger of this product for the environment it is recommended to use it within an area containing contamination control barriers in case of spillage, as well as having absorbent material in close proximity.

7.2 Conditions for safe storage, including any incompatibilities:

A.- Technical measures for storage

- Minimum Temp.: 15 °C
- Maximum Temp.: 25 °C
- Maximum time: 12 Months

B.- General conditions for storage

Avoid sources of heat, radiation, static electricity and contact with food. For additional information see subsection 10.5

7.3 Specific end use(s):

Except for the instructions already specified it is not necessary to provide any special recommendation regarding the uses of this product.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1 Control parameters:

Substances whose occupational exposure limits have to be monitored in the workplace (European OEL, not country-specific legislation):

Directive (EU) 2000/39, Directive 2004/37/EC, Directive (EU) 2006/15, Directive (EU) 2009/161, Directive (EU) 2017/164, Directive (EU) 2019/1831:

Identification	Occupational exposure limits		
	IOELV (8h)	50 ppm	241 mg/m ³
N-butyl acetate CAS: 123-86-4 EC: 204-658-1	IOELV (STEL)	150 ppm	723 mg/m ³
	IOELV (8h)	50 ppm	221 mg/m ³
Xylene CAS: 1330-20-7 EC: 215-535-7	IOELV (STEL)	100 ppm	442 mg/m ³
	IOELV (8h)	100 ppm	442 mg/m ³
Ethylbenzene CAS: 100-41-4 EC: 202-849-4	IOELV (STEL)	200 ppm	884 mg/m ³
	IOELV (8h)	50 ppm	275 mg/m ³
2-methoxy-1-methylethyl acetate CAS: 108-65-6 EC: 203-603-9	IOELV (STEL)	100 ppm	550 mg/m ³

DNEL (Workers):

Identification		Short exposure		Long exposure	
		Systemic	Local	Systemic	Local
N-butyl acetate CAS: 123-86-4 EC: 204-658-1	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
	Dermal	11 mg/kg	Non-applicable	11 mg/kg	Non-applicable
	Inhalation	600 mg/m ³	600 mg/m ³	300 mg/m ³	300 mg/m ³

BUMPER PAINT 1K NO STRUCTURE GLOSS

Printing: 20/12/2022

Date of compilation: 13/10/2020

Revised: 19/07/2022

Version: 2 (Replaced 1)

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION (continued)

Identification		Short exposure		Long exposure	
		Systemic	Local	Systemic	Local
Xylene CAS: 1330-20-7 EC: 215-535-7	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
	Dermal	Non-applicable	Non-applicable	212 mg/kg	Non-applicable
	Inhalation	442 mg/m ³	442 mg/m ³	221 mg/m ³	221 mg/m ³
Ethylbenzene CAS: 100-41-4 EC: 202-849-4	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
	Dermal	Non-applicable	Non-applicable	180 mg/kg	Non-applicable
	Inhalation	Non-applicable	293 mg/m ³	77 mg/m ³	Non-applicable
Solvent naphtha (petroleum), light arom., < 0.1 % EC 200-753-7 CAS: 64742-95-6 EC: 265-199-0	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
	Dermal	Non-applicable	Non-applicable	Non-applicable	Non-applicable
	Inhalation	1286,4 mg/m ³	1066,67 mg/m ³	Non-applicable	837,5 mg/m ³
2-methoxy-1-methylethyl acetate CAS: 108-65-6 EC: 203-603-9	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
	Dermal	Non-applicable	Non-applicable	796 mg/kg	Non-applicable
	Inhalation	Non-applicable	550 mg/m ³	275 mg/m ³	Non-applicable

DNEL (General population):

Identification		Short exposure		Long exposure	
		Systemic	Local	Systemic	Local
N-butyl acetate CAS: 123-86-4 EC: 204-658-1	Oral	2 mg/kg	Non-applicable	2 mg/kg	Non-applicable
	Dermal	6 mg/kg	Non-applicable	6 mg/kg	Non-applicable
	Inhalation	300 mg/m ³	300 mg/m ³	35,7 mg/m ³	35,7 mg/m ³
Xylene CAS: 1330-20-7 EC: 215-535-7	Oral	Non-applicable	Non-applicable	12,5 mg/kg	Non-applicable
	Dermal	Non-applicable	Non-applicable	125 mg/kg	Non-applicable
	Inhalation	260 mg/m ³	260 mg/m ³	65,3 mg/m ³	65,3 mg/m ³
Ethylbenzene CAS: 100-41-4 EC: 202-849-4	Oral	Non-applicable	Non-applicable	1,6 mg/kg	Non-applicable
	Dermal	Non-applicable	Non-applicable	Non-applicable	Non-applicable
	Inhalation	Non-applicable	Non-applicable	15 mg/m ³	Non-applicable
Solvent naphtha (petroleum), light arom., < 0.1 % EC 200-753-7 CAS: 64742-95-6 EC: 265-199-0	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
	Dermal	Non-applicable	Non-applicable	Non-applicable	Non-applicable
	Inhalation	1152 mg/m ³	640 mg/m ³	Non-applicable	178,57 mg/m ³
2-methoxy-1-methylethyl acetate CAS: 108-65-6 EC: 203-603-9	Oral	Non-applicable	Non-applicable	36 mg/kg	Non-applicable
	Dermal	Non-applicable	Non-applicable	320 mg/kg	Non-applicable
	Inhalation	Non-applicable	Non-applicable	33 mg/m ³	33 mg/m ³

PNEC:

Identification				
N-butyl acetate CAS: 123-86-4 EC: 204-658-1	STP	35,6 mg/L	Fresh water	0,18 mg/L
	Soil	0,09 mg/kg	Marine water	0,018 mg/L
	Intermittent	0,36 mg/L	Sediment (Fresh water)	0,981 mg/kg
	Oral	Non-applicable	Sediment (Marine water)	0,098 mg/kg
Xylene CAS: 1330-20-7 EC: 215-535-7	STP	6,58 mg/L	Fresh water	0,327 mg/L
	Soil	2,31 mg/kg	Marine water	0,327 mg/L
	Intermittent	0,327 mg/L	Sediment (Fresh water)	12,46 mg/kg
	Oral	Non-applicable	Sediment (Marine water)	12,46 mg/kg
Ethylbenzene CAS: 100-41-4 EC: 202-849-4	STP	9,6 mg/L	Fresh water	0,1 mg/L
	Soil	2,68 mg/kg	Marine water	0,01 mg/L
	Intermittent	0,1 mg/L	Sediment (Fresh water)	13,7 mg/kg
	Oral	0,02 g/kg	Sediment (Marine water)	1,37 mg/kg
2-methoxy-1-methylethyl acetate CAS: 108-65-6 EC: 203-603-9	STP	100 mg/L	Fresh water	0,635 mg/L
	Soil	0,29 mg/kg	Marine water	0,064 mg/L
	Intermittent	6,35 mg/L	Sediment (Fresh water)	3,29 mg/kg
	Oral	Non-applicable	Sediment (Marine water)	0,329 mg/kg

8.2 Exposure controls:

- CONTINUED ON NEXT PAGE -

BUMPER PAINT 1K NO STRUCTURE GLOSS

Printing: 20/12/2022

Date of compilation: 13/10/2020

Revised: 19/07/2022



Version: 2 (Replaced 1)

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION (continued)



A.- Individual protection measures, such as personal protective equipment

As a preventative measure it is recommended to use basic Personal Protective Equipment, with the corresponding <<CE marking>> in accordance with Regulation (EU) 2016/425. For more information on Personal Protective Equipment (storage, use, cleaning, maintenance, class of protection,...) consult the information leaflet provided by the manufacturer. For more information see subsection 7.1. All information contained herein is a recommendation which needs some specification from the labour risk prevention services as it is not known whether the company has additional measures at its disposal.

B.- Respiratory protection



Pictogram	PPE	Labelling	CEN Standard	Remarks
 Mandatory respiratory tract protection	Filter mask for gases and vapours (Filter type: A)		EN 405:2002+A1:2010	Replace when there is a taste or smell of the contaminant inside the face mask. If the contaminant comes with warnings it is recommended to use isolation equipment.

C.- Specific protection for the hands





Pictogram	PPE	Labelling	CEN Standard	Remarks
 Mandatory hand protection	NON-disposable chemical protective gloves (Material: Nitrile, Breakthrough time: > 480 min, Thickness: 0.4 mm)		EN ISO 374-1:2016+A1:2018 EN 16523-1:2015+A1:2018 EN ISO 21420:2020	The Breakthrough Time indicated by the manufacturer must exceed the period during which the product is being used. Do not use protective creams after the product has come into contact with skin.

As the product is a mixture of several substances, the resistance of the glove material can not be calculated in advance with total reliability and has therefore to be checked prior to the application.



D.- Eye and face protection

Pictogram	PPE	Labelling	CEN Standard	Remarks
 Mandatory face protection	Panoramic glasses against splash/projections.		EN 166:2002 EN ISO 4007:2018	Clean daily and disinfect periodically according to the manufacturer's instructions. Use if there is a risk of splashing.

E.- Body protection

Pictogram	PPE	Labelling	CEN Standard	Remarks
 Mandatory complete body protection	Disposable clothing for protection against chemical risks, with antistatic and fireproof properties		EN 1149-1,2,3 EN 13034:2005+A1:2009 EN ISO 13982-1:2004/A1:2010 EN ISO 6529:2013 EN ISO 6530:2005 EN ISO 13688:2013 EN 464:1994	For professional use only. Clean periodically according to the manufacturer's instructions.
 Mandatory foot protection	Safety footwear for protection against chemical risk, with antistatic and heat resistant properties		EN ISO 13287:2020 EN ISO 20345:2011 EN 13832-1:2019	Replace boots at any sign of deterioration.

F.- Additional emergency measures

Emergency measure	Standards	Emergency measure	Standards
 Emergency shower	ANSI Z358-1 ISO 3864-1:2011, ISO 3864-4:2011	 Eyewash stations	DIN 12 899 ISO 3864-1:2011, ISO 3864-4:2011

Environmental exposure controls:

In accordance with the community legislation for the protection of the environment it is recommended to avoid environmental spillage of both the product and its container. For additional information see subsection 7.1.D

Volatile organic compounds:

With regard to Directive 2010/75/EU, this product has the following characteristics:

V.O.C. (Supply): 67,48 % weight

BUMPER PAINT 1K NO STRUCTURE GLOSS

Printing: 20/12/2022

Date of compilation: 13/10/2020

Revised: 19/07/2022

Version: 2 (Replaced 1)

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION (continued)

V.O.C. density at 20 °C:	709 kg/m ³ (709 g/L)
Average carbon number:	6,54
Average molecular weight:	114,77 g/mol

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1 Information on basic physical and chemical properties:

For complete information see the product datasheet.

Appearance:

Physical state at 20 °C:	Liquid
Appearance:	Viscous
Colour:	 Black
Odour:	Characteristic
Odour threshold:	Non-applicable *

Volatility:

Boiling point at atmospheric pressure:	128 °C
Vapour pressure at 20 °C:	1431 Pa
Vapour pressure at 50 °C:	7329,97 Pa (7,33 kPa)
Evaporation rate at 20 °C:	Non-applicable *

Product description:

Density at 20 °C:	941,5 kg/m ³
Relative density at 20 °C:	0,941
Dynamic viscosity at 20 °C:	Non-applicable *
Kinematic viscosity at 20 °C:	Non-applicable *
Kinematic viscosity at 40 °C:	>20,5 mm ² /s
Concentration:	Non-applicable *
pH:	Non-applicable *
Vapour density at 20 °C:	Non-applicable *
Partition coefficient n-octanol/water 20 °C:	Non-applicable *
Solubility in water at 20 °C:	Non-applicable *
Solubility properties:	Non-applicable *
Decomposition temperature:	Non-applicable *
Melting point/freezing point:	Non-applicable *

Flammability:

Flash Point:	29 °C
Flammability (solid, gas):	Non-applicable *
Autoignition temperature:	315 °C
Lower flammability limit:	Not available
Upper flammability limit:	Not available

Particle characteristics:

Median equivalent diameter:	Non-applicable
-----------------------------	----------------

9.2 Other information:

Information with regard to physical hazard classes:

Explosive properties:	Non-applicable *
-----------------------	------------------

*Not relevant due to the nature of the product, not providing information property of its hazards.

BUMPER PAINT 1K NO STRUCTURE GLOSS

Printing: 20/12/2022 Date of compilation: 13/10/2020 Revised: 19/07/2022 Version: 2 (Replaced 1)

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES (continued)

- Oxidising properties: Non-applicable *
- Corrosive to metals: Non-applicable *
- Heat of combustion: Non-applicable *
- Aerosols-total percentage (by mass) of flammable components: Non-applicable *
- Other safety characteristics:**
- Surface tension at 20 °C: Non-applicable *
- Refraction index: Non-applicable *

*Not relevant due to the nature of the product, not providing information property of its hazards.

SECTION 10: STABILITY AND REACTIVITY

10.1 Reactivity:

No hazardous reactions are expected because the product is stable under recommended storage conditions. See section 7.

10.2 Chemical stability:

Chemically stable under the indicated conditions of storage, handling and use.

10.3 Possibility of hazardous reactions:

Under the specified conditions, hazardous reactions that lead to excessive temperatures or pressure are not expected.

10.4 Conditions to avoid:

Applicable for handling and storage at room temperature:

Shock and friction	Contact with air	Increase in temperature	Sunlight	Humidity
Not applicable	Not applicable	Risk of combustion	Avoid direct impact	Not applicable

10.5 Incompatible materials:

Acids	Water	Oxidising materials	Combustible materials	Others
Avoid strong acids	Not applicable	Avoid direct impact	Not applicable	Avoid alkalis or strong bases

10.6 Hazardous decomposition products:

See subsection 10.3, 10.4 and 10.5 to find out the specific decomposition products. Depending on the decomposition conditions, complex mixtures of chemical substances can be released: carbon dioxide (CO₂), carbon monoxide and other organic compounds.

SECTION 11: TOXICOLOGICAL INFORMATION

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008:

The experimental information related to the toxicological properties of the product itself is not available

Dangerous health implications:

In case of exposure that is repetitive, prolonged or at concentrations higher than the recommended occupational exposure limits, adverse effects on health may result, depending on the means of exposure:

A- Ingestion (acute effect):

- Acute toxicity : Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for consumption. For more information see section 3
- Corrosivity/Irritability: The consumption of a considerable dose can cause irritation in the throat, abdominal pain, nausea and vomiting.

B- Inhalation (acute effect):

- Acute toxicity : Based on available data, the classification criteria are not met. However, it contains substances classified as hazardous for inhalation. For more information see section 3.
- Corrosivity/Irritability: Based on available data, the classification criteria are not met. However, it contains substances classified as hazardous for inhalation. For more information see section 3.

C- Contact with the skin and the eyes (acute effect):

- Contact with the skin: Produces skin inflammation.
- Contact with the eyes: Produces eye damage after contact.

BUMPER PAINT 1K NO STRUCTURE GLOSS

Printing: 20/12/2022

Date of compilation: 13/10/2020

Revised: 19/07/2022

Version: 2 (Replaced 1)

SECTION 11: TOXICOLOGICAL INFORMATION (continued)

D- CMR effects (carcinogenicity, mutagenicity and toxicity to reproduction):

- Carcinogenicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for the effects mentioned. For more information see section 3.
IARC: Xylene (3); Ethylbenzene (2B); Solvent naphtha (petroleum), light arom., < 0.1 % EC 200-753-7 (3)
- Mutagenicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.
- Reproductive toxicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.

E- Sensitizing effects:

- Respiratory: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous with sensitising effects. For more information see section 3.
- Skin: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.

F- Specific target organ toxicity (STOT) - single exposure:

Exposure in high concentration can interfere with the central nervous system causing headache, dizziness, vertigo, nausea, vomiting, confusion, and in serious cases, loss of consciousness.

G- Specific target organ toxicity (STOT)-repeated exposure:

- Specific target organ toxicity (STOT)-repeated exposure: Exposure in high concentration can interfere with the central nervous system causing headache, dizziness, vertigo, nausea, vomiting, confusion, and in serious cases, loss of consciousness.
- Skin: Based on available data, the classification criteria are not met. However, it does contain substances which are classified as dangerous due to repetitive exposure. For more information see section 3.

H- Aspiration hazard:

Based on available data, the classification criteria are not met. However, it does contain substances classified as hazardous for this effect. For more information see section 3.

Other information:

Non-applicable

Specific toxicology information on the substances:

Identification	Acute toxicity		Genus
N-butyl acetate CAS: 123-86-4 EC: 204-658-1	LD50 oral	12789 mg/kg	Rat
	LD50 dermal	14112 mg/kg	Rabbit
	LC50 inhalation	23,4 mg/L (4 h)	Rat
Xylene CAS: 1330-20-7 EC: 215-535-7	LD50 oral	2100 mg/kg	Rat
	LD50 dermal	1100 mg/kg	Rat
	LC50 inhalation	11 mg/L (ATEI)	
Ethylbenzene CAS: 100-41-4 EC: 202-849-4	LD50 oral	3500 mg/kg	Rat
	LD50 dermal	15354 mg/kg	Rabbit
	LC50 inhalation	17,2 mg/L (4 h)	Rat
Solvent naphtha (petroleum), light arom., < 0.1 % EC 200-753-7 CAS: 64742-95-6 EC: 265-199-0	LD50 oral	2100 mg/kg	Rat
	LD50 dermal	2000 mg/kg	Rabbit
	LC50 inhalation	> 20 mg/L	
2-methoxy-1-methylethyl acetate CAS: 108-65-6 EC: 203-603-9	LD50 oral	8532 mg/kg	Rat
	LD50 dermal	5100 mg/kg	Rat
	LC50 inhalation	30 mg/L (4 h)	Rat

Acute Toxicity Estimate (ATE mix):

ATE mix		Ingredient(s) of unknown toxicity
Oral	>2000 mg/kg (Calculation method)	Non-applicable
Dermal	8404,66 mg/kg (Calculation method)	0 %
Inhalation	81,15 mg/L (4 h) (Calculation method)	0 %

11.2 Information on other hazards:

Endocrine disrupting properties

Endocrine-disrupting properties: The product fails to meet the criteria.

BUMPER PAINT 1K NO STRUCTURE GLOSS

Printing: 20/12/2022

Date of compilation: 13/10/2020

Revised: 19/07/2022

Version: 2 (Replaced 1)

SECTION 11: TOXICOLOGICAL INFORMATION (continued)

Other information

Non-applicable

SECTION 12: ECOLOGICAL INFORMATION

The experimental information related to the eco-toxicological properties of the product itself is not available

12.1 Toxicity:

Acute toxicity:

Identification	Concentration	Species	Genus
N-butyl acetate CAS: 123-86-4 EC: 204-658-1	LC50	Non-applicable	
	EC50	Non-applicable	
	EC50	675 mg/L (72 h)	Scenedesmus subspicatus Algae
Xylene CAS: 1330-20-7 EC: 215-535-7	LC50	>10 - 100 mg/L (96 h)	Fish
	EC50	>10 - 100 mg/L (48 h)	Crustacean
	EC50	>10 - 100 mg/L (72 h)	Algae
Ethylbenzene CAS: 100-41-4 EC: 202-849-4	LC50	42,3 mg/L (96 h)	Pimephales promelas Fish
	EC50	75 mg/L (48 h)	Daphnia magna Crustacean
	EC50	63 mg/L (3 h)	Chlorella vulgaris Algae
Solvent naphtha (petroleum), light arom., < 0.1 % EC 200-753-7 CAS: 64742-95-6 EC: 265-199-0	LC50	>1 - 10 mg/L (96 h)	Fish
	EC50	>1 - 10 mg/L (48 h)	Crustacean
	EC50	>1 - 10 mg/L (72 h)	Algae
2-methoxy-1-methylethyl acetate CAS: 108-65-6 EC: 203-603-9	LC50	161 mg/L (96 h)	Pimephales promelas Fish
	EC50	481 mg/L (48 h)	Daphnia sp. Crustacean
	EC50	Non-applicable	

Chronic toxicity:

Identification	Concentration	Species	Genus
N-butyl acetate CAS: 123-86-4 EC: 204-658-1	NOEC	Non-applicable	
	NOEC	23,2 mg/L	Daphnia magna Crustacean
Xylene CAS: 1330-20-7 EC: 215-535-7	NOEC	1,3 mg/L	Oncorhynchus mykiss Fish
	NOEC	1,17 mg/L	Ceriodaphnia dubia Crustacean
Ethylbenzene CAS: 100-41-4 EC: 202-849-4	NOEC	Non-applicable	
	NOEC	0,96 mg/L	Ceriodaphnia dubia Crustacean
2-methoxy-1-methylethyl acetate CAS: 108-65-6 EC: 203-603-9	NOEC	47,5 mg/L	Oryzias latipes Fish
	NOEC	100 mg/L	Daphnia magna Crustacean

12.2 Persistence and degradability:

Substance-specific information:

Identification	Degradability	Biodegradability
N-butyl acetate CAS: 123-86-4 EC: 204-658-1	BOD5	Non-applicable Concentration
	COD	Non-applicable Period
	BOD5/COD	Non-applicable % Biodegradable
Xylene CAS: 1330-20-7 EC: 215-535-7	BOD5	Non-applicable Concentration
	COD	Non-applicable Period
	BOD5/COD	Non-applicable % Biodegradable
Ethylbenzene CAS: 100-41-4 EC: 202-849-4	BOD5	Non-applicable Concentration
	COD	Non-applicable Period
	BOD5/COD	Non-applicable % Biodegradable
Solvent naphtha (petroleum), light arom., < 0.1 % EC 200-753-7 CAS: 64742-95-6 EC: 265-199-0	BOD5	0,19 g O2/g Concentration
	COD	0,44 g O2/g Period
	BOD5/COD	0,43 % Biodegradable

BUMPER PAINT 1K NO STRUCTURE GLOSS

Printing: 20/12/2022

Date of compilation: 13/10/2020

Revised: 19/07/2022

Version: 2 (Replaced 1)

SECTION 12: ECOLOGICAL INFORMATION (continued)

Identification	Degradability		Biodegradability	
	2-methoxy-1-methylethyl acetate CAS: 108-65-6 EC: 203-603-9	BOD5	Non-applicable	Concentration
	COD	Non-applicable	Period	8 days
	BOD5/COD	Non-applicable	% Biodegradable	100 %

12.3 Bioaccumulative potential:

Substance-specific information:

Identification	Bioaccumulation potential	
	N-butyl acetate CAS: 123-86-4 EC: 204-658-1	BCF
	Pow Log	1.78
	Potential	Low
Xylene CAS: 1330-20-7 EC: 215-535-7	BCF	9
	Pow Log	2.77
	Potential	Low
Ethylbenzene CAS: 100-41-4 EC: 202-849-4	BCF	1
	Pow Log	3.15
	Potential	Low
Solvent naphtha (petroleum), light arom., < 0.1 % EC 200-753-7 CAS: 64742-95-6 EC: 265-199-0	BCF	
	Pow Log	4
	Potential	
2-methoxy-1-methylethyl acetate CAS: 108-65-6 EC: 203-603-9	BCF	1
	Pow Log	0.43
	Potential	Low

12.4 Mobility in soil:

Identification	Absorption/desorption		Volatility	
	N-butyl acetate CAS: 123-86-4 EC: 204-658-1	Koc	Non-applicable	Henry
	Conclusion	Non-applicable	Dry soil	Non-applicable
	Surface tension	2,478E-2 N/m (25 °C)	Moist soil	Non-applicable
Xylene CAS: 1330-20-7 EC: 215-535-7	Koc	202	Henry	524,86 Pa·m ³ /mol
	Conclusion	Moderate	Dry soil	Yes
	Surface tension	Non-applicable	Moist soil	Yes
Ethylbenzene CAS: 100-41-4 EC: 202-849-4	Koc	520	Henry	798,44 Pa·m ³ /mol
	Conclusion	Moderate	Dry soil	Yes
	Surface tension	2,859E-2 N/m (25 °C)	Moist soil	Yes

12.5 Results of PBT and vPvB assessment:

Product fails to meet PBT/vPvB criteria

12.6 Endocrine disrupting properties:

Endocrine-disrupting properties: The product fails to meet the criteria.

12.7 Other adverse effects:

Not described

SECTION 13: DISPOSAL CONSIDERATIONS

13.1 Waste treatment methods:

Code	Description	Waste class (Regulation (EU) No 1357/2014)
08 01 11* 15 01 10*	waste paint and varnish containing organic solvents or other hazardous substances packaging containing residues of or contaminated by hazardous substances	Dangerous

Type of waste (Regulation (EU) No 1357/2014):

HP14 Ecotoxic, HP3 Flammable, HP5 Specific Target Organ Toxicity (STOT)/Aspiration Toxicity, HP4 Irritant — skin irritation and eye damage

Waste management (disposal and evaluation):

BUMPER PAINT 1K NO STRUCTURE GLOSS

Printing: 20/12/2022

Date of compilation: 13/10/2020

Revised: 19/07/2022

Version: 2 (Replaced 1)

SECTION 13: DISPOSAL CONSIDERATIONS (continued)

Consult the authorized waste service manager on the assessment and disposal operations in accordance with Annex 1 and Annex 2 (Directive 2008/98/EC). As under 15 01 (2014/955/EC) of the code and in case the container has been in direct contact with the product, it will be processed the same way as the actual product. Otherwise, it will be processed as non-dangerous residue. Waste should not be disposed of to drains. See paragraph 6.2.

Regulations related to waste management:

In accordance with Annex II of Regulation (EC) No 1907/2006 (REACH) the community or state provisions related to waste management are stated

Community legislation: Directive 2008/98/EC, 2014/955/EU, Regulation (EU) No 1357/2014

SECTION 14: TRANSPORT INFORMATION

Transport of dangerous goods by land:

With regard to ADR 2021 and RID 2021:



- 14.1 UN number or ID number:** UN1993
- 14.2 UN proper shipping name:** FLAMMABLE LIQUID, N.O.S. (N-butyl acetate)
- 14.3 Transport hazard class(es):** 3
Labels: 3
- 14.4 Packing group:** III
- 14.5 Environmental hazards:** No
- 14.6 Special precautions for user**
Special regulations: 274, 601
Tunnel restriction code: D/E
Physico-Chemical properties: see section 9
Limited quantities: 5 L
- 14.7 Maritime transport in bulk according to IMO instruments:** Non-applicable

Transport of dangerous goods by sea:

With regard to IMDG 40-20:



- 14.1 UN number or ID number:** UN1993
- 14.2 UN proper shipping name:** FLAMMABLE LIQUID, N.O.S. (N-butyl acetate)
- 14.3 Transport hazard class(es):** 3
Labels: 3
- 14.4 Packing group:** III
- 14.5 Marine pollutant:** No
- 14.6 Special precautions for user**
Special regulations: 274, 223, 955
EmS Codes: F-E, S-E
Physico-Chemical properties: see section 9
Limited quantities: 5 L
Segregation group: Non-applicable
- 14.7 Maritime transport in bulk according to IMO instruments:** Non-applicable

Transport of dangerous goods by air:

With regard to IATA/ICAO 2022:

BUMPER PAINT 1K NO STRUCTURE GLOSS

Printing: 20/12/2022

Date of compilation: 13/10/2020

Revised: 19/07/2022

Version: 2 (Replaced 1)

SECTION 14: TRANSPORT INFORMATION (continued)



- 14.1 UN number or ID number:** UN1993
- 14.2 UN proper shipping name:** FLAMMABLE LIQUID, N.O.S. (N-butyl acetate)
- 14.3 Transport hazard class(es):** 3
Labels: 3
- 14.4 Packing group:** III
- 14.5 Environmental hazards:** No
- 14.6 Special precautions for user**
Physico-Chemical properties: see section 9
- 14.7 Maritime transport in bulk according to IMO instruments:** Non-applicable

SECTION 15: REGULATORY INFORMATION

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture:

Candidate substances for authorisation under the Regulation (EC) No 1907/2006 (REACH): Non-applicable
 Substances included in Annex XIV of REACH ("Authorisation List") and sunset date: Non-applicable
 Regulation (EC) No 1005/2009, about substances that deplete the ozone layer: Non-applicable
 Article 95, REGULATION (EU) No 528/2012: Non-applicable
 REGULATION (EU) No 649/2012, in relation to the import and export of hazardous chemical products: Non-applicable

Seveso III:

Section	Description	Lower-tier requirements	Upper-tier requirements
P5c	FLAMMABLE LIQUIDS	5000	50000

Limitations to commercialisation and the use of certain dangerous substances and mixtures (Annex XVII REACH, etc):

Shall not be used in:
 —ornamental articles intended to produce light or colour effects by means of different phases, for example in ornamental lamps and ashtrays,
 —tricks and jokes,
 —games for one or more participants, or any article intended to be used as such, even with ornamental aspects.

Specific provisions in terms of protecting people or the environment:

It is recommended to use the information included in this safety data sheet as a basis for conducting workplace-specific risk assessments in order to establish the necessary risk prevention measures for the handling, use, storage and disposal of this product.

Other legislation:

The product could be affected by sectorial legislation

15.2 Chemical safety assessment:

The supplier has not carried out evaluation of chemical safety.

SECTION 16: OTHER INFORMATION

Legislation related to safety data sheets:

The SDS shall be supplied in an official language of the country where the product is placed on the market. This safety data sheet has been designed in accordance with ANNEX II-Guide to the compilation of safety data sheets of Regulation (EC) No 1907/2006 (COMMISSION REGULATION (EU) 2020/878).

Modifications related to the previous Safety Data Sheet which concerns the ways of managing risks.:

COMMISSION REGULATION (EU) 2020/878

Texts of the legislative phrases mentioned in section 2:

BUMPER PAINT 1K NO STRUCTURE GLOSS

Printing: 20/12/2022

Date of compilation: 13/10/2020

Revised: 19/07/2022

Version: 2 (Replaced 1)

SECTION 16: OTHER INFORMATION (continued)

H336: May cause drowsiness or dizziness.

H315: Causes skin irritation.

H412: Harmful to aquatic life with long lasting effects.

H373: May cause damage to organs through prolonged or repeated exposure (Oral).

H226: Flammable liquid and vapour.

H319: Causes serious eye irritation.

Texts of the legislative phrases mentioned in section 3:

The phrases indicated do not refer to the product itself; they are present merely for informative purposes and refer to the individual components which appear in section 3

CLP Regulation (EC) No 1272/2008:

Acute Tox. 4: H312+H332 - Harmful in contact with skin or if inhaled.

Acute Tox. 4: H332 - Harmful if inhaled.

Aquatic Chronic 2: H411 - Toxic to aquatic life with long lasting effects.

Aquatic Chronic 3: H412 - Harmful to aquatic life with long lasting effects.

Asp. Tox. 1: H304 - May be fatal if swallowed and enters airways.

Eye Irrit. 2: H319 - Causes serious eye irritation.

Flam. Liq. 2: H225 - Highly flammable liquid and vapour.

Flam. Liq. 3: H226 - Flammable liquid and vapour.

Skin Irrit. 2: H315 - Causes skin irritation.

STOT RE 2: H373 - May cause damage to organs through prolonged or repeated exposure (Oral).

STOT RE 2: H373 - May cause damage to organs through prolonged or repeated exposure.

STOT SE 3: H335 - May cause respiratory irritation.

STOT SE 3: H336 - May cause drowsiness or dizziness.

Classification procedure:

STOT SE 3: Calculation method

Skin Irrit. 2: Calculation method

Aquatic Chronic 3: Calculation method

STOT RE 2: Calculation method

Flam. Liq. 3: Calculation method (2.6.4.3)

Eye Irrit. 2: Calculation method

Advice related to training:

Training is recommended in order to prevent industrial risks for staff using this product and to facilitate their comprehension and interpretation of this safety data sheet, as well as the label on the product.

Principal bibliographical sources:<http://echa.europa.eu><http://eur-lex.europa.eu>**Abbreviations and acronyms:**

ADR: European agreement concerning the international carriage of dangerous goods by road

IMDG: International maritime dangerous goods code

IATA: International Air Transport Association

ICAO: International Civil Aviation Organisation

COD: Chemical Oxygen Demand

BOD5: 5day biochemical oxygen demand

BCF: Bioconcentration factor

LD50: Lethal Dose 50

LC50: Lethal Concentration 50

EC50: Effective concentration 50

LogPOW: Octanolwater partition coefficient

Koc: Partition coefficient of organic carbon

UFI: unique formula identifier

IARC: International Agency for Research on Cancer

The information contained in this safety data sheet is based on sources, technical knowledge and current legislation at European and state level, without being able to guarantee its accuracy. This information cannot be considered a guarantee of the properties of the product, it is simply a description of the security requirements. The occupational methodology and conditions for users of this product are not within our awareness or control, and it is ultimately the responsibility of the user to take the necessary measures to obtain the legal requirements concerning the manipulation, storage, use and disposal of chemical products. The information on this safety data sheet only refers to this product, which should not be used for needs other than those specified.

- END OF SAFETY DATA SHEET -