

CETOX-300E

Printing: 05/01/2023

Date of compilation: 21/06/2006





Revised: 30/11/2022

Version: 5 (Replaced 4)

SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

- 1.1 Product identifier:** CETOX-300E
- Other means of identification:**
Mixture of cyclohexanone peroxide and n-buthyl acetate
- UFI:** 8Q00-00C6-N00H-4MGJ
- 1.2 Relevant identified uses of the substance or mixture and uses advised against:**
Relevant uses: Hardener for coatings. For professional users only.
Polymerization initiator.
Uses advised against: All uses not specified in this section or in section 7.3
- 1.3 Details of the supplier of the safety data sheet:**
Oxytop Sp. z o.o.
Antoninek 2
62-060 Stęszew - Polska
Phone: +48 61 898 53 00, +48 61 898 53 01
dokumentacja@oxytop.pl
- 1.4 Emergency telephone number:** 112 (emergency telephone number)

SECTION 2: HAZARDS IDENTIFICATION

- 2.1 Classification of the substance or mixture:**
CLP Regulation (EC) No 1272/2008:
Classification of this product has been carried out in accordance with CLP Regulation (EC) No 1272/2008.
Flam. Liq. 3: Flammable liquids, Category 3, H226
Org. Perox. D: Organic peroxides, Category D, H242
Repr. 2: Reproductive toxicity, Category 2, H361
Skin Corr. 1B: Skin corrosion, Category 1B, H314
STOT SE 3: Respiratory tract toxicity, single exposure, Category 3, H335
STOT SE 3: Specific toxicity causing drowsiness and dizziness, single exposure, Category 3, H336
- 2.2 Label elements:**
CLP Regulation (EC) No 1272/2008:
Danger
- 



- Hazard statements:**
Flam. Liq. 3: H226 - Flammable liquid and vapour.
Org. Perox. D: H242 - Heating may cause a fire.
Repr. 2: H361 - Suspected of damaging fertility or the unborn child.
Skin Corr. 1B: H314 - Causes severe skin burns and eye damage.
STOT SE 3: H335 - May cause respiratory irritation.
STOT SE 3: H336 - May cause drowsiness or dizziness.
- Precautionary statements:**
P102: Keep out of reach of children.
P210: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P280: Wear protective gloves/protective clothing/respiratory protection/eye protection/protective footwear.
P303+P361+P353: IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower.
P304+P340: IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
- 2.3 Other hazards:**
Product fails to meet PBT/vPvB criteria
Endocrine-disrupting properties: The product fails to meet the criteria.

CETOX-300E

Printing: 05/01/2023

Date of compilation: 21/06/2006

Revised: 30/11/2022

Version: 5 (Replaced 4)

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

3.1 Substance:

Non-applicable

3.2 Mixture:

Chemical description: Organic peroxide/s

Components:

In accordance with Annex II of Regulation (EC) No 1907/2006 (point 3), the product contains:

Identification	Chemical name/Classification	Concentration
CAS: 123-86-4 EC: 204-658-1 Index: 607-025-00-1 REACH: 01-2119485493-29-XXXX	N-butyl acetate⁽¹⁾ ATP CLP00 Regulation 1272/2008 Flam. Liq. 3: H226; STOT SE 3: H336; EUH066 - Warning	35 - <45 %
CAS: 123-42-2 EC: 204-626-7 Index: 603-016-00-1 REACH: 01-2119473975-21-XXXX	4-hydroxy-4-methylpentan-2-one⁽¹⁾ Self-classified Regulation 1272/2008 Eye Irrit. 2: H319; Flam. Liq. 3: H226; Repr. 2: H361; STOT SE 3: H335 - Warning	18 - <23 %
CAS: 131-11-3 EC: 205-011-6 Index: Non-applicable REACH: 01-2119437229-36-XXXX	Dimethyl Phthalate⁽²⁾ Not classified Regulation 1272/2008	15 - <20 %
CAS: 12262-58-7 EC: 235-527-7 Index: 617-010-01-9 REACH: 01-2120762253-58-XXXX	Cyclohexanone, peroxide⁽¹⁾ Self-classified Regulation 1272/2008 Acute Tox. 4: H302; Org. Perox. D: H242; Skin Corr. 1B: H314 - Danger	10 - <15 %

⁽¹⁾ Substances presenting a health or environmental hazard which meet criteria laid down in Regulation (EU) No. 2020/878

⁽²⁾ Voluntarily-listed substance failing to meet any of the criteria set out in Regulation (EU) No. 2020/878

To obtain more information on the hazards of the substances consult sections 11, 12 and 16.

Other information:

Identification	Specific concentration limit
4-hydroxy-4-methylpentan-2-one CAS: 123-42-2 EC: 204-626-7	% (w/w) >=10: Eye Irrit. 2 - H319

SECTION 4: FIRST AID MEASURES

4.1 Description of first aid measures:

Request medical assistance immediately, showing the SDS of this product.

By inhalation:

Remove the person affected from the area of exposure, provide with fresh air and keep at rest. In serious cases such as cardiorespiratory failure, artificial resuscitation techniques will be necessary (mouth to mouth resuscitation, cardiac massage, oxygen supply, etc.) requiring immediate medical assistance.

By skin contact:

Remove contaminated clothing and footwear, rinse skin or shower the person affected if appropriate with plenty of cold water and neutral soap. In serious cases see a doctor. If the product causes burns or freezing, clothing should not be removed as this could worsen the injury caused if it is stuck to the skin. If blisters form on the skin, these should never be burst as this will increase the risk of infection.

By eye contact:

Rinse eyes thoroughly with water for at least 15 minutes. If the injured person uses contact lenses, these should be removed unless they are stuck to the eyes, in which case removal could cause further damage. In all cases, after cleaning, a doctor should be consulted as quickly as possible with the SDS for the product.

By ingestion/aspiration:

Request immediate medical assistance, showing the SDS of this product. Do not induce vomiting, because its expulsion from the stomach can be hazardous to the mucus of the main digestive tract, and also risk damage to the respiratory system through inhalation. Rinse out the mouth and throat, as they may have been affected during ingestion. In the case of loss of consciousness do not administer anything orally unless supervised by a doctor. Keep the person affected at rest.

CETOX-300E

Printing: 05/01/2023

Date of compilation: 21/06/2006

Revised: 30/11/2022

Version: 5 (Replaced 4)

SECTION 4: FIRST AID MEASURES (continued)

4.2 Most important symptoms and effects, both acute and delayed:

Acute and delayed effects are indicated in sections 2 and 11.

4.3 Indication of any immediate medical attention and special treatment needed:

Non-applicable

SECTION 5: FIREFIGHTING MEASURES

5.1 Extinguishing media:

Suitable extinguishing media:

If possible use polyvalent powder fire extinguishers (ABC powder), alternatively use foam or carbon dioxide extinguishers (CO₂).

Unsuitable extinguishing media:

IT IS RECOMMENDED NOT to use full jet water as an extinguishing agent.

5.2 Special hazards arising from the substance or mixture:

As a result of combustion or thermal decomposition reactive sub-products are created that can become highly toxic and, consequently, can present a serious health risk.

5.3 Advice for firefighters:

Depending on the magnitude of the fire it may be necessary to use full protective clothing and self-contained breathing apparatus (SCBA). Minimum emergency facilities and equipment should be available (fire blankets, portable first aid kit,...) in accordance with Directive 89/654/EC.

Additional provisions:

Act in accordance with the Internal Emergency Plan and the Information Sheets on actions to take after an accident or other emergencies. Eliminate all sources of ignition. In case of fire, cool the storage containers and tanks for products susceptible to combustion, explosion or BLEVE as a result of high temperatures. Avoid spillage of the products used to extinguish the fire into an aqueous medium.

SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1 Personal precautions, protective equipment and emergency procedures:

For non-emergency personnel:

HEATING MAY CAUSE A FIRE. Isolate leaks provided that there is no additional risk for the people performing this task. Evacuate the area and keep out those without protection. Personal protection equipment must be used against potential contact with the spilt product (See section 8). Above all prevent the formation of any vapour-air flammable mixtures, through either ventilation or the use of an inert medium. Destroy any source of ignition. Eliminate electrostatic charges by interconnecting all the conductive surfaces on which static electricity could form, and also ensuring that all surfaces are connected to the ground.

For emergency responders:

Wear protective equipment. Keep unprotected persons away. See section 8.

6.2 Environmental precautions:

This product is not classified as hazardous to the environment. Keep product away from drains, surface and underground water.

6.3 Methods and material for containment and cleaning up:

It is recommended:

Absorb the spillage using sand or inert absorbent and move it to a safe place. Do not absorb in sawdust or other combustible absorbents. For any concern related to disposal consult section 13.

6.4 Reference to other sections:

See sections 8 and 13.

SECTION 7: HANDLING AND STORAGE

7.1 Precautions for safe handling:

A.- General precautions for safe use

CETOX-300E

Printing: 05/01/2023

Date of compilation: 21/06/2006

Revised: 30/11/2022

Version: 5 (Replaced 4)

SECTION 7: HANDLING AND STORAGE (continued)

Comply with the current legislation concerning the prevention of industrial risks. Keep containers hermetically sealed. Control spills and residues, destroying them with safe methods (section 6). Avoid leakages from the container. Maintain order and cleanliness where dangerous products are used.

B.- Technical recommendations for the prevention of fires and explosions

AVOID ANY KIND OF HEATING. Devices and systems must comply with the essential safety and health requirements and, with the minimum requirements for improving the health and safety protection of workers. Consult section 10 for conditions and materials that should be avoided. KEEP ONLY IN ORIGINAL CONTAINER.

C.- Technical recommendations on general occupational hygiene

PREGNANT WOMEN SHOULD NOT BE EXPOSED TO THIS PRODUCT. Transfer in designated areas that comply with the necessary safety conditions (emergency showers and eyewash stations in close proximity), using personal protection equipment, especially on the hands and face (See section 8). Limit manual transfers to small amounts only. Do not eat or drink during the process, washing hands afterwards with suitable cleaning products.

D.- Technical recommendations to prevent environmental risks

It is recommended to have absorbent material available at close proximity to the product (See subsection 6.3)

7.2 Conditions for safe storage, including any incompatibilities:
A.- Technical measures for storage

Maximum Temp.: 25 °C

B.- General conditions for storage

Avoid sources of heat, radiation, static electricity and contact with food. For additional information see subsection 10.5

7.3 Specific end use(s):

Except for the instructions already specified it is not necessary to provide any special recommendation regarding the uses of this product.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION
8.1 Control parameters:

Substances whose occupational exposure limits have to be monitored in the workplace (European OEL, not country-specific legislation):

Directive (EU) 2000/39, Directive 2004/37/EC, Directive (EU) 2006/15, Directive (EU) 2009/161, Directive (EU) 2017/164, Directive (EU) 2019/1831:

Identification	Occupational exposure limits		
N-butyl acetate	IOELV (8h)	50 ppm	241 mg/m ³
CAS: 123-86-4 EC: 204-658-1	IOELV (STEL)	150 ppm	723 mg/m ³

DNEL (Workers):

Identification		Short exposure		Long exposure	
		Systemic	Local	Systemic	Local
N-butyl acetate CAS: 123-86-4 EC: 204-658-1	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
	Dermal	11 mg/kg	Non-applicable	11 mg/kg	Non-applicable
	Inhalation	600 mg/m ³	600 mg/m ³	300 mg/m ³	300 mg/m ³
4-hydroxy-4-methylpentan-2-one CAS: 123-42-2 EC: 204-626-7	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
	Dermal	Non-applicable	Non-applicable	467 mg/kg	Non-applicable
	Inhalation	Non-applicable	240 mg/m ³	32,6 mg/m ³	Non-applicable
Dimethyl Phthalate CAS: 131-11-3 EC: 205-011-6	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
	Dermal	Non-applicable	Non-applicable	135 mg/kg	Non-applicable
	Inhalation	Non-applicable	Non-applicable	66,1 mg/m ³	Non-applicable
Cyclohexanone, peroxide CAS: 12262-58-7 EC: 235-527-7	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
	Dermal	Non-applicable	Non-applicable	1 mg/kg	Non-applicable
	Inhalation	Non-applicable	Non-applicable	3,53 mg/m ³	Non-applicable

DNEL (General population):

Safety data sheet

This SDS is an English translation of COMMISSION REGULATION (EU) 2020/878, without any country-specific legislation

CETOX-300E

Printing: 05/01/2023

Date of compilation: 21/06/2006

Revised: 30/11/2022

Version: 5 (Replaced 4)

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION (continued)

Identification		Short exposure		Long exposure	
		Systemic	Local	Systemic	Local
N-butyl acetate CAS: 123-86-4 EC: 204-658-1	Oral	2 mg/kg	Non-applicable	2 mg/kg	Non-applicable
	Dermal	6 mg/kg	Non-applicable	6 mg/kg	Non-applicable
	Inhalation	300 mg/m ³	300 mg/m ³	35,7 mg/m ³	35,7 mg/m ³
4-hydroxy-4-methylpentan-2-one CAS: 123-42-2 EC: 204-626-7	Oral	Non-applicable	Non-applicable	1,67 mg/kg	Non-applicable
	Dermal	Non-applicable	Non-applicable	33 mg/kg	Non-applicable
	Inhalation	Non-applicable	Non-applicable	5,8 mg/m ³	Non-applicable
Dimethyl Phthalate CAS: 131-11-3 EC: 205-011-6	Oral	Non-applicable	Non-applicable	9,4 mg/kg	Non-applicable
	Dermal	Non-applicable	Non-applicable	67,5 mg/kg	Non-applicable
	Inhalation	Non-applicable	Non-applicable	16,3 mg/m ³	Non-applicable
Cyclohexanone, peroxide CAS: 12262-58-7 EC: 235-527-7	Oral	Non-applicable	Non-applicable	0,5 mg/kg	Non-applicable
	Dermal	Non-applicable	Non-applicable	0,5 mg/kg	Non-applicable
	Inhalation	Non-applicable	Non-applicable	0,87 mg/m ³	Non-applicable

PNEC:



Identification					
N-butyl acetate CAS: 123-86-4 EC: 204-658-1	STP	35,6 mg/L	Fresh water	0,18 mg/L	
	Soil	0,09 mg/kg	Marine water	0,018 mg/L	
	Intermittent	0,36 mg/L	Sediment (Fresh water)	0,981 mg/kg	
	Oral	Non-applicable	Sediment (Marine water)	0,098 mg/kg	
4-hydroxy-4-methylpentan-2-one CAS: 123-42-2 EC: 204-626-7	STP	100 mg/L	Fresh water	2 mg/L	
	Soil	0,3 mg/kg	Marine water	0,2 mg/L	
	Intermittent	1 mg/L	Sediment (Fresh water)	7,4 mg/kg	
	Oral	Non-applicable	Sediment (Marine water)	0,74 mg/kg	
Dimethyl Phthalate CAS: 131-11-3 EC: 205-011-6	STP	4 mg/L	Fresh water	0,192 mg/L	
	Soil	3,16 mg/kg	Marine water	0,019 mg/L	
	Intermittent	0,39 mg/L	Sediment (Fresh water)	1,3 mg/kg	
	Oral	Non-applicable	Sediment (Marine water)	0,13 mg/kg	
Cyclohexanone, peroxide CAS: 12262-58-7 EC: 235-527-7	STP	0,05 mg/L	Fresh water	0,011 mg/L	
	Soil	0,011 mg/kg	Marine water	0,00106 mg/L	
	Intermittent	0,017 mg/L	Sediment (Fresh water)	0,085 mg/kg	
	Oral	Non-applicable	Sediment (Marine water)	0,009 mg/kg	

8.2 Exposure controls:



A.- Individual protection measures, such as personal protective equipment

As a preventative measure it is recommended to use basic Personal Protective Equipment, with the corresponding <<CE marking>> in accordance with Regulation (EU) 2016/425. For more information on Personal Protective Equipment (storage, use, cleaning, maintenance, class of protection,...) consult the information leaflet provided by the manufacturer. For more information see subsection 7.1. All information contained herein is a recommendation which needs some specification from the labour risk prevention services as it is not known whether the company has additional measures at its disposal.

B.- Respiratory protection

Pictogram	PPE	Labelling	CEN Standard	Remarks
 Mandatory respiratory tract protection	Filter mask for gases and vapours (Filter type: A)	 CAT III	EN 405:2002+A1:2010	Replace when there is a taste or smell of the contaminant inside the face mask. If the contaminant comes with warnings it is recommended to use isolation equipment.

C.- Specific protection for the hands

Pictogram	PPE	Labelling	CEN Standard	Remarks
 Mandatory hand protection	Non-disposable heat-resistant chemical protection gloves (Material: Butyl, Breakthrough time: > 480 min)	 CAT III	EN ISO 374-1:2016+A1:2018 EN 16523-1:2015+A1:2018 EN ISO 21420:2020 EN 407:2020	The Breakthrough Time indicated by the manufacturer must exceed the period during which the product is being used. Do not use protective creams after the product has come into contact with skin.

- CONTINUED ON NEXT PAGE -

Safety data sheet

This SDS is an English translation of COMMISSION REGULATION (EU) 2020/878, without any country-specific legislation

CETOX-300E



Printing: 05/01/2023

Date of compilation: 21/06/2006

Revised: 30/11/2022



Version: 5 (Replaced 4)

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION (continued)





Pictogram	PPE	Labelling	CEN Standard	Remarks
 Mandatory hand protection	Non-disposable heat-resistant chemical protection gloves (Material: Nitrile/Neoprene, Breakthrough time: > 480 min)		EN ISO 374-1:2016+A1:2018 EN 16523-1:2015+A1:2018 EN ISO 21420:2020 EN 407:2020	The Breakthrough Time indicated by the manufacturer must exceed the period during which the product is being used. Do not use protective creams after the product has come into contact with skin.

As the product is a mixture of several substances, the resistance of the glove material can not be calculated in advance with total reliability and has therefore to be checked prior to the application.



D.- Eye and face protection

Pictogram	PPE	Labelling	CEN Standard	Remarks
 Mandatory face protection	Panoramic glasses against splash/projections.		EN 166:2002 EN ISO 4007:2018	Clean daily and disinfect periodically according to the manufacturer's instructions. Use if there is a risk of splashing.

E.- Body protection

Pictogram	PPE	Labelling	CEN Standard	Remarks
 Mandatory complete body protection	Disposable clothing for protection against chemical risks, with antistatic and fireproof properties		EN 1149-1,2,3 EN 13034:2005+A1:2009 EN ISO 13982-1:2004/A1:2010 EN ISO 6529:2013 EN ISO 6530:2005 EN ISO 13688:2013 EN 464:1994	For professional use only. Clean periodically according to the manufacturer's instructions.
 Mandatory foot protection	Safety footwear for protection against chemical risk, with antistatic and heat resistant properties		EN ISO 13287:2020 EN ISO 20345:2011 EN 13832-1:2019	Replace boots at any sign of deterioration.

F.- Additional emergency measures

Emergency measure	Standards	Emergency measure	Standards
 Emergency shower	ANSI Z358-1 ISO 3864-1:2011, ISO 3864-4:2011	 Eyewash stations	DIN 12 899 ISO 3864-1:2011, ISO 3864-4:2011

Environmental exposure controls:

In accordance with the community legislation for the protection of the environment it is recommended to avoid environmental spillage of both the product and its container. For additional information see subsection 7.1.D

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1 Information on basic physical and chemical properties:

For complete information see the product datasheet.

Appearance:

Physical state at 20 °C:	Liquid
Appearance:	Fluid
Colour:	Colourless
Odour:	Characteristic
Odour threshold:	Non-applicable *

Volatility:

Boiling point at atmospheric pressure:	153 °C
Vapour pressure at 20 °C:	766 Pa

*Not relevant due to the nature of the product, not providing information property of its hazards.

- CONTINUED ON NEXT PAGE -

CETOX-300E

Printing: 05/01/2023

Date of compilation: 21/06/2006

Revised: 30/11/2022

Version: 5 (Replaced 4)

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES (continued)

Vapour pressure at 50 °C: 3803,42 Pa (3,8 kPa)

Evaporation rate at 20 °C: Non-applicable *

Product description:

Density at 20 °C: 988 kg/m³

Relative density at 20 °C: ≈0,961

Dynamic viscosity at 20 °C: 2,61 cP

Kinematic viscosity at 20 °C: 2,71 mm²/s

Kinematic viscosity at 40 °C: Non-applicable *

Concentration: Non-applicable *

pH: Non-applicable *

Vapour density at 20 °C: Non-applicable *

Partition coefficient n-octanol/water 20 °C: Non-applicable *

Solubility in water at 20 °C: Non-applicable *

Solubility properties: Non-applicable *

Decomposition temperature: Non-applicable *

Melting point/freezing point: Non-applicable *

Flammability:

Flash Point: 30 °C

Flammability (solid, gas): Non-applicable *

Autoignition temperature: 421 °C

Lower flammability limit: Not available

Upper flammability limit: Not available

Particle characteristics:

Median equivalent diameter: Non-applicable

9.2 Other information:

Information with regard to physical hazard classes:

Explosive properties: Non-applicable *

Oxidising properties: H242 Heating may cause a fire.

Corrosive to metals: Non-applicable *

Heat of combustion: Non-applicable *

Aerosols-total percentage (by mass) of flammable components: Non-applicable *

Other safety characteristics:

Surface tension at 20 °C: Non-applicable *

Refraction index: Non-applicable *

Active oxygen content: 2,8-3,0%

*Not relevant due to the nature of the product, not providing information property of its hazards.

SECTION 10: STABILITY AND REACTIVITY

10.1 Reactivity:

No hazardous reactions are expected because the product is stable under recommended storage conditions. See section 7.

10.2 Chemical stability:

Chemically stable under the indicated conditions of storage, handling and use.

10.3 Possibility of hazardous reactions:

Under the specified conditions, hazardous reactions that lead to excessive temperatures or pressure are not expected.

- CONTINUED ON NEXT PAGE -

CETOX-300E

Printing: 05/01/2023

Date of compilation: 21/06/2006

Revised: 30/11/2022

Version: 5 (Replaced 4)

SECTION 10: STABILITY AND REACTIVITY (continued)

10.4 Conditions to avoid:

Applicable for handling and storage at room temperature:

Shock and friction	Contact with air	Increase in temperature	Sunlight	Humidity
Not applicable	Not applicable	Heating may cause a fire or explosion	Avoid direct impact	Not applicable

10.5 Incompatible materials:

Acids	Water	Oxidising materials	Combustible materials	Others
Avoid strong acids	Not applicable	Avoid direct impact	Avoid direct impact	Avoid alkalines, heavy metals, reducing agents, peroxide accelerating agents

10.6 Hazardous decomposition products:

See subsection 10.3, 10.4 and 10.5 to find out the specific decomposition products. Depending on the decomposition conditions, complex mixtures of chemical substances can be released: carbon dioxide (CO₂), carbon monoxide and other organic compounds.

SECTION 11: TOXICOLOGICAL INFORMATION

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008:

The experimental information related to the toxicological properties of the product itself is not available

Dangerous health implications:

In case of exposure that is repetitive, prolonged or at concentrations higher than the recommended occupational exposure limits, adverse effects on health may result, depending on the means of exposure:

A- Ingestion (acute effect):

- Acute toxicity : Based on available data, the classification criteria are not met, however, it contains substances classified as dangerous for consumption. For more information see section 3.
- Corrosivity/Irritability: Corrosive product, if it is swallowed causes burns destroying the tissues. For more information about secondary effects from skin contact see section 2.

B- Inhalation (acute effect):

- Acute toxicity : Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for inhalation. For more information see section 3.
- Corrosivity/Irritability: Prolonged inhalation of the product is corrosive to mucous membranes and the upper respiratory tract

C- Contact with the skin and the eyes (acute effect):

- Contact with the skin: Above all, skin contact may occur as fabrics of all thicknesses can be destroyed, resulting in burns. For more information on the secondary effects see section 2.
- Contact with the eyes: Produces serious eye damage after contact.

D- CMR effects (carcinogenicity, mutagenicity and toxicity to reproduction):

- Carcinogenicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for the effects mentioned. For more information see section 3.
IARC: Non-applicable
- Mutagenicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.
- Reproductive toxicity: Suspected of damaging fertility or the unborn child

E- Sensitizing effects:

- Respiratory: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous with sensitising effects. For more information see section 3.
- Skin: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.

F- Specific target organ toxicity (STOT) - single exposure:

Causes irritation in respiratory passages, which is normally reversible and limited to the upper respiratory passages.

G- Specific target organ toxicity (STOT)-repeated exposure:

CETOX-300E

Printing: 05/01/2023

Date of compilation: 21/06/2006

Revised: 30/11/2022

Version: 5 (Replaced 4)

SECTION 11: TOXICOLOGICAL INFORMATION (continued)

- Specific target organ toxicity (STOT)-repeated exposure: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.
- Skin: Based on available data, the classification criteria are not met. However, it does contain substances which are classified as dangerous due to repetitive exposure. For more information see section 3.

H- Aspiration hazard:

Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.

Other information:

Non-applicable

Specific toxicology information on the substances:

Identification	Acute toxicity		Genus
4-hydroxy-4-methylpentan-2-one	LD50 oral	3002 mg/kg	Rat
CAS: 123-42-2	LD50 dermal	>2000 mg/kg	
EC: 204-626-7	LC50 inhalation	>20 mg/L	
Dimethyl Phthalate	LD50 oral	>2000 mg/kg	
CAS: 131-11-3	LD50 dermal	>2000 mg/kg	
EC: 205-011-6	LC50 inhalation	>20 mg/L	
Cyclohexanone, peroxide	LD50 oral	500 mg/kg	Rat
CAS: 12262-58-7	LD50 dermal	1100 mg/kg	Rat
EC: 235-527-7	LC50 inhalation	11 mg/L (4 h)	Rat
N-butyl acetate	LD50 oral	12789 mg/kg	Rat
CAS: 123-86-4	LD50 dermal	14112 mg/kg	Rabbit
EC: 204-658-1	LC50 inhalation	23,4 mg/L (4 h)	Rat

11.2 Information on other hazards:

Endocrine disrupting properties

Endocrine-disrupting properties: The product fails to meet the criteria.

Other information

Non-applicable

SECTION 12: ECOLOGICAL INFORMATION

The experimental information related to the eco-toxicological properties of the product itself is not available

12.1 Toxicity:

Acute toxicity:

Identification	Concentration	Species	Genus
N-butyl acetate	LC50	Non-applicable	
CAS: 123-86-4	EC50	Non-applicable	
EC: 204-658-1	EC50	675 mg/L (72 h)	Scenedesmus subspicatus
4-hydroxy-4-methylpentan-2-one	LC50	110 mg/L (96 h)	Oryzias latipes
CAS: 123-42-2	EC50	1000 mg/L (48 h)	Daphnia magna
EC: 204-626-7	EC50	1000 mg/L (72 h)	Pseudokirchneriella subcapitata
Dimethyl Phthalate	LC50	39 mg/L (96 h)	Pimephales promelas
CAS: 131-11-3	EC50	150 mg/L (24 h)	Daphnia magna
EC: 205-011-6	EC50	204 mg/L (72 h)	Scenedesmus subspicatus

Chronic toxicity:

Identification	Concentration	Species	Genus
N-butyl acetate	NOEC	Non-applicable	
CAS: 123-86-4 EC: 204-658-1	NOEC	23,2 mg/L	Daphnia magna
4-hydroxy-4-methylpentan-2-one	NOEC	Non-applicable	
CAS: 123-42-2 EC: 204-626-7	NOEC	100 mg/L	Daphnia magna

- CONTINUED ON NEXT PAGE -

CETOX-300E

Printing: 05/01/2023

Date of compilation: 21/06/2006

Revised: 30/11/2022

Version: 5 (Replaced 4)

SECTION 12: ECOLOGICAL INFORMATION (continued)

Identification	Concentration	Species	Genus
Dimethyl Phthalate	NOEC 11 mg/L	Oncorhynchus mykiss	Fish
CAS: 131-11-3 EC: 205-011-6	NOEC 9,6 mg/L	Daphnia magna	Crustacean
Cyclohexanone, peroxide	NOEC Non-applicable		
CAS: 12262-58-7 EC: 235-527-7	NOEC 1,5 mg/L	Daphnia magna	Crustacean

12.2 Persistence and degradability:
Substance-specific information:

Identification	Degradability	Biodegradability
N-butyl acetate	BOD5 Non-applicable	Concentration Non-applicable
CAS: 123-86-4	COD Non-applicable	Period 5 days
EC: 204-658-1	BOD5/COD Non-applicable	% Biodegradable 84 %
4-hydroxy-4-methylpentan-2-one	BOD5 Non-applicable	Concentration 57.5 mg/L
CAS: 123-42-2	COD Non-applicable	Period 28 days
EC: 204-626-7	BOD5/COD Non-applicable	% Biodegradable 98,51 %
Dimethyl Phthalate	BOD5 1,12 g O ₂ /g	Concentration 100 mg/L
CAS: 131-11-3	COD 0,74 g O ₂ /g	Period 28 days
EC: 205-011-6	BOD5/COD 1,51	% Biodegradable 93 %

12.3 Bioaccumulative potential:
Substance-specific information:

Identification	Bioaccumulation potential
N-butyl acetate	BCF 4
CAS: 123-86-4	Pow Log 1.78
EC: 204-658-1	Potential Low
4-hydroxy-4-methylpentan-2-one	BCF 0.5
CAS: 123-42-2	Pow Log
EC: 204-626-7	Potential Low
Dimethyl Phthalate	BCF 57
CAS: 131-11-3	Pow Log 1.6
EC: 205-011-6	Potential Moderate

12.4 Mobility in soil:

Identification	Absorption/desorption	Volatility
N-butyl acetate	Koc Non-applicable	Henry Non-applicable
CAS: 123-86-4	Conclusion Non-applicable	Dry soil Non-applicable
EC: 204-658-1	Surface tension 2,478E-2 N/m (25 °C)	Moist soil Non-applicable
4-hydroxy-4-methylpentan-2-one	Koc 1	Henry Non-applicable
CAS: 123-42-2	Conclusion Very High	Dry soil Non-applicable
EC: 204-626-7	Surface tension 2,963E-2 N/m (25 °C)	Moist soil Non-applicable
Dimethyl Phthalate	Koc Non-applicable	Henry Non-applicable
CAS: 131-11-3	Conclusion Non-applicable	Dry soil Non-applicable
EC: 205-011-6	Surface tension 4,044E-2 N/m (25 °C)	Moist soil Non-applicable

12.5 Results of PBT and vPvB assessment:

Product fails to meet PBT/vPvB criteria

12.6 Endocrine disrupting properties:

Endocrine-disrupting properties: The product fails to meet the criteria.

12.7 Other adverse effects:

Not described

SECTION 13: DISPOSAL CONSIDERATIONS
13.1 Waste treatment methods:

CETOX-300E

Printing: 05/01/2023

Date of compilation: 21/06/2006

Revised: 30/11/2022

Version: 5 (Replaced 4)

SECTION 13: DISPOSAL CONSIDERATIONS (continued)

Code	Description	Waste class (Regulation (EU) No 1357/2014)
08 01 11*	waste paint and varnish containing organic solvents or other hazardous substances	Dangerous

Type of waste (Regulation (EU) No 1357/2014):

HP3 Flammable, HP5 Specific Target Organ Toxicity (STOT)/Aspiration Toxicity, HP10 Toxic for reproduction, HP8 Corrosive

Waste management (disposal and evaluation):

Consult the authorized waste service manager on the assessment and disposal operations in accordance with Annex 1 and Annex 2 (Directive 2008/98/EC). As under 15 01 (2014/955/EC) of the code and in case the container has been in direct contact with the product, it will be processed the same way as the actual product. Otherwise, it will be processed as non-dangerous residue. Waste should not be disposed of to drains. See paragraph 6.2.

Regulations related to waste management:

In accordance with Annex II of Regulation (EC) No 1907/2006 (REACH) the community or state provisions related to waste management are stated

Community legislation: Directive 2008/98/EC, 2014/955/EU, Regulation (EU) No 1357/2014

SECTION 14: TRANSPORT INFORMATION
Transport of dangerous goods by land:

With regard to ADR 2021 and RID 2021:



- 14.1 UN number or ID number:** UN3105
14.2 UN proper shipping name: ORGANIC PEROXIDE TYPE D, LIQUID (Cyclohexanone, peroxide)
14.3 Transport hazard class(es): 5.2
Labels: 5.2
14.4 Packing group: N/A
14.5 Environmental hazards: No
14.6 Special precautions for user
Special regulations: 122, 274
Tunnel restriction code: D
Physico-Chemical properties: see section 9
Limited quantities: 125 mL
14.7 Maritime transport in bulk according to IMO instruments: Non-applicable

Transport of dangerous goods by sea:

With regard to IMDG 40-20:



- 14.1 UN number or ID number:** UN3105
14.2 UN proper shipping name: ORGANIC PEROXIDE TYPE D, LIQUID (Cyclohexanone, peroxide)
14.3 Transport hazard class(es): 5.2
Labels: 5.2
14.4 Packing group: N/A
14.5 Marine pollutant: No
14.6 Special precautions for user
Special regulations: 274, 122
EmS Codes: F-J, S-R
Physico-Chemical properties: see section 9
Limited quantities: 125 mL
Segregation group: Non-applicable
14.7 Maritime transport in bulk according to IMO instruments: Non-applicable

Transport of dangerous goods by air:

With regard to IATA/ICAO 2022:

CETOX-300E

Printing: 05/01/2023

Date of compilation: 21/06/2006

Revised: 30/11/2022

Version: 5 (Replaced 4)

SECTION 14: TRANSPORT INFORMATION (continued)



- 14.1 UN number or ID number:** UN3105
14.2 UN proper shipping name: ORGANIC PEROXIDE TYPE D, LIQUID (Cyclohexanone, peroxide)
14.3 Transport hazard class(es): 5.2
Labels: 5.2
14.4 Packing group: N/A
14.5 Environmental hazards: No
14.6 Special precautions for user
 Physico-Chemical properties: see section 9
14.7 Maritime transport in bulk according to IMO instruments: Non-applicable

SECTION 15: REGULATORY INFORMATION

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture:

Candidate substances for authorisation under the Regulation (EC) No 1907/2006 (REACH): Non-applicable

Substances included in Annex XIV of REACH ("Authorisation List") and sunset date: Non-applicable

Regulation (EC) No 1005/2009, about substances that deplete the ozone layer: Non-applicable

Article 95, REGULATION (EU) No 528/2012: Non-applicable

REGULATION (EU) No 649/2012, in relation to the import and export of hazardous chemical products: Non-applicable

Seveso III:

Section	Description	Lower-tier requirements	Upper-tier requirements
P5c	FLAMMABLE LIQUIDS	5000	50000
P6b	SELF-REACTIVE SUBSTANCES AND MIXTURES and ORGANIC PEROXIDES	50	200

Limitations to commercialisation and the use of certain dangerous substances and mixtures (Annex XVII REACH, etc):

Shall not be used in:

- ornamental articles intended to produce light or colour effects by means of different phases, for example in ornamental lamps and ashtrays,
- tricks and jokes,
- games for one or more participants, or any article intended to be used as such, even with ornamental aspects.

Specific provisions in terms of protecting people or the environment:

It is recommended to use the information included in this safety data sheet as a basis for conducting workplace-specific risk assessments in order to establish the necessary risk prevention measures for the handling, use, storage and disposal of this product.

Other legislation:

The product could be affected by sectorial legislation

15.2 Chemical safety assessment:

The supplier has not carried out evaluation of chemical safety.

SECTION 16: OTHER INFORMATION

Legislation related to safety data sheets:

The SDS shall be supplied in an official language of the country where the product is placed on the market. This safety data sheet has been designed in accordance with ANNEX II-Guide to the compilation of safety data sheets of Regulation (EC) No 1907/2006 (COMMISSION REGULATION (EU) 2020/878).

Modifications related to the previous Safety Data Sheet which concerns the ways of managing risks.:

Non-applicable

Texts of the legislative phrases mentioned in section 2:

CETOX-300E

Printing: 05/01/2023

Date of compilation: 21/06/2006

Revised: 30/11/2022

Version: 5 (Replaced 4)

SECTION 16: OTHER INFORMATION (continued)

H335: May cause respiratory irritation.
H336: May cause drowsiness or dizziness.
H242: Heating may cause a fire.
H226: Flammable liquid and vapour.
H314: Causes severe skin burns and eye damage.
H361: Suspected of damaging fertility or the unborn child.

Texts of the legislative phrases mentioned in section 3:

The phrases indicated do not refer to the product itself; they are present merely for informative purposes and refer to the individual components which appear in section 3

CLP Regulation (EC) No 1272/2008:

Acute Tox. 4: H302 - Harmful if swallowed.
Eye Irrit. 2: H319 - Causes serious eye irritation.
Flam. Liq. 3: H226 - Flammable liquid and vapour.
Org. Perox. D: H242 - Heating may cause a fire.
Repr. 2: H361 - Suspected of damaging fertility or the unborn child.
Skin Corr. 1B: H314 - Causes severe skin burns and eye damage.
STOT SE 3: H335 - May cause respiratory irritation.
STOT SE 3: H336 - May cause drowsiness or dizziness.

Advice related to training:

Training is recommended in order to prevent industrial risks for staff using this product and to facilitate their comprehension and interpretation of this safety data sheet, as well as the label on the product.

Principal bibliographical sources:

<http://echa.europa.eu>
<http://eur-lex.europa.eu>

Abbreviations and acronyms:

ADR: European agreement concerning the international carriage of dangerous goods by road
IMDG: International maritime dangerous goods code
IATA: International Air Transport Association
ICAO: International Civil Aviation Organisation
COD: Chemical Oxygen Demand
BOD5: 5day biochemical oxygen demand
BCF: Bioconcentration factor
LD50: Lethal Dose 50
LC50: Lethal Concentration 50
EC50: Effective concentration 50
LogPOW: Octanolwater partition coefficient
Koc: Partition coefficient of organic carbon
UFI: unique formula identifier
IARC: International Agency for Research on Cancer

The information contained in this safety data sheet is based on sources, technical knowledge and current legislation at European and state level, without being able to guarantee its accuracy. This information cannot be considered a guarantee of the properties of the product, it is simply a description of the security requirements. The occupational methodology and conditions for users of this product are not within our awareness or control, and it is ultimately the responsibility of the user to take the necessary measures to obtain the legal requirements concerning the manipulation, storage, use and disposal of chemical products. The information on this safety data sheet only refers to this product, which should not be used for needs other than those specified.

- END OF SAFETY DATA SHEET -