

BLACK CARBON

| - | g: 19/12/2022 Date of compilation: 15/11/2011 Revised: 23/09/2022 Version: 7 (Replaced 6) | | | | | |
|----|---|---|--|--|--|--|
| EC | TION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING | | | | | |
| 1 | | | | | | |
| | Other means of identification: | | | | | |
| | UFI: YDJ6-Y0W1-F00H-VDKE | | | | | |
| 2 | | | | | | |
| | Relevant uses: Car repair; filler for joints, cracks, etc For professional users only. | | | | | |
| | Uses advised against: All uses not specified in this section or in section 7.3 | | | | | |
| 3 | Details of the supplier of the safety data sheet: | | | | | |
| | Troton Sp. z o.o. Ząbrowo 14A 78-120 Gościno - Zachodniopomorskie - Polska | | | | | |
| | Phone: +48 94 35 123 94 - Fax: +48 94 35 126 22 troton@troton.com.pl | | | | | |
| | www.troton.pl / www.troton.eu | | | | | |
| .4 | Emergency telephone number: (8am-4pm)+48 094 35 123 94; 112 | | | | | |
| | | _ | | | | |
| EC | TION 2: HAZARDS IDENTIFICATION | | | | | |
| .1 | Classification of the substance or mixture: | | | | | |
| | CLP Regulation (EC) No 1272/2008: | | | | | |
| | Classification of this product has been carried out in accordance with CLP Regulation (EC) No 1272/2008. | | | | | |
| | Eye Irrit. 2: Eye irritation, Category 2, H319 Flam. Liq. 3: Flammable liquids, Category 3, H226 Repr. 2: Reproductive toxicity, Category 2, H361d Skin Irrit. 2: Skin irritation, Category 2, H315 STOT RE 1: Specific target organ toxicity — Repeated exposure, Hazard Category 1, H372 | | | | | |
| .2 | Label elements: | | | | | |
| | CLP Regulation (EC) No 1272/2008: | | | | | |
| | Danger | | | | | |
| | | | | | | |
| | Hazard statements: | | | | | |
| | Eye Irrit. 2: H319 - Causes serious eye irritation. Flam. Liq. 3: H226 - Flammable liquid and vapour. Repr. 2: H361d - Suspected of damaging the unborn child. Skin Irrit. 2: H315 - Causes skin irritation. | | | | | |
| | STOT RE 1: H372 - Causes damage to organs through prolonged or repeated exposure. | | | | | |
| | Precautionary statements: | | | | | |
| | P201: Obtain special instructions before use. P210: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P280: Wear protective gloves/protective clothing/respiratory protection/eye protection/protective footwear. P302+P352: IF ON SKIN: Wash with plenty of water. | | | | | |
| | P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and eas do. Continue rinsing. P308+P313: IF exposed or concerned: Get medical advice/attention. P501: Dispose of contents/container in accordance with regulations on hazardous waste or packaging and packaging waste | | | | | |
| | respectively. Substances that contribute to the classification | | | | | |
| | styrene | | | | | |
| 3 | | | | | | |
| | Product fails to meet PBT/vPvB criteria | | | | | |



BLACK CARBON

Printing: 19/12/2022 Date of compilation: 15/11/2011 Revised: 23/09/2022 Version: 7 (Replaced 6)

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

3.1 Substance:

Non-applicable

3.2 Mixture:

Chemical description: Mixture composed of chemical products

Components:

In accordance with Annex II of Regulation (EC) No 1907/2006 (point 3), the product contains:

| | Identification | | Chemical name/Classification | | | | |
|-------------------------|--|------------------------|--|-----------------|------------|--|--|
| CAS: | | styrene ⁽¹⁾ | | ATP ATP06 | | | |
| EC: Index: REACH: | 202-851-5 601-026-00-0 01-2119457861-32- XXXX | | Acute Tox. 4: H332; Eye Irrit. 2: H319; Flam. Liq. 3: H226; Repr. 2: H361d; Skin Irrit. 2: H315; STOT RE 1: H372 - Danger | () () () | 10 - <25 % | | |
| CAS: | | Quartz (1 %< RCS < | 10%) ⁽²⁾ | Self-classified | | | |
| EC: Index: REACH: | 238-878-4 Non-applicable Non-applicable | Regulation 1272/2008 | STOT RE 2: H373 - Warning | ٠ | <1 % | | |

⁽¹⁾ Substances presenting a health or environmental hazard which meet criteria laid down in Regulation (EU) No. 2020/878

(2) Substance with a Union workplace exposure limit

To obtain more information on the hazards of the substances consult sections 11, 12 and 16.

SECTION 4: FIRST AID MEASURES

4.1 Description of first aid measures:

The symptoms resulting from intoxication can appear after exposure, therefore, in case of doubt, seek medical attention for direct exposure to the chemical product or persistent discomfort, showing the SDS of this product.

By inhalation:

Remove the person affected from the area of exposure, provide with fresh air and keep at rest. In serious cases such as cardiorespiratory failure, artificial resuscitation techniques will be necessary (mouth to mouth resuscitation, cardiac massage, oxygen supply, etc.) requiring immediate medical assistance.

By skin contact:

Remove contaminated clothing and footwear, rinse skin or shower the person affected if appropriate with plenty of cold water and neutral soap. In serious cases see a doctor. If the product causes burns or freezing, clothing should not be removed as this could worsen the injury caused if it is stuck to the skin. If blisters form on the skin, these should never be burst as this will increase the risk of infection.

By eye contact:

Rinse eyes thoroughly with lukewarm water for at least 15 minutes. Do not allow the person affected to rub or close their eyes. If the injured person uses contact lenses, these should be removed unless they are stuck to the eyes, in which case this could cause further damage. In all cases, after cleaning, a doctor should be consulted as quickly as possible with the SDS of the product.

By ingestion/aspiration:

Do not induce vomiting, but if it does happen keep the head down to avoid aspiration. Keep the person affected at rest. Rinse out the mouth and throat, as they may have been affected during ingestion.

4.2 Most important symptoms and effects, both acute and delayed:

Acute and delayed effects are indicated in sections 2 and 11.

4.3 Indication of any immediate medical attention and special treatment needed:

Non-applicable

SECTION 5: FIREFIGHTING MEASURES

5.1 Extinguishing media:

Suitable extinguishing media:

If possible use polyvalent powder fire extinguishers (ABC powder), alternatively use foam or carbon dioxide extinguishers (CO₂). **Unsuitable extinguishing media:**



BLACK CARBON

Printing: 19/12/2022 Date of compilation: 15/11/2011 Revised: 23/09/2022 Version:

Version: 7 (Replaced 6)

SECTION 5: FIREFIGHTING MEASURES (continued)

IT IS RECOMMENDED NOT to use full jet water as an extinguishing agent.

5.2 Special hazards arising from the substance or mixture:

As a result of combustion or thermal decomposition reactive sub-products are created that can become highly toxic and, consequently, can present a serious health risk.

5.3 Advice for firefighters:

Depending on the magnitude of the fire it may be necessary to use full protective clothing and self-contained breathing apparatus (SCBA). Minimum emergency facilities and equipment should be available (fire blankets, portable first aid kit,...) in accordance with Directive 89/654/EC.

Additional provisions:

Act in accordance with the Internal Emergency Plan and the Information Sheets on actions to take after an accident or other emergencies. Eliminate all sources of ignition. In case of fire, cool the storage containers and tanks for products susceptible to combustion, explosion or BLEVE as a result of high temperatures. Avoid spillage of the products used to extinguish the fire into an aqueous medium.

SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1 Personal precautions, protective equipment and emergency procedures:

For non-emergency personnel:

Isolate leaks provided that there is no additional risk for the people performing this task. Evacuate the area and keep out those without protection. Personal protection equipment must be used against potential contact with the spilt product (See section 8). Above all prevent the formation of any vapour-air flammable mixtures, through either ventilation or the use of an inert medium. Remove any source of ignition. Eliminate electrostatic charges by interconnecting all the conductive surfaces on which static electricity could form, and also ensuring that all surfaces are connected to the ground.

For emergency responders:

Wear protective equipment. Keep unprotected persons away. See section 8.

6.2 Environmental precautions:

This product is not classified as hazardous to the environment. Keep product away from drains, surface and underground water.

6.3 Methods and material for containment and cleaning up:

It is recommended:

Absorb the spillage using sand or inert absorbent and move it to a safe place. Do not absorb in sawdust or other combustible absorbents. For any concern related to disposal consult section 13.

6.4 Reference to other sections:

See sections 8 and 13.

SECTION 7: HANDLING AND STORAGE

7.1 Precautions for safe handling:

A.- General precautions for safe use

Comply with the current legislation concerning the prevention of industrial risks. Keep containers hermetically sealed. Control spills and residues, destroying them with safe methods (section 6). Avoid leakages from the container. Maintain order and cleanliness where dangerous products are used.

B.- Technical recommendations for the prevention of fires and explosions

Transfer in well ventilated areas, preferably through localized extraction. Fully control sources of ignition (mobile phones, sparks,...) and ventilate during cleaning operations. Avoid the existence of dangerous atmospheres inside containers, applying inertization systems where possible. Transfer at a slow speed to avoid the creation of electrostatic charges. Against the possibility of electrostatic charges: ensure a perfect equipotential connection, always use groundings, do not wear work clothes made of acrylic fibres, preferably wearing cotton clothing and conductive footwear. Comply with the essential security requirements for equipment and systems defined in Directive 2014/34/EC (ATEX 100) and with the minimum requirements for protecting the security and health of workers under the selection criteria of Directive 1999/92/EC (ATEX 137). Consult section 10 for conditions and materials that should be avoided.

C.- Technical recommendations on general occupational hygiene



BLACK CARBON

| ECT | · · · · | tion: 15/11/2011 | Revised: 23/09/202 | | n: 7 (Replaced | - |
|-----|---|--|--|--|--|---|
| | TION 7: HANDLING AND STOR | AGE (continued) | | | | |
| | PREGNANT WOMEN SHOULD N necessary safety conditions (en equipment, especially on the ha drink during the process, washi D Technical recommendations to | nergency showers and ey ands and face (See section ng hands afterwards with | ewash stations in clo n 8). Limit manual t n suitable cleaning p | ose proximity), us ransfers to small | sing personal | protection |
| | It is recommended to have abs | orbent material available | at close proximity to | o the product (Se | e subsection | 6.3) |
| 2 | Conditions for safe storage, inc | luding any incompati | pilities: | | | |
| | A Technical measures for storage | | | | | |
| | Minimum Temp.: 15 ° | С | | | | |
| | Maximum Temp.: 25 % | С | | | | |
| | Maximum time: 12 M | lonths | | | | |
| | B General conditions for storage | | | | | |
| | Avoid sources of heat, radiation | , static electricity and co | ntact with food. For | additional inform | nation see sub | osection 10.5 |
| 3 | Specific end use(s): | . , | | | | |
| | Except for the instructions already product. | specified it is not necess | ary to provide any sp | pecial recommend | dation regard | ing the uses of this |
| | | | | | | |
| CT | ION 8: EXPOSURE CONTROLS, | /PERSONAL PROTEC | TION | | | |
| 1 | Control parameters: | | | | | |
| | Substances whose occupational exp | oosure limits have to be | nonitored in the wor | rkplace (Europea | n OEL, not co | ountry-specific |
| | legislation): | | | | | , , |
| | Directive (EU) 2000/39, Directive 2004/37/EC, Directive (EU) 2006/15, Directive (EU) 2009/161, Directive (EU) 2017/164, Directive | | | | | |
| | | , , , , , <u>, , , , , , , , , , , , , , </u> | 2000, 19, 51 660, 60 | (20) 2005, 101, 2 | | 2017/104, Directiv |
| | (EU) 2019/1831: | | | | | |
| | | Identification | 2000,12, 2, 2, 2, 2, 2, 2, 2, 2, 2, 2, 2, 2, 2 | O IOELV (8h) | ccupational expo | |
| | (EU) 2019/1831: | | | 0 | | osure limits |
| | (EU) 2019/1831: Quartz (1 %< RCS < 10%) | | | O IOELV (8h) | | osure limits |
| | (EU) 2019/1831: Quartz (1 %< RCS < 10%) CAS: 14808-60-7 EC: 238-878-4 | | | O IOELV (8h) | ccupational expo | osure limits |
| | (EU) 2019/1831: Quartz (1 %< RCS < 10%) CAS: 14808-60-7 EC: 238-878-4 | | | O IOELV (8h) IOELV (STEL) | ccupational expo | osure limits 0,1 mg/m ³ |
| | (EU) 2019/1831: Quartz (1 %< RCS < 10%) CAS: 14808-60-7 EC: 238-878-4 DNEL (Workers): | | Short | O IOELV (8h) IOELV (STEL) exposure | ccupational expo | ong exposure Local |
| | (EU) 2019/1831: Quartz (1 %< RCS < 10%) CAS: 14808-60-7 EC: 238-878-4 DNEL (Workers): Identification styrene CAS: 100-42-5 | Identification Identification Oral Dermal | Short Systemic Non-applicable Non-applicable | exposure Local Non-applicable Non-applicable | ccupational expo Lc Systemic Non-applicable 406 mg/kg | osure limits 0,1 mg/m ³ ong exposure Local e Non-applicable Non-applicable |
| | (EU) 2019/1831: Quartz (1 %< RCS < 10%) CAS: 14808-60-7 EC: 238-878-4 DNEL (Workers): Identification styrene CAS: 100-42-5 EC: 202-851-5 | Identification Oral | Short Systemic Non-applicable | O IOELV (8h) IOELV (STEL) exposure Local Non-applicable | ccupational expo | ong exposure Local Non-applicable |
| | (EU) 2019/1831: Quartz (1 %< RCS < 10%) CAS: 14808-60-7 EC: 238-878-4 DNEL (Workers): Identification styrene CAS: 100-42-5 | Identification Identification Oral Dermal | Short Systemic Non-applicable Non-applicable | exposure Local Non-applicable Non-applicable | ccupational expo Lc Systemic Non-applicable 406 mg/kg | osure limits 0,1 mg/m ³ ong exposure Local e Non-applicable Non-applicable |
| | (EU) 2019/1831: Quartz (1 %< RCS < 10%) CAS: 14808-60-7 EC: 238-878-4 DNEL (Workers): Identification styrene CAS: 100-42-5 EC: 202-851-5 | Identification Identification Oral Dermal | Short Systemic Non-applicable Non-applicable 289 mg/m ³ | exposure Local Non-applicable Non-applicable | ccupational expo expo expo expo expo expo expo expo | osure limits 0,1 mg/m ³ ong exposure Local e Non-applicable Non-applicable |
| | (EU) 2019/1831: Quartz (1 %< RCS < 10%) CAS: 14808-60-7 EC: 238-878-4 DNEL (Workers): Identification styrene CAS: 100-42-5 EC: 202-851-5 DNEL (General population): Identification | Identification Identification Oral Dermal Inhalation | Short Systemic Non-applicable 289 mg/m ³ Short Systemic | O IOELV (8h) IOELV (8h) IOELV (STEL) exposure Local Non-applicable Non-applicable 306 mg/m3 exposure Local | ccupational expo ccupational expo ccupational expo ccupational expo ccupational expo ccupational expo ccupational expo systemic ccupational expo ccupational expo cc | osure limits 0,1 mg/m ³ 0,1 |
| | (EU) 2019/1831: Quartz (1 %< RCS < 10%) CAS: 14808-60-7 EC: 238-878-4 DNEL (Workers): Identification styrene CAS: 100-42-5 EC: 202-851-5 DNEL (General population): Identification styrene | Identification Identification Oral Dermal Inhalation Inhalation Oral Oral | Short Systemic Non-applicable Non-applicable 289 mg/m ³ Short Systemic Non-applicable | O IOELV (8h) IOELV (8h) IOELV (STEL) exposure Local Non-applicable 306 mg/m ³ exposure Local Non-applicable Non-applicable Non-applicable | ccupational expo ccupational expo ccupational expo ccupational expo ccupational expo ccupational expo Systemic ccupational expo ccupational expo ccupational expo systemic ccupational expo ccupational expo ccupationa | bisure limits 0,1 mg/m ³ 0,1 mg/m ³ Ding exposure Local Non-applicable Non-applicable Non-applicable Non-applicable Non-applicable |
| | (EU) 2019/1831: Quartz (1 %< RCS < 10%) CAS: 14808-60-7 EC: 238-878-4 DNEL (Workers): Identification styrene CAS: 100-42-5 EC: 202-851-5 DNEL (General population): Identification styrene CAS: 100-42-5 | Identification Identi | Short Systemic Non-applicable Non-applicable 289 mg/m ³ Short Systemic Non-applicable Non-applicable | O IOELV (8h) IOELV (8h) IOELV (STEL) exposure Local Non-applicable 306 mg/m ³ exposure Local Non-applicable Non-applicable Non-applicable Non-applicable Non-applicable | ccupational expo ccupational expo ccupational expo ccupational expo ccupational expo Systemic 2,1 mg/kg 343 mg/kg | bisure limits 0,1 mg/m ³ 0,1 mg/m ³ Ding exposure Local Non-applicable Non-applicable Ding exposure Local Non-applicable Non-applicable Non-applicable |
| | (EU) 2019/1831: Quartz (1 %< RCS < 10%) CAS: 14808-60-7 EC: 238-878-4 DNEL (Workers): Identification styrene CAS: 100-42-5 EC: 202-851-5 DNEL (General population): Identification styrene CAS: 100-42-5 EC: 202-851-5 | Identification Identification Oral Dermal Inhalation Inhalation Oral Oral | Short Systemic Non-applicable Non-applicable 289 mg/m ³ Short Systemic Non-applicable | O IOELV (8h) IOELV (8h) IOELV (STEL) exposure Local Non-applicable 306 mg/m ³ exposure Local Non-applicable Non-applicable Non-applicable | ccupational expo ccupational expo ccupational expo ccupational expo ccupational expo ccupational expo Systemic ccupational expo ccupational expo ccupational expo systemic ccupational expo ccupational expo ccupationa | bisure limits 0,1 mg/m ³ 0,1 mg/m ³ Ding exposure Local Non-applicable Non-applicable Non-applicable Non-applicable Non-applicable |
| | (EU) 2019/1831: Quartz (1 %< RCS < 10%) CAS: 14808-60-7 EC: 238-878-4 DNEL (Workers): Identification styrene CAS: 100-42-5 EC: 202-851-5 DNEL (General population): Identification styrene CAS: 100-42-5 EC: 202-851-5 PNEC: | Identification Identi | Short Systemic Non-applicable Non-applicable 289 mg/m ³ Short Systemic Non-applicable Non-applicable | O IOELV (8h) IOELV (8h) IOELV (STEL) exposure Local Non-applicable 306 mg/m ³ exposure Local Non-applicable Non-applicable Non-applicable Non-applicable Non-applicable | ccupational expo ccupational expo ccupational expo ccupational expo ccupational expo Systemic 2,1 mg/kg 343 mg/kg | bisure limits 0,1 mg/m ³ 0,1 mg/m ³ Ding exposure Local Non-applicable Non-applicable Ding exposure Local Non-applicable Non-applicable Non-applicable |
| | (EU) 2019/1831: Quartz (1 %< RCS < 10%) CAS: 14808-60-7 EC: 238-878-4 DNEL (Workers): Identification styrene CAS: 100-42-5 EC: 202-851-5 DNEL (General population): Identification styrene CAS: 100-42-5 EC: 202-851-5 PNEC: Identification | Identification Identi | Short Systemic Non-applicable Non-applicable 289 mg/m ³ Short Systemic Non-applicable Non-applicable 174,25 mg/m ³ | O IOELV (8h) IOELV (8h) IOELV (STEL) exposure Local Non-applicable 306 mg/m ³ exposure Local Non-applicable Non-applicable Non-applicable Non-applicable I82,75 mg/m ³ | ccupational expo ccupational expo ccupational expo ccupational expo ccupational expo Systemic 2,1 mg/kg 343 mg/kg | bisure limits 0,1 mg/m ³ 0,1 mg/m ³ Ding exposure Local Non-applicable Non-applicable Non-applicable Non-applicable Non-applicable Non-applicable Non-applicable Non-applicable |
| | (EU) 2019/1831: Quartz (1 %< RCS < 10%) CAS: 14808-60-7 EC: 238-878-4 DNEL (Workers): Identification styrene CAS: 100-42-5 EC: 202-851-5 DNEL (General population): Identification styrene CAS: 100-42-5 EC: 202-851-5 PNEC: | Identification Identi | Short Systemic Non-applicable Non-applicable 289 mg/m ³ Short Systemic Non-applicable Non-applicable 174,25 mg/m ³ | O IOELV (8h) IOELV (8h) IOELV (STEL) exposure Local Non-applicable 306 mg/m ³ exposure Local Non-applicable Non-applicable Non-applicable Non-applicable Non-applicable | ccupational expo ccupational expo ccupational expo ccupational expo ccupational expo Systemic 2,1 mg/kg 343 mg/kg | osure limits 0,1 mg/m³ 0,1 mg/m³ 0,1 mg/m³ 0,1 mg/m³ 0,0 mg/L 0,028 mg/L |
| | (EU) 2019/1831: Quartz (1 %< RCS < 10%) CAS: 14808-60-7 EC: 238-878-4 DNEL (Workers): Identification styrene CAS: 100-42-5 EC: 202-851-5 DNEL (General population): Identification styrene CAS: 100-42-5 EC: 202-851-5 PNEC: Identification styrene | Identification Identi | Short Systemic Non-applicable Non-applicable 289 mg/m ³ Short Systemic Non-applicable Non-applicable 174,25 mg/m ³ | O IOELV (8h) IOELV (8h) IOELV (STEL) exposure Local Non-applicable 306 mg/m ³ exposure Local Non-applicable 182,75 mg/m ³ Fresh water | ccupational expo ccupational expo ccupational expo ccupational expo ccupational expo Systemic A06 mg/kg 85 mg/m ³ Lcc Systemic 2,1 mg/kg 343 mg/kg 10,2 mg/m ³ | bisure limits 0,1 mg/m ³ 0,1 mg/m ³ Ding exposure Local Non-applicable Non-applicable Non-applicable Non-applicable Non-applicable Non-applicable Non-applicable Non-applicable |
| | (EU) 2019/1831: Quartz (1 %< RCS < 10%) CAS: 14808-60-7 EC: 238-878-4 DNEL (Workers): Identification styrene CAS: 100-42-5 EC: 202-851-5 DNEL (General population): Identification styrene CAS: 100-42-5 EC: 202-851-5 PNEC: Identification styrene CAS: 100-42-5 EC: 202-851-5 PNEC: | Identification Identi | Short Systemic Non-applicable Non-applicable 289 mg/m ³ Short Systemic Non-applicable Non-applicable 174,25 mg/m ³ Start S mg/L 0,2 mg/kg | | ccupational expo ccupational expo Systemic Non-applicable 406 mg/kg 85 mg/m ³ Lcc Systemic 2,1 mg/kg 343 mg/kg 10,2 mg/m ³ Lcc n water) | sure limits 0,1 mg/m ³ 0,1 mg/m ³ Local Non-applicable |
| 2 | (EU) 2019/1831: Quartz (1 %< RCS < 10%) CAS: 14808-60-7 EC: 238-878-4 DNEL (Workers): Identification styrene CAS: 100-42-5 EC: 202-851-5 DNEL (General population): Identification styrene CAS: 100-42-5 EC: 202-851-5 PNEC: Identification styrene CAS: 100-42-5 EC: 202-851-5 | Identification Identi | Short Systemic Non-applicable Non-applicable 289 mg/m ³ Short Systemic Non-applicable Non-applicable 174,25 mg/m ³ Start S mg/L 0,2 mg/kg 0,04 mg/L | | ccupational expo ccupational expo Systemic Non-applicable 406 mg/kg 85 mg/m ³ Lcc Systemic 2,1 mg/kg 343 mg/kg 10,2 mg/m ³ Lcc n water) | sure limits 0,1 mg/m ³ 0,1 mg/m ³ Local Non-applicable |
| 2 | (EU) 2019/1831: Quartz (1 %< RCS < 10%) CAS: 14808-60-7 EC: 238-878-4 DNEL (Workers): Identification styrene CAS: 100-42-5 EC: 202-851-5 DNEL (General population): Identification styrene CAS: 100-42-5 EC: 202-851-5 PNEC: Identification styrene CAS: 100-42-5 EC: 202-851-5 PNEC: | Identification Identi | Short Systemic Non-applicable Non-applicable 289 mg/m ³ Short Non-applicable Non-applicable Non-applicable 174,25 mg/m ³ Short S mg/L O,2 mg/kg O,04 mg/L Non-applicable | | ccupational expo ccupational expo Systemic Non-applicable 406 mg/kg 85 mg/m ³ Lcc Systemic 2,1 mg/kg 343 mg/kg 10,2 mg/m ³ Lcc n water) | sure limits 0,1 mg/m ³ 0,1 mg/m ³ Local Non-applicable |
| 2 | (EU) 2019/1831: Quartz (1 %< RCS < 10%) CAS: 14808-60-7 EC: 238-878-4 DNEL (Workers): Identification styrene CAS: 100-42-5 EC: 202-851-5 DNEL (General population): Identification styrene CAS: 100-42-5 EC: 202-851-5 PNEC: Identification styrene CAS: 100-42-5 EC: 202-851-5 PNEC: Identification styrene CAS: 100-42-5 EC: 202-851-5 PNEC: Identification | Identification Identi | Short Systemic Non-applicable Non-applicable 289 mg/m ³ Short Non-applicable Non-applicable Non-applicable 174,25 mg/m ³ Short S mg/L O,2 mg/kg O,04 mg/L Non-applicable | | ccupational expo ccupational expo Systemic Non-applicable 406 mg/kg 85 mg/m ³ Lcc Systemic 2,1 mg/kg 343 mg/kg 10,2 mg/m ³ Lcc n water) | sure limits 0,1 mg/m ³ 0,1 mg/m ³ Local Non-applicable |
| 2 | (EU) 2019/1831: Quartz (1 %< RCS < 10%) CAS: 14808-60-7 EC: 238-878-4 DNEL (Workers): Identification styrene CAS: 100-42-5 EC: 202-851-5 DNEL (General population): Identification styrene CAS: 100-42-5 EC: 202-851-5 PNEC: Identification styrene CAS: 100-42-5 EC: 202-851-5 PNEC: Identification styrene CAS: 100-42-5 EC: 202-851-5 PNEC: Identification | Identification Identi | Short Systemic Non-applicable Non-applicable 289 mg/m ³ Short Non-applicable Non-applicable Non-applicable 174,25 mg/m ³ Short S mg/L O,2 mg/kg O,04 mg/L Non-applicable | | ccupational expo ccupational expo Systemic Non-applicable 406 mg/kg 85 mg/m ³ Lcc Systemic 2,1 mg/kg 343 mg/kg 10,2 mg/m ³ Lcc n water) | sure limits 0,1 mg/m ³ 0,1 mg/m ³ Local Non-applicable |



BLACK CARBON

| ng: 19/3 | 12/2022 D | ate of co | mpilation: 15/11 | /2011 | Revised: 23/09/2022 | Ver | sion: 7 (Replaced 6) |
|------------------------------|---|---|---|---|--|--|--|
| CTION | 8: EXPOSURE | CONTR | OLS/PERSON | AL PROTECT | ON (continued) | | |
| В | localized extractic case of using per- information on Per information leafle All information co | on in the sonal pro rsonal Pi t provide ntained I whethe | work area as a stective equipme rotective Equipme d by the manufa nerein is a recon | collective protect ont it should have nent (storage, u acturer. For add nmendation wh | tion measure to avoid re CE marking in accord se, cleaning, maintena itional information see | exceeding dance with nce, class subsectio cation fro | 8/24/EC) it is recommended to use g the occupational exposure limits. h Directive 2016/425/EC. For more s of protection,) consult the n 7.1. m the labour risk prevention service |
| | Pictogram | | PPE | Labelling | CEN Standard | | Remarks |
| | Mandatory respiratory tract protection | | ask for gases and 's (Filter type: A) | CAT III | EN 405:2002+A1:2010 | C | place when there is a taste or smell of the contaminant inside the face mask. If the contaminant comes with warnings it is commended to use isolation equipment. |
| C | Specific protection | n for the | hands | | | | |
| | Pictogram | | PPE | Labelling | CEN Standard | | Remarks |
| | Mandatory hand protection | protectiv Nitrile, Br | sposable chemical e gloves (Material: eakthrough time: > Thickness: 0.4 mm) | | EN ISO 374-1:2016+A1:20 EN 16523-1:2015+A1:20 EN ISO 21420:2020 | 018 manuf 18 the p | The Breakthrough Time indicated by the acturer must exceed the period during wh roduct is being used. Do not use protectiv ms after the product has come into contac with skin. |
| | As the product is total reliability and | | | | | aterial car | n not be calculated in advance with |
| D | Eye and face prot | | | | | | |
| | Pictogram | | PPE | Labelling | CEN Standard | | Remarks |
| | Mandatory face protection | | nic glasses against sh/projections. | CAT II | EN 166:2002 EN ISO 4007:2018 | | daily and disinfect periodically according nanufacturer's instructions. Use if there is risk of splashing. |
| E | Body protection | | | | | | |
| | Pictogram | | PPE | Labelling | CEN Standard | | Remarks |
| | Mandatory complete body protection | protectio risks, w | able clothing for n against chemical <i>i</i> ith antistatic and roof properties | CAT III | EN 1149-1,2,3 EN 13034:2005+A1:200 EN ISO 13982- 1:2004/A1:2010 EN ISO 6529:2013 EN ISO 6530:2005 EN ISO 13688:2013 EN 464:1994 | For | r professional use only. Clean periodically ording to the manufacturer's instructions. |
| | Mandatory foot protection | protectio risk, with | ty footwear for n against chemical antistatic and heat tant properties | | EN ISO 13287:2020 EN ISO 20345:2011 EN 13832-1:2019 | Re | eplace boots at any sign of deterioration. |
| F | Additional emerge | ency mea | asures | | • | | |
| | Emergency mea | asure | S | tandards | Emergency me | easure | Standards |
| | Emergency sho | ower | | SI Z358-1 111, ISO 3864-4:20 | 11 Eyewash sta | tions | DIN 12 899 ISO 3864-1:2011, ISO 3864-4:2011 |
| In spil Spil Vo | llage of both the p latile organic co | ne comm roduct ar mpounc | unity legislation nd its container. Is: | For additional i | on of the environment nformation see subsec lowing characteristics: | tion 7.1.D | mmended to avoid environmental |



BLACK CARBON

| nting: 19/1 | · · | | Revised: 23/09/2022 | Version: 7 (Replaced 6) |
|-------------|---|--------------------------|-------------------------|-------------------------|
| SECTION | 8: EXPOSURE CONTROLS/PE | RSONAL PROT | ECTION (continued) | |
| | V.O.C. (Supply): | 17,47 % weigh | | |
| | V.O.C. density at 20 °C: | 41 kg/m ³ (41 | g/L) | |
| | Average carbon number: | 8,02 | | |
| | Average molecular weight: | 104,43 g/mol | | |
| SECTION | 9: PHYSICAL AND CHEMICAL | PROPERTIES | | |
| 9.1 Inf | formation on basic physical and | chemical prop | erties: | |
| For | complete information see the prod | uct datasheet. | | |
| Ар | pearance: | | | |
| Phy | vsical state at 20 °C: | | Liquid | |
| Арр | pearance: | | Viscous | |
| Col | our: | | Black | |
| Ode | our: | | Undefined | |
| Ode | our threshold: | | Non-applicable * | |
| Vo | latility: | | | |
| Boi | ling point at atmospheric pressure: | | 114 °C | |
| Vap | oour pressure at 20 °C: | | 2177 Pa | |
| Vap | oour pressure at 50 °C: | | 11471,63 Pa (11,47 kPa) | |
| Eva | aporation rate at 20 °C: | | Non-applicable * | |
| Pro | oduct description: | | | |
| Der | nsity at 20 °C: | | 1800 kg/m³ | |
| Rel | ative density at 20 °C: | | 1,8 | |
| Dyr | namic viscosity at 20 °C: | | 2,55 cP | |
| Kin | ematic viscosity at 20 °C: | | 1,52 mm²/s | |
| Kin | ematic viscosity at 40 °C: | | >20,5 mm²/s | |
| Cor | ncentration: | | Non-applicable * | |
| pH: | : | | Non-applicable * | |
| Vap | oour density at 20 ºC: | | Non-applicable * | |
| Par | tition coefficient n-octanol/water 20 |) °C: | Non-applicable * | |
| Sol | ubility in water at 20 °C: | | Non-applicable * | |
| Sol | ubility properties: | | Non-applicable * | |
| | composition temperature: | | Non-applicable * | |
| | Iting point/freezing point: | | Non-applicable * | |
| | mmability: | | | |
| Flas | sh Point: | | 39 °C | |
| Flai | mmability (solid, gas): | | Non-applicable * | |
| | coignition temperature: | | 345 °C | |
| | ver flammability limit: | | Not available | |
| | per flammability limit: | | Not available | |
| | rticle characteristics: | | | |
| | dian equivalent diameter: | | Non-applicable | |
| | her information: | | . F.F. Samera | |
| | formation with regard to physic | al hazard class | es: | |
| | t relevant due to the nature of the product | | | |



BLACK CARBON

| Printing: 19/12/2022 | Date of compilation: 15/11/2011 | Revised: 23/09/2022 | Version: 7 (Replaced 6) |
|----------------------|--|----------------------------------|-------------------------|
| SECTION 9: PHYSIC | CAL AND CHEMICAL PROPERTIE | S (continued) | |
| Explosive prope | rties: | Non-applicable * | |
| Oxidising prope | rties: | Non-applicable * | |
| Corrosive to me | tals: | Non-applicable * | |
| Heat of combus | tion: | Non-applicable * | |
| components: | ercentage (by mass) of flammable | Non-applicable * | |
| Surface tension | at 20 °C: | Non-applicable * | |
| Refraction index | <: | Non-applicable * | |
| *Not relevant due t | to the nature of the product, not providing info | rmation property of its hazards. | |

*Not relevant due to the nature of the product, not providing information property of its hazards

SECTION 10: STABILITY AND REACTIVITY

10.1 Reactivity:

No hazardous reactions are expected because the product is stable under recommended storage conditions. See section 7.

10.2 Chemical stability:

Chemically stable under the indicated conditions of storage, handling and use.

10.3 Possibility of hazardous reactions:

Under the specified conditions, hazardous reactions that lead to excessive temperatures or pressure are not expected.

10.4 Conditions to avoid:

Applicable for handling and storage at room temperature:

| Shock and friction | Contact with air | Increase in temperature | Sunlight | Humidity |
|--------------------|------------------|-------------------------|---------------------|----------------|
| Not applicable | Not applicable | Risk of combustion | Avoid direct impact | Not applicable |

10.5 Incompatible materials:

| Acids | Water | Oxidising materials | Combustible materials | Others |
|--------------------|----------------|---------------------|-----------------------|-------------------------------|
| Avoid strong acids | Not applicable | Avoid direct impact | Not applicable | Avoid alkalis or strong bases |

10.6 Hazardous decomposition products:

Contains susbstances highly reactive and can auto-polymerize as a result of internal peroxide accumulation. The peroxides formed in these reactions are extremely shock- and heat-sensitive.

SECTION 11: TOXICOLOGICAL INFORMATION

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008:

The experimental information related to the toxicological properties of the product itself is not available

Dangerous health implications:

In case of exposure that is repetitive, prolonged or at concentrations higher than the recommended occupational exposure limits, adverse effects on health may result, depending on the means of exposure:

A- Ingestion (acute effect):

- Acute toxicity : Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for consumption. For more information see section 3
- Corrosivity/Irritability: The consumption of a considerable dose can cause irritation in the throat, abdominal pain, nausea and vomiting.
- B- Inhalation (acute effect):
 - Acute toxicity : Based on available data, the classification criteria are not met. However, it contains substances classified as hazardous for inhalation. For more information see section 3.
 - Corrosivity/Irritability: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.
- C- Contact with the skin and the eyes (acute effect):



BLACK CARBON

| : 19/12/2022 | Date of compilation: 15/11/2011 | Revised: 23/09/2022 | Ve | rsion: 7 (Replaced 6) |) |
|--|--|---|--------------------------|--|--------------------------------------|
| FION 11: TOXI | COLOGICAL INFORMATION (contin | ued) | | | |
| - Contact | with the skin: Produces skin inflammation. with the eyes: Produces eye damage after (carcinogenicity, mutagenicity and toxicit | contact. | | | |
| as hazardou IARC: sty % EC 200-7 - Mutagen hazardous f | enicity: Based on available data, the class is for the effects mentioned. For more info rene (2A); Hydrocarbons, C10, aromatics, '53-7 (3); 2,6-di-tert-butyl-p-cresol (3); Ca icity: Based on available data, the classific or this effect. For more information see se ctive toxicity: Suspected of damaging the effects: | ormation see section 3. < 1% naphthalene (3); arbon black (2B); Quartz cation criteria are not me ection 3. | Solvent nar (1 %< RCS | ohtha (petroleum), li 5 < 10%) (1); Talc (3 | ght arom., < 0.1 3); styrene (2A) |
| hazardous v - Skin: Bas hazardous f | E- Sensitizing effects: Respiratory: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous with sensitising effects. For more information see section 3. Skin: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3. F- Specific target organ toxicity (STOT) - single exposure: | | | | |
| this effect. | vailable data, the classification criteria are For more information see section 3. Jet organ toxicity (STOT)-repeated exposu | · | contain subs | stances classified as | hazardous for |
| including de - Skin: Bas | arget organ toxicity (STOT)-repeated exp eath, serious functional disorders or morph sed on available data, the classification cri or this effect. For more information see se azard: | nological changes of toxi teria are not met, as it c | cological im | portance. | |
| | vailable data, the classification criteria are For more information see section 3. ation: | not met, as it does not | contain subs | stances classified as | hazardous for |
| Non-applicable | | | | | |
| Specific toxic | ology information on the substances | : | | | |
| | Identification | | Acu | ute toxicity | Genus |
| styrene | | LD50 c | oral | >2000 mg/kg | |
| CAS: 100-42-5 | | LD50 c | lermal | >2000 mg/kg | |
| CAS. 100 HZ S | | | halation | 12 | |
| EC: 202-851-5 | | LC50 in | Indiduon | 12 mg/L (4 h) | Rat |
| | 5 < 10%) | LC50 ii LD50 c | | >2000 mg/kg | Rat |
| EC: 202-851-5 | 5 < 10%) | | oral | | Rat |

Acute Toxicity Estimate (ATE mix):

| | Ingredient(s) of unknown toxicity | |
|------------|---------------------------------------|----------------|
| Oral | >2000 mg/kg (Calculation method) | Non-applicable |
| Dermal | >2000 mg/kg (Calculation method) | Non-applicable |
| Inhalation | 85,99 mg/L (4 h) (Calculation method) | 0 % |

11.2 Information on other hazards:

Endocrine disrupting properties

Endocrine-disrupting properties: The product fails to meet the criteria.

Other information

Non-applicable

SECTION 12: ECOLOGICAL INFORMATION

The experimental information related to the eco-toxicological properties of the product itself is not available

12.1 Toxicity:



BLACK CARBON

| rinting: | 19/12/2022 | Date of compilation: 15/1 | .1/2011 F | levised: 23/09/2022 | Version: 7 (Re | eplaced 6) |
|----------|----------------|---------------------------|----------------|------------------------|----------------|----------------|
| SECT | TON 12: ECOL | OGICAL INFORMATION (| (continued) | | | |
| | Not available | | | | | |
| 12.2 | Persistence a | nd degradability: | | | | |
| | Not available | | | | | |
| 12.3 | Bioaccumulat | ive potential: | | | | |
| | Not available | | | | | |
| 12.4 | Mobility in so | il: | | | | |
| | | Identification | At | osorption/desorption | | Volatility |
| | styrene | | Кос | Non-applicable | Henry | Non-applicable |
| | CAS: 100-42-5 | | Conclusion | Non-applicable | Dry soil | Non-applicable |
| | EC: 202-851-5 | | Surface tensio | on 3,21E-2 N/m (25 °C) | Moist soil | Non-applicable |

12.5 Results of PBT and vPvB assessment:

Product fails to meet PBT/vPvB criteria

12.6 Endocrine disrupting properties:

Endocrine-disrupting properties: The product fails to meet the criteria.

12.7 Other adverse effects:

Not described

SECTION 13: DISPOSAL CONSIDERATIONS

13.1 Waste treatment methods:

| Code | Description | Waste class (Regulation (EU) No 1357/2014) |
|------|---|---|
| | waste paint and varnish containing organic solvents or other hazardous substances packaging containing residues of or contaminated by hazardous substances | Dangerous |

Type of waste (Regulation (EU) No 1357/2014):

HP3 Flammable, HP5 Specific Target Organ Toxicity (STOT)/Aspiration Toxicity, HP10 Toxic for reproduction, HP4 Irritant — skin irritation and eye damage

Waste management (disposal and evaluation):

Consult the authorized waste service manager on the assessment and disposal operations in accordance with Annex 1 and Annex 2 (Directive 2008/98/EC). As under 15 01 (2014/955/EC) of the code and in case the container has been in direct contact with the product, it will be processed the same way as the actual product. Otherwise, it will be processed as non-dangerous residue. Waste should not be disposed of to drains. See paragraph 6.2.

Regulations related to waste management:

In accordance with Annex II of Regulation (EC) No 1907/2006 (REACH) the community or state provisions related to waste management are stated

Community legislation: Directive 2008/98/EC, 2014/955/EU, Regulation (EU) No 1357/2014

SECTION 14: TRANSPORT INFORMATION

Transport of dangerous goods by land:

With regard to ADR 2021 and RID 2021:



BLACK CARBON

| Printing: 19/12/2022 | Date of compilation: 15/11/2011 | | Revised: 23/09/2022 | Version: 7 (Replaced 6) | | | |
|---|---------------------------------|---|---|-------------------------|--|--|--|
| SECTION 14: TRANSPORT INFORMATION (continued) | | | | | | | |
| | 14.2 | UN number or ID number: UN proper shipping name: Transport hazard class(es): Labels: | UN3269 POLYESTER RESIN KIT, liqu 3 3 | id base material | | | |
| | 14.4 | Packing group: | III | | | | |
| 3 | | Environmental hazards: | No | | | | |
| | 14.6 | Special precautions for user Special regulations: | 236, 340 | | | | |
| | | Tunnel restriction code: | E | | | | |
| | | Physico-Chemical properties: | see section 9 | | | | |
| | | Limited quantities: | 5 L | | | | |
| | 14.7 | Maritime transport in bulk according to IMO instruments: | Non-applicable | | | | |
| Transport of da | ngero | us goods by sea: | | | | | |
| With regard to IM | 1DG 40 | -20: | | | | | |
| | 14.1 | UN number or ID number: | UN3269 | | | | |
| | | UN proper shipping name: | POLYESTER RESIN KIT, liqu | id base material | | | |
| she | 14.3 | Transport hazard class(es): Labels: | 3 3 | | | | |
| | 14.4 | Packing group: | 3 III | | | | |
| | | Marine pollutant: | No | | | | |
| 3 | | Special precautions for user | | | | | |
| | | Special regulations: | 340, 236 | | | | |
| | | EmS Codes: | F-E, S-D | | | | |
| | | Physico-Chemical properties: | see section 9 5 L | | | | |
| | | Limited quantities: Segregation group: | Non-applicable | | | | |
| | 14.7 | Maritime transport in bulk according to IMO instruments: | Non-applicable | | | | |
| Transport of da | naero | us goods by air: | | | | | |
| With regard to IA | - | | | | | | |
| | 14.1 | UN number or ID number: | UN3269 | | | | |
| | 14.2 | UN proper shipping name: | POLYESTER RESIN KIT, liqu | id base material | | | |
| | 14.3 | Transport hazard class(es): | 3 | | | | |
| 3 | 144 | Labels: | 3 III | | | | |
| ▼ | | Packing group: Environmental hazards: | No | | | | |
| | | Special precautions for user | | | | | |
| | | Physico-Chemical properties: | see section 9 | | | | |
| | 14.7 | Maritime transport in bulk according to IMO instruments: | Non-applicable | | | | |
| | | | | | | | |

SECTION 15: REGULATORY INFORMATION

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture: Candidate substances for authorisation under the Regulation (EC) No 1907/2006 (REACH): Non-applicable

Substances included in Annex XIV of REACH ("Authorisation List") and sunset date: Non-applicable

Regulation (EC) No 1005/2009, about substances that deplete the ozone layer: Non-applicable

Article 95, REGULATION (EU) No 528/2012: Non-applicable



Safety data sheet

This SDS is an English translation of COMMISSION REGULATION (EU) 2020/878, without any country-specific legislation

BLACK CARBON

Printing: 19/12/2022 Date of compilation: 15/11/2011 Revised: 23/09/2022 Version: 7 (Replaced 6) SECTION 15: REGULATORY INFORMATION (continued) REGULATION (EU) No 649/2012, in relation to the import and export of hazardous chemical products: Non-applicable Seveso III: Lower-tier Upper-tier Section Description requirements requirements P5c FLAMMABLE LIQUIDS 5000 50000 Limitations to commercialisation and the use of certain dangerous substances and mixtures (Annex XVII REACH, etc): Shall not be used in: and ashtravs. -tricks and jokes, -games for one or more participants, or any article intended to be used as such, even with ornamental aspects. Occupational exposure to respirable crystalline silica must be controlled pursuant to Directive (EU) 2019/130. Specific provisions in terms of protecting people or the environment: It is recommended to use the information included in this safety data sheet as a basis for conducting workplace-specific risk assessments in order to establish the necessary risk prevention measures for the handling, use, storage and disposal of this product. Other legislation: The product could be affected by sectorial legislation 15.2 Chemical safety assessment: The supplier has not carried out evaluation of chemical safety. SECTION 16: OTHER INFORMATION Legislation related to safety data sheets: The SDS shall be supplied in an official language of the country where the product is placed on the market. This safety data sheet has been designed in accordance with ANNEX II-Guide to the compilation of safety data sheets of Regulation (EC) No 1907/2006 (COMMISSION REGULATION (EU) 2020/878). Modifications related to the previous Safety Data Sheet which concerns the ways of managing risks.: COMMISSION REGULATION (EU) 2020/878 Texts of the legislative phrases mentioned in section 2: H315: Causes skin irritation. H372: Causes damage to organs through prolonged or repeated exposure. H361d: Suspected of damaging the unborn child. H226: Flammable liquid and vapour. H319: Causes serious eye irritation. Texts of the legislative phrases mentioned in section 3: The phrases indicated do not refer to the product itself; they are present merely for informative purposes and refer to the individual components which appear in section 3 CLP Regulation (EC) No 1272/2008: Acute Tox. 4: H332 - Harmful if inhaled. Eye Irrit. 2: H319 - Causes serious eye irritation. Flam. Lig. 3: H226 - Flammable liquid and vapour. Repr. 2: H361d - Suspected of damaging the unborn child. Skin Irrit. 2: H315 - Causes skin irritation. STOT RE 1: H372 - Causes damage to organs through prolonged or repeated exposure. STOT RE 2: H373 - May cause damage to organs through prolonged or repeated exposure (Inhalation). Classification procedure: Skin Irrit, 2: Calculation method STOT RE 1: Calculation method Repr. 2: Calculation method Flam. Liq. 3: Calculation method (2.6.4.3) Eye Irrit. 2: Calculation method Advice related to training: Training is recommended in order to prevent industrial risks for staff using this product and to facilitate their comprehension and

interpretation of this safety data sheet, as well as the label on the product.

Principal bibliographical sources:



BLACK CARBON

| Printing: 19/12/2022 | Date of compilation: 15/11/2011 | Revised: 23/09/2022 | Version: 7 (Replaced 6) | | | | | |
|--|---------------------------------|---------------------|-------------------------|--|--|--|--|--|
| SECTION 16: OTHE | ER INFORMATION (continued) | | | | | | | |
| http://echa.euro | opa.eu | | | | | | | |
| http://eur-lex.europa.eu | | | | | | | | |
| Abbreviations and acronyms: | | | | | | | | |
| ADR: European agreement concerning the international carriage of dangerous goods by road | | | | | | | | |
| IMDG: International maritime dangerous goods code | | | | | | | | |
| IATA: International Air Transport Association | | | | | | | | |
| ICAO: International Civil Aviation Organisation | | | | | | | | |
| COD: Chemical Oxygen Demand | | | | | | | | |
| BOD5: 5day biochemical oxygen demand | | | | | | | | |
| BCF: Bioconcentration factor | | | | | | | | |
| LD50: Lethal Dose 50 | | | | | | | | |
| LC50: Lethal Concentration 50 | | | | | | | | |
| EC50: Effective concentration 50 | | | | | | | | |
| LogPOW: Octanolwater partition coefficient Koc: Partition coefficient of organic carbon | | | | | | | | |
| UFI: unique formula identifier | | | | | | | | |
| IARC: International Agency for Research on Cancer | | | | | | | | |

The information contained in this safety data sheet is based on sources, technical knowledge and current legislation at European and state level, without being able to guarantee its accuracy. This information cannot be considered a guarantee of the properties of the product, it is simply a description of the security requirements. The occupational methodology and conditions for users of this product are not within our awareness or control, and it is ultimately the responsibility of the user to take the necessary measures to obtain the legal requirements concerning the manipulation, storage, use and disposal of chemical products. The information on this safety data sheet only refers to this product, which should not be used for needs other than those specified.