

CLEAR COAT C2007 UHS 2:1

rinting:	23/12/2022 Date of compilation: 26/06/2011 Revised: 09/11/2022 Version: 6 (Replaced 5)
SECT	TON 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING
1.1	Product identifier: CLEAR COAT C2007 UHS 2:1
	Other means of identification:
	UFI: C3K3-V0W9-600H-SE52
1.2	Relevant identified uses of the substance or mixture and uses advised against:
	Relevant uses: Car repair; paints and varnishes. For professional users only.
	Uses advised against: All uses not specified in this section or in section 7.3
1.3	Details of the supplier of the safety data sheet:
	Troton Sp. z o.o.
	Ząbrowo 14A 78-120 Gościno - Zachodniopomorskie - Polska
	Phone: +48 94 35 123 94 - Fax: +48 94 35 126 22
	troton@troton.com.pl www.troton.pl / www.troton.eu
1.4	Emergency telephone number: (8am-4pm)+48 094 35 123 94; 112
SECT	TON 2: HAZARDS IDENTIFICATION **
2.1	Classification of the substance or mixture:
	CLP Regulation (EC) No 1272/2008:
	Classification of this product has been carried out in accordance with CLP Regulation (EC) No 1272/2008.
	Aquatic Chronic 3: Hazardous to the aquatic environment, long-term hazard, Category 3, H412
	Carc. 2: Carcinogenicity, Category 2, H351
	Eye Irrit. 2: Eye irritation, Category 2, H319 Flam. Liq. 3: Flammable liquids, Category 3, H226
	Skin Irrit. 2: Skin irritation, Category 2, H315
	Skin Sens. 1A: Sensitisation, skin, Category 1A, H317 STOT RE 2: Specific target organ toxicity — Repeated exposure, Hazard Category 2 (Oral), H373
2.2	Label elements:
	CLP Regulation (EC) No 1272/2008:
	Warning
	Hazard statements:
	Aquatic Chronic 3: H412 - Harmful to aquatic life with long lasting effects.
	Carc. 2: H351 - Suspected of causing cancer.
	Eye Irrit. 2: H319 - Causes serious eye irritation. Flam. Lig. 3: H226 - Flammable liguid and vapour.
	Skin Irrit. 2: H315 - Causes skin irritation.
	Skin Sens. 1A: H317 - May cause an allergic skin reaction.
	STOT RE 2: H373 - May cause damage to organs through prolonged or repeated exposure (Oral). Precautionary statements:
	P201: Obtain special instructions before use.
	P210: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
	P280: Wear protective gloves/protective clothing/respiratory protection/eye protection/protective footwear. P302+P352: IF ON SKIN: Wash with plenty of water.
	P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to
	do. Continue rinsing.
	P308+P313: IF exposed or concerned: Get medical advice/attention. P501: Dispose of contents/container in accordance with regulations on hazardous waste or packaging and packaging waste
	respectively.
	Supplementary information:
	EUH208: Contains Hydroxyphenyl benzotriazol derivative, isobutyl methacrylate. May produce an allergic reaction.



Printing: 23/12/2022 Date of compilation: 26/06/2011 Revised: 09/11/2022 Version: 6 (Replaced 5)

SECTION 2: HAZARDS IDENTIFICATION ** (continued) Substances that contribute to the classification

Xylene; 4-methylpentan-2-one; Reaction mass of Bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and Methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate

2.3 Other hazards:

Product fails to meet PBT/vPvB criteria Endocrine-disrupting properties: The product fails to meet the criteria.

** Changes with regards to the previous version

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS **

3.1 Substance:

Non-applicable

3.2 Mixture:

Chemical description: Mixture composed of chemical products

Components:

In accordance with Annex II of Regulation (EC) No 1907/2006 (point 3), the product contains:

	Identification		Chemical name/Classification	Concentratio
CAS:	123-86-4	N-butyl acetate ⁽¹⁾	ATP CLP00	
	204-658-1 607-025-00-1 01-2119485493-29- XXXX	25-00-1 Elam Lig 3: H226: STOT SE 3: H236: El H066 - Warping		10 - <25 %
CAS:	1330-20-7	Xylene ⁽¹⁾	Self-classifie	d
	215-535-7 601-022-00-9 01-2119488216-32- XXXX	Regulation 1272/2008	Acute Tox. 4: H312+H332; Aquatic Chronic 3: H412; Asp. Tox. 1: H304; Eye Irrit. 2: H319; Flam. Liq. 3: H226; Skin Irrit. 2: H315; STOT RE 2: H373; STOT SE 3: H335 - Danger	10 - <25 %
CAS:	110-43-0	heptan-2-one ⁽¹⁾	ATP CLP00	
	203-767-1 606-024-00-3 01-2119902391-49- XXXX	Regulation 1272/2008	Acute Tox. 4: H302+H332; Flam. Liq. 3: H226 - Warning	5 - <10 %
CAS:	108-65-6	2-methoxy-1-methy	lethyl acetate ⁽²⁾ ATP ATP01	
	203-603-9 607-195-00-7 01-2119475791-29- XXXX	Regulation 1272/2008	Flam. Liq. 3: H226 - Warning	5 - <10 %
CAS:	108-10-1 203-550-1 606-004-00-4 01-2119473980-30- XXXX	4-methylpentan-2-o	ne ⁽¹⁾ ATP ATP17	
		Regulation 1272/2008	Acute Tox. 4: H332; Carc. 2: H351; Eye Irrit. 2: H319; Flam. Liq. 2: H225; STOT SE 🔅 🐼 🏈	2,5 - <5 %
CAS:	75-65-0	2-methylpropan-2-o	(1) ATP ATP01	
	200-889-7 603-005-00-1 01-2119444321-51- XXXX	Regulation 1272/2008	Acute Tox. 4: H332; Eye Irrit. 2: H319; Flam. Liq. 2: H225; STOT SE 3: H335 - Danger 🔅 🤅	1 - <2,5 %
CAS:	67-64-1	acetone ⁽¹⁾	ATP CLP00	
	200-662-2 606-001-00-8 01-2119471330-49- XXXX	Regulation 1272/2008	Eye Irrit. 2: H319; Flam. Liq. 2: H225; STOT SE 3: H336; EUH066 - Danger	1 - <2,5 %
CAS:	Non-applicable	Hydroxyphenyl benz	totriazol derivative ⁽¹⁾ ATP CLP00	
REACH:	400-830-7 607-176-00-3 01-0000015075-76- XXXX	Regulation 1272/2008	Aquatic Chronic 2: H411; Skin Sens. 1: H317 - Warning	<1 %
CAS: EC:	1065336-91-5 915-687-0		(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and Methyl Self-classifie yl-4-piperidyl sebacate ⁽¹⁾	-
REACH:	Non-applicable 01-2119491304-40- XXXX	Regulation 1272/2008	Aquatic Acute 1: H400; Aquatic Chronic 1: H410; Repr. 2: H361f; Skin Sens. 1A:	<1 %

⁽¹⁾ Substances presenting a health or environmental hazard which meet criteria laid down in Regulation (EU) N ⁽²⁾ Substance with a Union workplace exposure limit

** Changes with regards to the previous version



Printing: 23/12/2022 Date of compilation: 26/06/2011 Revised: 09/11/2022 Version: 6 (Replaced 5)

	Identification Chemical name/Classification			Concent	
CAS:	97-86-9	isobutyl methacrylat	te ⁽¹⁾	ATP ATP13	
EC: Index: REACH:	202-613-0 607-113-00-X : 01-2119488331-38- XXXX Regulation 1272/2008 Flam. Liq. 3: H226; Skin Irrit. 2: H315; Skin Sens. 1B: H317; STOT SE 3: H335 Warning	(1) (1)	<1 %		
CAS:	100-41-4	Ethylbenzene ⁽²⁾ ATP ATPO			
EC: Index: REACH:	202-849-4 601-023-00-4 1: 01-2119489370-35- XXXX	Regulation 1272/2008	Acute Tox. 4: H332; Asp. Tox. 1: H304; Flam. Liq. 2: H225; STOT RE 2: H373 - Danger	(1) 🚯 🚯	<1 9
CAS:	108-88-3	Toluene ⁽²⁾	•	Self-classified	
EC: Index: REACH:	203-625-9 601-021-00-3 01-2119471310-51- XXXX	Regulation 1272/2008	Aquatic Chronic 3: H412; Asp. Tox. 1: H304; Flam. Liq. 2: H225; Repr. 2: H361 kin Irrit. 2: H315; STOT RE 2: H373; STOT SE 3: H336 - Danger	() 🔕 🚸	<1 9

⁽²⁾ Substance with a Union workplace exposure limit

To obtain more information on the hazards of the substances consult sections 11, 12 and 16.

** Changes with regards to the previous version

SECTION 4: FIRST AID MEASURES

4.1 Description of first aid measures:

The symptoms resulting from intoxication can appear after exposure, therefore, in case of doubt, seek medical attention for direct exposure to the chemical product or persistent discomfort, showing the SDS of this product.

By inhalation:

This product is not classified as hazardous through inhalation. However, in case of intoxication symptoms it is recommended to remove the person affected from the area of exposure, provide clean air and keep at rest. Request medical attention if symptoms persist.

By skin contact:

Remove contaminated clothing and footwear, rinse skin or shower the person affected if appropriate with plenty of cold water and neutral soap. In serious cases see a doctor. If the product causes burns or freezing, clothing should not be removed as this could worsen the injury caused if it is stuck to the skin. If blisters form on the skin, these should never be burst as this will increase the risk of infection.

By eye contact:

Rinse eyes thoroughly with water for at least 15 minutes. If the injured person uses contact lenses, these should be removed unless they are stuck to the eyes, in which case removal could cause further damage. In all cases, after cleaning, a doctor should be consulted as quickly as possible with the SDS for the product.

By ingestion/aspiration:

Do not induce vomiting, but if it does happen keep the head down to avoid aspiration. Keep the person affected at rest. Rinse out the mouth and throat, as they may have been affected during ingestion.

4.2 Most important symptoms and effects, both acute and delayed:

Acute and delayed effects are indicated in sections 2 and 11.

4.3 Indication of any immediate medical attention and special treatment needed:

Non-applicable

SECTION 5: FIREFIGHTING MEASURES

5.1 Extinguishing media:

Suitable extinguishing media:

If possible use polyvalent powder fire extinguishers (ABC powder), alternatively use foam or carbon dioxide extinguishers (CO₂).

Unsuitable extinguishing media:

IT IS RECOMMENDED NOT to use full jet water as an extinguishing agent.

5.2 Special hazards arising from the substance or mixture:

As a result of combustion or thermal decomposition reactive sub-products are created that can become highly toxic and, consequently, can present a serious health risk.

Printing: 23/12/2022 Date of compilation: 26/06/2011 Revised: 09/11/2022 Version: 6 (Replaced 5)	Printing: 23/12/2022	Date of compilation: 26/06/2011	Revised: 09/11/2022	Version: 6 (Replaced 5)	
--	----------------------	---------------------------------	---------------------	-------------------------	--

SECTION 5: FIREFIGHTING MEASURES (continued)

5.3 Advice for firefighters:

Depending on the magnitude of the fire it may be necessary to use full protective clothing and self-contained breathing apparatus (SCBA). Minimum emergency facilities and equipment should be available (fire blankets, portable first aid kit,...) in accordance with Directive 89/654/EC.

Additional provisions:

Act in accordance with the Internal Emergency Plan and the Information Sheets on actions to take after an accident or other emergencies. Eliminate all sources of ignition. In case of fire, cool the storage containers and tanks for products susceptible to combustion, explosion or BLEVE as a result of high temperatures. Avoid spillage of the products used to extinguish the fire into an aqueous medium.

SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1 Personal precautions, protective equipment and emergency procedures:

For non-emergency personnel:

Isolate leaks provided that there is no additional risk for the people performing this task. Evacuate the area and keep out those without protection. Personal protection equipment must be used against potential contact with the spilt product (See section 8). Above all prevent the formation of any vapour-air flammable mixtures, through either ventilation or the use of an inert medium. Remove any source of ignition. Eliminate electrostatic charges by interconnecting all the conductive surfaces on which static electricity could form, and also ensuring that all surfaces are connected to the ground.

For emergency responders:

Wear protective equipment. Keep unprotected persons away. See section 8.

6.2 Environmental precautions:

Avoid at all cost any type of spillage into an aqueous medium. Contain the product absorbed appropriately in hermetically sealed containers. Notify the relevant authority in case of exposure to the general public or the environment.

6.3 Methods and material for containment and cleaning up:

It is recommended:

Absorb the spillage using sand or inert absorbent and move it to a safe place. Do not absorb in sawdust or other combustible absorbents. For any concern related to disposal consult section 13.

6.4 Reference to other sections:

See sections 8 and 13.

SECTION 7: HANDLING AND STORAGE

7.1 Precautions for safe handling:

A.- General precautions for safe use

Comply with the current legislation concerning the prevention of industrial risks. Keep containers hermetically sealed. Control spills and residues, destroying them with safe methods (section 6). Avoid leakages from the container. Maintain order and cleanliness where dangerous products are used.

B.- Technical recommendations for the prevention of fires and explosions

Transfer in well ventilated areas, preferably through localized extraction. Fully control sources of ignition (mobile phones, sparks,...) and ventilate during cleaning operations. Avoid the existence of dangerous atmospheres inside containers, applying inertization systems where possible. Transfer at a slow speed to avoid the creation of electrostatic charges. Against the possibility of electrostatic charges: ensure a perfect equipotential connection, always use groundings, do not wear work clothes made of acrylic fibres, preferably wearing cotton clothing and conductive footwear. Comply with the essential security requirements for equipment and systems defined in Directive 2014/34/EC (ATEX 100) and with the minimum requirements for protecting the security and health of workers under the selection criteria of Directive 1999/92/EC (ATEX 137). Consult section 10 for conditions and materials that should be avoided.

C.- Technical recommendations on general occupational hygiene

Do not eat or drink during the process, washing hands afterwards with suitable cleaning products.

D.- Technical recommendations to prevent environmental risks

Due to the danger of this product for the environment it is recommended to use it within an area containing contamination control barriers in case of spillage, as well as having absorbent material in close proximity.

7.2 Conditions for safe storage, including any incompatibilities:



CLEAR COAT C2007 UHS 2:1

Printing: 23/12/2022	Date of compilation: 26/06/2011	Revised: 09/11/2022	Version: 6 (Replaced 5)
SECTION 7: HANI	DLING AND STORAGE (continued)		
A Technical	measures for storage		
Minimum	Temp.: 15 °C		
Maximum	Temp.: 25 °C		
Maximum	time: 12 Months		
B General co	onditions for storage		
Avoid sou	rces of heat, radiation, static electricity a	and contact with food. For addition	onal information see subsection 10.5
7.3 Specific end	use(s):		

Except for the instructions already specified it is not necessary to provide any special recommendation regarding the uses of this product.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1 Control parameters:

Substances whose occupational exposure limits have to be monitored in the workplace (European OEL, not country-specific legislation):

Directive (EU) 2000/39, Directive 2004/37/EC, Directive (EU) 2006/15, Directive (EU) 2009/161, Directive (EU) 2017/164, Directive (EU) 2019/1831:

Identification	Occ	Occupational exposure limits		
N-butyl acetate	IOELV (8h)	50 ppm	241 mg/m ³	
CAS: 123-86-4 EC: 204-658-1	IOELV (STEL)	150 ppm	723 mg/m ³	
Xylene	IOELV (8h)	50 ppm	221 mg/m ³	
CAS: 1330-20-7 EC: 215-535-7	IOELV (STEL)	100 ppm	442 mg/m ³	
heptan-2-one	IOELV (8h)	50 ppm	238 mg/m ³	
CAS: 110-43-0 EC: 203-767-1	IOELV (STEL)	100 ppm	475 mg/m ³	
2-methoxy-1-methylethyl acetate	IOELV (8h)	50 ppm	275 mg/m ³	
CAS: 108-65-6 EC: 203-603-9	IOELV (STEL)	100 ppm	550 mg/m ³	
4-methylpentan-2-one	IOELV (8h)	20 ppm	83 mg/m ³	
CAS: 108-10-1 EC: 203-550-1	IOELV (STEL)	50 ppm	208 mg/m ³	
acetone	IOELV (8h)	500 ppm	1210 mg/m ³	
CAS: 67-64-1 EC: 200-662-2	IOELV (STEL)			
Ethylbenzene	IOELV (8h)	100 ppm	442 mg/m ³	
CAS: 100-41-4 EC: 202-849-4	IOELV (STEL)	200 ppm	884 mg/m ³	
Toluene	IOELV (8h)	50 ppm	192 mg/m ³	
CAS: 108-88-3 EC: 203-625-9	IOELV (STEL)	100 ppm	384 mg/m ³	

DNEL (Workers):

		Short	Short exposure		Long exposure	
Identification		Systemic	Local	Systemic	Local	
N-butyl acetate	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable	
CAS: 123-86-4	Dermal	11 mg/kg	Non-applicable	11 mg/kg	Non-applicable	
EC: 204-658-1	Inhalation	600 mg/m ³	600 mg/m ³	300 mg/m ³	300 mg/m ³	
Xylene	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable	
CAS: 1330-20-7	Dermal	Non-applicable	Non-applicable	212 mg/kg	Non-applicable	
EC: 215-535-7	Inhalation	442 mg/m ³	442 mg/m ³	221 mg/m ³	221 mg/m ³	
heptan-2-one	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable	
CAS: 110-43-0	Dermal	Non-applicable	Non-applicable	54,27 mg/kg	Non-applicable	
EC: 203-767-1	Inhalation	1516 mg/m ³	Non-applicable	394,25 mg/m ³	Non-applicable	
2-methoxy-1-methylethyl acetate	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable	
CAS: 108-65-6	Dermal	Non-applicable	Non-applicable	796 mg/kg	Non-applicable	
EC: 203-603-9	Inhalation	Non-applicable	550 mg/m ³	275 mg/m ³	Non-applicable	
4-methylpentan-2-one	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable	
CAS: 108-10-1	Dermal	Non-applicable	Non-applicable	11,8 mg/kg	Non-applicable	
EC: 203-550-1	Inhalation	208 mg/m ³	208 mg/m ³	83 mg/m ³	83 mg/m ³	



Printing: 23/12/2022

Date of compilation: 26/06/2011

Revised: 09/11/2022

Version: 6 (Replaced 5)

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION (continued)

		Short	exposure	Long exposure	
Identification		Systemic	Local	Systemic	Local
2-methylpropan-2-ol	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
CAS: 75-65-0	Dermal	Non-applicable	Non-applicable	5,5 mg/kg	Non-applicable
EC: 200-889-7	Inhalation	214 mg/m ³	Non-applicable	2,7 mg/m ³	Non-applicable
acetone	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
CAS: 67-64-1	Dermal	Non-applicable	Non-applicable	186 mg/kg	Non-applicable
EC: 200-662-2	Inhalation	Non-applicable	2420 mg/m ³	1210 mg/m ³	Non-applicable
Hydroxyphenyl benzotriazol derivative	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
CAS: Non-applicable	Dermal	Non-applicable	Non-applicable	0,5 mg/kg	Non-applicable
EC: 400-830-7	Inhalation	Non-applicable	Non-applicable	0,35 mg/m ³	Non-applicable
Reaction mass of Bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and Methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
CAS: 1065336-91-5	Dermal	Non-applicable	Non-applicable	0,5 mg/kg	Non-applicable
EC: 915-687-0	Inhalation	Non-applicable	Non-applicable	0,68 mg/m ³	Non-applicable
isobutyl methacrylate	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
CAS: 97-86-9	Dermal	Non-applicable	Non-applicable	5 mg/kg	Non-applicable
EC: 202-613-0	Inhalation	Non-applicable	Non-applicable	415,9 mg/m ³	409 mg/m ³
Ethylbenzene	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
CAS: 100-41-4	Dermal	Non-applicable	Non-applicable	180 mg/kg	Non-applicable
EC: 202-849-4	Inhalation	Non-applicable	293 mg/m ³	77 mg/m ³	Non-applicable
Toluene	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
CAS: 108-88-3	Dermal	Non-applicable	Non-applicable	384 mg/kg	Non-applicable
EC: 203-625-9	Inhalation	384 mg/m ³	384 mg/m ³	192 mg/m ³	192 mg/m ³

DNEL (General population):

		Short e	exposure	Long e	xposure
Identification		Systemic	Local	Systemic	Local
N-butyl acetate	Oral	2 mg/kg	Non-applicable	2 mg/kg	Non-applicable
CAS: 123-86-4	Dermal	6 mg/kg	Non-applicable	6 mg/kg	Non-applicable
EC: 204-658-1	Inhalation	300 mg/m ³	300 mg/m ³	35,7 mg/m ³	35,7 mg/m ³
Xylene	Oral	Non-applicable	Non-applicable	12,5 mg/kg	Non-applicable
CAS: 1330-20-7	Dermal	Non-applicable	Non-applicable	125 mg/kg	Non-applicable
EC: 215-535-7	Inhalation	260 mg/m ³	260 mg/m ³	65,3 mg/m ³	65,3 mg/m ³
heptan-2-one	Oral	Non-applicable	Non-applicable	23,32 mg/kg	Non-applicable
CAS: 110-43-0	Dermal	Non-applicable	Non-applicable	23,32 mg/kg	Non-applicable
EC: 203-767-1	Inhalation	Non-applicable	Non-applicable	84,31 mg/m ³	Non-applicable
2-methoxy-1-methylethyl acetate	Oral	Non-applicable	Non-applicable	36 mg/kg	Non-applicable
CAS: 108-65-6	Dermal	Non-applicable	Non-applicable	320 mg/kg	Non-applicable
EC: 203-603-9	Inhalation	Non-applicable	Non-applicable	33 mg/m ³	33 mg/m ³
4-methylpentan-2-one	Oral	Non-applicable	Non-applicable	4,2 mg/kg	Non-applicable
CAS: 108-10-1	Dermal	Non-applicable	Non-applicable	4,2 mg/kg	Non-applicable
EC: 203-550-1	Inhalation	155,2 mg/m ³	155,2 mg/m ³	14,7 mg/m ³	14,7 mg/m ³
2-methylpropan-2-ol	Oral	Non-applicable	Non-applicable	0,3 mg/kg	Non-applicable
CAS: 75-65-0	Dermal	Non-applicable	Non-applicable	2,7 mg/kg	Non-applicable
EC: 200-889-7	Inhalation	159,8 mg/m ³	Non-applicable	0,5 mg/m ³	Non-applicable
acetone	Oral	Non-applicable	Non-applicable	62 mg/kg	Non-applicable
CAS: 67-64-1	Dermal	Non-applicable	Non-applicable	62 mg/kg	Non-applicable
EC: 200-662-2	Inhalation	Non-applicable	Non-applicable	200 mg/m ³	Non-applicable
Hydroxyphenyl benzotriazol derivative	Oral	Non-applicable	Non-applicable	0,025 mg/kg	Non-applicable
CAS: Non-applicable	Dermal	Non-applicable	Non-applicable	0,25 mg/kg	Non-applicable
EC: 400-830-7	Inhalation	Non-applicable	Non-applicable	0,085 mg/m ³	Non-applicable



ON 8: EXPOSURE CONTROLS/PERSONAL		in (continued)			
		Short	: exposure	Lo	ong exposure
Identification		Systemic	Local	Systemic	
Reaction mass of Bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and Methyl 1,2,2,6,6-pentamethyl-4-piperidyl	Oral	Non-applicable	Non-applicable	0,05 mg/kg	Non-applical
sebacate CAS: 1065336-91-5	Dermal	Non-applicable	Non-applicable	0,25 mg/kg	Non-applical
EC: 915-687-0	Inhalation	Non-applicable	Non-applicable	0,17 mg/m ³	Non-applicat
isobutyl methacrylate	Oral	Non-applicable	Non-applicable	Non-applicable	
CAS: 97-86-9	Dermal	Non-applicable	Non-applicable	3 mg/kg	Non-applicat
EC: 202-613-0	Inhalation	Non-applicable	Non-applicable	66,5 mg/m ³	366,4 mg/m
Ethylbenzene	Oral	Non-applicable	Non-applicable	1,6 mg/kg	Non-applical
CAS: 100-41-4	Dermal	Non-applicable	Non-applicable	Non-applicable	
EC: 202-849-4	Inhalation	Non-applicable	Non-applicable	15 mg/m ³	Non-applicat
Toluene	Oral	Non-applicable	Non-applicable	8,13 mg/kg	Non-applicat
CAS: 108-88-3	Dermal	Non-applicable	Non-applicable	226 mg/kg	Non-applicat
EC: 203-625-9	Inhalation	226 mg/m ³	226 mg/m ³	56,5 mg/m ³	56,5 mg/m ³
PNEC:	1	220	220	0070 mg/m	00,0 mg/m
Identification					
N-butyl acetate	STP	35,6 mg/L	Fresh water		0,18 mg/L
CAS: 123-86-4	Soil	0,09 mg/kg	Marine water		0,018 mg/L
EC: 204-658-1	Intermittent	0,36 mg/L	Sediment (Fresh	n water)	0,981 mg/kg
	Oral	Non-applicable	Sediment (Marin		0,098 mg/kg
Xylene	STP	6,58 mg/L	Fresh water	,	0,327 mg/L
CAS: 1330-20-7	Soil	2,31 mg/kg	Marine water		0,327 mg/L
EC: 215-535-7	Intermittent	0,327 mg/L	Sediment (Fresh	n water)	12,46 mg/kg
	Oral	Non-applicable	Sediment (Marin		12,46 mg/kg
heptan-2-one	STP	12,5 mg/L	Fresh water	,	0,098 mg/L
CAS: 110-43-0	Soil	0,321 mg/kg	Marine water		0,01 mg/L
EC: 203-767-1	Intermittent	0,982 mg/L	Sediment (Fresh	h water)	1,89 mg/kg
	Oral	Non-applicable	Sediment (Marin	ne water)	0,189 mg/kg
2-methoxy-1-methylethyl acetate	STP	100 mg/L	Fresh water		0,635 mg/L
CAS: 108-65-6	Soil	0,29 mg/kg	Marine water		0,064 mg/L
EC: 203-603-9	Intermittent	6,35 mg/L	Sediment (Fresh	n water)	3,29 mg/kg
	Oral	Non-applicable	Sediment (Marin		0,329 mg/kg
4-methylpentan-2-one	STP	27,5 mg/L	Fresh water		0,6 mg/L
CAS: 108-10-1	Soil	1,3 mg/kg	Marine water		0,06 mg/L
EC: 203-550-1	Intermittent	1,5 mg/L	Sediment (Fresh	n water)	8,27 mg/kg
	Oral	Non-applicable	Sediment (Marin		0,83 mg/kg
2-methylpropan-2-ol	STP	690 mg/L	Fresh water		2 mg/L
CAS: 75-65-0	Soil	1 mg/kg	Marine water		0,2 mg/L
EC: 200-889-7	Intermittent	9,33 mg/L	Sediment (Fresh	n water)	8,04 mg/kg
	Oral	88700 g/kg	Sediment (Marin	ne water)	0,804 mg/kg
acetone	STP	100 mg/L	Fresh water		10,6 mg/L
CAS: 67-64-1	Soil	29,5 mg/kg	Marine water		1,06 mg/L
EC: 200-662-2	Intermittent	21 mg/L	Sediment (Fresh	n water)	30,4 mg/kg
	Oral	Non-applicable	Sediment (Marin	ne water)	3,04 mg/kg
Hydroxyphenyl benzotriazol derivative	STP	10 mg/L	Fresh water		0,002 mg/L
CAS: Non-applicable	Soil	2 mg/kg	Marine water		0 mg/L
EC: 400-830-7	Intermittent	0,028 mg/L	Sediment (Fresh	n water)	3,37 mg/kg
	Oral	Non-applicable	Sediment (Marin		0,337 mg/kg



Printing: 23/12/2022 Date of compilation: 26/06/2011

Revised: 09/11/2022

Version: 6 (Replaced 5)

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION (continued)

Identification				
Reaction mass of Bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and Methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate	STP	1 mg/L	Fresh water	0,002 mg/L
CAS: 1065336-91-5	Soil	0,21 mg/kg	Marine water	0 mg/L
EC: 915-687-0	Intermittent	0,009 mg/L	Sediment (Fresh water)	1,05 mg/kg
	Oral	Non-applicable	Sediment (Marine water)	0,11 mg/kg
isobutyl methacrylate	STP	10 mg/L	Fresh water	0,021 mg/L
CAS: 97-86-9	Soil	1,16 mg/kg	Marine water	0,002 mg/L
EC: 202-613-0	Intermittent	0,2 mg/L	Sediment (Fresh water)	5,89 mg/kg
	Oral	Non-applicable	Sediment (Marine water)	0,589 mg/kg
Ethylbenzene	STP	9,6 mg/L	Fresh water	0,1 mg/L
CAS: 100-41-4	Soil	2,68 mg/kg	Marine water	0,01 mg/L
EC: 202-849-4	Intermittent	0,1 mg/L	Sediment (Fresh water)	13,7 mg/kg
	Oral	0,02 g/kg	Sediment (Marine water)	1,37 mg/kg
Toluene	STP	13,61 mg/L	Fresh water	0,68 mg/L
CAS: 108-88-3	Soil	2,89 mg/kg	Marine water	0,68 mg/L
EC: 203-625-9	Intermittent	0,68 mg/L	Sediment (Fresh water)	16,39 mg/kg
	Oral	Non-applicable	Sediment (Marine water)	16,39 mg/kg

8.2 Exposure controls:

A.- Individual protection measures, such as personal protective equipment

As a preventative measure it is recommended to use basic Personal Protective Equipment, with the corresponding <<CE marking>> in accordance with Regulation (EU) 2016/425. For more information on Personal Protective Equipment (storage, use, cleaning, maintenance, class of protection,...) consult the information leaflet provided by the manufacturer. For more information see subsection 7.1. All information contained herein is a recommendation which needs some specification from the labour risk prevention services as it is not known whether the company has additional measures at its disposal.

B.- Respiratory protection

Pictogram	PPE	Labelling	CEN Standard	Remarks
Mandatory respiratory tract protection	Filter mask for gases and vapours (Filter type: A)	CAT III	EN 405:2002+A1:2010	Replace when there is a taste or smell of the contaminant inside the face mask. If the contaminant comes with warnings it is recommended to use isolation equipment.

C.- Specific protection for the hands

Pictogram	PPE	Labelling	CEN Standard	Remarks
Mandatory hand protection	NON-disposable chemical protective gloves (Material: Latex (natural rubber), Breakthrough time: > 480 min, Thickness: 0.4 mm)		EN ISO 374-1:2016+A1:2018 EN 16523-1:2015+A1:2018 EN ISO 21420:2020	The Breakthrough Time indicated by the manufacturer must exceed the period during which the product is being used. Do not use protective creams after the product has come into contact with skin.

As the product is a mixture of several substances, the resistance of the glove material can not be calculated in advance with total reliability and has therefore to be checked prior to the application.

D.- Eye and face protection

	Pictogram	PPE	Labelling	CEN Standard	Remarks
	Mandatory face protection	Panoramic glasses against splash/projections.	CAT II	EN 166:2002 EN ISO 4007:2018	Clean daily and disinfect periodically according to the manufacturer's instructions. Use if there is a risk of splashing.
E	Body protection				



	0, EVDACUDE					ontinuod)		
NOT	8: EXPOSURE	CONTR	COLS/PERSON	AL PROTECT	ION (C	ontinued)		
	Pictogram		PPE	Labelling		CEN Standard		Remarks
	Mandatory complete body protection	protectio risks, w	sable clothing for n against chemical vith antistatic and roof properties	CAT III	EN 13 1 EN EN	EN 1149-1,2,3 034:2005+A1:2009 EN ISO 13982- :2004/A1:2010 I ISO 6529:2013 I ISO 6530:2005 ISO 13688:2013 EN 464:1994		professional use only. Clean periodicall ording to the manufacturer's instruction
	Mandatory foot protection	protectio risk, with	ty footwear for on against chemical a antistatic and heat stant properties		EN	ISO 13287:2020 ISO 20345:2011 N 13832-1:2019	Re	place boots at any sign of deterioration.
F	Additional emerge	ency mea	asures					
	Emergency mea	isure	St	tandards		Emergency measu	ıre	Standards
	Emergency sho	ower		SI Z358-1 11, ISO 3864-4:2	011	Eyewash station	S	DIN 12 899 ISO 3864-1:2011, ISO 3864-4:201:
	Average molecula 9: PHYSICAL A			56 g/mol PERTIES				
	ormation on bas				es:			
	complete informa	tion see	the product data	asheet.				
	pearance: sical state at 20 º	c.		Liqu	uid			
	earance:	с.		Flui				
Colo					ourless			
Odo					iracterist	ic		
	our threshold:				n-applica			
Vol	atility:							
	ing point at atmos	spheric p	pressure:	112	°C			
	our pressure at 2				0 Pa			
	our pressure at 5			118	09,82 P	a (11,81 kPa)		
	poration rate at 2				n-applica			
	duct description							
Pro								
	nsity at 20 °C:			990	kg/m³			
Der	-				kg/m³ n-applica	ble *		
Der Rela	nsity at 20 °C:	°C:		Nor	•	ble *		

- CONTINUED ON NEXT PAGE -

*Not relevant due to the nature of the product, not providing information property of its hazards.

Kinematic viscosity at 20 °C:

2724,52 mm²/s



Printing:	23/12/2022	Date of compilation: 26/06/2011	Revised: 09/11/2022	Version: 6 (Replaced 5)
SECT	TION 9: PHYSIC	AL AND CHEMICAL PROPERTIE	S (continued)	
	Kinematic viscosi	ity at 40 °C:	Non-applicable *	
	Concentration:		Non-applicable *	
	pH:		Non-applicable *	
	Vapour density a	t 20 ºC:	Non-applicable *	
	Partition coefficie	ent n-octanol/water 20 °C:	Non-applicable *	
	Solubility in wate	er at 20 °C:	Non-applicable *	
	Solubility propert	ties:	Non-applicable *	
	Decomposition te	emperature:	Non-applicable *	
	Melting point/free	ezing point:	Non-applicable *	
	Flammability:			
	Flash Point:		34 °C	
	Flammability (sol	lid, gas):	Non-applicable *	
	Autoignition temp	perature:	315 °C	
	Lower flammabili	ity limit:	Not available	
	Upper flammabili	ity limit:	Not available	
	Particle charac	teristics:		
	Median equivaler	nt diameter:	Non-applicable	
9.2	Other informat	tion:		
	Information wi	ith regard to physical hazard clas	ises:	
	Explosive propert	ties:	Non-applicable *	
	Oxidising propert	ties:	Non-applicable *	
	Corrosive to meta	als:	Non-applicable *	
	Heat of combusti	ion:	Non-applicable *	
	components:	rcentage (by mass) of flammable	Non-applicable *	
	Other safety ch			
	Surface tension a	at 20 °C:	Non-applicable *	
	Refraction index:	:	Non-applicable *	
	*Not relevant due to	the nature of the product, not providing info	rmation property of its hazards.	

1	Reactivity:				
	No hazardous reactions are	expected because the	product is stable under reco	mmended storage condit	tions. See section 7.
2	Chemical stability:				
	Chemically stable under the	indicated conditions of	storage, handling and use.		
;	Possibility of hazardous	reactions:			
	-				
	Under the specified condition	ons, hazardous reactions	s that lead to excessive tem	peratures or pressure are	e not expected.
ŀ	Under the specified condition Conditions to avoid:	ons, hazardous reactions	s that lead to excessive tem	peratures or pressure are	e not expected.
	Conditions to avoid: Applicable for handling and	storage at room tempe	rature:		
ŀ	Conditions to avoid:			peratures or pressure are Sunlight Avoid direct impact	e not expected. Humidity Not applicable
_	Conditions to avoid: Applicable for handling and Shock and friction	storage at room tempe Contact with air Not applicable	rature: Increase in temperature	Sunlight	Humidity
5	Conditions to avoid: Applicable for handling and Shock and friction Not applicable	storage at room tempe Contact with air Not applicable	rature: Increase in temperature	Sunlight	Humidity



CLEAR COAT C2007 UHS 2:1

Printing: 23/12/2022 Date of compilation: 26/06/2011 Revised: 09/11/2022 Version: 6 (Replaced 5) SECTION 10: STABILITY AND REACTIVITY (continued) Contains substances which require external energy for spontaneous decomposition. Form explosive peroxides when distilled, evaporated or otherwise concentrated. SECTION 11: TOXICOLOGICAL INFORMATION ** 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008: The experimental information related to the toxicological properties of the product itself is not available **Dangerous health implications:** In case of exposure that is repetitive, prolonged or at concentrations higher than the recommended occupational exposure limits, adverse effects on health may result, depending on the means of exposure: A- Ingestion (acute effect): - Acute toxicity : Based on available data, the classification criteria are not met, however, it contains substances classified as dangerous for consumption. For more information see section 3. Corrosivity/Irritability: The consumption of a considerable dose can cause irritation in the throat, abdominal pain, nausea and vomiting B- Inhalation (acute effect): - Acute toxicity : Based on available data, the classification criteria are not met. However, it contains substances classified as hazardous for inhalation. For more information see section 3. Corrosivity/Irritability: Based on available data, the classification criteria are not met. However, it contains substances classified as hazardous for inhalation. For more information see section 3. C- Contact with the skin and the eyes (acute effect): - Contact with the skin: Produces skin inflammation. Contact with the eyes: Produces eye damage after contact. D- CMR effects (carcinogenicity, mutagenicity and toxicity to reproduction): Carcinogenicity: Exposure to this product can cause cancer. For more specific information on the possible health effects see section 2. IARC: 4-methylpentan-2-one (2B); Xylene (3); Ethylbenzene (2B); Toluene (3) Mutagenicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3. Reproductive toxicity: Based on available data, the classification criteria are not met. However, it does contain substances classified as hazardous for this effect. For more information see section 3. E- Sensitizing effects: - Respiratory: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous with sensitising effects. For more information see section 3. Skin: Prolonged contact with the skin can result in episodes of allergic contact dermatitis. F- Specific target organ toxicity (STOT) - single exposure: Based on available data, the classification criteria are not met. However, it contains substances classified as hazardous for inhalation. For more information see section 3. G- Specific target organ toxicity (STOT)-repeated exposure: - Specific target organ toxicity (STOT)-repeated exposure: Exposure in high concentration can interfere with the central nervous system causing headache, dizziness, vertigo, nausea, vomiting, confusion, and in serious cases, loss of consciousness. Skin: Based on available data, the classification criteria are not met. However, it does contain substances which are classified as dangerous due to repetitive exposure. For more information see section 3. H- Aspiration hazard: Based on available data, the classification criteria are not met. However, it does contain substances classified as hazardous for this effect. For more information see section 3. Other information: Non-applicable Specific toxicology information on the substances:

** Changes with regards to the previous version



	CAL INFORMATION ** (continued)			
	Identification		Acute toxicity	Ge
N-butyl acetate		LD50 oral	12789 mg/kg	R
CAS: 123-86-4		LD50 dermal	14112 mg/kg	Ra
EC: 204-658-1		LC50 inhalation	n 23,4 mg/L (4 h)	F
2-methylpropan-2-ol		LD50 oral	3500 mg/kg	F
CAS: 75-65-0		LD50 dermal	>2000 mg/kg	
EC: 200-889-7		LC50 inhalation	n 11 mg/L (ATEi)	
acetone		LD50 oral	5800 mg/kg	F
CAS: 67-64-1		LD50 dermal	7426 mg/kg	Ra
EC: 200-662-2		LC50 inhalation	n 76 mg/L (4 h)	F
heptan-2-one		LD50 oral	1600 mg/kg	F
CAS: 110-43-0		LD50 dermal	>2000 mg/kg	
EC: 203-767-1		LC50 inhalation	n 11 mg/L (4 h)	F
2-methoxy-1-methylethyl ace	tate	LD50 oral	8532 mg/kg	F
CAS: 108-65-6		LD50 dermal	5100 mg/kg	F
EC: 203-603-9		LC50 inhalation	n 30 mg/L (4 h)	F
4-methylpentan-2-one		LD50 oral	>2000 mg/kg	
CAS: 108-10-1		LD50 dermal	>2000 mg/kg	
EC: 203-550-1		LC50 inhalation	n 11 mg/L (4 h)	I
Xylene		LD50 oral	2100 mg/kg	
CAS: 1330-20-7		LD50 dermal	1100 mg/kg	F
EC: 215-535-7		LC50 inhalation	n 11 mg/L (ATEi)	
Hydroxyphenyl benzotriazol d	lerivative	LD50 oral	>2000 mg/kg	
CAS: Non-applicable		LD50 dermal	>2000 mg/kg	
EC: 400-830-7		LC50 inhalation	n >20 mg/L	
Reaction mass of Bis(1,2,2,6,6 pentamethyl-4-piperidyl sebao	6-pentamethyl-4-piperidyl) sebacate and Methyl 1,2,2,6,6 cate	LD50 oral	3230 mg/kg	ł
CAS: 1065336-91-5		LD50 dermal	>2000 mg/kg	
EC: 915-687-0		LC50 inhalation	n >20 mg/L	
isobutyl methacrylate		LD50 oral	9600 mg/kg	I
CAS: 97-86-9		LD50 dermal	>2000 mg/kg	
EC: 202-613-0		LC50 inhalation	n >20 mg/L	
Ethylbenzene		LD50 oral	3500 mg/kg	I
CAS: 100-41-4		LD50 dermal	15354 mg/kg	Ra
EC: 202-849-4		LC50 inhalation	n 17,2 mg/L (4 h)	I
Toluene		LD50 oral	5580 mg/kg	I
CAS: 108-88-3		LD50 dermal	12124 mg/kg	I
EC: 203-625-9		LC50 inhalation	n 28,1 mg/L (4 h)	I
Acute Toxicity Estimat	te (ATE mix):			
	ATE mix		Ingredient(s) of unknow	own toxicity
Oral	22857,14 mg/kg (Calculation method)		0 %	
Dermal	7971,01 mg/kg (Calculation method)		0 %	

11.2 Information on other hazards:

Endocrine disrupting properties

Endocrine-disrupting properties: The product fails to meet the criteria.

Other information

Non-applicable

** Changes with regards to the previous version

** Changes with regards to the previous version



CLEAR COAT C2007 UHS 2:1

Printing: 23/12/2022

Date of compilation: 26/06/2011

Revised: 09/11/2022

Version: 6 (Replaced 5)

SECTION 12: ECOLOGICAL INFORMATION **

The experimental information related to the eco-toxicological properties of the product itself is not available

12.1 Toxicity:

Acute toxicity:

Identification		Concentration	Species	Genus
N-butyl acetate	LC50	Non-applicable		
CAS: 123-86-4	EC50	Non-applicable		
EC: 204-658-1	EC50	675 mg/L (72 h)	Scenedesmus subspicatus	Algae
Xylene	LC50	>10 - 100 mg/L (96 h)		Fish
CAS: 1330-20-7	EC50	>10 - 100 mg/L (48 h)		Crustacear
EC: 215-535-7	EC50	>10 - 100 mg/L (72 h)		Algae
heptan-2-one	LC50	131 mg/L (96 h)	Pimephales promelas	Fish
CAS: 110-43-0	EC50	Non-applicable		
EC: 203-767-1	EC50	Non-applicable		
2-methoxy-1-methylethyl acetate	LC50	161 mg/L (96 h)	Pimephales promelas	Fish
CAS: 108-65-6	EC50	481 mg/L (48 h)	Daphnia sp.	Crustacear
EC: 203-603-9	EC50	Non-applicable		
4-methylpentan-2-one	LC50	900 mg/L (48 h)	Leuciscus idus	Fish
CAS: 108-10-1	EC50	862 mg/L (24 h)	Daphnia magna	Crustacear
EC: 203-550-1	EC50	980 mg/L (48 h)	Scenedesmus subspicatus	Algae
2-methylpropan-2-ol	LC50	961 mg/L (96 h)	Pimephales promelas	Fish
CAS: 75-65-0	EC50	Non-applicable		
EC: 200-889-7	EC50	Non-applicable		
acetone	LC50	5540 mg/L (96 h)	Oncorhynchus mykiss	Fish
CAS: 67-64-1	EC50	8800 mg/L (48 h)	Daphnia pulex	Crustacea
EC: 200-662-2	EC50	3400 mg/L (48 h)	Chlorella pyrenoidosa	Algae
Hydroxyphenyl benzotriazol derivative	LC50	>1 - 10 mg/L (96 h)		Fish
CAS: Non-applicable	EC50	>1 - 10 mg/L (48 h)		Crustacea
EC: 400-830-7	EC50	>1 - 10 mg/L (72 h)		Algae
Reaction mass of Bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and Methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate	LC50	0,9 mg/L (96 h)	Danio rerio	Fish
CAS: 1065336-91-5	EC50	Non-applicable		
EC: 915-687-0	EC50	1,7 mg/L (72 h)	Desmodesmus subspicatus	Algae
isobutyl methacrylate	LC50	20 mg/L (96 h)	Oncorhynchus mykiss	Fish
CAS: 97-86-9	EC50	23 mg/L (48 h)	Daphnia magna	Crustacea
EC: 202-613-0	EC50	0,29 mg/L (96 h)	Selenastrum capricornutum	Algae
Ethylbenzene	LC50	42,3 mg/L (96 h)	Pimephales promelas	Fish
CAS: 100-41-4	EC50	75 mg/L (48 h)	Daphnia magna	Crustacea
EC: 202-849-4	EC50	63 mg/L (3 h)	Chlorella vulgaris	Algae
Toluene	LC50	13 mg/L (96 h)	Carassius auratus	Fish
CAS: 108-88-3	EC50	11,5 mg/L (48 h)	Daphnia magna	Crustacea
EC: 203-625-9	EC50	Non-applicable	-	
Chronic toxicity:		-	•	•
Identification		Concentration	Species	Genus
N-butyl acetate	NOEC	Non-applicable		
CAS: 123-86-4 EC: 204-658-1	NOEC	23,2 mg/L	Daphnia magna	Crustacea
Xylene	NOEC	1,3 mg/L	Oncorhynchus mykiss	Fish
CAS: 1330-20-7 EC: 215-535-7	NOEC	1,17 mg/L	Ceriodaphnia dubia	Crustacea
2-methoxy-1-methylethyl acetate	NOEC	47,5 mg/L	Oryzias latipes	Fish
CAS: 108-65-6 EC: 203-603-9	NOEC	100 mg/L	Daphnia magna	Crustacea
4-methylpentan-2-one	NOEC	Non-applicable		2. 2000000
	NOEC			

** Changes with regards to the previous version

CAS: 108-10-1 EC: 203-550-1

- CONTINUED ON NEXT PAGE -

78 mg/L

NOEC

Crustacean

Daphnia magna



ECT	ION 12: ECOLOGICAL INFORMATION ** ((conti	inued)					
	Identification			Concentration		Cassis		Conus
	Identification		11050	Concentration		Specie		Genus
	2-methylpropan-2-ol		NOEC	332 mg/L		Clarias Gari		Fish
	CAS: 75-65-0 EC: 200-889-7		NOEC	100 mg/L		Daphnia m	nagna	Crustacea
	acetone		NOEC	Non-applicable				
	CAS: 67-64-1 EC: 200-662-2		NOEC	2212 mg/L		Daphnia m	nagna	Crustacea
	Reaction mass of Bis(1,2,2,6,6-pentamethyl-4-piperidyl) se and Methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate	ebacate	NOEC	Non-applicable				
	CAS: 1065336-91-5 EC: 915-687-0		NOEC	1 mg/L		Daphnia m	nagna	Crustacear
	Ethylbenzene		NOEC	Non-applicable				
	CAS: 100-41-4 EC: 202-849-4		NOEC	0,96 mg/L		Ceriodaphni	a dubia	Crustacea
2.2	Persistence and degradability: Substance-specific information:							
	Identification		D	egradability		Biode	egradabilit	v
	N-butyl acetate	BOD		Non-applicable	Conce	ntration	-	on-applicable
	CAS: 123-86-4	COD		Non-applicable	Period			days
							_	uays 4 %
	EC: 204-658-1		5/COD -	Non-applicable	_	degradable		
	Xylene	BOD	5	Non-applicable		ntration		on-applicable
	CAS: 1330-20-7	COD	- 1005	Non-applicable	Period			8 days
	EC: 215-535-7		5/COD	Non-applicable	% Bio	degradable		8 %
	2-methoxy-1-methylethyl acetate	BODS	5	Non-applicable	Conce	ntration	78	85 mg/L
	CAS: 108-65-6	COD		Non-applicable	Period		8	days
	EC: 203-603-9	BODS	5/COD	Non-applicable	% Bio	degradable	10	00 %
	4-methylpentan-2-one	BOD	5	2,06 g O2/g	Conce	ntration	10	00 mg/L
	CAS: 108-10-1	COD		2,16 g O2/g	Period		14	4 days
	EC: 203-550-1	BOD	5/COD	0,95	% Bio	degradable	84	4 %
	acetone	BOD	5	Non-applicable	Conce	ntration	10	00 mg/L
	CAS: 67-64-1	COD		Non-applicable	Period		28	8 days
	EC: 200-662-2	BOD	5/COD	Non-applicable	% Bio	degradable		6 %
	Reaction mass of Bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and Methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate	BOD		Non-applicable		ntration		0 mg/L
	CAS: 1065336-91-5	COD		Non-applicable	Period		28	8 days
	EC: 915-687-0	BOD	5/COD	Non-applicable	% Bio	degradable	38	8 %
	Ethylbenzene	BOD	5	Non-applicable	Conce	ntration	10	00 mg/L
	CAS: 100-41-4	COD		Non-applicable	Period			4 days
	EC: 202-849-4		5/COD	Non-applicable		degradable		0 %
	Toluene	BOD		2,5 g O2/g		ntration	1(00 mg/L
	CAS: 108-88-3	COD		Non-applicable	Period			4 days
	EC: 203-625-9	-	5/COD	Non-applicable		degradable		00 %
2.3	Bioaccumulative potential:				- 2.0	<u>,</u>		-
	Substance-specific information:							
	Identification					Bioaccun	nulation p	otential
	N-butyl acetate				BCF	:	4	
	CAS: 123-86-4				Pow	/ Log	1.78	
	EC: 204-658-1					ential	Low	
	Xylene				BCF		9	
	CAS: 1330-20-7					/ Log	2.77	
	EC: 215-535-7					ential	Low	
					_		LOW 7	
	heptan-2-one				BCF			
	CAS: 110-43-0				Pow	/ Log	1.98	

** Changes with regards to the previous version



CTION	I 12: ECOLOGICAL INFORMATION ** ((continued)				
	Identification			Bioac	cumulatio	n potential
2-m	nethoxy-1-methylethyl acetate		В	CF	1	·
	S: 108-65-6			ow Log	0.43	
	: 203-603-9			otential	Low	
	nethylpentan-2-one			CF	2	
	S: 108-10-1			ow Log	1.31	
	: 203-550-1			otential	Low	
				CF	1	
	etone S: 67-64-1			ow Log	-0.24	
	: 200-662-2			otential	Low	
	butyl methacrylate			CF	26	
	S: 97-86-9			ow Log	2.66	
	: 202-613-0			otential	Low	
	ylbenzene			CF	1	
	5: 100-41-4			ow Log	3.15	
EC:	: 202-849-4			otential	Low	
Tolu	uene		В	CF	90	
CAS	S: 108-88-3		P	ow Log	2.73	
	: 203-625-9		P	otential	Mode	rate
4 Mo	bility in soil:					
	Identification	Absorp	tion/desorption		Volat	tility
N-b	putyl acetate	Кос	Non-applicable	Henry		Non-applicable
CAS	S: 123-86-4	Conclusion	Non-applicable	Dry soil		Non-applicable
EC:	: 204-658-1	Surface tension	2,478E-2 N/m (25 °C)	Moist soil		Non-applicable
Xyle	ene	Кос	202	Henry		524,86 Pa·m ³ /mo
CAS	S: 1330-20-7	Conclusion	Moderate	Dry soil		Yes
EC:	: 215-535-7	Surface tension	Non-applicable	Moist soil		Yes
hep	otan-2-one	Кос	280	Henry		17,12 Pa·m ³ /mol
CAS	S: 110-43-0	Conclusion	Moderate	Dry soil		Yes
EC:	: 203-767-1	Surface tension	2,612E-2 N/m (25 °C)	Moist soil		Yes
4-m	nethylpentan-2-one	Кос	Non-applicable	Henry		Non-applicable
CAS	S: 108-10-1	Conclusion	Non-applicable	Dry soil		Non-applicable
EC:	: 203-550-1	Surface tension	2,35E-2 N/m (25 °C)	Moist soil		Non-applicable
2-m	nethylpropan-2-ol	Кос	Non-applicable	Henry		Non-applicable
	S: 75-65-0	Conclusion	Non-applicable	Dry soil		Non-applicable
	: 200-889-7	Surface tension	2,111E-2 N/m (25 °C)	Moist soil		Non-applicable
ace	etone	Кос	1	Henry		2,93 Pa·m³/mol
	S: 67-64-1	Conclusion	Very High	Dry soil		Yes
	: 200-662-2	Surface tension	2,304E-2 N/m (25 °C)	Moist soil		Yes
seb	action mass of Bis(1,2,2,6,6-pentamethyl-4-piperidyl) vacate and Methyl 1,2,2,6,6-pentamethyl-4-piperidyl vacate	Кос	204400	Henry		0E+0 Pa·m³/mol
	S: 1065336-91-5	Conclusion	Immobile	Dry soil		No
	: 915-687-0	Surface tension	Non-applicable	Moist soil		No
	butyl methacrylate	Koc	1480	Henry		52,69 Pa·m ³ /mol
	S: 97-86-9	Conclusion	Moderate	Dry soil		Yes
	: 202-613-0	Surface tension	Non-applicable	Moist soil		Yes
		Koc	520			798,44 Pa·m ³ /mc
	lylbenzene		Moderate	Henry Dry coil		
	S: 100-41-4 : 202-849-4	Conclusion		Dry soil		Yes
		Surface tension	2,859E-2 N/m (25 °C)	Moist soil		Yes
		Koc	178	Henry		672,8 Pa·m ³ /mol
	S: 108-88-3	Conclusion	Moderate	Dry soil		Yes

** Changes with regards to the previous version



CLEAR COAT C2007 UHS 2:1

Printing: 23/12/2022	Date of compilation: 26/06/2011	Revised: 09/11/2022	Version: 6 (Replaced 5)	
SECTION 12: ECOL	OGICAL INFORMATION ** (contin	ued)		
12.5 Results of PB	T and vPvB assessment:			
Product fails to	meet PBT/vPvB criteria			

12.6 Endocrine disrupting properties:

Endocrine-disrupting properties: The product fails to meet the criteria.

12.7 Other adverse effects:

Not described

** Changes with regards to the previous version

SECTION 13: DISPOSAL CONSIDERATIONS

13.1 Waste treatment methods:

Code	Description	Waste class (Regulation (EU) No 1357/2014)
	waste paint and varnish containing organic solvents or other hazardous substances packaging containing residues of or contaminated by hazardous substances	Dangerous

Type of waste (Regulation (EU) No 1357/2014):

HP14 Ecotoxic, HP3 Flammable, HP5 Specific Target Organ Toxicity (STOT)/Aspiration Toxicity, HP6 Acute Toxicity, HP7 Carcinogenic, HP4 Irritant — skin irritation and eye damage

Waste management (disposal and evaluation):

Consult the authorized waste service manager on the assessment and disposal operations in accordance with Annex 1 and Annex 2 (Directive 2008/98/EC). As under 15 01 (2014/955/EC) of the code and in case the container has been in direct contact with the product, it will be processed the same way as the actual product. Otherwise, it will be processed as non-dangerous residue. Waste should not be disposed of to drains. See paragraph 6.2.

Regulations related to waste management:

In accordance with Annex II of Regulation (EC) No 1907/2006 (REACH) the community or state provisions related to waste management are stated

Community legislation: Directive 2008/98/EC, 2014/955/EU, Regulation (EU) No 1357/2014

SECTION 14: TRANSPORT INFORMATION

Transport of dangerous goods by land:

With regard to ADR 2021 and RID 2021:

	14.1	UN number or ID number:	UN1263	
	14.2	UN proper shipping name:	PAINT	
	14.3	Transport hazard class(es):	3	
$\langle \simeq \rangle$		Labels:	3	
	14.4	Packing group:	III	
3	14.5	Environmental hazards:	No	
÷	14.6	Special precautions for user		
		Special regulations:	163, 367, 650	
		Tunnel restriction code:	D/E	
		Physico-Chemical properties:	see section 9	
		Limited quantities:	5 L	
	14.7	Maritime transport in bulk according to IMO instruments:	Non-applicable	
Transport of d	angero	us goods by sea:		
With regard to I	MDG 40	-20:		



CLEAR COAT C2007 UHS 2:1

Printing: 23/12/2022	Date o	of compilation: 26/06/2011	Revised: 09/11/2022	Version: 6 (Replaced 5)	
SECTION 14: TRANSPO	SECTION 14: TRANSPORT INFORMATION (continued)				
	14.2 14.3	Special precautions for user Special regulations: EmS Codes: Physico-Chemical properties:	UN1263 PAINT 3 3 III No 223, 955, 163, 367 F-E, S-E see section 9		
Transport of dar		Limited quantities: Segregation group: Maritime transport in bulk according to IMO instruments: us goods by air:	5 L Non-applicable Non-applicable		
With regard to IAT	TA/ICA	NO 2022:			
	14.2 14.3 14.4 14.5	UN number or ID number: UN proper shipping name: Transport hazard class(es): Labels: Packing group: Environmental hazards: Special precautions for user	UN1263 PAINT 3 3 III No		
	1110	Physico-Chemical properties:	see section 9		
	14.7	Maritime transport in bulk according to IMO instruments:	Non-applicable		
SECTION 15: REGULA	TORY	' INFORMATION			

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture:

Regulation (EC) No 528/2012: contains a preservative to protect the initial properties of the treated article. Contains 2-phenoxyethanol.

Candidate substances for authorisation under the Regulation (EC) No 1907/2006 (REACH): Non-applicable

Substances included in Annex XIV of REACH ("Authorisation List") and sunset date: Non-applicable

Regulation (EC) No 1005/2009, about substances that deplete the ozone layer: Non-applicable

Article 95, REGULATION (EU) No 528/2012: Non-applicable

REGULATION (EU) No 649/2012, in relation to the import and export of hazardous chemical products: Non-applicable

Seveso III:

Section	Description	Lower-tier requirements	Upper-tier requirements		
P5c	FLAMMABLE LIQUIDS	5000	50000		
Limitations to commercialisation and the use of certain dangerous substances and mixtures (Annex XVII REACH, etc):					



CLEAR COAT C2007 UHS 2:1						
rinting:	23/12/2022	Date of compilation: 26/06/2011	Revised: 09/11/2022	Version: 6 (Replaced 5)		
SECT	ION 15: REGL	ILATORY INFORMATION (continued	d)			
	Article 9. Howe extraction of the Shall not be use	ver, products that contain explosives prec e explosives precursors is technically extr ed in:	ursors only to such a small exemption only to such a small exemption of the exclusion of th	ins acetone. Product under the provisions of xtent and in such complex mixtures that the uded from the scope of this Regulation. t phases, for example in ornamental lamps		
	and ashtrays, —tricks and jok —games for on	es, e or more participants, or any article inter	nded to be used as such, eve	n with ornamental aspects.		
	Contains Octamethylcyclotetrasiloxane, Decamethylcyclopentasiloxane. 1. Shall not be placed on the market in wash-off cosmetic products in a concentration equal to or greater than 0,1 % by weight of either substance, after 31 January 2020. 2. For the purposes of this entry, "wash-off cosmetic products" means cosmetic products as defined in Article 2(1)(a) of Regulation (EC) No 1223/2009 that, under normal conditions of use, are washed off with water after application.' Specific provisions in terms of protecting people or the environment:					
	It is recommended to use the information included in this safety data sheet as a basis for conducting workplace-specific risk assessments in order to establish the necessary risk prevention measures for the handling, use, storage and disposal of this product.					
	Other legislat	ion:				
	The product co	uld be affected by sectorial legislation				
15.2	Chemical safe	ety assessment:				
	The supplier ha	s not carried out evaluation of chemical s	afety.			
	The SDS shall be supplied in an official language of the country where the product is placed on the market. This safety data sheet has been designed in accordance with ANNEX II-Guide to the compilation of safety data sheets of Regulation (EC) No 1907/2006 (COMMISSION REGULATION (EU) 2020/878). Modifications related to the previous Safety Data Sheet which concerns the ways of managing risks.:					
	COMPOSITION · New declare	INFORMATION ON INGREDIENTS (SECT)				
	Hydroxyphenyl benzotriazol derivative Reaction mass of Bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and Methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate (1065336-91-5) Toluene (108-88-3)					
	 Removed substances Bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate (41556-26-7) Methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate (82919-37-7) 					
	Substances that contribute to the classification (SECTION 2): • New declared substances Reaction mass of Bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and Methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate (1065336-91-5)					
	CLP Regulation Hazard state Supplement	(EC) No 1272/2008 (SECTION 2, SECTIO ements ary information	N 16):			
	· New decla Hydroxyp	contained in EUH208: ared substances whenyl benzotriazol derivative				
	Bis(1,2,2 Methyl 1,	substances ,6,6-pentamethyl-4-piperidyl) sebacate (4 2,2,6,6-pentamethyl-4-piperidyl sebacate egislative phrases mentioned in secti	(82919-37-7)			
	H319: Causes s	erious eye irritation.				
	H317: May caus H351: Suspecte	to aquatic life with long lasting effects. Se an allergic skin reaction. Ed of causing cancer.				
	H315: Causes s					

H315: Causes skin irritation.

H373: May cause damage to organs through prolonged or repeated exposure (Oral).

H226: Flammable liquid and vapour.

Texts of the legislative phrases mentioned in section 3:

** Changes with regards to the previous version



CLEAR COAT C2007 UHS 2:1

Printing: 23/12/2022	Date of compilation: 26/06/2011	Revised: 09/11/2022	Version: 6 (Replaced 5)
SECTION 16: OTHE	ER INFORMATION ** (continued)		
The phrases individual comp CLP Regulatio Acute Tox. 4: H Acute Tox. 4: H Acute Tox. 4: H Acute Tox. 4: H Aquatic Chronic Aquatic Chronic Aquatic Chronic Aquatic Chronic Aquatic Chronic Aquatic Chronic Aquatic Chronic Aquatic Chronic Aguatic Chronic Aguatic Chronic Aguatic Chronic Aguatic Chronic Aguatic Chronic Aguatic Chronic Aguatic Chronic Sin Sens. 1: H Skin Sens. 11: STOT RE 2: H3 STOT RE 2: H3 STOT SE 3: H3 STOT SE 3: H3 Classification Eye Irrit. 2: Cal Aquatic Chronic Skin Sens. 1A: Carc. 2: Calcula Skin Irrit. 2: Cal	dicated do not refer to the product itself; ionents which appear in section 3 on (EC) No 1272/2008: 1302+H332 - Harmful if swallowed or if ir 1312+H332 - Harmful in contact with skir 1323 - Harmful if inhaled. 1: H400 - Very toxic to aquatic life. 1: H410 - Very toxic to aquatic life with 2: H411 - Toxic to aquatic life with long 3: H412 - Harmful to aquatic life with long 3: H412 - Harmful to aquatic life with long 4: Suspected of causing cancer. 19 - Causes serious eye irritation. 225 - Highly flammable liquid and vapour 226 - Flammable liquid and vapour. - Suspected of damaging fertility. 815 - Causes skin irritation. 317 - May cause an allergic skin reaction H317 - May cause an allergic skin reaction H317 - May cause an allergic skin reaction 35 - May cause damage to organs throug 35 - May cause drowsiness or dizziness. procedure: culation method calculation method liculation method culation method culation method alculation method alculation method alculation method alculation method alculation method (2.6.4.3)	nhaled. n or if inhaled. long lasting effects. lasting effects. s airways. ld.	osure (Oral).
interpretation o Principal bibli http://echa.eur http://eur-lex.eu Abbreviations ADR: European IMDG: Internati IATA: Internatic ICAO: Internati COD: Chemical BOD5: 5day bio BCF: Bioconcen LD50: Lethal Do LC50: Lethal Do LC50: Lethal Co EC50: Effective LogPOW: Octar Koc: Partition c UFI: unique for	f this safety data sheet, as well as the la ographical sources: opa.eu uropa.eu s and acronyms: agreement concerning the international ional maritime dangerous goods code onal Air Transport Association onal Civil Aviation Organisation Oxygen Demand ochemical oxygen demand tration factor ose 50 oncentration 50 concentration 50 nolwater partition coefficient oefficient of organic carbon	bel on the product.	t and to facilitate their comprehension and

** Changes with regards to the previous version

The information contained in this safety data sheet is based on sources, technical knowledge and current legislation at European and state level, without being able to guarantee its accuracy. This information cannot be considered a guarantee of the properties of the product, it is simply a description of the security requirements. The occupational methodology and conditions for users of this product are not within our awareness or control, and it is ultimately the responsibility of the user to take the necessary measures to obtain the legal requirements concerning the manipulation, storage, use and disposal of chemical products. The information on this safety data sheet only refers to this product, which should not be used for needs other than those specified.