

HS 4:1

ECT	TION 1: IDENTIFICATION OF THE SU	JBSTANCE/M	IXTURE AND OF THE CO	MPANY/UNDERTAKING
.1	Product identifier:	HS 4:1		
	Other means of identification:			
	UFI:	51P3-30CS-M0	DC-90Y8	
.2	Relevant identified uses of the subst	ance or mixtu	ire and uses advised agair	ist:
	Relevant uses: Car repair; base for coatin	igs. For professi	onal users only.	
	Uses advised against: All uses not specifie	ed in this sectio	n or in section 7.3	
L .3	Details of the supplier of the safety o	lata sheet:		
	Troton Sp. z o.o. Ząbrowo 14A 78-120 Gościno - Zachodniopomorskie - F Phone: +48 94 35 123 94 - Fax: +48 94 3 troton@troton.com.pl www.troton.pl / www.troton.eu	35 126 22		
L .4	Emergency telephone number: (8ar	m-4pm)+48 094	4 35 123 94; 112	
сгот		**		
	TION 2: HAZARDS IDENTIFICATION			
2.1	Classification of the substance or mi			
	CLP Regulation (EC) No 1272/2008:			(FC) No. 1272/2000
	Classification of this product has been ca		ordance with CLP Regulation ((EC) No 1272/2008.
2.2	Asp. Tox. 1: Aspiration hazard, Category Eye Irrit. 2: Eye irritation, Category 2, H3 Flam. Liq. 3: Flammable liquids, Category Skin Irrit. 2: Skin irritation, Category 2, H STOT RE 2: Specific target organ toxicity Label elements:	319 7 3, H226 1315	posure, Hazard Category 2 (C	Dral), H373
	CLP Regulation (EC) No 1272/2008:			
	Danger			
	Hazard statements:			
	Asp. Tox. 1: H304 - May be fatal if swallo Eye Irrit. 2: H319 - Causes serious eye in Flam. Liq. 3: H226 - Flammable liquid an Skin Irrit. 2: H315 - Causes skin irritation STOT RE 2: H373 - May cause damage to Precautionary statements:	ritation. d vapour.		osure (Oral).
	P210: Keep away from heat, hot surfaces P280: Wear protective gloves/protective of P301+P310: IF SWALLOWED: Immediate P302+P352: IF ON SKIN: Wash with pler P305+P351+P338: IF IN EYES: Rinse can do. Continue rinsing.	clothing/respirately call a POISO nty of water.	tory protection/eye protection N CENTER/doctor.	n/protective footwear.
	P403+P235: Store in a well-ventilated pla P501: Dispose of contents/container in a respectively.		regulations on hazardous was	ste or packaging and packaging waste
	Supplementary information:		.	
	EUH211: Warning! Hazardous respirable		e formed when sprayed. Do n	ot breathe spray or mist.
	Substances that contribute to the classical and the state of the state	assification		



Safety data sheet This SDS is an English translation of COMMISSION REGULATION (EU) 2020/878, without any country-specific legislation

Printing	: 27/01/2023	Date of compilation: 06/06/2006	Revised: 15/09/2022	Version: 7 (Replaced 6)	
SEC	TION 2: HAZARI	DS IDENTIFICATION ** (continue	d)		
2.3	Other hazards:				
		neet PBT/vPvB criteria ting properties: The product fails to mee	et the criteria.		

** Changes with regards to the previous version

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS **

3.1 Substance:

Non-applicable

3.2 Mixture:

Chemical description: Mixture composed of chemical products

Components:

In accordance with Annex II of Regulation (EC) No 1907/2006 (point 3), the product contains:

	Identification		Chemical name/Classification		Concentration	
CAS:	1330-20-7	Xylene ⁽¹⁾		Self-classified		
	215-535-7 601-022-00-9 01-2119488216-32- XXXX	Regulation 1272/2008	Acute Tox. 4: H312+H332; Aquatic Chronic 3: H412; Asp. Tox. 1: H304; Eye Irrit. 2: H319; Flam. Liq. 3: H226; Skin Irrit. 2: H315; STOT RE 2: H373; STOT SE 3: H335 - Danger	() 🔅 🚸	10 - <25 %	
CAS:	13463-67-7	Titanium dioxide (ae	rodynamic diameter $\leq 10 \ \mu m$) ⁽¹⁾	ATP ATP14		
	236-675-5 022-006-00-2 01-2119489379-17- XXXX	Regulation 1272/2008	Carc. 2: H351 - Warning	*	5 - <10 %	
CAS:	123-86-4	N-butyl acetate ⁽¹⁾		ATP CLP00		
	204-658-1 607-025-00-1 01-2119485493-29- XXXX	Regulation 1272/2008	Flam. Liq. 3: H226; STOT SE 3: H336; EUH066 - Warning		5 - <10 %	
CAS:	112-07-2	2-butoxyethyl acetat	te ⁽¹⁾	ATP CLP00	00	
	203-933-3 607-038-00-2 01-2119475112-47- XXXX	Regulation 1272/2008	Acute Tox. 4: H312+H332 - Warning	(٢)	1 - <2,5 %	
CAS:	100-41-4	Ethylbenzene ⁽²⁾		ATP ATP06		
EC: Index: REACH:	202-849-4 601-023-00-4 01-2119489370-35- XXXX	Regulation 1272/2008	Acute Tox. 4: H332; Asp. Tox. 1: H304; Flam. Liq. 2: H225; STOT RE 2: H373 - Danger	() 🔊 🔇	<1 %	
CAS:	108-65-6	2-methoxy-1-methy	lethyl acetate ⁽²⁾	ATP ATP01		
	203-603-9 607-195-00-7 01-2119475791-29- XXXX	Regulation 1272/2008	Flam. Liq. 3: H226 - Warning	٨	<1 %	
CAS:	14808-60-7	Quartz (1 %< RCS <	: 10%) ⁽²⁾	Self-classified		
EC: Index: REACH:	238-878-4 Non-applicable Non-applicable	Regulation 1272/2008	STOT RE 2: H373 - Warning	٠	<1 %	
CAS:	80-62-6	Methyl methacrylate	(2)	ATP CLP00		
	201-297-1 607-035-00-6 01-2119452498-28- XXXX	Regulation 1272/2008	Flam. Liq. 2: H225; Skin Irrit. 2: H315; Skin Sens. 1: H317; STOT SE 3: H335 - D	anger 🚺 🕭	<1 %	
CAS:	141-32-2	n-butyl acrylate ⁽²⁾		Self-classified		
	205-480-7 607-062-00-3 01-2119453155-43- XXXX	Regulation 1272/2008	Acute Tox. 4: H332; Aquatic Chronic 3: H412; Eye Irrit. 2: H319; Flam. Liq. 3: H2 Skin Irrit. 2: H315; Skin Sens. 1B: H317; STOT SE 3: H335 - Warning	26; 🚺 🍅	<1 %	
CAS:	111-76-2	2-butoxyethanol ⁽²⁾		ATP ATP18		
	203-905-0 603-014-00-0 01-2119475108-36- XXXX	Regulation 1272/2008	Acute Tox. 3: H331; Acute Tox. 4: H302; Eye Irrit. 2: H319; Skin Irrit. 2: H315 - I	Danger 🔗	<1 %	

⁽¹⁾ Substances presenting a health or environmental hazard which meet criteria laid down in Regulation (EU) No. 2020/878 ⁽²⁾ Substance with a Union workplace exposure limit

** Changes with regards to the previous version



Safety data sheet

This SDS is an English translation of COMMISSION REGULATION (EU) 2020/878, without any country-specific legislation

HS 4:1

Printing: 27/01/2023 Date of compilation: 06/06/2006 Revised: 15/09/2022 Version: 7 (Replaced 6) SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS ** (continued) To obtain more information on the hazards of the substances consult sections 11, 12 and 16. ** Changes with regards to the previous version SECTION 4: FIRST AID MEASURES 4.1 Description of first aid measures: The symptoms resulting from intoxication can appear after exposure, therefore, in case of doubt, seek medical attention for direct exposure to the chemical product or persistent discomfort, showing the SDS of this product. By inhalation: This product is not classified as hazardous through inhalation. However, in case of intoxication symptoms it is recommended to remove the person affected from the area of exposure, provide clean air and keep at rest. Request medical attention if symptoms persist. By skin contact: Remove contaminated clothing and footwear, rinse skin or shower the person affected if appropriate with plenty of cold water and neutral soap. In serious cases see a doctor. If the product causes burns or freezing, clothing should not be removed as this could worsen the injury caused if it is stuck to the skin. If blisters form on the skin, these should never be burst as this will increase the risk of infection. By eye contact: Rinse eyes thoroughly with water for at least 15 minutes. If the injured person uses contact lenses, these should be removed unless they are stuck to the eyes, in which case removal could cause further damage. In all cases, after cleaning, a doctor should be consulted as quickly as possible with the SDS for the product. By ingestion/aspiration: Request medical assistance immediately, showing the SDS of this product. Do not induce vomiting, but if it does happen keep the head down to avoid aspiration. In the case of loss of consciousness do not administer anything orally unless supervised by a doctor. Rinse out the mouth and throat, as they may have been affected during ingestion. Keep the person affected at rest. 4.2 Most important symptoms and effects, both acute and delayed: Acute and delayed effects are indicated in sections 2 and 11. 4.3 Indication of any immediate medical attention and special treatment needed: Non-applicable SECTION 5: FIREFIGHTING MEASURES 5.1 Extinguishing media: Suitable extinguishing media: If possible use polyvalent powder fire extinguishers (ABC powder), alternatively use foam or carbon dioxide extinguishers (CO2). Unsuitable extinguishing media: IT IS RECOMMENDED NOT to use full jet water as an extinguishing agent. 5.2 Special hazards arising from the substance or mixture: As a result of combustion or thermal decomposition reactive sub-products are created that can become highly toxic and, consequently, can present a serious health risk. 5.3 Advice for firefighters:

Depending on the magnitude of the fire it may be necessary to use full protective clothing and self-contained breathing apparatus (SCBA). Minimum emergency facilities and equipment should be available (fire blankets, portable first aid kit,...) in accordance with Directive 89/654/EC.

Additional provisions:

Act in accordance with the Internal Emergency Plan and the Information Sheets on actions to take after an accident or other emergencies. Eliminate all sources of ignition. In case of fire, cool the storage containers and tanks for products susceptible to combustion, explosion or BLEVE as a result of high temperatures. Avoid spillage of the products used to extinguish the fire into an aqueous medium.

SECTION 6: ACCIDENTAL RELEASE MEASURES



HS 4:1

nting	: 27/01/2023 Date of compilation: 06/06/2006 Revised: 15/09/2022 Version: 7 (Replaced 6)
SEC	TION 6: ACCIDENTAL RELEASE MEASURES (continued)
5.1	Personal precautions, protective equipment and emergency procedures:
	For non-emergency personnel:
	Isolate leaks provided that there is no additional risk for the people performing this task. Evacuate the area and keep out those without protection. Personal protection equipment must be used against potential contact with the spilt product (See section 8). Above all prevent the formation of any vapour-air flammable mixtures, through either ventilation or the use of an inert medium. Remove any source of ignition. Eliminate electrostatic charges by interconnecting all the conductive surfaces on which static electricity could form, and also ensuring that all surfaces are connected to the ground. For emergency responders:
	Wear protective equipment. Keep unprotected persons away. See section 8.
5.2	Environmental precautions:
	This product is not classified as hazardous to the environment. Keep product away from drains, surface and underground water.
6.3	Methods and material for containment and cleaning up:
	It is recommended:
6.4	Absorb the spillage using sand or inert absorbent and move it to a safe place. Do not absorb in sawdust or other combustible absorbents. For any concern related to disposal consult section 13. Reference to other sections:
	See sections 8 and 13.
SEC	TION 7: HANDLING AND STORAGE
7.1	Precautions for safe handling:
	A General precautions for safe use
	Comply with the current legislation concerning the prevention of industrial risks. Keep containers hermetically sealed. Control spills and residues, destroying them with safe methods (section 6). Avoid leakages from the container. Maintain order and cleanliness where dangerous products are used.B Technical recommendations for the prevention of fires and explosions
	Transfer in well ventilated areas, preferably through localized extraction. Fully control sources of ignition (mobile phones, sparks,) and ventilate during cleaning operations. Avoid the existence of dangerous atmospheres inside containers, applying inertization systems where possible. Transfer at a slow speed to avoid the creation of electrostatic charges. Against the possibility of electrostatic charges: ensure a perfect equipotential connection, always use groundings, do not wear work clothes made of acrylic fibres, preferably wearing cotton clothing and conductive footwear. Comply with the essential security requirements for equipment and systems defined in Directive 2014/34/EC (ATEX 100) and with the minimum requirements for
	protecting the security and health of workers under the selection criteria of Directive 1999/92/EC (ATEX 137). Consult section 10 for conditions and materials that should be avoided.
	protecting the security and health of workers under the selection criteria of Directive 1999/92/EC (ATEX 137). Consult section 10 for conditions and materials that should be avoided. C Technical recommendations on general occupational hygiene
	 protecting the security and health of workers under the selection criteria of Directive 1999/92/EC (ATEX 137). Consult section 10 for conditions and materials that should be avoided. C Technical recommendations on general occupational hygiene Do not eat or drink during the process, washing hands afterwards with suitable cleaning products.
	protecting the security and health of workers under the selection criteria of Directive 1999/92/EC (ATEX 137). Consult section 10 for conditions and materials that should be avoided. C Technical recommendations on general occupational hygiene

7.2 Conditions for safe storage, including any incompatibilities:

A.- Technical measures for storage

Minimum Temp.:	15 °C
Maximum Temp.:	25 °C
Maximum time:	12 Months

B.- General conditions for storage

Avoid sources of heat, radiation, static electricity and contact with food. For additional information see subsection 10.5

7.3 Specific end use(s):

Except for the instructions already specified it is not necessary to provide any special recommendation regarding the uses of this product.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION



HS 4:1

			ONI (acations d)			
IION 8: EXPO	SURE CONTROLS/PER	SONAL PROTECTION	JN (continued)			
Control para	meters:					
Substances wh	nose occupational exposure	e limits have to be mo	nitored in the wor	rkplace (Europea	n OEL, not coun	try-specific
legislation):				F (F	- ,	- /
Directive (EU)	2000/39, Directive 2004/32	7/EC,Directive (EU) 20	06/15, Directive ((EU) 2009/161, D	Directive (EU) 20	17/164, Dire
(EU) 2019/183	1:					
	Identi	ification			ccupational exposu	
Xylene				IOELV (8h)	50 ppm	221 mg/m ³
CAS: 1330-20-7	EC: 215-535-7			IOELV (STEL)	100 ppm	442 mg/m ³
N-butyl acetate CAS: 123-86-4	EC: 204-658-1			IOELV (8h) IOELV (STEL)	50 ppm 150 ppm	241 mg/m ³ 723 mg/m ³
2-butoxyethyl aceta				IOELV (8h)	20 ppm	133 mg/m ³
CAS: 112-07-2	EC: 203-933-3			IOELV (STEL)	50 ppm	333 mg/m ³
Ethylbenzene				IOELV (8h)	100 ppm	442 mg/m ³
	EC: 202-849-4			IOELV (STEL)	200 ppm	884 mg/m ³
2-methoxy-1-methy				IOELV (8h)	50 ppm	275 mg/m ³
-	EC: 203-603-9			IOELV (STEL) IOELV (8h)	100 ppm	550 mg/m ³
Quartz (1 %< RCS CAS: 14808-60-7	< 10%) EC: 238-878-4			IOELV (8h) IOELV (STEL)		0,1 mg/m ³
Methyl methacrylat				IOELV (8h)	50 ppm	
	EC: 201-297-1			IOELV (STEL)	100 ppm	
n-butyl acrylate				IOELV (8h)	2 ppm	11 mg/m ³
CAS: 141-32-2	EC: 205-480-7			IOELV (STEL)	10 ppm	53 mg/m ³
2-butoxyethanol				IOELV (8h)	20 ppm	98 mg/m ³
CAS: 111-76-2	EC: 203-905-0			IOELV (STEL)	50 ppm	246 mg/m ³
DNEL (Work	ers):		Short	exposure	Long	exposure
DNEL (Worke	ers): Identification		Short	exposure Local	Long Systemic	exposure Local
DNEL (Worke		Oral		<u> </u>		Local
		Oral Dermal	Systemic	Local	Systemic	Local Non-applicat
Xylene			Systemic Non-applicable	Local Non-applicable	Systemic Non-applicable	Local Non-applicat
Xylene CAS: 1330-20-7		Dermal	Systemic Non-applicable Non-applicable	Local Non-applicable Non-applicable	Systemic Non-applicable 212 mg/kg	Local Non-applicat Non-applicat 221 mg/m ³
Xylene CAS: 1330-20-7 EC: 215-535-7		Dermal Inhalation	Systemic Non-applicable Non-applicable 442 mg/m ³	Local Non-applicable Non-applicable 442 mg/m ³	Systemic Non-applicable 212 mg/kg 221 mg/m³	Local Non-applicat Non-applicat 221 mg/m ³ Non-applicat
Xylene CAS: 1330-20-7 EC: 215-535-7 N-butyl acetate		Dermal Inhalation Oral	Systemic Non-applicable Non-applicable 442 mg/m ³ Non-applicable	Local Non-applicable Non-applicable 442 mg/m ³ Non-applicable	Systemic Non-applicable 212 mg/kg 221 mg/m ³ Non-applicable	Local Non-applicat Non-applicat 221 mg/m ³ Non-applicat
Xylene CAS: 1330-20-7 EC: 215-535-7 N-butyl acetate CAS: 123-86-4	Identification	Dermal Inhalation Oral Dermal	Systemic Non-applicable Non-applicable 442 mg/m³ Non-applicable 11 mg/kg	Local Non-applicable Non-applicable 442 mg/m ³ Non-applicable Non-applicable	Systemic Non-applicable 212 mg/kg 221 mg/m ³ Non-applicable 11 mg/kg	Local Non-applicab Non-applicab 221 mg/m ³ Non-applicab Non-applicab 300 mg/m ³
Xylene CAS: 1330-20-7 EC: 215-535-7 N-butyl acetate CAS: 123-86-4 EC: 204-658-1	Identification	Dermal Inhalation Oral Dermal Inhalation	Systemic Non-applicable Non-applicable 442 mg/m³ Non-applicable 11 mg/kg 600 mg/m³	Local Non-applicable Non-applicable 442 mg/m ³ Non-applicable Non-applicable 600 mg/m ³	Systemic Non-applicable 212 mg/kg 221 mg/m ³ Non-applicable 11 mg/kg 300 mg/m ³	Local Non-applicate Non-applicate 221 mg/m³ Non-applicate 300 mg/m³ Non-applicate
Xylene CAS: 1330-20-7 EC: 215-535-7 N-butyl acetate CAS: 123-86-4 EC: 204-658-1 2-butoxyethyl ace	Identification	Dermal Inhalation Oral Dermal Inhalation Oral	Systemic Non-applicable Non-applicable 442 mg/m³ Non-applicable 11 mg/kg 600 mg/m³ Non-applicable	Local Non-applicable Non-applicable 442 mg/m ³ Non-applicable Non-applicable 600 mg/m ³ Non-applicable	Systemic Non-applicable 212 mg/kg 221 mg/m³ Non-applicable 11 mg/kg 300 mg/m³ Non-applicable	Local Non-applicate Non-applicate 221 mg/m³ Non-applicate Non-applicate 300 mg/m³ Non-applicate Non-applicate Non-applicate Non-applicate Non-applicate Non-applicate
Xylene CAS: 1330-20-7 EC: 215-535-7 N-butyl acetate CAS: 123-86-4 EC: 204-658-1 2-butoxyethyl ac CAS: 112-07-2	Identification	Dermal Inhalation Oral Dermal Inhalation Oral Dermal	Systemic Non-applicable Non-applicable 442 mg/m³ Non-applicable 11 mg/kg 600 mg/m³ Non-applicable 120 mg/kg	Local Non-applicable Non-applicable 442 mg/m ³ Non-applicable Non-applicable 600 mg/m ³ Non-applicable Non-applicable	Systemic Non-applicable 212 mg/kg 221 mg/m ³ Non-applicable 11 mg/kg 300 mg/m ³ Non-applicable 169 mg/kg	Local Non-applicate Non-applicate 221 mg/m³ Non-applicate
Xylene CAS: 1330-20-7 EC: 215-535-7 N-butyl acetate CAS: 123-86-4 EC: 204-658-1 2-butoxyethyl ac CAS: 112-07-2 EC: 203-933-3	Identification	Dermal Inhalation Oral Dermal Inhalation Oral Dermal Inhalation	Systemic Non-applicable Non-applicable 442 mg/m³ Non-applicable 11 mg/kg 600 mg/m³ Non-applicable 120 mg/kg Non-applicable	Local Non-applicable Non-applicable 442 mg/m ³ Non-applicable 600 mg/m ³ Non-applicable Non-applicable 333 mg/m ³	Systemic Non-applicable 212 mg/kg 221 mg/m ³ Non-applicable 11 mg/kg 300 mg/m ³ Non-applicable 169 mg/kg 133 mg/m ³	Local Non-applicab Non-applicab 221 mg/m ³ Non-applicab 300 mg/m ³ Non-applicab Non-applicab Non-applicab Non-applicab
Xylene CAS: 1330-20-7 EC: 215-535-7 N-butyl acetate CAS: 123-86-4 EC: 204-658-1 2-butoxyethyl ac CAS: 112-07-2 EC: 203-933-3 Ethylbenzene	Identification	Dermal Inhalation Oral Dermal Inhalation Oral Inhalation Oral Oral	Systemic Non-applicable Non-applicable 442 mg/m³ Non-applicable 11 mg/kg 600 mg/m³ Non-applicable 120 mg/kg Non-applicable Non-applicable Non-applicable	Local Non-applicable Non-applicable 442 mg/m ³ Non-applicable 600 mg/m ³ Non-applicable 333 mg/m ³ Non-applicable	Systemic Non-applicable 212 mg/kg 221 mg/m ³ Non-applicable 11 mg/kg 300 mg/m ³ Non-applicable 169 mg/kg 133 mg/m ³ Non-applicable	Local Non-applicab Non-applicab 221 mg/m³ Non-applicab Non-applicab 300 mg/m³ Non-applicab
Xylene CAS: 1330-20-7 EC: 215-535-7 N-butyl acetate CAS: 123-86-4 EC: 204-658-1 2-butoxyethyl ac CAS: 112-07-2 EC: 203-933-3 Ethylbenzene CAS: 100-41-4 EC: 202-849-4	Identification	Dermal Inhalation Oral Dermal Inhalation Oral Dermal Oral Dermal	Systemic Non-applicable Non-applicable 442 mg/m³ Non-applicable 11 mg/kg 600 mg/m³ Non-applicable 120 mg/kg Non-applicable Non-applicable Non-applicable Non-applicable Non-applicable Non-applicable Non-applicable	Local Non-applicable Non-applicable 442 mg/m ³ Non-applicable 600 mg/m ³ Non-applicable Non-applicable 333 mg/m ³ Non-applicable Non-applicable	Systemic Non-applicable 212 mg/kg 221 mg/m3 Non-applicable 11 mg/kg 300 mg/m3 Non-applicable 169 mg/kg 133 mg/m3 Non-applicable 180 mg/kg	Local Non-applicate Non-applicate 221 mg/m ³ Non-applicate 300 mg/m ³ Non-applicate
Xylene CAS: 1330-20-7 EC: 215-535-7 N-butyl acetate CAS: 123-86-4 EC: 204-658-1 2-butoxyethyl ac CAS: 112-07-2 EC: 203-933-3 Ethylbenzene CAS: 100-41-4 EC: 202-849-4	Identification	Dermal Inhalation Oral Dermal Inhalation Oral Dermal Inhalation Oral Dermal Inhalation	Systemic Non-applicable Non-applicable 442 mg/m³ Non-applicable 11 mg/kg 600 mg/m³ Non-applicable 120 mg/kg Non-applicable Non-applicable Non-applicable Non-applicable Non-applicable Non-applicable Non-applicable Non-applicable Non-applicable	Local Non-applicable Non-applicable 442 mg/m ³ Non-applicable 600 mg/m ³ Non-applicable Non-applicable 333 mg/m ³ Non-applicable Non-applicable 293 mg/m ³	Systemic Non-applicable 212 mg/kg 221 mg/m³ Non-applicable 11 mg/kg 300 mg/m³ Non-applicable 169 mg/kg 133 mg/m³ Non-applicable 180 mg/kg 77 mg/m³	Local Non-applicate Non-applicate 221 mg/m ³ Non-applicate 300 mg/m ³ Non-applicate 300 mg/m ³ Non-applicate
Xylene CAS: 1330-20-7 EC: 215-535-7 N-butyl acetate CAS: 123-86-4 EC: 204-658-1 2-butoxyethyl ac CAS: 112-07-2 EC: 203-933-3 Ethylbenzene CAS: 100-41-4 EC: 202-849-4 2-methoxy-1-me	Identification	Dermal Inhalation Oral Dermal Inhalation Oral Dermal Inhalation Oral Dermal Inhalation Oral	Systemic Non-applicable Non-applicable 442 mg/m³ Non-applicable 11 mg/kg 600 mg/m³ Non-applicable 120 mg/kg Non-applicable	Local Non-applicable Non-applicable 442 mg/m ³ Non-applicable 600 mg/m ³ Non-applicable Non-applicable 333 mg/m ³ Non-applicable 293 mg/m ³ Non-applicable	Systemic Non-applicable 212 mg/kg 221 mg/m³ Non-applicable 11 mg/kg 300 mg/m³ Non-applicable 169 mg/kg 133 mg/m³ Non-applicable 180 mg/kg 77 mg/m³ Non-applicable	Local Non-applicate Non-applicate 221 mg/m³ Non-applicate
Xylene CAS: 1330-20-7 EC: 215-535-7 N-butyl acetate CAS: 123-86-4 EC: 204-658-1 2-butoxyethyl ac CAS: 112-07-2 EC: 203-933-3 Ethylbenzene CAS: 100-41-4 EC: 202-849-4 2-methoxy-1-me CAS: 108-65-6	etate	Dermal Inhalation Oral Dermal Inhalation Oral Dermal Inhalation Oral Dermal Inhalation Oral Dermal	Systemic Non-applicable Non-applicable 442 mg/m³ Non-applicable 11 mg/kg 600 mg/m³ Non-applicable 120 mg/kg Non-applicable	Local Non-applicable Non-applicable 442 mg/m ³ Non-applicable Non-applicable 600 mg/m ³ Non-applicable 333 mg/m ³ Non-applicable 293 mg/m ³ Non-applicable 293 mg/m ³	Systemic Non-applicable 212 mg/kg 221 mg/m³ Non-applicable 11 mg/kg 300 mg/m³ Non-applicable 169 mg/kg 133 mg/m³ Non-applicable 180 mg/kg 77 mg/m³ Non-applicable 796 mg/kg	Local Non-applicate Non-applicate 221 mg/m³ Non-applicate
Xylene CAS: 1330-20-7 EC: 215-535-7 N-butyl acetate CAS: 123-86-4 EC: 204-658-1 2-butoxyethyl ac CAS: 112-07-2 EC: 203-933-3 Ethylbenzene CAS: 100-41-4 EC: 202-849-4 2-methoxy-1-me CAS: 108-65-6 EC: 203-603-9	etate	Dermal Inhalation Oral Dermal Inhalation Oral Dermal Inhalation Oral Dermal Inhalation Oral Dermal Inhalation	Systemic Non-applicable Non-applicable 442 mg/m³ Non-applicable 11 mg/kg 600 mg/m³ Non-applicable 120 mg/kg Non-applicable	Local Non-applicable Non-applicable 442 mg/m ³ Non-applicable Non-applicable 600 mg/m ³ Non-applicable 333 mg/m ³ Non-applicable 333 mg/m ³ Non-applicable 293 mg/m ³ Non-applicable 550 mg/m ³	Systemic Non-applicable 212 mg/kg 221 mg/m³ Non-applicable 11 mg/kg 300 mg/m³ Non-applicable 169 mg/kg 133 mg/m³ Non-applicable 180 mg/kg 77 mg/m³ Non-applicable 275 mg/m³	Local Non-applicate Non-applicate 221 mg/m³ Non-applicate
Xylene CAS: 1330-20-7 EC: 215-535-7 N-butyl acetate CAS: 123-86-4 EC: 204-658-1 2-butoxyethyl ac CAS: 112-07-2 EC: 203-933-3 Ethylbenzene CAS: 100-41-4 EC: 202-849-4 2-methoxy-1-me CAS: 108-65-6 EC: 203-603-9 Methyl methacry	etate	Dermal Inhalation Oral Dermal Inhalation Oral Dermal Inhalation Oral Dermal Inhalation Oral Dermal Inhalation Oral Dermal Inhalation	Systemic Non-applicable Non-applicable 442 mg/m³ Non-applicable 11 mg/kg 600 mg/m³ Non-applicable 120 mg/kg Non-applicable 120 mg/kg Non-applicable	Local Non-applicable Non-applicable 442 mg/m ³ Non-applicable 600 mg/m ³ Non-applicable 333 mg/m ³ Non-applicable 333 mg/m ³ Non-applicable 293 mg/m ³ Non-applicable 550 mg/m ³ Non-applicable	Systemic Non-applicable 212 mg/kg 221 mg/m³ Non-applicable 11 mg/kg 300 mg/m³ Non-applicable 169 mg/kg 133 mg/m³ Non-applicable 180 mg/kg 77 mg/m³ Non-applicable 796 mg/kg 275 mg/m³ Non-applicable	Local Non-applicate Non-applicate 221 mg/m³ Non-applicate
Xylene CAS: 1330-20-7 EC: 215-535-7 N-butyl acetate CAS: 123-86-4 EC: 204-658-1 2-butoxyethyl ac CAS: 112-07-2 EC: 203-933-3 Ethylbenzene CAS: 100-41-4 EC: 202-849-4 2-methoxy-1-me CAS: 108-65-6 EC: 203-603-9 Methyl methacry CAS: 80-62-6 EC: 201-297-1	etate	Dermal Inhalation Oral Dermal Inhalation Oral Dermal Inhalation Oral Dermal Inhalation Oral Dermal Inhalation Oral Dermal	Systemic Non-applicable Non-applicable 442 mg/m³ Non-applicable 11 mg/kg 600 mg/m³ Non-applicable 120 mg/kg Non-applicable	Local Non-applicable Non-applicable 442 mg/m ³ Non-applicable 600 mg/m ³ Non-applicable 600 mg/m ³ Non-applicable 333 mg/m ³ Non-applicable 293 mg/m ³ Non-applicable 293 mg/m ³ Non-applicable 550 mg/m ³ Non-applicable Non-applicable 416 mg/m ³	Systemic Non-applicable 212 mg/kg 221 mg/m³ Non-applicable 11 mg/kg 300 mg/m³ Non-applicable 169 mg/kg 133 mg/m³ Non-applicable 180 mg/kg 77 mg/m³ Non-applicable 796 mg/kg 275 mg/m³ Non-applicable 13,67 mg/kg 348,4 mg/m³	Local Non-applicate Non-applicate 221 mg/m³ Non-applicate 300 mg/m³ Non-applicate 300 mg/m³ Non-applicate
Xylene CAS: 1330-20-7 EC: 215-535-7 N-butyl acetate CAS: 123-86-4 EC: 204-658-1 2-butoxyethyl ac CAS: 112-07-2 EC: 203-933-3 Ethylbenzene CAS: 100-41-4 EC: 202-849-4 2-methoxy-1-me CAS: 108-65-6 EC: 203-603-9 Methyl methacry CAS: 80-62-6	etate	Dermal Inhalation Oral Dermal Inhalation Oral Dermal Inhalation Oral Dermal Inhalation Oral Dermal Inhalation Oral Dermal Inhalation	Systemic Non-applicable Non-applicable 442 mg/m ³ Non-applicable 11 mg/kg 600 mg/m ³ Non-applicable 120 mg/kg Non-applicable	Local Non-applicable Non-applicable 442 mg/m ³ Non-applicable 600 mg/m ³ Non-applicable 333 mg/m ³ Non-applicable 333 mg/m ³ Non-applicable 293 mg/m ³ Non-applicable 550 mg/m ³ Non-applicable 550 mg/m ³	Systemic Non-applicable 212 mg/kg 221 mg/m³ Non-applicable 11 mg/kg 300 mg/m³ Non-applicable 169 mg/kg 133 mg/m³ Non-applicable 180 mg/kg 77 mg/m³ Non-applicable 296 mg/kg 275 mg/m³ Non-applicable 13,67 mg/kg	Local Non-applicate Non-applicate 221 mg/m³ Non-applicate 300 mg/m³ Non-applicate 300 mg/m³ Non-applicate Non-applicate
Xylene CAS: 1330-20-7 EC: 215-535-7 N-butyl acetate CAS: 123-86-4 EC: 204-658-1 2-butoxyethyl ac CAS: 112-07-2 EC: 203-933-3 Ethylbenzene CAS: 100-41-4 EC: 202-849-4 2-methoxy-1-me CAS: 108-65-6 EC: 203-603-9 Methyl methacry CAS: 80-62-6 EC: 201-297-1 n-butyl acrylate	etate	DermalInhalationOralDermalInhalationOralDermalInhalationOralDermalInhalationOralDermalInhalationOralDermalInhalationOralDermalInhalationOralDermalInhalationOralDermalInhalationOralDermalInhalationOralOral	Systemic Non-applicable Non-applicable 442 mg/m³ Non-applicable 11 mg/kg 600 mg/m³ Non-applicable 120 mg/kg Non-applicable 120 mg/kg Non-applicable	Local Non-applicable Non-applicable 442 mg/m ³ Non-applicable 600 mg/m ³ Non-applicable 00 mg/m ³ Non-applicable 333 mg/m ³ Non-applicable 293 mg/m ³ Non-applicable Non-applicable 550 mg/m ³ Non-applicable Non-applicable Non-applicable Non-applicable Non-applicable	Systemic Non-applicable 212 mg/kg 221 mg/m³ Non-applicable 11 mg/kg 300 mg/m³ Non-applicable 169 mg/kg 133 mg/m³ Non-applicable 169 mg/kg 17 mg/m³ Non-applicable 180 mg/kg 77 mg/m³ Non-applicable 796 mg/kg 275 mg/m³ Non-applicable 13,67 mg/kg 348,4 mg/m³ Non-applicable	Local Non-applicate Non-applicate 221 mg/m³ Non-applicate 300 mg/m³ Non-applicate 300 mg/m³ Non-applicate Non-applicate
Xylene CAS: 1330-20-7 EC: 215-535-7 N-butyl acetate CAS: 123-86-4 EC: 204-658-1 2-butoxyethyl ac CAS: 112-07-2 EC: 203-933-3 Ethylbenzene CAS: 100-41-4 EC: 202-849-4 2-methoxy-1-me CAS: 108-65-6 EC: 203-603-9 Methyl methacry CAS: 80-62-6 EC: 201-297-1 n-butyl acrylate CAS: 141-32-2 EC: 205-480-7	Identification Identification etate thylethyl acetate late	DermalInhalationOralDermalInhalationOralDermalInhalationOralDermalInhalationOralDermalInhalationOralDermalInhalationOralDermalInhalationOralDermalInhalationOralDermalInhalationOralDermalInhalationOralDermalInhalationInhalation	Systemic Non-applicable Non-applicable 442 mg/m³ Non-applicable 11 mg/kg 600 mg/m³ Non-applicable 120 mg/kg Non-applicable 120 mg/kg Non-applicable Non-applicable	Local Non-applicable Non-applicable 442 mg/m ³ Non-applicable 600 mg/m ³ Non-applicable 00 mg/m ³ Non-applicable 333 mg/m ³ Non-applicable 293 mg/m ³ Non-applicable 293 mg/m ³ Non-applicable 550 mg/m ³ Non-applicable 550 mg/m ³ Non-applicable Non-applicable 416 mg/m ³ Non-applicable Non-applicable Non-applicable Non-applicable	Systemic Non-applicable 212 mg/kg 221 mg/m³ Non-applicable 11 mg/kg 300 mg/m³ Non-applicable 169 mg/kg 133 mg/m³ Non-applicable 180 mg/kg 77 mg/m³ Non-applicable 180 mg/kg 275 mg/m³ Non-applicable 13,67 mg/kg 348,4 mg/m³ Non-applicable Non-applicable	Local Non-applicate Non-applicate 221 mg/m³ Non-applicate 300 mg/m³ Non-applicate Non-applicate
Xylene CAS: 1330-20-7 EC: 215-535-7 N-butyl acetate CAS: 123-86-4 EC: 204-658-1 2-butoxyethyl ac CAS: 112-07-2 EC: 203-933-3 Ethylbenzene CAS: 100-41-4 EC: 202-849-4 2-methoxy-1-me CAS: 108-65-6 EC: 203-603-9 Methyl methacry CAS: 80-62-6 EC: 201-297-1 n-butyl acrylate CAS: 141-32-2	Identification Identification etate thylethyl acetate late	Dermal Inhalation Oral Dermal Inhalation Oral Dermal Inhalation Oral Dermal Inhalation Oral Dermal Inhalation Oral Dermal Inhalation Oral Dermal	Systemic Non-applicable Non-applicable 442 mg/m³ Non-applicable 11 mg/kg 600 mg/m³ Non-applicable 120 mg/kg Non-applicable 120 mg/kg Non-applicable Non-applicable	Local Non-applicable Non-applicable 442 mg/m ³ Non-applicable 600 mg/m ³ Non-applicable 333 mg/m ³ Non-applicable 333 mg/m ³ Non-applicable 293 mg/m ³ Non-applicable 293 mg/m ³ Non-applicable 550 mg/m ³ Non-applicable 416 mg/m ³ Non-applicable Non-applicable Non-applicable	Systemic Non-applicable 212 mg/kg 221 mg/m³ Non-applicable 11 mg/kg 300 mg/m³ Non-applicable 169 mg/kg 133 mg/m³ Non-applicable 180 mg/kg 77 mg/m³ Non-applicable 796 mg/kg 275 mg/m³ Non-applicable 13,67 mg/kg 348,4 mg/m³ Non-applicable Non-applicable	Local Non-applicate Non-applicate 221 mg/m³ Non-applicate 300 mg/m³ Non-applicate 300 mg/m³ Non-applicate Non-applicate



Safety data sheet This SDS is an English translation of COMMISSION REGULATION (EU) 2020/878, without any country-specific legislation

Revised: 15/09/2022

Version: 7 (Replaced 6)

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION (continued)

Date of compilation: 06/06/2006

		Short	Short exposure		Long exposure	
Identification		Systemic	Local	Systemic	Local	
Xylene	Oral	Non-applicable	Non-applicable	12,5 mg/kg	Non-applicable	
CAS: 1330-20-7	Dermal	Non-applicable	Non-applicable	125 mg/kg	Non-applicable	
EC: 215-535-7	Inhalation	260 mg/m ³	260 mg/m ³	65,3 mg/m ³	65,3 mg/m ³	
N-butyl acetate	Oral	2 mg/kg	Non-applicable	2 mg/kg	Non-applicable	
CAS: 123-86-4	Dermal	6 mg/kg	Non-applicable	6 mg/kg	Non-applicable	
EC: 204-658-1	Inhalation	300 mg/m ³	300 mg/m ³	35,7 mg/m ³	35,7 mg/m ³	
2-butoxyethyl acetate	Oral	36 mg/kg	Non-applicable	8,6 mg/kg	Non-applicable	
CAS: 112-07-2	Dermal	72 mg/kg	Non-applicable	102 mg/kg	Non-applicable	
EC: 203-933-3	Inhalation	Non-applicable	200 mg/m ³	80 mg/m ³	Non-applicable	
Ethylbenzene	Oral	Non-applicable	Non-applicable	1,6 mg/kg	Non-applicable	
CAS: 100-41-4	Dermal	Non-applicable	Non-applicable	Non-applicable	Non-applicable	
EC: 202-849-4	Inhalation	Non-applicable	Non-applicable	15 mg/m ³	Non-applicable	
2-methoxy-1-methylethyl acetate	Oral	Non-applicable	Non-applicable	36 mg/kg	Non-applicable	
CAS: 108-65-6	Dermal	Non-applicable	Non-applicable	320 mg/kg	Non-applicable	
EC: 203-603-9	Inhalation	Non-applicable	Non-applicable	33 mg/m ³	33 mg/m ³	
Methyl methacrylate	Oral	Non-applicable	Non-applicable	8,2 mg/kg	Non-applicable	
CAS: 80-62-6	Dermal	Non-applicable	Non-applicable	8,2 mg/kg	Non-applicable	
EC: 201-297-1	Inhalation	Non-applicable	208 mg/m ³	74,3 mg/m ³	104 mg/m ³	
2-butoxyethanol	Oral	Non-applicable	Non-applicable	6,3 mg/kg	Non-applicable	
CAS: 111-76-2	Dermal	89 mg/kg	Non-applicable	75 mg/kg	Non-applicable	
EC: 203-905-0	Inhalation	426 mg/m ³	147 mg/m ³	59 mg/m ³	Non-applicable	

PNEC:

Printing: 27/01/2023

Identification				
Xylene	STP	6,58 mg/L	Fresh water	0,327 mg/L
CAS: 1330-20-7	Soil	2,31 mg/kg	Marine water	0,327 mg/L
EC: 215-535-7	Intermittent	0,327 mg/L	Sediment (Fresh water)	12,46 mg/kg
	Oral	Non-applicable	Sediment (Marine water)	12,46 mg/kg
N-butyl acetate	STP	35,6 mg/L	Fresh water	0,18 mg/L
CAS: 123-86-4	Soil	0,09 mg/kg	Marine water	0,018 mg/L
EC: 204-658-1	Intermittent	0,36 mg/L	Sediment (Fresh water)	0,981 mg/kg
	Oral	Non-applicable	Sediment (Marine water)	0,098 mg/kg
2-butoxyethyl acetate	STP	90 mg/L	Fresh water	0,304 mg/L
CAS: 112-07-2	Soil	0,415 mg/kg	Marine water	0,03 mg/L
EC: 203-933-3	Intermittent	0,56 mg/L	Sediment (Fresh water)	2,03 mg/kg
	Oral	0,06 g/kg	Sediment (Marine water)	0,203 mg/kg
Ethylbenzene	STP	9,6 mg/L	Fresh water	0,1 mg/L
CAS: 100-41-4	Soil	2,68 mg/kg	Marine water	0,01 mg/L
EC: 202-849-4	Intermittent	0,1 mg/L	Sediment (Fresh water)	13,7 mg/kg
	Oral	0,02 g/kg	Sediment (Marine water)	1,37 mg/kg
2-methoxy-1-methylethyl acetate	STP	100 mg/L	Fresh water	0,635 mg/L
CAS: 108-65-6	Soil	0,29 mg/kg	Marine water	0,064 mg/L
EC: 203-603-9	Intermittent	6,35 mg/L	Sediment (Fresh water)	3,29 mg/kg
	Oral	Non-applicable	Sediment (Marine water)	0,329 mg/kg
Methyl methacrylate	STP	10 mg/L	Fresh water	0,94 mg/L
CAS: 80-62-6	Soil	1,48 mg/kg	Marine water	0,094 mg/L
EC: 201-297-1	Intermittent	0,94 mg/L	Sediment (Fresh water)	10,2 mg/kg
	Oral	Non-applicable	Sediment (Marine water)	0,102 mg/kg
n-butyl acrylate	STP	3,5 mg/L	Fresh water	0,003 mg/L
CAS: 141-32-2	Soil	1 mg/kg	Marine water	0 mg/L
EC: 205-480-7	Intermittent	0,011 mg/L	Sediment (Fresh water)	0,034 mg/kg
	Oral	Non-applicable	Sediment (Marine water)	0,003 mg/kg



HS 4:1

		I O. LAFOJORL	CONTROLS/PERSONA				
			dentification				
		utoxyethanol		STP	463 mg/L 2,33 mg/kg	Fresh water Marine water	8,8 mg/L 0,88 mg/L
		S: 111-76-2 203-905-0		Intermittent	26,4 mg/L	Sediment (Fresh water)	34,6 mg/kg
	LC.	205 505 0		Oral	0,02 g/kg	Sediment (Marine water)	3,46 mg/kg
2	Ex	posure controls	:	0.0	0,02 9,119		0,10,119,119
		As a preventative marking>> in ac use, cleaning, ma information see s the labour risk pr	tion measures, such as per e measure it is recommend cordance with Regulation (aintenance, class of protec subsection 7.1. All informa revention services as it is n	led to use basi (EU) 2016/425 tion,) consul tion contained	ic Personal Protective 5. For more informatio It the information leaf I herein is a recomme	n on Personal Protective let provided by the man ndation which needs so	e Equipment (storage sufacturer. For more me specification from
	D	Respiratory prote	PPE	Labelling	CEN Standard		Remarks
		Mandatory respiratory tract protection	Filter mask for gases and vapours (Filter type: A)		EN 405:2002+A1:201	Replace when ther 0 contaminant insi contaminant co	e is a taste or smell of the de the face mask. If the mes with warnings it is use isolation equipment.
		Mandatory respiratory tract protection	Filter mask for gases and vapours (Filter type: FFP3)		EN 405:2002+A1:201	0 contaminant insi contaminant co	e is a taste or smell of the de the face mask. If the mes with warnings it is use isolation equipment.
	C	Specific protectio	on for the hands				
		Pictogram	PPE	Labelling	CEN Standard	F	Remarks
		Mandatory hand protection	NON-disposable chemical protective gloves (Material: Nitrile, Breakthrough time: > 480 min, Thickness: 0.4 mm)		EN ISO 374-1:2016+A1:: EN 16523-1:2015+A1:2 EN ISO 21420:2020	2018 manufacturer must ex 018 the product is being creams after the pro	h Time indicated by the ceed the period during wl used. Do not use protecti oduct has come into conta vith skin.
		As the product is	a mixture of several subst ad has therefore to be cheo tection			naterial can not be calco	ulated in advance wit
		Pictogram	PPE	Labelling	CEN Standard	F	Remarks
		Mandatory face protection	Panoramic glasses against splash/projections.		EN 166:2002 EN ISO 4007:2018	the manufacturer's i	fect periodically according nstructions. Use if there is of splashing.
	E	Body protection					
		Pictogram	PPE	Labelling	CEN Standard	F	Remarks
		Mandatory complete body protection	Disposable clothing for protection against chemical risks, with antistatic and fireproof properties		EN 1149-1,2,3 EN 13034:2005+A1:20 EN ISO 13982- 1:2004/A1:2010 EN ISO 6529:2013 EN ISO 6530:2005 EN ISO 13688:2013 EN 464:1994	For professional us according to the m	se only. Clean periodically anufacturer´s instructions
		Mandatory foot	Safety footwear for protection against chemical risk, with antistatic and heat resistant properties		EN ISO 13287:2020 EN ISO 20345:2011 EN 13832-1:2019		any sign of deterioration.



HS 4:1

Emergency shower Eyewash stations Environmental exposure controls: In accordance with the community legislation for the protection of the environment it is recommende spillage of both the product and its container. For additional information see subsection 7.1.0 Volatile organic compounds: With regard to Directive 2010/75/EU, this product has the following characteristics: V.O.C. (Supply): 23,11 % weight V.O.C. density at 20 °C: 538 kg/m² (538 g/L) Average carbon number: 7,22 Average molecular weight: 115,31 g/mol CTION 9: PHYSICAL AND CHEMICAL PROPERTIES ** Information on basic physical and chemical properties: For complete information see the product datasheet. Appearance: Physical state at 20 °C: Liquid Appearance: Viscous Colour: Characteristic Odour: Characteristic Odour: Characteristic Odour: 118 °C Vapour pressure at 20 °C: 1040,17 Pa (11,04 kPa) Evaporation rate at 20 °C: Non-applicable * Volatility: Density at 20 °C: 1620 kg/m³ Boiling point at atmospheric pressure: 118 °C Vapour pressure at 20 °C:								
ANSI 2238-1 150 3864-1:2011, 150 3864-4:2011 Image: Descent and the second and the	Standards							
Environmental exposure controls: In accordance with the community legislation for the protection of the environment it is recommende spillage of both the product and its container. For additional information see subsection 7.1.D Volatile organic compounds: With regard to Directive 2010/75/EU, this product has the following characteristics: V.O.C. (Supply): 23,11 % weight V.O.C. density at 20 °C: 538 kg/m³ (538 g/L) Average carbon number: 7,22 Average molecular weight: 115,31 g/mol Environmental exposure controls: For complete information see the product datasheet. Appearance: Physical state at 20 °C: Physical state at 20 °C: Liquid Appearance: Viscous Colour: Characteristic Odour: Characteristic Odour: Characteristic Odour threshold: Non-applicable * Vapour pressure at 20 °C: 118 °C Vapour pressure at 20 °C: 1040,17 Pa (11,04 kPa) Evaporation rate at 20 °C: 1040,17 Pa (11,04 kPa) Evaporation rate at 20 °C: 1040,17 Pa (11,04 kPa) Evaporation rate at 20 °C: 1020 kg/m³ Relative density at 20 °C: 1620 kg/m³ <td>DIN 12 899 D 3864-1:2011, ISO 3864-4:201</td>	DIN 12 899 D 3864-1:2011, ISO 3864-4:201							
In accordance with the community legislation for the protection of the environment it is recommende spillage of both the product and its container. For additional information see subsection 7.1.D Volatile organic compounds: With regard to Directive 2010/75/EU, this product has the following characteristics: V.O.C. (Supply): 23,11 % weight V.O.C. density at 20 °C: 538 kg/m ³ (538 g/L) Average carbon number: 7,22 Average molecular weight: 115,31 g/mol TOTON 9: PHYSICAL AND CHEMICAL PROPERTIES ** Thformation on basic physical and chemical properties: For complete information see the product datasheet. Appearance: Physical state at 20 °C: Liquid Appearance: Odour: Characteristic Odour: Characteristic Odour: Characteristic Odour threshold: Non-applicable * Volatility: Boiling point at atmospheric pressure: 118 °C Vapour pressure at 20 °C: 2098 Pa Vapour pressure at 20 °C: 1040,17 Pa (11,04 kPa) Evaporation rate at 20 °C: 1620 kg/m ³ Relative density at 20 °C: 1,62 Dynamic viscosity at 20 °C: 1,62 Dynamic viscosity at 20 °C: 1,62 Dynamic viscosity at 20 °C: 1,62 Minematic viscosity at 20 °C: 1,28 mm²/s Kinematic viscosity at 20 °C: 1,28 mm²/s Kinematic viscosity at 20 °C: 1,28 mm²/s Kinematic viscosity at 20 °C: Non-applicable * Vapour density at 20 °C: 1,28 mm²/s Kinematic viscosity at 20 °C: 1,28 mm²/s Kinematic viscosity at 20 °C: Non-applicable * Vapour density at 20 °C: Non-applicable * Vapour density at 20 °C: Non-applicable * Vapour density at 20 °C: Non-applicable *								
V.O.C. (Supply):23,11 % weightV.O.C. density at 20 °C:538 kg/m³ (538 g/L)Average carbon number:7,22Average molecular weight:115,31 g/molCTION 9: PHYSICAL AND CHEMICAL PROPERTIES **CTION 9: PHYSICAL AND CHEMICAL PROPERTIES **CTION 9: PHYSICAL AND CHEMICAL PROPERTIESFor complete information see the product datasheet.Appearance:LiquidAppearance:ViscousColour:According to the markings on the packageOdour:CharacteristicOdour threshold:Non-applicable *Volatility:UisousBoiling point at atmospheric pressure:118 °CVapour pressure at 20 °C:2098 PaVapour pressure at 20 °C:1040,17 Pa (11,04 kPa)Evaporation rate at 20 °C:1620 kg/m³Relative density at 20 °C:1620 kg/m³Bensity at 20 °C:2,03 cPKinematic viscosity at 40 °C:<20,5 mm²/sKinematic viscosity at 40 °C:<20,5 mm²/sConcentration:Non-applicable *PH:Non-applicable *Vapour density at 20 °C:Non-applicable *PH:Non-applicable *Phi:Non-applicable *Phi:Non-applicable *Phi:Non-applicable *Partition coefficient n-octanol/water 20 °C:Non-applicable *Partition coefficient n-octanol/water 20 °C:Non-applicable *	led to avoid environmenta							
V.O.C. density at 20 °C:538 kg/m³ (538 g/L)Average carbon number:7,22Average molecular weight:115,31 g/molCITON 9: PHYSICAL AND CHEMICAL PROPERTIES **CITON 9: PHYSICAL AND CHEMICAL PROPERTIES **Adverage molecular weight:115,31 g/molAdverage molecular weight:LiquidAppearance:ViscousColour:According to the markings on the packageOdour:CharacteristicOdour:CharacteristicOdour:CharacteristicVolatility:Boiling point at atmospheric pressure:118 °CVapour pressure at 20 °C:Non-applicable *Vapour pressure at 20 °C:1620 kg/m³Relative density at 20 °C:1620 kg/m³Relative density at 20								
Average carbon number: 7,22 Average molecular weight: 115,31 g/mol CTION 9: PHYSICAL AND CHEMICAL PROPERTIES ** CTION 9: PHYSICAL AND CHEMICAL PROPERTIES ** Information on basic physical and chemical properties: For complete information see the product datasheet. Appearance: Physical state at 20 °C: Liquid Appearance: Viscous Colour: According to the markings on the package Odour: Characteristic Odour threshold: Non-applicable * Volatility: Boiling point at atmospheric pressure: 118 °C Vapour pressure at 20 °C: 2098 Pa Vapour pressure at 20 °C: 2098 Pa Vapour pressure at 20 °C: 1040,17 Pa (11,04 kPa) Evaporation rate at 20 °C: 1620 kg/m³ Relative density at 20 °C: 1,62 Dynamic viscosity at 20 °C: 2,03 cP Kinematic viscosity at 20 °C: 1,28 mm²/s Kinematic viscosity at 40 °C: <20,5 mm²/s								
Average molecular weight: 115,31 g/mol CTION 9: PHYSICAL AND CHEMICAL PROPERTIES ** CTION 9: PHYSICAL AND CHEMICAL PROPERTIES ** Information on basic physical and chemical properties: For complete information see the product datasheet: Appearance: Liquid Appearance: Viscous Colour: According to the markings on the package Odour: Characteristic Odour threshold: Non-applicable * Volatility: Uagour pressure at 20 °C: Clava Page Mayour pressure at 50 °C: 11040,17 Pa (11,04 kPa) Evapour pressure at 50 °C: Non-applicable * Poduct description: 1620 kg/m³ Relative density at 20 °C: 1,621 Ponanic viscosity at 20 °C: 2,03 cP Kinematic viscosity at 20 °C: 2,03 cP Kinematic viscosity at 20 °C: 2,05 mm²/s Kinematic viscosity at 20 °C: 2,05 mm²/s Concentration: Non-applicable * Pit: Non-applicable * Pit: Non-applicable * Partition coefficient n-octanol/water 20 °C: Non-applicable *								
CTION 9: PHYSICAL AND CHEMICAL PROPERTIES ** Information on basic physical and chemical properties: For complete information see the product datasheet. Appearance: Physical state at 20 °C: Liquid Appearance: Viscous Colour: According to the markings on the package Odour: Characteristic Odour threshold: Non-applicable * Volatility: Boiling point at atmospheric pressure: 118 °C Vapour pressure at 20 °C: 2098 Pa Vapour pressure at 20 °C: 11040,17 Pa (11,04 kPa) Evaporation rate at 20 °C: Non-applicable * Product description: Inf20 kg/m³ Density at 20 °C: 1,62 Dynamic viscosity at 20 °C: 2,03 cP Kinematic viscosity at 20 °C: 1,28 mm²/s Kinematic viscosity at 0°C: 20,5 mm²/s Concentration: Non-applicable * pH: Non-applicable * Yapour density at 20 °C: Non-applicable * Pit: Non-applicable * Pit: Non-applicable * Pit: Non-applicable * Partition coefficient n-octanol/water 2								
Information on basic physical and chemical properties: For complete information see the product datasheet. Appearance: Physical state at 20 °C: Liquid Appearance: Viscous Colour: According to the markings on the package Odour: Characteristic Odour threshold: Non-applicable * Volatility: Boiling point at atmospheric pressure: 118 °C Vapour pressure at 20 °C: 2098 Pa Vapour pressure at 20 °C: 2098 Pa Vapour pressure at 20 °C: 11040,17 Pa (11,04 kPa) Evaporation rate at 20 °C: Non-applicable * Product description: If 20 kg/m³ Relative density at 20 °C: 1,620 kg/m³ Relative density at 20 °C: 2,03 cP Kinematic viscosity at 20 °C: 1,28 mm²/s Kinematic viscosity at 40 °C: <20,5 mm²/s								
Information on basic physical and chemical properties: For complete information see the product datasheet. Appearance: Physical state at 20 °C: Liquid Appearance: Viscous Colour: According to the markings on the package Odour: Characteristic Odour threshold: Non-applicable * Volatility: Boiling point at atmospheric pressure: 118 °C Vapour pressure at 20 °C: 2098 Pa Vapour pressure at 50 °C: 11040,17 Pa (11,04 kPa) Evaporation rate at 20 °C: Non-applicable * Product description: Density at 20 °C: 1620 kg/m³ Relative density at 20 °C: 1,62 Dynamic viscosity at 20 °C: 2,03 cP Kinematic viscosity at 20 °C: 1,28 mm²/s Kinematic viscosity at 40 °C: <20,5 mm²/s								
For complete information see the product datasheet.Appearance:LiquidPhysical state at 20 °C:LiquidAppearance:ViscousColour:According to the markings on the packageOdour:CharacteristicOdour threshold:Non-applicable *Volatility:UiscousBoiling point at atmospheric pressure:118 °CVapour pressure at 20 °C:2098 PaVapour pressure at 50 °C:11040,17 Pa (11,04 kPa)Evaporation rate at 20 °C:Non-applicable *Product description:1620 kg/m³Density at 20 °C:1,62Dynamic viscosity at 20 °C:1,28 mm²/sKinematic viscosity at 20 °C:1,28 mm²/sKinematic viscosity at 20 °C:2,03 cPKinematic viscosity at 40 °C:<20,5 mm²/s								
Appearance:Physical state at 20 °C:LiquidAppearance:ViscousColour:According to the markings on the packageOdour:CharacteristicOdour threshold:Non-applicable *Odour threshold:Non-applicable *Valatility:118 °CBoiling point at atmospheric pressure:118 °CVapour pressure at 20 °C:2098 PaVapour pressure at 20 °C:11040,17 Pa (11,04 kPa)Evaporation rate at 20 °C:Non-applicable *Product description:1620 kg/m³Pensity at 20 °C:1,62Dynamic viscosity at 20 °C:2,03 cPKinematic viscosity at 20 °C:1,28 mm²/sKinematic viscosity at 40 °C:20,5 mm²/sKon-applicable *Non-applicable *PH:Non-applicable *Vapour density at 20 °C:Non-applicable *Ph:Non-applicable * <tr <="" td=""><td></td></tr> <tr><td>Physical state at 20 °C:LiquidAppearance:ViscousColour:According to the markings on the packageOdour:CharacteristicOdour threshold:Non-applicable *Volatility:II8 °CBoiling point at atmospheric pressure:118 °CVapour pressure at 20 °C:2098 PaVapour pressure at 50 °C:11040,17 Pa (11,04 kPa)Evaporation rate at 20 °C:Non-applicable *Product description:1620 kg/m³Pensity at 20 °C:1,62Dynamic viscosity at 20 °C:2,03 cPKinematic viscosity at 20 °C:1,28 mm²/sKinematic viscosity at 20 °C:20,5 mm²/sConcentration:Non-applicable *pH:Non-applicable *pH:Non-applicable *pH:Non-applicable *Partition coefficient n-octanol/water 20 °C:Non-applicable *</td><td></td></tr> <tr><td>Appearance:ViscousColour:According to the markings on the packageOdour:CharacteristicOdour threshold:Non-applicable *Volatility:Non-applicable *Boiling point at atmospheric pressure:118 °CVapour pressure at 20 °C:2098 PaVapour pressure at 50 °C:11040,17 Pa (11,04 kPa)Evaporation rate at 20 °C:Non-applicable *Product description:1620 kg/m³Relative density at 20 °C:1,62Dynamic viscosity at 20 °C:2,03 cPKinematic viscosity at 20 °C:1,28 mm²/sKinematic viscosity at 40 °C:<20,5 mm²/s</td>Concentration:Non-applicable *pH:Non-applicable *Vapour density at 20 °C:Non-applicable *pH:Non-applicable *pH:Non-applicable *Vapour density at 20 °C:Non-applicable *pH:Non-applicable *pH:Non-applicable *pH:Non-applicable *Partition coefficient n-octanol/water 20 °C:Non-applicable *</tr>		Physical state at 20 °C:LiquidAppearance:ViscousColour:According to the markings on the packageOdour:CharacteristicOdour threshold:Non-applicable *Volatility:II8 °CBoiling point at atmospheric pressure:118 °CVapour pressure at 20 °C:2098 PaVapour pressure at 50 °C:11040,17 Pa (11,04 kPa)Evaporation rate at 20 °C:Non-applicable *Product description:1620 kg/m³Pensity at 20 °C:1,62Dynamic viscosity at 20 °C:2,03 cPKinematic viscosity at 20 °C:1,28 mm²/sKinematic viscosity at 20 °C:20,5 mm²/sConcentration:Non-applicable *pH:Non-applicable *pH:Non-applicable *pH:Non-applicable *Partition coefficient n-octanol/water 20 °C:Non-applicable *		Appearance:ViscousColour:According to the markings on the packageOdour:CharacteristicOdour threshold:Non-applicable *Volatility:Non-applicable *Boiling point at atmospheric pressure:118 °CVapour pressure at 20 °C:2098 PaVapour pressure at 50 °C:11040,17 Pa (11,04 kPa)Evaporation rate at 20 °C:Non-applicable *Product description:1620 kg/m³Relative density at 20 °C:1,62Dynamic viscosity at 20 °C:2,03 cPKinematic viscosity at 20 °C:1,28 mm²/sKinematic viscosity at 40 °C:<20,5 mm²/s	Liquid			
Physical state at 20 °C:LiquidAppearance:ViscousColour:According to the markings on the packageOdour:CharacteristicOdour threshold:Non-applicable *Volatility:II8 °CBoiling point at atmospheric pressure:118 °CVapour pressure at 20 °C:2098 PaVapour pressure at 50 °C:11040,17 Pa (11,04 kPa)Evaporation rate at 20 °C:Non-applicable *Product description:1620 kg/m³Pensity at 20 °C:1,62Dynamic viscosity at 20 °C:2,03 cPKinematic viscosity at 20 °C:1,28 mm²/sKinematic viscosity at 20 °C:20,5 mm²/sConcentration:Non-applicable *pH:Non-applicable *pH:Non-applicable *pH:Non-applicable *Partition coefficient n-octanol/water 20 °C:Non-applicable *								
Appearance:ViscousColour:According to the markings on the packageOdour:CharacteristicOdour threshold:Non-applicable *Volatility:Non-applicable *Boiling point at atmospheric pressure:118 °CVapour pressure at 20 °C:2098 PaVapour pressure at 50 °C:11040,17 Pa (11,04 kPa)Evaporation rate at 20 °C:Non-applicable *Product description:1620 kg/m³Relative density at 20 °C:1,62Dynamic viscosity at 20 °C:2,03 cPKinematic viscosity at 20 °C:1,28 mm²/sKinematic viscosity at 40 °C:<20,5 mm²/s								
Colour:According to the markings on the packageOdour:CharacteristicOdour threshold:Non-applicable *Volatility:InterventionBoiling point at atmospheric pressure:118 °CVapour pressure at 20 °C:2098 PaVapour pressure at 50 °C:11040,17 Pa (11,04 kPa)Evaporation rate at 20 °C:Non-applicable *Product description:InterventionDensity at 20 °C:1620 kg/m³Relative density at 20 °C:1,62Dynamic viscosity at 20 °C:2,03 cPKinematic viscosity at 20 °C:1,28 mm²/sKinematic viscosity at 40 °C:<20,5 mm²/s								
Odour:CharacteristicOdour threshold:Non-applicable *Volatility:Non-applicable *Boiling point at atmospheric pressure:118 °CVapour pressure at 20 °C:2098 PaVapour pressure at 50 °C:11040,17 Pa (11,04 kPa)Evaporation rate at 20 °C:Non-applicable *Product description:1620 kg/m³Density at 20 °C:1,62Dynamic viscosity at 20 °C:2,03 cPKinematic viscosity at 20 °C:1,28 mm²/sKinematic viscosity at 40 °C:<20,5 mm²/s								
Odour threshold:Non-applicable *Volatility:Boiling point at atmospheric pressure:118 °CVapour pressure at 20 °C:2098 PaVapour pressure at 50 °C:11040,17 Pa (11,04 kPa)Evaporation rate at 20 °C:Non-applicable *Product description:Non-applicable *Density at 20 °C:1620 kg/m³Relative density at 20 °C:2,03 cPKinematic viscosity at 20 °C:1,28 mm²/sKinematic viscosity at 40 °C:<20,5 mm²/s								
Volatility:Boiling point at atmospheric pressure:118 °CVapour pressure at 20 °C:2098 PaVapour pressure at 50 °C:11040,17 Pa (11,04 kPa)Evaporation rate at 20 °C:Non-applicable *Product description:1620 kg/m³Density at 20 °C:1,62Dynamic viscosity at 20 °C:2,03 cPKinematic viscosity at 20 °C:1,28 mm²/sKinematic viscosity at 20 °C:2,05 mm²/sFrom the second of the second								
Boiling point at atmospheric pressure:118 °CVapour pressure at 20 °C:2098 PaVapour pressure at 50 °C:11040,17 Pa (11,04 kPa)Evaporation rate at 20 °C:Non-applicable * Product description: 1620 kg/m³Density at 20 °C:1,62Dynamic viscosity at 20 °C:2,03 cPKinematic viscosity at 20 °C:1,28 mm²/sKinematic viscosity at 40 °C:<20,5 mm²/s								
Vapour pressure at 20 °C:2098 PaVapour pressure at 50 °C:11040,17 Pa (11,04 kPa)Evaporation rate at 20 °C:Non-applicable *Product description:Image: Construction of the second								
Vapour pressure at 50 °C:11040,17 Pa (11,04 kPa)Evaporation rate at 20 °C:Non-applicable *Product description:1620 kg/m³Density at 20 °C:1,62Relative density at 20 °C:2,03 cPKinematic viscosity at 20 °C:1,28 mm²/sKinematic viscosity at 20 °C:<20,5 mm²/s								
Evaporation rate at 20 °C:Non-applicable *Product description:1620 kg/m³Density at 20 °C:1,62Dynamic viscosity at 20 °C:2,03 cPKinematic viscosity at 20 °C:1,28 mm²/sKinematic viscosity at 40 °C:<20,5 mm²/s								
Product description:Density at 20 °C:1620 kg/m³Relative density at 20 °C:1,62Dynamic viscosity at 20 °C:2,03 cPKinematic viscosity at 20 °C:1,28 mm²/sKinematic viscosity at 40 °C:<20,5 mm²/s								
Density at 20 °C:1620 kg/m³Relative density at 20 °C:1,62Dynamic viscosity at 20 °C:2,03 cPKinematic viscosity at 20 °C:1,28 mm²/sKinematic viscosity at 40 °C:<20,5 mm²/s								
Relative density at 20 °C:1,62Dynamic viscosity at 20 °C:2,03 cPKinematic viscosity at 20 °C:1,28 mm²/sKinematic viscosity at 40 °C:<20,5 mm²/s								
Dynamic viscosity at 20 °C:2,03 cPKinematic viscosity at 20 °C:1,28 mm²/sKinematic viscosity at 40 °C:<20,5 mm²/s								
Kinematic viscosity at 20 °C:1,28 mm²/sKinematic viscosity at 40 °C:<20,5 mm²/s								
Kinematic viscosity at 40 °C:<20,5 mm²/sConcentration:Non-applicable *pH:Non-applicable *Vapour density at 20 °C:Non-applicable *Partition coefficient n-octanol/water 20 °C:Non-applicable *								
Concentration:Non-applicable *pH:Non-applicable *Vapour density at 20 °C:Non-applicable *Partition coefficient n-octanol/water 20 °C:Non-applicable *								
pH:Non-applicable *Vapour density at 20 °C:Non-applicable *Partition coefficient n-octanol/water 20 °C:Non-applicable *								
Vapour density at 20 °C:Non-applicable *Partition coefficient n-octanol/water 20 °C:Non-applicable *								
Partition coefficient n-octanol/water 20 °C: Non-applicable *								
Solubility in water at 20 °C: Non-applicable *								
Solubility properties: Non-applicable *								
Decomposition temperature: Non-applicable *								
Melting point/freezing point: Non-applicable *								

** Changes with regards to the previous version



HS 4:1

Printing	: 27/01/2023	Date of compilation: 06/06/2006	Revised: 15/09/2022	Version: 7 (Replaced 6)
SEC	TION 9: PHYSIC	CAL AND CHEMICAL PROPERTIE	S ** (continued)	
	Flash Point:		34 °C	
	Flammability (so	lid, gas):	Non-applicable *	
	Autoignition tem	iperature:	238 °C	
	Lower flammabil	lity limit:	Not available	
	Upper flammabil	ity limit:	Not available	
	Particle charac	cteristics:		
	Median equivale	nt diameter:	Non-applicable	
9.2	Other informat	tion:		
	Information w	ith regard to physical hazard clas	sses:	
	Explosive proper	ties:	Non-applicable *	
	Oxidising proper	ties:	Non-applicable *	
	Corrosive to met	als:	Non-applicable *	
	Heat of combust	ion:	Non-applicable *	
	components:	ercentage (by mass) of flammable	Non-applicable *	
	Other safety cl			
	Surface tension a	at 20 ºC:	Non-applicable *	
	Refraction index	:	Non-applicable *	
	*Not relevant due to	o the nature of the product, not providing info	prmation property of its hazards.	

** Changes with regards to the previous version

	Reactivity:				
	No hazardous reactions are	e expected because the	product is stable under reco	mmended storage condit	tions. See section 7.
0.2	Chemical stability:				
	Chemically stable under the	e indicated conditions of	f storage, handling and use.		
0.3	Possibility of hazardous	reactions:			
	•		s that lead to excessive tem	peratures or pressure ar	a not expected
	·			perdures of pressure and	e not expected
0.4	Conditions to avoid:				
	Applicable for handling and	l storage at room tempe	erature:		
	Shock and friction	Contact with air	Increase in temperature	Sunlight	Humidity
	Not applicable	Not applicable	Risk of combustion	Avoid direct impact	Not applicable
0.5	Incompatible materials	:			
0.5	Incompatible materials Acids	Water	Oxidising materials	Combustible materials	Others
0.5			Oxidising materials Avoid direct impact	Combustible materials Not applicable	Others Avoid alkalis or strong bases
0.5	Acids Avoid strong acids	Water Not applicable	-		

SECTION 11: TOXICOLOGICAL INFORMATION **

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008:

The experimental information related to the toxicological properties of the product itself is not available

Contains glycols. It is recommended not to breathe the vapours for prolonged periods of time due to the possibility of effects that are hazardous to the health .

** Changes with regards to the previous version



HS 4:1

	Date of compilation: 06/06/2006	Revised: 15/09/202	22 Version: 7 (Replace	a 6)
ON 11: TOXI	COLOGICAL INFORMATION ** (co	ntinued)		
Dangerous he	alth implications:			
	sure that is repetitive, prolonged or at co on health may result, depending on the cute effect):		n the recommended occupatic	onal exposure lim
as dangero	-	n see section 3.		
 Acute to: as hazardou Corrosivi classified as 	kicity : Based on available data, the class is for inhalation. For more information se ty/Irritability: Based on available data, th hazardous for inhalation. For more infor in the skin and the eyes (acute effect):	e section 3. le classification criteria a		
- Contact	with the skin: Produces skin inflammatior with the eyes: Produces eye damage afte (carcinogenicity, mutagenicity and toxici	er contact.		
as dangerou IARC: Xyl isoalkanes, Titanium diu - Mutagen hazardous f - Reprodu classified as	enicity: Based on available data, the class is with carcinogenic effects. For more infe ene (3); Ethylbenzene (2B); Methyl meth cyclics, aromatics (2-25%) (3); 2-butoxyd oxide (aerodynamic diameter $\leq 10 \ \mu$ m) (2 icity: Based on available data, the classifi or this effect. For more information see s trive toxicity: Based on available data, the hazardous for this effect. For more infor	ormation see section 3. hacrylate (3); n-butyl acr ethanol (3); Talc (3); Ca 2B) ication criteria are not m section 3. e classification criteria a	ylate (3); Hydrocarbons, C9-C Irbon black (2B); Quartz (1 % net, as it does not contain sub:	C12, n-alkanes, < RCS < 10%) (stances classified
hazardous v - Skin: Bas dangerous v	effects: bry: Based on available data, the classification with sensitising effects. For more informal sed on available data, the classification cr with sensitising effects. For more informa get organ toxicity (STOT) - single exposu	tion see section 3. riteria are not met. How tion see section 3.		
Based on av inhalation. I	vailable data, the classification criteria are for more information see section 3. Jet organ toxicity (STOT)-repeated expos	e not met. However, it c	contains substances classified	as hazardous foi
nervous sys consciousne - Skin: Bas	ed on available data, the classification cr dangerous due to repetitive exposure. F	, nausea, vomiting, con riteria are not met. How	fusion, and in serious cases, lo vever, it does contain substanc	oss of
The consum	ption of a considerable dose can cause p	oulmonary damage.		
Other inform	ition:			
		er < 10 um). The classi		
CAS 13463-67- to mixtures in p aerodynamic di	7 Titanium dioxide (aerodynamic diametrowder form containing 1 % or more of tiameter \leq 10 µm	itanium dioxide which is	in the form of or incorporated	l in particles wit
CAS 13463-67- to mixtures in p aerodynamic di	owder form containing 1 % or more of the substances of the subs	itanium dioxide which is		
CAS 13463-67- to mixtures in p aerodynamic di Specific toxic	owder form containing 1 % or more of the ameter \leq 10 μ m	itanium dioxide which is	Acute toxicity	Genus
CAS 13463-67- to mixtures in p aerodynamic di	owder form containing 1 % or more of the substances of the subs	itanium dioxide which is s: LD50	Acute toxicity	

** Changes with regards to the previous version



g: 27/01/2023 Date of compilation: 06/06/2006	6 Revised: 15/09/2022	Version: 7 (Replaced	6)
CTION 11: TOXICOLOGICAL INFORMATION **	(continued)		
Identification		Acute toxicity	Genus
Xylene	LD50 oral	2100 mg/kg	Rat
CAS: 1330-20-7	LD50 derr	mal 1100 mg/kg	Rat
EC: 215-535-7	LC50 inha	lation 11 mg/L (ATEi)	
2-butoxyethyl acetate	LD50 oral	2100 mg/kg	Rat
CAS: 112-07-2	LD50 derr	mal 1480 mg/kg	Rabbit
EC: 203-933-3	LC50 inha	lation 11 mg/L (4 h)	Rat
Titanium dioxide (aerodynamic diameter \leq 10 µm)	LD50 oral	10000 mg/kg	Rat
CAS: 13463-67-7	LD50 derr	nal 10000 mg/kg	Rabbit
EC: 236-675-5	LC50 inha	lation >5 mg/L	
Ethylbenzene	LD50 oral	3500 mg/kg	Rat
CAS: 100-41-4	LD50 derr	mal 15354 mg/kg	Rabbit
EC: 202-849-4	LC50 inha	lation 17,2 mg/L (4 h)	Rat
2-methoxy-1-methylethyl acetate	LD50 oral	8532 mg/kg	Rat
CAS: 108-65-6	LD50 derr	mal 5100 mg/kg	Rat
EC: 203-603-9	LC50 inha	lation 30 mg/L (4 h)	Rat
Quartz (1 %< RCS < 10%)	LD50 oral	>2000 mg/kg	
CAS: 14808-60-7	LD50 derr	mal >2000 mg/kg	
EC: 238-878-4	LC50 inha	lation >5 mg/L	
Methyl methacrylate	LD50 oral	>2000 mg/kg	
CAS: 80-62-6	LD50 derr	mal >2000 mg/kg	
EC: 201-297-1	LC50 inha	lation >20 mg/L	
n-butyl acrylate	LD50 oral	4000 mg/kg	
CAS: 141-32-2	LD50 derr	mal >2000 mg/kg	
EC: 205-480-7	LC50 inha	lation >20 mg/L	
2-butoxyethanol	LD50 oral	1200 mg/kg	Rat
CAS: 111-76-2	LD50 derr	mal 3000 mg/kg	Rabbit
EC: 203-905-0	LC50 inha	lation 3 mg/L	

Acute Toxicity Estimate (ATE mix):

	ATE mix	Ingredient(s) of unknown toxicity
Oral	Dral >2000 mg/kg (Calculation method)	
Dermal	Dermal 8821,78 mg/kg (Calculation method)	
Inhalation	84,76 mg/L (4 h) (Calculation method)	0 %

11.2 Information on other hazards:

Endocrine disrupting properties

Endocrine-disrupting properties: The product fails to meet the criteria.

Other information

Non-applicable

** Changes with regards to the previous version

SECTION 12: ECOLOGICAL INFORMATION **

The experimental information related to the eco-toxicological properties of the product itself is not available

12.1 Toxicity:

Acute toxicity:

Identification		Concentration	Species	Genus
Xylene	LC50	>10 - 100 mg/L (96 h)		Fish
CAS: 1330-20-7	EC50	>10 - 100 mg/L (48 h)		Crustacean
EC: 215-535-7	EC50	>10 - 100 mg/L (72 h)		Algae

** Changes with regards to the previous version



Genus

Algae

Fish

Crustacean

Algae

Fish

Crustacean

Algae

Fish

Crustacean

Fish

Crustacean

Algae

Fish

Crustacean

Algae

Fish

Crustacean

Algae

HS 4:1

Printing: 27/01/2023 Date of compilation: 06/06/2006 Revised: 15/09/2022 Version: 7 (Replaced 6) SECTION 12: ECOLOGICAL INFORMATION ** (continued) Identification Concentration Species LC50 Non-applicable N-butyl acetate CAS: 123-86-4 EC50 Non-applicable EC: 204-658-1 EC50 675 mg/L (72 h) Scenedesmus subspicatus LC50 80 mg/L (48 h) 2-butoxyethyl acetate Leuciscus idus EC50 CAS: 112-07-2 37 mg/L (48 h) Daphnia magna EC: 203-933-3 EC50 500 mg/L (72 h) Scenedesmus subspicatus Ethylbenzene LC50 42,3 mg/L (96 h) Pimephales promelas EC50 Daphnia magna CAS: 100-41-4 75 mg/L (48 h) EC50 EC: 202-849-4 63 mg/L (3 h) Chlorella vulgaris 2-methoxy-1-methylethyl acetate LC50 161 mg/L (96 h) Pimephales promelas CAS: 108-65-6 EC50 481 mg/L (48 h) Daphnia sp. EC: 203-603-9 EC50 Non-applicable 191 mg/L (96 h) LC50 Methyl methacrylate Lepomis macrochirus EC50 CAS: 80-62-6 69 mg/L (48 h) Daphnia magna EC: 201-297-1 EC50 170 mg/L (96 h) Selenastrum capricornutum LC50 5,2 mg/L (96 h) n-butyl acrylate Salmo gairdneri CAS: 141-32-2 EC50 230 mg/L (24 h) Daphnia magna EC: 205-480-7 EC50 5,5 mg/L (96 h) Selenastrum capricornutum LC50 2-butoxyethanol 1490 mg/L (96 h) Lepomis macrochirus EC50 CAS: 111-76-2 1815 mg/L (48 h) Daphnia magna EC: 203-905-0 EC50 911 mg/L (72 h) Pseudokirchneriella subcapitata

Chronic toxicity:

Identification	Conc	entration	Species	Genus
Xylene	NOEC 1,3 mg/	/L	Oncorhynchus mykiss	Fish
CAS: 1330-20-7 EC: 215-535-7	NOEC 1,17 mg	g/L	Ceriodaphnia dubia	Crustacean
N-butyl acetate	NOEC Non-ap	plicable		
CAS: 123-86-4 EC: 204-658-1	NOEC 23,2 mg	g/L	Daphnia magna	Crustacean
Ethylbenzene	NOEC Non-ap	plicable		
CAS: 100-41-4 EC: 202-849-4	NOEC 0,96 mg	g/L	Ceriodaphnia dubia	Crustacean
2-methoxy-1-methylethyl acetate	NOEC 47,5 mg	g/L	Oryzias latipes	Fish
CAS: 108-65-6 EC: 203-603-9	NOEC 100 mg	/L	Daphnia magna	Crustacean
Methyl methacrylate	NOEC 9,4 mg/	/L	Danio rerio	Fish
CAS: 80-62-6 EC: 201-297-1	NOEC 37 mg/l	L	Daphnia magna	Crustacean
n-butyl acrylate	NOEC Non-ap	plicable		
CAS: 141-32-2 EC: 205-480-7	NOEC 0,136 m	ng/L	Daphnia magna	Crustacean
2-butoxyethanol	NOEC 100 mg	/L	Danio rerio	Fish
CAS: 111-76-2 EC: 203-905-0	NOEC 100 mg	/L	Daphnia magna	Crustacean

12.2 Persistence and degradability:

Substance-specific information:

Identification	Degra	adability	Biodegradat	bility
Xylene	BOD5	Non-applicable	Concentration	Non-applicable
CAS: 1330-20-7	COD	Non-applicable	Period	28 days
EC: 215-535-7	BOD5/COD	Non-applicable	% Biodegradable	88 %
N-butyl acetate	BOD5	Non-applicable	Concentration	Non-applicable
CAS: 123-86-4	COD	Non-applicable	Period	5 days
EC: 204-658-1	BOD5/COD	Non-applicable	% Biodegradable	84 %
2-butoxyethyl acetate	BOD5	Non-applicable	Concentration	30 mg/L
CAS: 112-07-2	COD	Non-applicable	Period	28 days
EC: 203-933-3	BOD5/COD	Non-applicable	% Biodegradable	77,3 %

** Changes with regards to the previous version



Safety data sheet This SDS is an English translation of COMMISSION REGULATION (EU) 2020/878, without any country-specific legislation

HS 4:1

			continued)					
	Identification		De	egradability		В	iodegrada	bility
	Ethylbenzene		BOD5	Non-applicable	Conc	entration		100
	CAS: 100-41-4		COD	Non-applicable	Perio	d		14
	EC: 202-849-4		BOD5/COD	Non-applicable	% Bi	odegradable		90
	2-methoxy-1-methylethyl acetate		BOD5	Non-applicable	Conc	entration		785
	CAS: 108-65-6		COD	Non-applicable	Perio	d		8 d
	EC: 203-603-9		BOD5/COD	Non-applicable	% Bi	odegradable		100
	Methyl methacrylate		BOD5	Non-applicable	Conc	entration		100
	CAS: 80-62-6		COD	Non-applicable	Perio	d		14
	EC: 201-297-1		BOD5/COD	Non-applicable	% Bi	odegradable		94,
	n-butyl acrylate		BOD5	Non-applicable	Conc	entration		100
	CAS: 141-32-2		COD	Non-applicable	Perio	d		14
	EC: 205-480-7		BOD5/COD	Non-applicable	% Bi	odegradable		61,3
	2-butoxyethanol		BOD5	0,71 g O2/g	Conc	entration		100
	CAS: 111-76-2		COD	2,2 g O2/g	Perio	d		14 (
	EC: 203-905-0		BOD5/COD	0,32	% Bi	odegradable		96 9
		lentification					cumulatio	n pot
		lentification					-	n pot
	Xylene				BC		9	
	CAS: 1330-20-7					w Log	2.77	
	EC: 215-535-7					tential	Low	
	N-butyl acetate				BC		4	
	CAS: 123-86-4					w Log	1.78	
	EC: 204-658-1					tential	Low	
	2-butoxyethyl acetate				BC		3	
	CAS: 112-07-2					w Log	1.51	
	EC: 203-933-3					tential	Low	
	Ethylbenzene				BC		1	
	CAS: 100-41-4					w Log	3.15	
	EC: 202-849-4					tential	Low	
	2-methoxy-1-methylethyl acetate				BC		1	
	CAS: 108-65-6					w Log	0.43	
	EC: 203-603-9					tential	Low	
	Methyl methacrylate				BC		7	
	CAS: 80-62-6					w Log	1.38	
	EC: 201-297-1					tential	Low	
	n-butyl acrylate				BC		37	
	CAS: 141-32-2					w Log	2.36	
	EC: 205-480-7					tential	Mode	rate
	2-butoxyethanol				BC		3	
	CAS: 111-76-2					w Log	0.83	
	EC: 203-905-0				Po	tential	Low	
2.4	Mobility in soil:							
	Identification		Abs	orption/desorption			Vola	tility

Identification	Absorption/desorption		Volat	ility
Xylene	Кос	202	Henry	524,86 Pa·m ³ /mol
CAS: 1330-20-7	Conclusion	Moderate	Dry soil	Yes
EC: 215-535-7	Surface tension	Non-applicable	Moist soil	Yes
N-butyl acetate	Кос	Non-applicable	Henry	Non-applicable
CAS: 123-86-4	Conclusion	Non-applicable	Dry soil	Non-applicable
EC: 204-658-1	Surface tension	2,478E-2 N/m (25 °C)	Moist soil	Non-applicable

** Changes with regards to the previous version

- CONTINUED ON NEXT PAGE -



Safety data sheet This SDS is an English translation of COMMISSION REGULATION (EU) 2020/878, without any country-specific legislation

Printing: 27/01/2023 Date of compilation: 06/06/2006 Revised: 15/09/2022 Version: 7 (Replaced 6) SECTION 12: ECOLOGICAL INFORMATION ** (continued) Identification Volatility Absorption/desorption 5,532E-1 Pa·m³/mol 2-butoxyethyl acetate Кос Non-applicable Henry Conclusion CAS: 112-07-2 Non-applicable Dry soil No EC: 203-933-3 Surface tension Non-applicable Moist soil Yes Кос 520 Henry 798,44 Pa·m³/mol Ethylbenzene CAS: 100-41-4 Conclusion Moderate Dry soil Yes EC: 202-849-4 Surface tension 2,859E-2 N/m (25 °C) Moist soil Yes Methyl methacrylate Кос Non-applicable Henry Non-applicable CAS: 80-62-6 Conclusion Non-applicable Dry soil Non-applicable Surface tension 2,551E-2 N/m (25 °C) Moist soil EC: 201-297-1 Non-applicable n-butyl acrylate Кос Non-applicable Henry Non-applicable CAS: 141-32-2 Conclusion Non-applicable Dry soil Non-applicable EC: 205-480-7 Surface tension 2,598E-2 N/m (25 °C) Moist soil Non-applicable 1,621E-1 Pa⁻m³/mol 2-butoxyethanol Koc Henry CAS: 111-76-2 Conclusion Very High Dry soil No FC: 203-905-0 2,729E-2 N/m (25 °C) Moist soil Surface tension Yes 12.5 Results of PBT and vPvB assessment: Product fails to meet PBT/vPvB criteria

12.6 Endocrine disrupting properties:

Endocrine-disrupting properties: The product fails to meet the criteria.

12.7 Other adverse effects:

Not described

** Changes with regards to the previous version

SECTION 13: DISPOSAL CONSIDERATIONS

13.1 Waste treatment methods:

Code	Description	Waste class (Regulation (EU) No 1357/2014)
08 01 11*	waste paint and varnish containing organic solvents or other hazardous substances	Dangerous
15 01 10*	packaging containing residues of or contaminated by hazardous substances	Dangerous

Type of waste (Regulation (EU) No 1357/2014):

HP5 Specific Target Organ Toxicity (STOT)/Aspiration Toxicity, HP3 Flammable, HP4 Irritant — skin irritation and eye damage

Waste management (disposal and evaluation):

Consult the authorized waste service manager on the assessment and disposal operations in accordance with Annex 1 and Annex 2 (Directive 2008/98/EC). As under 15 01 (2014/955/EC) of the code and in case the container has been in direct contact with the product, it will be processed the same way as the actual product. Otherwise, it will be processed as non-dangerous residue. Waste should not be disposed of to drains. See paragraph 6.2.

Regulations related to waste management:

In accordance with Annex II of Regulation (EC) No 1907/2006 (REACH) the community or state provisions related to waste management are stated

Community legislation: Directive 2008/98/EC, 2014/955/EU, Regulation (EU) No 1357/2014

SECTION 14: TRANSPORT INFORMATION

Transport of dangerous goods by land:

With regard to ADR 2021 and RID 2021:

HS 4:1

Printing: 27/01/2023 D	Date c	of compilation: 06/06/2006	Revised: 15/09/2022	Version: 7 (Replaced 6)
SECTION 14: TRANSPO	ORT I	NFORMATION (continued)		
	L4.2 L4.3 L4.4 L4.5	UN number or ID number: UN proper shipping name: Transport hazard class(es): Labels: Packing group: Environmental hazards: Special precautions for user	UN1263 PAINT 3 3 III No	
		Special regulations: Tunnel restriction code: Physico-Chemical properties: Limited quantities: Maritime transport in bulk	163, 367, 650 D/E see section 9 5 L Non-applicable	
		according to IMO instruments:		
Transport of dang	gero	us goods by sea:		
With regard to IMD	G 40-	-20:		
		UN number or ID number:	UN1263	
		UN proper shipping name:	PAINT	
	14.3	Transport hazard class(es): Labels:	3 3	
	4.4	Packing group:	III	
		Marine pollutant:	No	
		Special precautions for user		
		Special regulations:	223, 955, 163, 367	
		EmS Codes:	F-E, S-E	
		Physico-Chemical properties:	see section 9	
		Limited quantities:	5 L	
		Segregation group:	Non-applicable	
1	14.7	Maritime transport in bulk according to IMO instruments:	Non-applicable	
Transport of dan	gero	us goods by air:		
With regard to IATA	A/ICA	O 2023:		
	L 4.1	UN number or ID number:	UN1263	
		UN proper shipping name:	PAINT	
	14.3	Transport hazard class(es):	3	
3		Labels: Packing group:	3 III	
· · · · · · · · · · · · · · · · · · ·		Environmental hazards:	No	
		Special precautions for user		
		Physico-Chemical properties:	see section 9	
1	14.7	Maritime transport in bulk according to IMO instruments:	Non-applicable	

SECTION 15: REGULATORY INFORMATION

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture: Candidate substances for authorisation under the Regulation (EC) No 1907/2006 (REACH): Non-applicable Substances included in Annex XIV of REACH ("Authorisation List") and sunset date: Non-applicable

Regulation (EC) No 1005/2009, about substances that deplete the ozone layer: Non-applicable

Article 95, REGULATION (EU) No 528/2012: Non-applicable



Safety data sheet

This SDS is an English translation of COMMISSION REGULATION (EU) 2020/878, without any country-specific legislation

HS 4:1

		D			Lower-tier	Upper-tier
Section P5c	FLAMMABLE LIQUIDS	Descrip	tion		requirements 5000	requirement 50000
		and the use of co	ertain dangerous substa	nces and mixt		
and ashtrays —tricks and —games for Occupationa	al articles intended to proc s, jokes, one or more participants,	or any article inter ystalline silica mus	effects by means of different nded to be used as such, e t be controlled pursuant to or the environment:	ven with orname	ntal aspects.	amental lamp
	in order to establish the		s safety data sheet as a ba rention measures for the ha			
-	could be affected by sect	orial legislation				
	afety assessment:					
	has not carried out evalu	ation of chemical s	afety.			
Legislation The SDS sha has been de		sheets: I language of the c ANNEX II-Guide to	ountry where the product the compilation of safety			
Legislation The SDS sha has been de (COMMISSIO Modificatio COMMISSIO COMPOSITIO · New dec	related to safety data ill be supplied in an officia signed in accordance with DN REGULATION (EU) 202 ons related to the previo N REGULATION (EU) 2020 DN/INFORMATION ON ING lared substances	sheets: I language of the c ANNEX II-Guide to 0/878). ous Safety Data 0/878		data sheets of Rone ways of mar	egulation (EC)) No 1907/200
Legislation The SDS sha has been de (COMMISSIO COMMISSIO COMPOSITIO New dec n-buty CLP Regulati Hazard s Information	related to safety data ill be supplied in an officia signed in accordance with DN REGULATION (EU) 202 ons related to the previo N REGULATION (EU) 2020 DN/INFORMATION ON ING lared substances /l acrylate (141-32-2) ion (EC) No 1272/2008 (Si tatements on basic physical and che	sheets: I language of the c ANNEX II-Guide to 0/878). DUS Safety Data D/878 GREDIENTS (SECT ECTION 2, SECTIO	b the compilation of safety Sheet which concerns t ION 3, SECTION 11, SECTI N 16):	data sheets of Rone ways of mar	egulation (EC)) No 1907/200
Legislation The SDS sha has been de (COMMISSIO COMMISSIO COMPOSITIO New dec n-buty CLP Regulati Hazard s Information Flash Poi Texts of th H315: Cause H373: May c H304: May b	related to safety data ill be supplied in an officia signed in accordance with DN REGULATION (EU) 202 ons related to the previo N REGULATION (EU) 2020 DN/INFORMATION ON ING lared substances // acrylate (141-32-2) ion (EC) No 1272/2008 (Si tatements on basic physical and chein te legislative phrases m es skin irritation.	sheets: I language of the c ANNEX II-Guide to 0/878). OUS Safety Data D/878 GREDIENTS (SECT: ECTION 2, SECTIO mical properties (S entioned in sect prough prolonged of	b the compilation of safety Sheet which concerns t TON 3, SECTION 11, SECTI N 16): ECTION 9):	data sheets of Rone ways of mar ON 12):	egulation (EC)) No 1907/200

** Changes with regards to the previous version

Safety data sheet

This SDS is an English translation of COMMISSION REGULATION (EU) 2020/878, without any country-specific legislation

HS 4:1

Printing: 27/01/2023	Date of compilation: 06/06/2006	Revised: 15/09/2022	Version: 7 (Replaced 6)
SECTION 16: OTHE	ER INFORMATION ** (continued)		
Acute Tox. 4: H Acute Tox. 4: H Acute Tox. 4: H Aquatic Tox. 4: H Aquatic Chronic Asp. Tox. 1: H3 Carc. 2: H351 - Eye Irrit. 2: H3 Flam. Liq. 2: H Flam. Liq. 3: H Skin Irrit. 2: H3 Skin Sens. 11: H Skin Sens. 12: H3 STOT RE 2: H3 STOT RE 2: H3 STOT RE 2: H3	 1331 - Toxic if inhaled. 1302 - Harmful if swallowed. 1312+H332 - Harmful in contact with skin 1332 - Harmful if inhaled. 23: H412 - Harmful to aquatic life with low 204 - May be fatal if swallowed and enterer Suspected of causing cancer (Inhalation 19 - Causes serious eye irritation. 225 - Highly flammable liquid and vapour. 235 - Causes skin irritation. 1317 - May cause an allergic skin reaction 1317 - May cause an allergic skin reaction 73 - May cause damage to organs throug. 73 - May cause damage to organs throug. 73 - May cause damage to organs throug. 75 - May cause damage to organs throug. 76 - May cause drowsiness or dizziness. 	ong lasting effects. s airways. n). r. n. gh prolonged or repeated expo gh prolonged or repeated expo	osure (Oral).
Classification	procedure:		
STOT RE 2: Cal Asp. Tox. 1: Ca Flam. Liq. 3: Ca	lculation method culation method lculation method alculation method (2.6.4.3) culation method		
Advice relate			
Training is reco	5		t and to facilitate their comprehension and
Principal bibl	ographical sources:		
http://echa.eur http://eur-lex.e	1		
Abbreviations	and acronyms:		
IMDG: Internat IATA: Internation ICAO: Internation COD: Chemical BOD5: 5day bion BCF: Bioconcer LD50: Lethal Do LC50: Lethal Co EC50: Effective	ose 50		, , , , , , , , , , , , , , , , , , ,
UFI: unique for	oefficient of organic carbon mula identifier onal Agency for Research on Cancer		

** Changes with regards to the previous version

The information contained in this safety data sheet is based on sources, technical knowledge and current legislation at European and state level, without being able to guarantee its accuracy. This information cannot be considered a guarantee of the properties of the product, it is simply a description of the security requirements. The occupational methodology and conditions for users of this product are not within our awareness or control, and it is ultimately the responsibility of the user to take the necessary measures to obtain the legal requirements concerning the manipulation, storage, use and disposal of chemical products. The information on this safety data sheet only refers to this product, which should not be used for needs other than those specified.