STER

This SDS is an English translation of COMMISSION REGULATION (EU) 2020/878, without any country-specific legislation

HYBRID

	HIRKID
nting:	: 19/12/2022 Date of compilation: 26/06/2011 Revised: 25/02/2022 Version: 7 (Replaced 6)
SECT	TION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING
1.1	Product identifier: HYBRID
	Other means of identification:
	UFI: KHMU-F08H-T00F-110W
L.2	Relevant identified uses of the substance or mixture and uses advised against:
	Relevant uses: Car repair. For professional users only.
	Uses advised against: All uses not specified in this section or in section 7.3
L.3	Details of the supplier of the safety data sheet:
	Troton Sp. z o.o. Ząbrowo 14A 78-120 Gościno - Zachodniopomorskie - Polska Phone: +48 94 35 123 94 - Fax: +48 94 35 126 22 troton@troton.com.pl www.troton.pl / www.troton.eu
1.4	Emergency telephone number: (8am-4pm)+48 094 35 123 94; 112
SECT	TION 2: HAZARDS IDENTIFICATION
2.1	Classification of the substance or mixture:
	CLP Regulation (EC) No 1272/2008:
	Classification of this product has been carried out in accordance with CLP Regulation (EC) No 1272/2008.
2.2	Flam. Liq. 3: Flammable liquids, Category 3, H226 Repr. 2: Reproductive toxicity, Category 2, H361d Skin Irrit. 2: Skin irritation, Category 2, H315 STOT RE 1: Specific target organ toxicity — Repeated exposure, Hazard Category 1, H372 Label elements:
2.2	CLP Regulation (EC) No 1272/2008:
	Danger
	Hazard statements:
	Eye Irrit. 2: H319 - Causes serious eye irritation. Flam. Liq. 3: H226 - Flammable liquid and vapour. Repr. 2: H361d - Suspected of damaging the unborn child. Skin Irrit. 2: H315 - Causes skin irritation. STOT RE 1: H372 - Causes damage to organs through prolonged or repeated exposure.
	Precautionary statements:
	 P201: Obtain special instructions before use. P210: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P280: Wear protective gloves/protective clothing/respiratory protection/eye protection/protective footwear. P302+P352: IF ON SKIN: Wash with plenty of water. P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P308+P313: IF exposed or concerned: Get medical advice/attention.
	P501: Dispose of contents/container in accordance with regulations on hazardous waste or packaging and packaging waste respectively.
	Supplementary information:
	EUH211: Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.
	Substances that contribute to the classification
	styrene Other hazards:
2.3	



HYBRID

Printing	: 19/12/2022 Dat	e of compilation: 26/0	06/2011	Revised: 25/02/2022	Version: 7 (Rep	placed 6)				
SECT	TION 2: HAZARDS ID	ENTIFICATION (co	ontinued)							
	Product fails to meet P Endocrine-disrupting p	,	t fails to meet t	ne criteria.						
SECT	FION 3: COMPOSITIC	N/INFORMATION	ON INGREDI	ENTS						
3.1	Substance:									
	Non-applicable									
3.2	Mixture:									
	Chemical description: Mixture composed of chemical products									
	Components:									
	In accordance with Annex II of Regulation (EC) No 1907/2006 (point 3), the product contains:									
	Identification		Concentration							
	CAS: 100-42-5 EC: 202-851-5	styrene ⁽¹⁾				ATP ATP06				
	EC: 202-851-5 Index: 601-026-00-0 REACH: 01-2119457861-32- XXXX	Regulation 1272/2008		Eye Irrit. 2: H319; Flam. Liq. 3: H22 RE 1: H372 - Danger	6; Repr. 2: H361d; Skin	(!)	10 - <25 %			
	CAS: 13463-67-7	Titanium dioxide (ae	erodynamic diam	eter ≤ 10 µm) ⁽¹⁾		ATP ATP14				
	EC: 236-675-5 Index: 022-006-00-2 REACH: 01-2119489379-17- XXXX	Regulation 1272/2008	Carc. 2: H351 - War	ning		\$	1 - <2,5 %			
	CAS: 141-78-6 EC: 205-500-4	Ethyl acetate ⁽¹⁾	•			ATP CLP00				
	Index: 607-022-00-5 REACH: 01-2119475103-46- XXXX	Regulation 1272/2008	Eye Irrit. 2: H319; F	ilam. Liq. 2: H225; STOT SE 3: H336	; EUH066 - Danger	(!)	1 - <2,5 %			
	CAS: 111-76-2	2-butoxyethanol ⁽²⁾ ATP ATP15				ATP ATP15				
	EC: 203-905-0 Index: 603-014-00-0 REACH: 01-2119475108-36- XXXX	Regulation 1272/2008	Acute Tox. 4: H302-	+H332; Eye Irrit. 2: H319; Skin Irrit.	2: H315 - Warning	()	<1 %			
	CAS: 14808-60-7	Quartz (1 %< RCS <	< 10%) ⁽²⁾			Self-classified				
	EC: 238-878-4 Index: Non-applicable REACH: Non-applicable	Regulation 1272/2008	STOT RE 2: H373 -	Warning		\$	<1 %			

⁽¹⁾ Substances presenting a health or environmental hazard which meet criteria laid down in Regulation (EU) No. 2020/878 ⁽²⁾ Substance with a Union workplace exposure limit

To obtain more information on the hazards of the substances consult sections 11, 12 and 16.

SECTION 4: FIRST AID MEASURES

4.1 Description of first aid measures:

The symptoms resulting from intoxication can appear after exposure, therefore, in case of doubt, seek medical attention for direct exposure to the chemical product or persistent discomfort, showing the SDS of this product.

By inhalation:

Remove the person affected from the area of exposure, provide with fresh air and keep at rest. In serious cases such as cardiorespiratory failure, artificial resuscitation techniques will be necessary (mouth to mouth resuscitation, cardiac massage, oxygen supply, etc.) requiring immediate medical assistance.

By skin contact:

Remove contaminated clothing and footwear, rinse skin or shower the person affected if appropriate with plenty of cold water and neutral soap. In serious cases see a doctor. If the product causes burns or freezing, clothing should not be removed as this could worsen the injury caused if it is stuck to the skin. If blisters form on the skin, these should never be burst as this will increase the risk of infection.

By eye contact:

Rinse eyes thoroughly with water for at least 15 minutes. If the injured person uses contact lenses, these should be removed unless they are stuck to the eyes, in which case removal could cause further damage. In all cases, after cleaning, a doctor should be consulted as quickly as possible with the SDS for the product.

By ingestion/aspiration:



This SDS is an English translation of COMMISSION REGULATION (EU) 2020/878, without any country-specific legislation

HYBRID

Printing: 19/12/2022	Date of compilation: 26/06/2011	Revised: 25/02/2022	Version: 7 (Replaced 6)	
----------------------	---------------------------------	---------------------	-------------------------	--

SECTION 4: FIRST AID MEASURES (continued)

Do not induce vomiting, but if it does happen keep the head down to avoid aspiration. Keep the person affected at rest. Rinse out the mouth and throat, as they may have been affected during ingestion. **Most important symptoms and effects, both acute and delayed:**

Acute and delayed effects are indicated in sections 2 and 11.

4.3 Indication of any immediate medical attention and special treatment needed:

Non-applicable

4.2

SECTION 5: FIREFIGHTING MEASURES

5.1 Extinguishing media:

Suitable extinguishing media:

If possible use polyvalent powder fire extinguishers (ABC powder), alternatively use foam or carbon dioxide extinguishers (CO₂).

Unsuitable extinguishing media:

IT IS RECOMMENDED NOT to use full jet water as an extinguishing agent.

5.2 Special hazards arising from the substance or mixture:

As a result of combustion or thermal decomposition reactive sub-products are created that can become highly toxic and, consequently, can present a serious health risk.

5.3 Advice for firefighters:

Depending on the magnitude of the fire it may be necessary to use full protective clothing and self-contained breathing apparatus (SCBA). Minimum emergency facilities and equipment should be available (fire blankets, portable first aid kit,...) in accordance with Directive 89/654/EC.

Additional provisions:

Act in accordance with the Internal Emergency Plan and the Information Sheets on actions to take after an accident or other emergencies. Eliminate all sources of ignition. In case of fire, cool the storage containers and tanks for products susceptible to combustion, explosion or BLEVE as a result of high temperatures. Avoid spillage of the products used to extinguish the fire into an aqueous medium.

SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1 Personal precautions, protective equipment and emergency procedures:

For non-emergency personnel:

Isolate leaks provided that there is no additional risk for the people performing this task. Evacuate the area and keep out those without protection. Personal protection equipment must be used against potential contact with the spilt product (See section 8). Above all prevent the formation of any vapour-air flammable mixtures, through either ventilation or the use of an inert medium. Remove any source of ignition. Eliminate electrostatic charges by interconnecting all the conductive surfaces on which static electricity could form, and also ensuring that all surfaces are connected to the ground.

For emergency responders:

Wear protective equipment. Keep unprotected persons away. See section 8.

6.2 Environmental precautions:

This product is not classified as hazardous to the environment. Keep product away from drains, surface and underground water.

6.3 Methods and material for containment and cleaning up:

It is recommended:

Absorb the spillage using sand or inert absorbent and move it to a safe place. Do not absorb in sawdust or other combustible absorbents. For any concern related to disposal consult section 13.

6.4 Reference to other sections:

See sections 8 and 13.

SECTION 7: HANDLING AND STORAGE

7.1 Precautions for safe handling:

A.- General precautions for safe use



This SDS is an English translation of COMMISSION REGULATION (EU) 2020/878, without any country-specific legislation

HYBRID

inting:	: 19/12/2022	Date of	compilation: 26/06/2011	Revised: 25/02/2022	2 Version	: 7 (Replaced 6))			
SECT	TION 7: HAND	LING AND	STORAGE (continued)							
	spills and re cleanliness	esidues, dest where dange	t legislation concerning the p roying them with safe metho erous products are used. tions for the prevention of fin	ods (section 6). Avoid lea						
	sparks,) a inertization possibility o clothes mad requiremen protecting t 10 for cond	and ventilate systems whe of electrostati de of acrylic f its for equipn the security a litions and ma	ed areas, preferably through during cleaning operations. ere possible. Transfer at a sli ic charges: ensure a perfect fibres, preferably wearing co nent and systems defined in and health of workers under aterials that should be avoid ions on general occupationa	Avoid the existence of da ow speed to avoid the cre equipotential connection, otton clothing and conduc Directive 2014/34/EC (AT the selection criteria of D led.	ngerous atmosp eation of electros , always use grou tive footwear. Co FEX 100) and wit	heres inside con tatic charges. A undings, do not omply with the e ch the minimum	tainers, applying gainst the wear work ssential security requirements for			
	necessary s equipment, drink during	safety condition especially or g the process	OULD NOT BE EXPOSED TO ions (emergency showers an n the hands and face (See s s, washing hands afterwards ions to prevent environment	nd eyewash stations in clo ection 8). Limit manual tr with suitable cleaning pr	se proximity), us ansfers to small	sing personal pro	otection			
	It is recom	mended to ha	ave absorbent material avail	able at close proximity to	the product (Se	e subsection 6.3	3)			
7.2	Conditions for safe storage, including any incompatibilities:									
	A Technical n	neasures for	storage							
	Minimum T	emp	15 °C							
			25 °C							
	Maximum time: 12 Months									
	B General co	nditions for s	torage							
	Avoid source	es of heat, r	adiation, static electricity an	d contact with food. For a	additional inform	ation see subse	ction 10.5			
7.3	Specific end	use(s):								
	Except for the product.	instructions a	already specified it is not neo	cessary to provide any spo	ecial recommend	lation regarding	the uses of this			
SECT	TION 8: EXPOS	SURE CONT	TROLS/PERSONAL PROT	ECTION						
8.1	Control para	neters:								
	legislation):		onal exposure limits have to			-				
	Directive (EU) 2 (EU) 2019/1831		ective 2004/37/EC,Directive ((EU) 2006/15, Directive (E	EU) 2009/161, D	irective (EU) 20	17/164, Directive			
			Identification			cupational exposur				
	Ethyl acetate				IOELV (8h)	200 ppm	734 mg/m ³			
	CAS: 141-78-6 2-butoxyethanol	EC: 205-500-4			IOELV (STEL) IOELV (8h)	400 ppm 20 ppm	1468 mg/m ³ 98 mg/m ³			
	2-DULOAYELI Idi IOI									

DNEL (Workers):

Quartz (1 %< RCS < 10%) CAS: 14808-60-7 EC: 238-878-4

		Short e	xposure	Long e	xposure
Identification		Systemic	Local	Systemic	Local
styrene	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
CAS: 100-42-5	Dermal	Non-applicable	Non-applicable	406 mg/kg	Non-applicable
EC: 202-851-5	Inhalation	289 mg/m ³	306 mg/m ³	85 mg/m³	Non-applicable
Ethyl acetate	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
CAS: 141-78-6	Dermal	Non-applicable	Non-applicable	63 mg/kg	Non-applicable
EC: 205-500-4	Inhalation	1468 mg/m ³	1468 mg/m ³	734 mg/m ³	734 mg/m ³

IOELV (8h) IOELV (STEL)

- CONTINUED ON NEXT PAGE -

0,1 mg/m³



Safety data sheet This SDS is an English translation of COMMISSION REGULATION (EU) 2020/878, without any country-specific legislation

HYBRID

Printing:	19/12/2022	Date of compilation: 26/06/20	11 Revis	sed: 25/02/2022	Version	7 (Replaced 6)	
SECT	ION 8: EXPOSU	RE CONTROLS/PERSONAL	PROTECTION	(continued)			
				Short e	exposure	Long e	xposure
		Identification		Systemic	Local	Systemic	Local
	2-butoxyethanol		Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
	CAS: 111-76-2		Dermal	89 mg/kg	Non-applicable	125 mg/kg	Non-applicable
	EC: 203-905-0		Inhalation	1091 mg/m ³	246 mg/m ³	98 mg/m ³	Non-applicable
	DNEL (General	population):					
1							

		Short e	xposure	Long exposure	
Identification		Systemic	Local	Systemic	Local
styrene	Oral	Non-applicable	Non-applicable	2,1 mg/kg	Non-applicable
CAS: 100-42-5	Dermal	Non-applicable	Non-applicable	343 mg/kg	Non-applicable
EC: 202-851-5	Inhalation	174,25 mg/m ³	182,75 mg/m ³	10,2 mg/m ³	Non-applicable
Ethyl acetate	Oral	Non-applicable	Non-applicable	4,5 mg/kg	Non-applicable
CAS: 141-78-6	Dermal	Non-applicable	Non-applicable	37 mg/kg	Non-applicable
EC: 205-500-4	Inhalation	734 mg/m ³	734 mg/m ³	367 mg/m ³	367 mg/m ³
2-butoxyethanol	Oral	Non-applicable	Non-applicable	6,3 mg/kg	Non-applicable
CAS: 111-76-2	Dermal	89 mg/kg	Non-applicable	75 mg/kg	Non-applicable
EC: 203-905-0	Inhalation	426 mg/m ³	147 mg/m ³	59 mg/m ³	Non-applicable

PNEC:

Identification				
styrene	STP	5 mg/L	Fresh water	0,028 mg/L
CAS: 100-42-5	Soil	0,2 mg/kg	Marine water	0,014 mg/L
EC: 202-851-5	Intermittent	0,04 mg/L	Sediment (Fresh water)	0,614 mg/kg
	Oral	Non-applicable	Sediment (Marine water)	0,307 mg/kg
Ethyl acetate	STP	650 mg/L	Fresh water	0,24 mg/L
CAS: 141-78-6	Soil	0,148 mg/kg	Marine water	0,024 mg/L
EC: 205-500-4	Intermittent	1,65 mg/L	Sediment (Fresh water)	1,15 mg/kg
	Oral	0,2 g/kg	Sediment (Marine water)	0,115 mg/kg
2-butoxyethanol	STP	463 mg/L	Fresh water	8,8 mg/L
CAS: 111-76-2	Soil	2,33 mg/kg	Marine water	0,88 mg/L
EC: 203-905-0	Intermittent	26,4 mg/L	Sediment (Fresh water)	34,6 mg/kg
	Oral	0,02 g/kg	Sediment (Marine water)	3,46 mg/kg

8.2 **Exposure controls:**

A.- Individual protection measures, such as personal protective equipment

In accordance with the order of importance to control professional exposure (Directive 98/24/EC) it is recommended to use localized extraction in the work area as a collective protection measure to avoid exceeding the occupational exposure limits. In case of using personal protective equipment it should have CE marking in accordance with Directive 2016/425/EC. For more information on Personal Protective Equipment (storage, use, cleaning, maintenance, class of protection,...) consult the information leaflet provided by the manufacturer. For additional information see subsection 7.1. All information contained herein is a recommendation which needs some specification from the labour risk prevention services

as it is not known whether the company has additional measures at its disposal.

B.- Respiratory protection

Mandatory	Filter mask for gases and	CE		
respiratory tract protection	vapours (Filter type: A)	CAT III	EN 405:2002+A1:2010	Replace when there is a taste or smell of the contaminant inside the face mask. If the contaminant comes with warnings it is recommended to use isolation equipment.
	Filter mask for gases and vapours (Filter type: FFP3)		EN 405:2002+A1:2010	Replace when there is a taste or smell of the contaminant inside the face mask. If the contaminant comes with warnings it is recommended to use isolation equipment.



HYBRID

101	N 8: EXPOSURE	CONTROLS/PERSO	VAL PROTECT	TON (continued)		
	Pictogram	PPE	Labelling		CEN Standard		Remarks
	Mandatory hand protection	NON-disposable chemical protective gloves	CAT III	EN 10	D 374-1:2016+A1:2018 5523-1:2015+A1:2018 N ISO 21420:2020	manufa the p	he Breakthrough Time indicated by the acturer must exceed the period during v roduct is being used. Do not use protec ms after the product has come into cont with skin.
D		d has therefore to be ch				rial car	n not be calculated in advance wi
	Pictogram	PPE	Labelling		CEN Standard		Remarks
	Mandatory face protection	Panoramic glasses against splash/projections.		E	EN 166:2002 EN ISO 4007:2018		daily and disinfect periodically accordin anufacturer´s instructions. Use if there risk of splashing.
E	Body protection	-					
	Pictogram	PPE	Labelling		CEN Standard		Remarks
	Mandatory complete body protection	Disposable clothing for protection against chemica risks, with antistatic and fireproof properties		E	EN 1149-1,2,3 13034:2005+A1:2009 EN ISO 13982- 1:2004/A1:2010 EN ISO 6529:2013 FN ISO 6530:2005 N ISO 13688:2013 EN 464:1994		r professional use only. Clean periodicall ording to the manufacturer's instruction
	Mandatory foot protection	Safety footwear for protection against chemica risk, with antistatic and hea resistant properties		E	N ISO 13287:2020 N ISO 20345:2011 EN 13832-1:2019	Re	place boots at any sign of deterioration
F	Additional emerge	ency measures					
	Emergency mea	asure	Standards		Emergency measur		Standards
	Emergency sho	ISO 3864-1:2	NSI Z358-1 2011, ISO 3864-4:2	011	Eyewash station	5	DIN 12 899 ISO 3864-1:2011, ISO 3864-4:201
In spi Vo	illage of both the p Ilatile organic co th regard to Direct	ne community legislation product and its containen mpounds: ive 2010/75/EU, this pr	r. For additional oduct has the fo	inform	ation see subsectior		nmended to avoid environmenta
	V.O.C. (Supply):		2 % weight				
	V.O.C. density at Average carbon n		<g (32="" g="" l)<="" m³="" td=""><td></td><td></td><td></td><td></td></g>				
	Average molecula		,29 g/mol				
	-	-	-				
		AND CHEMICAL PRO					
		ation see the product da		:5.			
	pearance:						
A 1	-		Lie	uid			
-	ysical state at 20 °	<i>'</i> C:					
Ph	ysical state at 20 ^o pearance:	C:	Liqı Der				



HYBRID

Printing	: 19/12/2022	Date of compilation: 26/06/2011	Revised: 25/02/2022	Version: 7 (Replaced 6)
SECT	TION 9: PHYSIC	AL AND CHEMICAL PROPERTIES	S ** (continued)	
	Colour:		White	
	Odour:		Characteristic	
	Odour threshold:		Non-applicable *	
	Volatility:			
	Boiling point at a	tmospheric pressure:	117 °C	
	Vapour pressure	at 20 °C:	2175 Pa	
	Vapour pressure	at 50 °C:	11291,06 Pa (11,29 kPa)	
	Evaporation rate	at 20 °C:	Non-applicable *	
	Product descrip	ption:		
	Density at 20 °C:	:	1810 kg/m³	
	Relative density a	at 20 ºC:	Non-applicable *	
	Dynamic viscosity	y at 20 °C:	Non-applicable *	
	Kinematic viscosi	ty at 20 °C:	Non-applicable *	
	Kinematic viscosi	ty at 40 °C:	Non-applicable *	
	Concentration:		Non-applicable *	
	pH:		Non-applicable *	
	Vapour density a	t 20 ºC:	Non-applicable *	
	Partition coefficie	ent n-octanol/water 20 °C:	Non-applicable *	
	Solubility in wate	er at 20 °C:	Non-applicable *	
	Solubility propert	ies:	Non-applicable *	
	Decomposition te	emperature:	Non-applicable *	
	Melting point/free	ezing point:	Non-applicable *	
	Flammability:			
	Flash Point:		35 °C	
	Flammability (sol	id, gas):	Non-applicable *	
	Autoignition temp		238 °C	
	Lower flammabili		Not available	
	Upper flammabili		Not available	
	Particle charac	teristics:		
	Median equivaler		Non-applicable	
9.2	Other informat			
		ith regard to physical hazard clas		
	Explosive propert		Non-applicable *	
	Oxidising propert		Non-applicable *	
	Corrosive to meta		Non-applicable *	
	Heat of combusti		Non-applicable *	
	components:	rcentage (by mass) of flammable	Non-applicable *	
	Other safety ch		ALC DE LE SE	
	Surface tension a		Non-applicable *	
	Refraction index:		Non-applicable *	
** 0		the nature of the product, not providing info	mation property of its hazards.	

** Changes with regards to the previous version

SECTION 10: STABILITY AND REACTIVITY



HYBRID

inting:	19/12/2022	Date of compilation: 26/06/2011	Revised: 25/02/20	22 Version: 7 (Rep	placed 6)					
SECT	TON 10: STABI	LITY AND REACTIVITY (contin	nued)							
10.1	Reactivity:									
	No hazardous reactions are expected because the product is stable under recommended storage conditions. See section 7.									
10.2	Chemical stab	ility:								
	Chemically stabl	e under the indicated conditions of	storage, handling and use.							
10.3	Possibility of hazardous reactions:									
	Under the specif	ied conditions, hazardous reactions	that lead to excessive temp	peratures or pressure are	not expected.					
10.4	Conditions to a	avoid:								
	Applicable for ha	andling and storage at room temper	ature:							
	Shock and fr	iction Contact with air	Increase in temperature	Sunlight	Humidity					
	Not applica	able Not applicable	Risk of combustion	Avoid direct impact	Not applicable					

10.5 Incompatible materials:

Acids	Water	Oxidising materials	Combustible materials	Others
Avoid strong acids	Not applicable	Avoid direct impact	Not applicable	Avoid alkalis or strong bases

10.6 Hazardous decomposition products:

Contains susbstances highly reactive and can auto-polymerize as a result of internal peroxide accumulation. The peroxides formed in these reactions are extremely shock- and heat-sensitive.

SECTION 11: TOXICOLOGICAL INFORMATION

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008:

The experimental information related to the toxicological properties of the product itself is not available

Contains glycols. It is recommended not to breathe the vapours for prolonged periods of time due to the possibility of effects that are hazardous to the health .

Dangerous health implications:

In case of exposure that is repetitive, prolonged or at concentrations higher than the recommended occupational exposure limits, adverse effects on health may result, depending on the means of exposure:

- A- Ingestion (acute effect):
 - Acute toxicity : Based on available data, the classification criteria are not met, however, it contains substances classified
 - as dangerous for consumption. For more information see section 3.
 - Corrosivity/Irritability: The consumption of a considerable dose can cause irritation in the throat, abdominal pain, nausea and vomiting.
- B- Inhalation (acute effect):
 - Acute toxicity : Based on available data, the classification criteria are not met. However, it contains substances classified as hazardous for inhalation. For more information see section 3.
 - Corrosivity/Irritability: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.
- C- Contact with the skin and the eyes (acute effect):
 - Contact with the skin: Produces skin inflammation.
 - Contact with the eyes: Produces eye damage after contact.
- D- CMR effects (carcinogenicity, mutagenicity and toxicity to reproduction):
 - Carcinogenicity: Based on available data, the classification criteria are not met. However, it contains substances classified as dangerous with carcinogenic effects. For more information see section 3.
 - IARC: styrene (2A); 2-butoxyethanol (3); Talc (3); Titanium dioxide (aerodynamic diameter \leq 10 µm) (2B); Quartz (1 % < RCS < 10%) (1)
 - Mutagenicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.
 - Reproductive toxicity: Suspected of damaging the unborn child.
- E- Sensitizing effects:



This SDS is an English translation of COMMISSION REGULATION (EU) 2020/878, without any country-specific legislation

HYBRID

19/12/2022	Date of compilation: 26/06/2011	Revised: 25/02/2022	· · ·	
TON 11: TOXI	COLOGICAL INFORMATION (cont	tinued)		
hazardous w - Skin: Bas hazardous fe	bry: Based on available data, the classif with sensitising effects. For more inform sed on available data, the classification or this effect. For more information see get organ toxicity (STOT) - single expos	nation see section 3. criteria are not met, as it do e section 3.		
inhalation. F	vailable data, the classification criteria a For more information see section 3. Jet organ toxicity (STOT)-repeated exp		tains substances classified as	hazardous for
including de - Skin: Bas	arget organ toxicity (STOT)-repeated e eath, serious functional disorders or mo sed on available data, the classification dangerous due to repetitive exposure. azard:	rphological changes of toxico criteria are not met. Howev	ological importance. er, it does contain substances	
	vailable data, the classification criteria a For more information see section 3.	are not met, as it does not co	ntain substances classified as	s hazardous fo
aerodynamic dia	where form containing 1 % or more of ameter $\leq 10 \ \mu m$		the form of or incorporated in	n particles witl
aerodynamic dia				
aerodynamic dia	ameter $\leq 10 \ \mu m$ blogy information on the substanc	es:	Acute toxicity	
aerodynamic dia Specific toxico styrene	ameter $\leq 10 \ \mu m$ blogy information on the substanc		Acute toxicity I >2000 mg/kg	
aerodynamic dia	ameter $\leq 10 \ \mu m$ blogy information on the substanc	es: LD50 ora	Acute toxicity I >2000 mg/kg mal >2000 mg/kg	
aerodynamic dia Specific toxico styrene CAS: 100-42-5 EC: 202-851-5	ameter $\leq 10 \ \mu m$ blogy information on the substanc	LD50 ora LD50 der	Acute toxicity I >2000 mg/kg mal >2000 mg/kg alation 12 mg/L (4 h)	Genus
aerodynamic dia Specific toxico styrene CAS: 100-42-5 EC: 202-851-5	ameter ≤ 10 µm blogy information on the substanc Identification	es: LD50 ora LD50 der LC50 inh	Acute toxicity I >2000 mg/kg mal >2000 mg/kg alation 12 mg/L (4 h) I 10000 mg/kg	Genus Rat
aerodynamic dia Specific toxico styrene CAS: 100-42-5 EC: 202-851-5 Titanium dioxide (a	ameter ≤ 10 µm blogy information on the substanc Identification	es: LD50 ora LD50 der LC50 inh LD50 ora	Acute toxicity I >2000 mg/kg mal >2000 mg/kg alation 12 mg/L (4 h) I 10000 mg/kg mal 10000 mg/kg	Genus Rat
aerodynamic dia Specific toxico styrene CAS: 100-42-5 EC: 202-851-5 Titanium dioxide (a CAS: 13463-67-7	ameter ≤ 10 µm blogy information on the substanc Identification	es: LD50 ora LD50 der LC50 inh LD50 ora LD50 der	Acute toxicity I >2000 mg/kg mal >2000 mg/kg alation 12 mg/L (4 h) I 10000 mg/kg mal 55 mg/L	Genus Rat
aerodynamic dia Specific toxico styrene CAS: 100-42-5 EC: 202-851-5 Titanium dioxide (CAS: 13463-67-7 EC: 236-675-5	ameter ≤ 10 µm blogy information on the substanc Identification	LD50 ora LD50 der LC50 inh LD50 der LC50 inh LD50 der LC50 inh	Acute toxicity I >2000 mg/kg mal >2000 mg/kg alation 12 mg/L (4 h) I 10000 mg/kg mal >5 mg/L I 4100 mg/kg	Genus Rat Rat Rabbi Rat
aerodynamic dia Specific toxico styrene CAS: 100-42-5 EC: 202-851-5 Titanium dioxide (CAS: 13463-67-7 EC: 236-675-5 Ethyl acetate	ameter ≤ 10 µm blogy information on the substanc Identification	LD50 ora LD50 der LC50 inh LD50 der LC50 inh LD50 der LC50 inh LD50 der LC50 inh	Acute toxicity I >2000 mg/kg mal >2000 mg/kg alation 12 mg/L (4 h) I 10000 mg/kg mal 10000 mg/kg alation 5 mg/L I 4100 mg/kg mal 20000 mg/kg	Genus Rat Rat Rabbi
aerodynamic dia Specific toxico styrene CAS: 100-42-5 EC: 202-851-5 Titanium dioxide (r CAS: 13463-67-7 EC: 236-675-5 Ethyl acetate CAS: 141-78-6 EC: 205-500-4 2-butoxyethanol	ameter ≤ 10 µm blogy information on the substanc Identification	es: LD50 ora LD50 der LC50 inh LD50 ora LD50 der LC50 inh LD50 ora LD50 ora LD50 der LC50 inh	Acute toxicity I >2000 mg/kg mal >2000 mg/kg alation 12 mg/L (4 h) I 10000 mg/kg mal 10000 mg/kg alation >5 mg/L I 4100 mg/kg mal 20000 mg/kg alation >5 mg/L I 4100 mg/kg mal 20000 mg/kg alation >20 mg/L I 1200 mg/kg	Genus Rat Rat Rat Rabbi Rat Rabbi
aerodynamic dia Specific toxico styrene CAS: 100-42-5 EC: 202-851-5 Titanium dioxide (c CAS: 13463-67-7 EC: 236-675-5 Ethyl acetate CAS: 141-78-6 EC: 205-500-4 2-butoxyethanol CAS: 111-76-2	ameter ≤ 10 µm blogy information on the substanc Identification	es: LD50 ora LD50 der LC50 inh LD50 der LC50 inh LD50 der LC50 inh LD50 ora LD50 der LC50 inh LD50 ora LD50 der LD50 ora LD50 der	Acute toxicity I >2000 mg/kg mal >2000 mg/kg alation 12 mg/L (4 h) I 10000 mg/kg mal 10000 mg/kg alation >5 mg/L I 4100 mg/kg mal 20000 mg/kg alation >5 mg/L I 4100 mg/kg mal 20000 mg/kg alation >20 mg/L I 1200 mg/kg	Genus Rat Rat Rat Rabbit Rabbit Rat Rabbit
aerodynamic dia Specific toxico styrene CAS: 100-42-5 EC: 202-851-5 Titanium dioxide (r CAS: 13463-67-7 EC: 236-675-5 Ethyl acetate CAS: 141-78-6 EC: 205-500-4 2-butoxyethanol	ameter ≤ 10 µm blogy information on the substanc Identification	es: LD50 ora LD50 der LC50 inh LD50 der LC50 inh LD50 ora LD50 der LC50 inh LD50 der LC50 inh LD50 ora LD50 der LD50 ora LD50 der LC50 inh	Acute toxicity I >2000 mg/kg mal >2000 mg/kg alation 12 mg/L (4 h) I 10000 mg/kg mal 10000 mg/kg alation >5 mg/L I 4100 mg/kg mal 20000 mg/kg alation >2 mg/L I 1200 mg/kg mal 3000 mg/kg alation >20 mg/L	Genus Rat Rat Rat Rabbit Rabbit Rat Rabbit
aerodynamic dia Specific toxico styrene CAS: 100-42-5 EC: 202-851-5 Titanium dioxide (: CAS: 13463-67-7 EC: 236-675-5 Ethyl acetate CAS: 141-78-6 EC: 205-500-4 2-butoxyethanol CAS: 111-76-2 EC: 203-905-0 Quartz (1 %< RCS	ameter ≤ 10 µm blogy information on the substanc Identification aerodynamic diameter ≤ 10 µm)	es: LD50 ora LD50 der LC50 inh LD50 der LC50 inh LD50 der LC50 inh LD50 ora LD50 der LC50 inh LD50 ora LD50 ora LD50 ora LD50 ora LD50 ora LD50 ora LD50 ora LD50 ora LD50 ora LD50 ora	Acute toxicity I >2000 mg/kg mal >2000 mg/kg alation 12 mg/L (4 h) I 10000 mg/kg mal 10000 mg/kg alation >5 mg/L I 4100 mg/kg mal 20000 mg/kg alation >20 mg/L I 1200 mg/kg mal 3000 mg/kg alation >20 mg/L I 2000 mg/kg	Genus Rat Rat Rat Rabbit Rabbit Rat Rabbit
aerodynamic dia Specific toxico styrene CAS: 100-42-5 EC: 202-851-5 Titanium dioxide (x CAS: 13463-67-7 EC: 236-675-5 Ethyl acetate CAS: 141-78-6 EC: 205-500-4 2-butoxyethanol CAS: 111-76-2 EC: 203-905-0 Quartz (1 % < RCS CAS: 14808-60-7	ameter ≤ 10 µm blogy information on the substanc Identification aerodynamic diameter ≤ 10 µm)	es: LD50 ora LD50 der LC50 inh LD50 der LD50 der LD50 der LD50 ora LD50 der LD50 ora LD50 ora LD50 der LC50 inh LD50 ora LD50 der LD50 ora LD50 der LD50 ora LD50 der LD50 ora LD50 der LD50 ora LD50 der LD50 ora	Acute toxicity I >2000 mg/kg mal >2000 mg/kg alation 12 mg/L (4 h) I 10000 mg/kg mal 10000 mg/kg mal 10000 mg/kg alation >5 mg/L I 4100 mg/kg mal 20000 mg/kg alation >20 mg/L I 1200 mg/kg mal 3000 mg/kg alation >20 mg/L I 2000 mg/kg mal 3000 mg/kg mal >200 mg/L I >2000 mg/kg	Genus Rat Rat Rat Rabbit Rabbit Rat Rabbit
aerodynamic dia Specific toxico styrene CAS: 100-42-5 EC: 202-851-5 Titanium dioxide (c CAS: 13463-67-7 EC: 236-675-5 Ethyl acetate CAS: 141-78-6 EC: 205-500-4 2-butoxyethanol CAS: 111-76-2 EC: 203-905-0 Quartz (1 %< RCS CAS: 14808-60-7 EC: 238-878-4	ameter ≤ 10 µm blogy information on the substance Identification aerodynamic diameter ≤ 10 µm) 5 < 10%)	es: LD50 ora LD50 der LC50 inh LD50 der LC50 inh LD50 der LC50 inh LD50 ora LD50 der LC50 inh LD50 ora LD50 ora LD50 ora LD50 ora LD50 ora LD50 ora LD50 ora LD50 ora LD50 ora LD50 ora	Acute toxicity I >2000 mg/kg mal >2000 mg/kg alation 12 mg/L (4 h) I 10000 mg/kg mal 10000 mg/kg mal 10000 mg/kg alation >5 mg/L I 4100 mg/kg mal 20000 mg/kg alation >20 mg/L I 1200 mg/kg mal 3000 mg/kg alation >20 mg/L I 2000 mg/kg mal 3000 mg/kg mal >200 mg/L I >2000 mg/kg	Genus Rat Rat Rat Rabbi Rat Rabbi
aerodynamic dia Specific toxico styrene CAS: 100-42-5 EC: 202-851-5 Titanium dioxide (c CAS: 13463-67-7 EC: 236-675-5 Ethyl acetate CAS: 141-78-6 EC: 205-500-4 2-butoxyethanol CAS: 111-76-2 EC: 203-905-0 Quartz (1 %< RCS CAS: 14808-60-7 EC: 238-878-4	ameter ≤ 10 µm blogy information on the substance Identification aerodynamic diameter ≤ 10 µm) 5 < 10%) y Estimate (ATE mix):	es: LD50 ora LD50 der LC50 inh LD50 der LD50 der LD50 der LD50 ora LD50 der LD50 ora LD50 ora LD50 der LC50 inh LD50 ora LD50 der LD50 ora LD50 der LD50 ora LD50 der LD50 ora LD50 der LD50 ora LD50 der LD50 ora	Acute toxicity I >2000 mg/kg mal >2000 mg/kg alation 12 mg/L (4 h) I 10000 mg/kg mal 10000 mg/kg alation >5 mg/L I 4100 mg/kg mal 20000 mg/kg alation >20 mg/L I 1200 mg/kg mal 3000 mg/kg alation >20 mg/L I 2000 mg/kg mal 3000 mg/kg alation >20 mg/L I >2000 mg/kg alation >20 mg/L I >2000 mg/kg alation >2000 mg/kg	Genus Genus Rat Rat Rabbi Rat Rabbi Rat Rabbi
aerodynamic dia Specific toxico styrene CAS: 100-42-5 EC: 202-851-5 Titanium dioxide (x CAS: 13463-67-7 EC: 236-675-5 Ethyl acetate CAS: 141-78-6 EC: 205-500-4 2-butoxyethanol CAS: 111-76-2 EC: 203-905-0 Quartz (1 %< RCS CAS: 14808-60-7 EC: 238-878-4 Acute Toxicity	ameter ≤ 10 µm blogy information on the substance Identification aerodynamic diameter ≤ 10 µm) 5 < 10%) y Estimate (ATE mix): ATE mix	es: LD50 ora LD50 der LC50 inh LD50 der LC50 inh LD50 der LC50 inh LD50 der LC50 inh LD50 der LC50 inh LD50 der LD50 der LC50 inh LD50 der LC50 inh LD50 der LC50 inh	Acute toxicity I >2000 mg/kg mal >2000 mg/kg alation 12 mg/L (4 h) I 10000 mg/kg mal 10000 mg/kg alation >5 mg/L I 4100 mg/kg mal 20000 mg/kg alation >20 mg/L I 1200 mg/kg mal 3000 mg/kg alation >20 mg/L I 20000 mg/kg alation >20 mg/L I \$2000 mg/kg alation >20 mg/L I \$2000 mg/kg alation >20 mg/L I \$2000 mg/kg mal \$2000 mg/kg mal >20000 mg/kg	Genus Genus Rat Rat Rabbi Rat Rabbi Rat Rabbi
aerodynamic dia Specific toxico styrene CAS: 100-42-5 EC: 202-851-5 Titanium dioxide (x CAS: 13463-67-7 EC: 236-675-5 Ethyl acetate CAS: 141-78-6 EC: 205-500-4 2-butoxyethanol CAS: 111-76-2 EC: 203-905-0 Quartz (1 %< RCS CAS: 14808-60-7 EC: 238-878-4 Acute Toxicity Oral	ameter ≤ 10 µm blogy information on the substance Identification aerodynamic diameter ≤ 10 µm) 5 < 10%) y Estimate (ATE mix): ATE mix >2000 mg/kg (Calcul	es: LD50 ora LD50 der LC50 inh LD50 der LC50 inh LD50 der LC50 inh LD50 ora LD50 der LC50 inh LD50 der LC50 inh LD50 der LC50 inh LD50 der LC50 inh LD50 der LC50 inh	Acute toxicity I >2000 mg/kg mal >2000 mg/kg alation 12 mg/L (4 h) I 10000 mg/kg mal 10000 mg/kg alation >5 mg/L I 4100 mg/kg mal 20000 mg/kg alation >20 mg/L I 1200 mg/kg mal 3000 mg/kg alation >20 mg/L I 2000 mg/kg mal 3000 mg/kg alation >20 mg/L I 2000 mg/kg mal 3000 mg/kg alation >20 mg/L I >2000 mg/kg mal >5 mg/L	Genus Genus Rat Rat Rat Rabbit Rat Rat Rabbit Rat Rat Rabbit Rat Rat Rabbit Rat Rat Rat Rat Rabbit Rat Rat Rat Rat Rat Rat Rat Rat Rat Ra
aerodynamic dia Specific toxico styrene CAS: 100-42-5 EC: 202-851-5 Titanium dioxide (x CAS: 13463-67-7 EC: 236-675-5 Ethyl acetate CAS: 141-78-6 EC: 205-500-4 2-butoxyethanol CAS: 111-76-2 EC: 203-905-0 Quartz (1 %< RCS CAS: 14808-60-7 EC: 238-878-4 Acute Toxicity	ameter ≤ 10 µm blogy information on the substance Identification aerodynamic diameter ≤ 10 µm) 5 < 10%) y Estimate (ATE mix): ATE mix	es: LD50 ora LD50 der LC50 inh LD50 der LC50 inh LD50 der LC50 inh LD50 ora LD50 ora LD50 ora LD50 der LC50 inh LD50 ora LD50 ora L	Acute toxicity I >2000 mg/kg mal >2000 mg/kg alation 12 mg/L (4 h) I 10000 mg/kg mal 10000 mg/kg alation >5 mg/L I 4100 mg/kg mal 20000 mg/kg alation >20 mg/L I 1200 mg/kg mal 3000 mg/kg alation >20 mg/L I 20000 mg/kg alation >20 mg/L I \$2000 mg/kg alation >20 mg/L I \$2000 mg/kg alation >20 mg/L I \$2000 mg/kg mal \$2000 mg/kg mal >20000 mg/kg	Genus Rat Rat Rabbi Rabbi Rat Rabbi

Endocrine-disrupting properties: The product fails to meet the criteria.

Other information

Non-applicable

SECTION 12: ECOLOGICAL INFORMATION

The experimental information related to the eco-toxicological properties of the product itself is not available

12.1 Toxicity:



HYBRID

	TION 12: ECOLOGICAL INFORMATION (c	ontinued)						
		onenaca	/						
	Acute toxicity:								
	Identification			Concentration		Specie	es		Genus
	Ethyl acetate	LC	C50	230 mg/L (96 h)		Pimephales p	oromela	S	Fish
	CAS: 141-78-6	EC	C50	717 mg/L (48 h)		Daphnia n	nagna		Crustacea
	EC: 205-500-4	EC	C50	3300 mg/L (48 h)		Scenedesmus s	ubspica	atus	Algae
	2-butoxyethanol	LC	C50	1490 mg/L (96 h)		Lepomis mad	rochiru	S	Fish
	CAS: 111-76-2	EC	C50	1815 mg/L (48 h)		Daphnia n	nagna		Crustacear
	EC: 203-905-0	EC	C50	911 mg/L (72 h)		Pseudokirchneriel	a subca	apitata	Algae
	Chronic toxicity:								
	Identification			Concentration		Specie	es		Genus
	Ethyl acetate	N	OEC	9,65 mg/L		Pimephales p	oromela	S	Fish
	CAS: 141-78-6 EC: 205-500-4	N	OEC	2,4 mg/L		Daphnia n	nagna		Crustacea
	2-butoxyethanol	N	OEC	100 mg/L		Danio re	erio		Fish
	CAS: 111-76-2 EC: 203-905-0	N	OEC	100 mg/L		Daphnia n	nagna		Crustacea
.2	Persistence and degradability:					•			
	Substance-specific information:								
	·		-	1.1.10		S . 1			
	Identification		Deg	gradability	_		egradab	· ·	
	Ethyl acetate	BOD5		1,36 g O2/g		ntration		100 mg	
	CAS: 141-78-6	COD	00	1,69 g O2/g	Period			14 days	5
	EC: 205-500-4	BOD5/CO	.OD			degradable		83 %	
	2-butoxyethanol	BOD5		0,71 g O2/g		ntration		100 mg	
	CAS: 111-76-2	COD	00	2,2 g O2/g	Period			14 days	5
.3	EC: 203-905-0 Bioaccumulative potential:	BOD5/CO	.00	0,32	% BIO	Biodegradable 96 %		96 %	
	Identificatio	n				Bioaccur	nulatior	n potenti	al
	Ethyl acetate				BCF	:	30		
	CAS: 141-78-6				Pov	v Log	0.73		
	EC: 205-500-4				Pot	ential	Moder	ate	
					BCF	:	3		
	2-butoxyethanol								
	CAS: 111-76-2					v Log	0.83		
	CAS: 111-76-2 EC: 203-905-0					v Log ential	0.83 Low		
.4	CAS: 111-76-2								
.4	CAS: 111-76-2 EC: 203-905-0		Abso	rption/desorption				ility	
.4	CAS: 111-76-2 EC: 203-905-0 Mobility in soil:	Кос	Absc	rption/desorption			Low	ility Non-ap	plicable
.4	CAS: 111-76-2 EC: 203-905-0 Mobility in soil: Identification	Koc Conclusio				ential	Low	-	
.4	CAS: 111-76-2 EC: 203-905-0 Mobility in soil: Identification styrene	-	ion	Non-applicable	Pot	Henry	Low	Non-ap	plicable
.4	CAS: 111-76-2 EC: 203-905-0 Mobility in soil: Identification styrene CAS: 100-42-5	Conclusio	ion	Non-applicable Non-applicable	Pot	Henry Dry soil	Low	Non-ap Non-ap Non-ap	plicable
.4	CAS: 111-76-2 EC: 203-905-0 Mobility in soil: Identification styrene CAS: 100-42-5 EC: 202-851-5	Conclusion Surface 1	ion tension	Non-applicable Non-applicable 3,21E-2 N/m (25 °	Pot	Henry Dry soil Moist soil	Low	Non-ap Non-ap Non-ap	plicable plicable
.4	CAS: 111-76-2 EC: 203-905-0 Mobility in soil: Identification styrene CAS: 100-42-5 EC: 202-851-5 Ethyl acetate	Conclusion Surface 1 Koc	ion tension ion	Non-applicable Non-applicable 3,21E-2 N/m (25 ° 59	Potr	Henry Dry soil Moist soil Henry	Low	Non-ap Non-ap Non-ap 13,58 P	plicable plicable
.4	CAS: 111-76-2 EC: 203-905-0 Mobility in soil: Identification styrene CAS: 100-42-5 EC: 202-851-5 Ethyl acetate CAS: 141-78-6	Conclusion Surface 1 Koc Conclusion	ion tension ion	Non-applicable Non-applicable 3,21E-2 N/m (25 °) 59 Very High	Pot	Henry Dry soil Moist soil Henry Dry soil	Low	Non-ap Non-ap Non-ap 13,58 P Yes Yes	plicable plicable
.4	CAS: 111-76-2 EC: 203-905-0 Mobility in soil: Identification styrene CAS: 100-42-5 EC: 202-851-5 Ethyl acetate CAS: 141-78-6 EC: 205-500-4	Conclusion Surface to Koc Conclusion Surface to	ion tension ion tension	Non-applicable Non-applicable 3,21E-2 N/m (25 ° 59 Very High 2,324E-2 N/m (25 °	Pot	Henry Dry soil Moist soil Henry Dry soil Moist soil	Low	Non-ap Non-ap Non-ap 13,58 P Yes Yes	plicable plicable 'a·m³/mol
.4	CAS: 111-76-2 EC: 203-905-0 Mobility in soil: Identification styrene CAS: 100-42-5 EC: 202-851-5 Ethyl acetate CAS: 141-78-6 EC: 205-500-4 2-butoxyethanol	Conclusio Surface t Koc Conclusio Surface t Koc	ion tension ion tension ion	Non-applicable Non-applicable 3,21E-2 N/m (25 ° 59 Very High 2,324E-2 N/m (25 8	Pot	Henry Dry soil Moist soil Henry Dry soil Moist soil Henry Henry	Low	Non-ap Non-ap 13,58 P Yes Yes 1,621E-	plicable plicable 'a·m³/mol
	CAS: 111-76-2 EC: 203-905-0 Mobility in soil: Identification styrene CAS: 100-42-5 EC: 202-851-5 Ethyl acetate CAS: 141-78-6 EC: 205-500-4 2-butoxyethanol CAS: 111-76-2	Conclusio Surface t Koc Conclusio Surface t Koc Conclusio	ion tension ion tension ion	Non-applicable Non-applicable 3,21E-2 N/m (25 ° 59 Very High 2,324E-2 N/m (25 ° 8 Very High	Pot	Henry Dry soil Moist soil Henry Dry soil Moist soil Henry Dry soil Dry soil	Low	Non-ap Non-ap 13,58 P Yes Yes 1,621E- No	plicable plicable 'a·m³/mol
	CAS: 111-76-2 EC: 203-905-0 Mobility in soil: Identification styrene CAS: 100-42-5 EC: 202-851-5 Ethyl acetate CAS: 141-78-6 EC: 205-500-4 2-butoxyethanol CAS: 111-76-2 EC: 203-905-0	Conclusio Surface t Koc Conclusio Surface t Koc Conclusio	ion tension ion tension ion	Non-applicable Non-applicable 3,21E-2 N/m (25 ° 59 Very High 2,324E-2 N/m (25 ° 8 Very High	Pot	Henry Dry soil Moist soil Henry Dry soil Moist soil Henry Dry soil Dry soil	Low	Non-ap Non-ap 13,58 P Yes Yes 1,621E- No	plicable plicable 'a·m³/mol
5	CAS: 111-76-2 EC: 203-905-0 Mobility in soil: Identification styrene CAS: 100-42-5 EC: 202-851-5 Ethyl acetate CAS: 141-78-6 EC: 205-500-4 2-butoxyethanol CAS: 111-76-2 EC: 203-905-0 Results of PBT and vPvB assessment: Product fails to meet PBT/vPvB criteria	Conclusio Surface t Koc Conclusio Surface t Koc Conclusio	ion tension ion tension ion	Non-applicable Non-applicable 3,21E-2 N/m (25 ° 59 Very High 2,324E-2 N/m (25 ° 8 Very High	Pot	Henry Dry soil Moist soil Henry Dry soil Moist soil Henry Dry soil Dry soil	Low	Non-ap Non-ap 13,58 P Yes Yes 1,621E- No	plicable plicable 'a·m³/mol
5	CAS: 111-76-2 EC: 203-905-0 Mobility in soil: Identification styrene CAS: 100-42-5 EC: 202-851-5 Ethyl acetate CAS: 141-78-6 EC: 205-500-4 2-butoxyethanol CAS: 111-76-2 EC: 203-905-0 Results of PBT and vPvB assessment: Product fails to meet PBT/vPvB criteria Endocrine disrupting properties:	Conclusie Surface t Koc Conclusie Surface t Koc Conclusie Surface t	ion tension ion tension tension	Non-applicable Non-applicable 3,21E-2 N/m (25 ° 59 Very High 2,324E-2 N/m (25 ° 8 Very High 2,729E-2 N/m (25 °	Pot	Henry Dry soil Moist soil Henry Dry soil Moist soil Henry Dry soil Dry soil	Low	Non-ap Non-ap 13,58 P Yes Yes 1,621E- No	plicable plicable 'a·m³/mol
5	CAS: 111-76-2 EC: 203-905-0 Mobility in soil: Identification styrene CAS: 100-42-5 EC: 202-851-5 Ethyl acetate CAS: 141-78-6 EC: 205-500-4 2-butoxyethanol CAS: 111-76-2 EC: 203-905-0 Results of PBT and vPvB assessment: Product fails to meet PBT/vPvB criteria	Conclusie Surface t Koc Conclusie Surface t Koc Conclusie Surface t	ion tension ion tension tension	Non-applicable Non-applicable 3,21E-2 N/m (25 ° 59 Very High 2,324E-2 N/m (25 ° 8 Very High 2,729E-2 N/m (25 °	Pot	Henry Dry soil Moist soil Henry Dry soil Moist soil Henry Dry soil Dry soil	Low	Non-ap Non-ap 13,58 P Yes Yes 1,621E- No	plicable plicable 'a·m³/mol



ıg: 19/	12/2022	Date	of compilation: 26/06/2011	Revised: 25/02/2022	Version: 7 (Replaced 6)
CTIO	N 13: DISP	osal co	INSIDERATIONS		
.1 Wa	aste treatn	nent metl	nods:		
	Code		Descri	ption	Waste class (Regulation (EU) N
			and varnish containing organic solvents	s or other hazardous substances	1357/2014) Dangerous
			ontaining residues of or contaminated b	by hazardous substances	Dungelous
HP irri	3 Flammable tation and e	e, HP5 Spe ye damage		T)/Aspiration Toxicity, HP10 T	oxic for reproduction, HP4 Irritant — skin
2 (the Wa	Directive 20 e product, it aste should r	08/98/EC) will be pro not be disp	. As under 15 01 (2014/955/EC)	of the code and in case the cual product. Otherwise, it wil	ions in accordance with Annex 1 and Anr container has been in direct contact with I be processed as non-dangerous residue
ma	nagement a	re stated		. ,	y or state provisions related to waste
Co	mmunity leg	islation: D	irective 2008/98/EC, 2014/955/l	EU, Regulation (EU) No 1357,	/2014
CTION			INFORMATION		
	-	-	us goods by land: 1 and RID 2021:		
v	nui regatu u		UN number or ID number:	UN3269	
		14.2	UN proper shipping name:	POLYESTER RESIN KIT, li	quid base material
		14.3	Transport hazard class(es)		
		>	Labels:	3	
	3		Packing group:	III	
			Environmental hazards: Special precautions for use	No	
		14.0	Special regulations:	236, 340	
			Tunnel restriction code:	E	
			Physico-Chemical properties:	see section 9	
			Limited quantities:	5 L	
		14.7	Maritime transport in bulk according to IMO instruments:	Non-applicable	
т	ransport of	f dangero	us goods by sea:		
W	/ith regard to	o IMDG 40	-20:		
		14.1	UN number or ID number:	UN3269	
		14.2	UN proper shipping name:	POLYESTER RESIN KIT, li	quid base material
	, LL,	14.3	Transport hazard class(es)		
			Labels:	3	
			Packing group:	III	
	3		Marine pollutant: Special precautions for use	No	
	•	14.0	Special regulations:	340, 236	
			EmS Codes:	F-E, S-D	
			Physico-Chemical properties:	see section 9	
			Limited quantities:	5 L	
			Segregation group:	Non-applicable	
		14.7	Maritime transport in bulk according to IMO instruments:	Non-applicable	
т	ransport of	f dangero	us goods by air:		
				IED ON NEXT PAGE -	
			000000		



HYBRID

Printing: 19/12/2022	Date of compilation: 26/06/2011	Revised: 25/02/2022 Version: 7 (Replaced 6)				
SECTION 14: TRANS	PORT INFORMATION (continued)				
With regard to I	ATA/ICAO 2022:					
	 14.1 UN number or ID number 14.2 UN proper shipping name 14.3 Transport hazard class(es Labels: 14.4 Packing group: 14.5 Environmental hazards: 14.6 Special precautions for us 	 POLYESTER RESIN KIT, liquid base material 3 III No 				
	Physico-Chemical properties:					
	14.7 Maritime transport in bull according to IMO instruments:	c Non-applicable				
SECTION 15: REGULATORY INFORMATION						
15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture: Candidate substances for authorisation under the Regulation (EC) No 1907/2006 (REACH): Non-applicable Substances included in Annex XIV of REACH ("Authorisation List") and sunset date: Non-applicable						

Regulation (EC) No 1005/2009, about substances that deplete the ozone layer: Non-applicable

Article 95, REGULATION (EU) No 528/2012: Non-applicable

REGULATION (EU) No 649/2012, in relation to the import and export of hazardous chemical products: Non-applicable

Seveso III:

Section	Description	Lower-tier requirements	Upper-tier requirements
P5c	FLAMMABLE LIQUIDS	5000	50000

Limitations to commercialisation and the use of certain dangerous substances and mixtures (Annex XVII REACH, etc):

Shall not be used in:

—ornamental articles intended to produce light or colour effects by means of different phases, for example in ornamental lamps and ashtrays,

-tricks and jokes,

-games for one or more participants, or any article intended to be used as such, even with ornamental aspects.

Occupational exposure to respirable crystalline silica must be controlled pursuant to Directive (EU) 2019/130.

Specific provisions in terms of protecting people or the environment:

It is recommended to use the information included in this safety data sheet as a basis for conducting workplace-specific risk assessments in order to establish the necessary risk prevention measures for the handling, use, storage and disposal of this product.

Other legislation:

The product could be affected by sectorial legislation

15.2 Chemical safety assessment:

The supplier has not carried out evaluation of chemical safety.

SECTION 16: OTHER INFORMATION

Legislation related to safety data sheets:

The SDS shall be supplied in an official language of the country where the product is placed on the market. This safety data sheet has been designed in accordance with ANNEX II-Guide to the compilation of safety data sheets of Regulation (EC) No 1907/2006 (COMMISSION REGULATION (EU) 2020/878).

Modifications related to the previous Safety Data Sheet which concerns the ways of managing risks.:

COMMISSION REGULATION (EU) 2020/878

Information on basic physical and chemical properties (SECTION 9):

Flash Point

Texts of the legislative phrases mentioned in section 2:

This SDS is an English translation of COMMISSION REGULATION (EU) 2020/878, without any country-specific legislation

HYBRID

Printing: 19/12/2022	Date of compilation: 26/06/2011	Revised: 25/02/2022	Version: 7 (Replaced 6)
SECTION 16: OTH	ER INFORMATION (continued)		
H361d: Suspec H226: Flamma	skin irritation. damage to organs through prolonged or ted of damaging the unborn child. ble liquid and vapour. serious eye irritation.	repeated exposure.	
	egislative phrases mentioned in sec	tion 3:	
The phrases in individual comp	dicated do not refer to the product itself; ponents which appear in section 3		nformative purposes and refer to the
CLP Regulation	on (EC) No 1272/2008:		
Acute Tox. 4: H Carc. 2: H351 Eye Irrit. 2: H3 Flam. Liq. 2: H Flam. Liq. 3: H Repr. 2: H3610 Skin Irrit. 2: H3 STOT RE 1: H3 STOT RE 2: H3	 H302+H332 - Harmful if swallowed or if i H332 - Harmful if inhaled. Suspected of causing cancer (Inhalation Highly flammable liquid and vapou Flammable liquid and vapour. Suspected of damaging the unborn ch Causes skin irritation. Causes damage to organs through May cause drowsiness or dizziness. 	n). r. ild. prolonged or repeated exposu	
Classification			
Skin Irrit. 2: Ca STOT RE 1: Ca Repr. 2: Calcula Flam. Liq. 3: Ca	alculation method Iculation method		
Advice relate			
Training is reco interpretation o	mmended in order to prevent industrial of this safety data sheet, as well as the la		ct and to facilitate their comprehension and
-	iographical sources:		
http://echa.eur			
http://eur-lex.e	s and acronyms:		
IMDG: Internati IATA: Internati ICAO: Internati COD: Chemical BOD5: 5day bio BCF: Bioconcer LD50: Lethal D LC50: Lethal C EC50: Effective LogPOW: Octa	ose 50 oncentration 50 e concentration 50 nolwater partition coefficient coefficient of organic carbon	carriage of dangerous goods	by road
	ional Agency for Research on Cancer		

The information contained in this safety data sheet is based on sources, technical knowledge and current legislation at European and state level, without being able to guarantee its accuracy. This information cannot be considered a guarantee of the properties of the product, it is simply a description of the security requirements. The occupational methodology and conditions for users of this product are not within our awareness or control, and it is ultimately the responsibility of the user to take the necessary measures to obtain the legal requirements concerning the manipulation, storage, use and disposal of chemical products. The information on this safety data sheet only refers to this product, which should not be used for needs other than those specified.

STER