MASTER

Safety data sheet

This SDS is an English translation of COMMISSION REGULATION (EU) 2020/878, without any country-specific legislation

SUPER-T

EC	TION 1: IDENTIFICATION OF THE SUBSTA	ANCE/MIXT <u>URE AND OF THE</u>	COMPANY/UNDERTAKING
.1	Product identifier: SUPER		
	Other means of identification:	X-1	
		T180-P00N-00WE	
.2	Relevant identified uses of the substance of		azinst
	Relevant uses: Car repair. For professional users		guilist.
	Uses advised against: All uses not specified in th		
1.3	Details of the supplier of the safety data sl		
	Troton Sp. z o.o. Ząbrowo 14A 78-120 Gościno - Zachodniopomorskie - Polska Phone: +48 94 35 123 94 - Fax: +48 94 35 126 troton@troton.com.pl www.troton.pl / www.troton.eu		
1.4	Emergency telephone number: (8am-4pm)	n)+48 094 35 123 94; 112	
SECT	TION 2: HAZARDS IDENTIFICATION **		
2.1	Classification of the substance or mixture:	:	
	CLP Regulation (EC) No 1272/2008:		
	Classification of this product has been carried or	out in accordance with CLP Regulat	tion (EC) No 1272/2008.
	Eye Irrit. 2: Eye irritation, Category 2, H319 Flam. Liq. 3: Flammable liquids, Category 3, H2: Repr. 2: Reproductive toxicity, Category 2, H361 Skin Irrit. 2: Skin irritation, Category 2, H315 STOT RE 1: Specific target organ toxicity — Rep	1d	² 1, H372
2.2	Label elements:		
	CLP Regulation (EC) No 1272/2008: Danger		
	Hazard statements:		
	Eye Irrit. 2: H319 - Causes serious eye irritation Flam. Liq. 3: H226 - Flammable liquid and vapor Repr. 2: H361d - Suspected of damaging the un Skin Irrit. 2: H315 - Causes skin irritation. STOT RE 1: H372 - Causes damage to organs the	bur. hborn child.	osure.
	Precautionary statements: P201: Obtain special instructions before use.		
	P210: Keep away from heat, hot surfaces, spark P280: Wear protective gloves/protective clothing P302+P352: IF ON SKIN: Wash with plenty of w	g/respiratory protection/eye prote water.	ction/protective footwear.
	P305+P351+P338: IF IN EYES: Rinse cautiously do. Continue rinsing. P308+P313: IF exposed or concerned: Get med P501: Dispose of contents/container in accordar respectively.	dical advice/attention.	
	Supplementary information:		
	EUH211: Warning! Hazardous respirable droplet	ts may be formed when sprayed.	Do not breathe spray or mist.
	Substances that contribute to the classific	cation	
	styrene		



SUPER-T

Printing	: 19/12/2022	Date of compilation: 02/09/2019	Revised: 24/01/2022	Version: 4 (Replaced 3)	
SEC	TION 2: HAZARI	DS IDENTIFICATION ** (continued	(t		
2.3	Other hazards:				
_	• • • • • • • • • • • • • • • • • • • •				

** Changes with regards to the previous version

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

3.1 Substance:

Non-applicable

3.2 Mixture:

Chemical description: Mixture composed of chemical products

Components:

In accordance with Annex II of Regulation (EC) No 1907/2006 (point 3), the product contains:

	Identification		Chemical name/Classification		Concentration
CAS:		styrene ⁽¹⁾		ATP ATP06	
EC: Index: REACH:	202-851-5 601-026-00-0 01-2119457861-32- XXXX	Regulation 1272/2008	Acute Tox. 4: H332; Eye Irrit. 2: H319; Flam. Liq. 3: H226; Repr. 2: H361d; Skin Irrit. 2: H315; STOT RE 1: H372 - Danger	♦	10 - <25 %
CAS:	13463-67-7	Titanium dioxide (ae	rodynamic diameter ≤ 10 μm) ⁽¹⁾	ATP ATP14	
EC: Index: REACH:	236-675-5 022-006-00-2 01-2119489379-17- XXXX	Regulation 1272/2008	Carc. 2: H351 - Warning		1 - <2,5 %
	111-76-2	2-butoxyethanol ⁽²⁾		ATP ATP15	
EC: Index: REACH:	203-905-0 603-014-00-0 01-2119475108-36- XXXX	Regulation 1272/2008	Acute Tox. 4: H302+H332; Eye Irrit. 2: H319; Skin Irrit. 2: H315 - Warning		<1 %

⁽¹⁾ Substances presenting a health or environmental hazard which meet criteria laid down in Regulation (EU) No. 2020/878

⁽²⁾ Substance with a Union workplace exposure limit

To obtain more information on the hazards of the substances consult sections 11, 12 and 16.

SECTION 4: FIRST AID MEASURES

4.1 Description of first aid measures:

The symptoms resulting from intoxication can appear after exposure, therefore, in case of doubt, seek medical attention for direct exposure to the chemical product or persistent discomfort, showing the SDS of this product.

By inhalation:

Remove the person affected from the area of exposure, provide with fresh air and keep at rest. In serious cases such as cardiorespiratory failure, artificial resuscitation techniques will be necessary (mouth to mouth resuscitation, cardiac massage, oxygen supply, etc.) requiring immediate medical assistance.

By skin contact:

Remove contaminated clothing and footwear, rinse skin or shower the person affected if appropriate with plenty of cold water and neutral soap. In serious cases see a doctor. If the product causes burns or freezing, clothing should not be removed as this could worsen the injury caused if it is stuck to the skin. If blisters form on the skin, these should never be burst as this will increase the risk of infection.

By eye contact:

Rinse eyes thoroughly with lukewarm water for at least 15 minutes. Do not allow the person affected to rub or close their eyes. If the injured person uses contact lenses, these should be removed unless they are stuck to the eyes, in which case this could cause further damage. In all cases, after cleaning, a doctor should be consulted as quickly as possible with the SDS of the product.

By ingestion/aspiration:

Do not induce vomiting, but if it does happen keep the head down to avoid aspiration. Keep the person affected at rest. Rinse out the mouth and throat, as they may have been affected during ingestion.

4.2 Most important symptoms and effects, both acute and delayed:



Safety data sheet

This SDS is an English translation of COMMISSION REGULATION (EU) 2020/878, without any country-specific legislation

SUPER-T

 Printing: 19/12/2022
 Date of compilation: 02/09/2019
 Revised: 24/01/2022
 Version: 4 (Replaced 3)

SECTION 4: FIRST AID MEASURES (continued)

Acute and delayed effects are indicated in sections 2 and 11.

4.3 Indication of any immediate medical attention and special treatment needed:

Non-applicable

SECTION 5: FIREFIGHTING MEASURES

5.1 Extinguishing media:

Suitable extinguishing media:

If possible use polyvalent powder fire extinguishers (ABC powder), alternatively use foam or carbon dioxide extinguishers (CO2).

Unsuitable extinguishing media:

IT IS RECOMMENDED NOT to use full jet water as an extinguishing agent.

5.2 Special hazards arising from the substance or mixture:

As a result of combustion or thermal decomposition reactive sub-products are created that can become highly toxic and, consequently, can present a serious health risk.

5.3 Advice for firefighters:

Depending on the magnitude of the fire it may be necessary to use full protective clothing and self-contained breathing apparatus (SCBA). Minimum emergency facilities and equipment should be available (fire blankets, portable first aid kit,...) in accordance with Directive 89/654/EC.

Additional provisions:

Act in accordance with the Internal Emergency Plan and the Information Sheets on actions to take after an accident or other emergencies. Eliminate all sources of ignition. In case of fire, cool the storage containers and tanks for products susceptible to combustion, explosion or BLEVE as a result of high temperatures. Avoid spillage of the products used to extinguish the fire into an aqueous medium.

SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1 Personal precautions, protective equipment and emergency procedures:

For non-emergency personnel:

Isolate leaks provided that there is no additional risk for the people performing this task. Evacuate the area and keep out those without protection. Personal protection equipment must be used against potential contact with the spilt product (See section 8). Above all prevent the formation of any vapour-air flammable mixtures, through either ventilation or the use of an inert medium. Remove any source of ignition. Eliminate electrostatic charges by interconnecting all the conductive surfaces on which static electricity could form, and also ensuring that all surfaces are connected to the ground.

For emergency responders:

Wear protective equipment. Keep unprotected persons away. See section 8.

6.2 Environmental precautions:

This product is not classified as hazardous to the environment. Keep product away from drains, surface and underground water.

6.3 Methods and material for containment and cleaning up:

It is recommended:

Absorb the spillage using sand or inert absorbent and move it to a safe place. Do not absorb in sawdust or other combustible absorbents. For any concern related to disposal consult section 13.

6.4 Reference to other sections:

See sections 8 and 13.

SECTION 7: HANDLING AND STORAGE

7.1 Precautions for safe handling:

A.- General precautions for safe use

Comply with the current legislation concerning the prevention of industrial risks. Keep containers hermetically sealed. Control spills and residues, destroying them with safe methods (section 6). Avoid leakages from the container. Maintain order and cleanliness where dangerous products are used.



Safety data sheet

This SDS is an English translation of COMMISSION REGULATION (EU) 2020/878, without any country-specific legislation

SUPER-T

Drinting	: 19/12/2022	Date of compilation: 02/09/2019	Revised: 24/01/2022	Version: 4 (Replaced 3)
-		• • • •	Revised: 24/01/2022	
SEC	IION /: HANDI	ING AND STORAGE (continued)		
	B Technical re	ecommendations for the prevention of f	ires and explosions	
	sparks,) a inertization possibility o clothes mad requirement protecting t 10 for condi	nd ventilate during cleaning operations systems where possible. Transfer at a s f electrostatic charges: ensure a perfec le of acrylic fibres, preferably wearing c ts for equipment and systems defined in	Avoid the existence of dangers slow speed to avoid the creation t equipotential connection, alw totton clothing and conductive n Directive 2014/34/EC (ATEX r the selection criteria of Direct ded.	
	necessary s equipment, drink during	WOMEN SHOULD NOT BE EXPOSED TO afety conditions (emergency showers a especially on the hands and face (See the process, washing hands afterward commendations to prevent environmer	nd eyewash stations in close p section 8). Limit manual transf s with suitable cleaning produc	roximity), using personal protection ers to small amounts only. Do not eat or
	It is recomn	nended to have absorbent material ava	ilable at close proximity to the	product (See subsection 6.3)
7.2	Conditions for	r safe storage, including any incom	patibilities:	
	A Technical m	leasures for storage		
	Minimum Te	emp.: 15 °C		
	Maximum T	emp.: 25 °C		
	Maximum ti	me: 12 Months		
	B General con	ditions for storage		
	Avoid source	es of heat, radiation, static electricity a	nd contact with food. For addit	tional information see subsection 10.5
7.3	Specific end u	ise(s):		
	Except for the in product.	nstructions already specified it is not ne	ecessary to provide any special	recommendation regarding the uses of this
SECT	TION 8: EXPOS	SURE CONTROLS/PERSONAL PRO	TECTION	
8.1	Control paran	neters:		
	Substances who	ose occupational exposure limits have to	o be monitored in the workplac	ce (European OEL, not country-specific

legislation):

Directive (EU) 2000/39, Directive 2004/37/EC, Directive (EU) 2006/15, Directive (EU) 2009/161, Directive (EU) 2017/164, Directive (EU) 2019/1831:

Identification	Occupa	ational exposure lir	nits
2-butoxyethanol	IOELV (8h)	20 ppm	98 mg/m ³
CAS: 111-76-2 EC: 203-905-0	IOELV (STEL)	50 ppm	246 mg/m ³

DNEL (Workers):

		Short e	xposure	Long e	xposure
Identification		Systemic	Local	Systemic	Local
styrene	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
CAS: 100-42-5	Dermal	Non-applicable	Non-applicable	406 mg/kg	Non-applicable
EC: 202-851-5	Inhalation	289 mg/m ³	306 mg/m ³	85 mg/m ³	Non-applicable
2-butoxyethanol	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
CAS: 111-76-2	Dermal	89 mg/kg	Non-applicable	125 mg/kg	Non-applicable
EC: 203-905-0	Inhalation	1091 mg/m ³	246 mg/m ³	98 mg/m ³	Non-applicable

DNEL (General population):

		Short e	xposure	Long ex	kposure
Identification		Systemic	Local	Systemic	Local
styrene	Oral	Non-applicable	Non-applicable	2,1 mg/kg	Non-applicable
CAS: 100-42-5	Dermal	Non-applicable	Non-applicable	343 mg/kg	Non-applicable
EC: 202-851-5	Inhalation	174,25 mg/m ³	182,75 mg/m ³	10,2 mg/m ³	Non-applicable



SUPER-T

Printing: 19/12/2022	Date of compilation: 02/09/20	019 Rev	vised: 24/01/2022	2 Version	1: 4 (Replaced	13)
SECTION 8: EXPOS	URE CONTROLS/PERSONAL	PROTECTIO	N (continued)			
			Short	exposure	Lo	ng exposure
	Identification		Systemic	Local	Systemic	Local
2-butoxyethanol		Oral	Non-applicable	Non-applicable	6,3 mg/kg	Non-applicable
CAS: 111-76-2		Dermal	89 mg/kg	Non-applicable	75 mg/kg	Non-applicable
EC: 203-905-0		Inhalation	426 mg/m ³	147 mg/m ³	59 mg/m ³	Non-applicable
PNEC:						
	Identification					
styrene		STP	5 mg/L	Fresh water		0,028 mg/L
CAS: 100-42-5		Soil	0,2 mg/kg	Marine water		0,014 mg/L
EC: 202-851-5		Intermittent	0,04 mg/L	Sediment (Fresh	water)	0,614 mg/kg
		Oral	Non-applicable	Sediment (Marin	e water)	0,307 mg/kg
2-butoxyethanol		STP	463 mg/L	Fresh water		8,8 mg/L
CAS: 111-76-2		Soil	2,33 mg/kg	Marine water		0,88 mg/L
EC: 203-905-0		Intermittent	26,4 mg/L	Sediment (Fresh	water)	34,6 mg/kg
		Oral	0,02 g/kg	Sediment (Marin	e water)	3,46 mg/kg

8.2 Exposure controls:

A.- Individual protection measures, such as personal protective equipment

In accordance with the order of importance to control professional exposure (Directive 98/24/EC) it is recommended to use localized extraction in the work area as a collective protection measure to avoid exceeding the occupational exposure limits. In case of using personal protective equipment it should have CE marking in accordance with Directive 2016/425/EC. For more information on Personal Protective Equipment (storage, use, cleaning, maintenance, class of protection,...) consult the information leaflet provided by the manufacturer. For additional information see subsection 7.1.

All information contained herein is a recommendation which needs some specification from the labour risk prevention services as it is not known whether the company has additional measures at its disposal.

B.- Respiratory protection

Pictogram	PPE	Labelling	CEN Standard	Remarks
Mandatory respiratory tract protection	Filter mask for gases and vapours (Filter type: A)		EN 405:2002+A1:2010	Replace when there is a taste or smell of the contaminant inside the face mask. If the contaminant comes with warnings it is recommended to use isolation equipment.
Mandatory respiratory tract protection	Filter mask for gases, vapours and particles (Filter type: FFP3)		EN 149:2001+A1:2009 EN 405:2002+A1:2010 EN ISO 136:1998	Replace when an increase in resistence to breathing is observed and/or a smell or taste of the contaminant is detected.

C.- Specific protection for the hands

Pictogram	PPE	Labelling	CEN Standard	Remarks
	NON-disposable chemical protective gloves (Material: Nitrile, Breakthrough time: > 480 min, Thickness: 0.4 mm)	して	EN ISO 374-1:2016+A1:2018 EN 16523-1:2015+A1:2018 EN ISO 21420:2020	The Breakthrough Time indicated by the manufacturer must exceed the period during which the product is being used. Do not use protective creams after the product has come into contact with skin.

As the product is a mixture of several substances, the resistance of the glove material can not be calculated in advance with total reliability and has therefore to be checked prior to the application.

D.- Eye and face protection

	Pictogram	PPE	Labelling	CEN Standard	Remarks
	Mandatory face protection	Panoramic glasses against splash/projections.	CAT II	EN 166:2002 EN ISO 4007:2018	Clean daily and disinfect periodically according to the manufacturer's instructions. Use if there is a risk of splashing.
E	Body protection				



SUPER-T

	0/12/2022 Da		mpilation: 02/09	/2019	Revise	d: 24/01/2022	Ver	
SECTIO	N 8: EXPOSURE	CONTR	OLS/PERSON/	AL PROTECT	ION (continued)		
	Pictogram		PPE	Labelling		CEN Standard		Remarks
	Mandatory complete body protection	protectio risks, w	sable clothing for on against chemical vith antistatic and roof properties		E	EN 1149-1,2,3 3034:2005+A1:2009 EN ISO 13982- 1:2004/A1:2010 N ISO 6529:2013 N ISO 6530:2005 N ISO 13688:2013 EN 464:1994		r professional use only. Clean periodically ording to the manufacturer's instructions.
	Mandatory foot protection	protectio risk, with	ty footwear for on against chemical antistatic and heat tant properties		E	N ISO 13287:2020 N ISO 20345:2011 EN 13832-1:2019	Re	eplace boots at any sign of deterioration.
F.	- Additional emerge	ency mea	asures					
	Emergency mea	asure	St	andards		Emergency measu	re	Standards
	Emergency sho	ower		5I Z358-1 11, ISO 3864-4:20)11	Eyewash stations	5	DIN 12 899 ISO 3864-1:2011, ISO 3864-4:2011
W	<pre>/ith regard to Direct V.O.C. (Supply):</pre>	ive 2010	/75/EU, this proc	duct has the fo	llowing	characteristics:		
5ECTIO	V.O.C. density at Average carbon n Average molecula	umber: Ir weight	80 kg 8 :: 104,4	% weight /m ³ (80 g/L) 5 g/mol PERTIES				
	V.O.C. density at Average carbon n Average molecula DN 9: PHYSICAL A	umber: Ir weight AND CH	80 kg 8 :: 104,4 IEMICAL PROP	/m ³ (80 g/L) 5 g/mol PERTIES	s:			
).1 Iı	V.O.C. density at Average carbon n Average molecula	umber: Ir weight AND CH sic phys	80 kg 8 :: 104,4 IEMICAL PROP	r/m ³ (80 g/L) 15 g/mol PERTIES cal propertie	s:			
).1 I I	V.O.C. density at Average carbon n Average molecula DN 9: PHYSICAL A	umber: Ir weight AND CH sic phys	80 kg 8 :: 104,4 IEMICAL PROP	r/m ³ (80 g/L) 15 g/mol PERTIES cal propertie	s:			
9.1 II Fo A	V.O.C. density at Average carbon n Average molecula ON 9: PHYSICAL A Information on base or complete informa	AND CH	80 kg 8 :: 104,4 IEMICAL PROP	r/m ³ (80 g/L) 15 g/mol PERTIES cal propertie				
9.1 II Fo A Pl	V.O.C. density at Average carbon n Average molecula DN 9: PHYSICAL A Information on base or complete informa	AND CH	80 kg 8 :: 104,4 IEMICAL PROP	r/m ³ (80 g/L) 5 g/mol PERTIES cal properties asheet.	id			
).1 In Fo A Ph Aj	V.O.C. density at Average carbon n Average molecula DN 9: PHYSICAL A Information on bas or complete informa Information complete informa	AND CH	80 kg 8 :: 104,4 IEMICAL PROP	r/m ³ (80 g/L) 15 g/mol 2ERTIES cal properties asheet. Liqu Visco	id			
9.1 II Fo A Ph Aj Co	V.O.C. density at Average carbon n Average molecula N 9: PHYSICAL A nformation on bas or complete informa appearance: hysical state at 20 ° ppearance:	AND CH	80 kg 8 :: 104,4 IEMICAL PROP	r/m ³ (80 g/L) 15 g/mol PERTIES cal properties asheet. Liqu Visco	id ous			
9.1 II Fo A Pł A Ca O	V.O.C. density at Average carbon n Average molecula DN 9: PHYSICAL A Information on bas or complete informa Information on bas or complete at 20 ° ppearance: olour:	AND CH	80 kg 8 :: 104,4 IEMICAL PROP	r/m ³ (80 g/L) 15 g/mol PERTIES Cal properties asheet. Liqu Visco Chai	id ous Beige	stic		
9.1 In Fc A Pł A Cc O O	V.O.C. density at Average carbon n Average molecula DN 9: PHYSICAL A Information on bas or complete informa Information on bas or complete a state at 20 ° ppearance: hysical state at 20 ° ppearance: olour:	AND CH	80 kg 8 :: 104,4 IEMICAL PROP	r/m ³ (80 g/L) 15 g/mol PERTIES Cal properties asheet. Liqu Visco Chai	id ous Beige racteris	stic		
9.1 In Fo A Pi A Co O O V	V.O.C. density at Average carbon n Average molecula IN 9: PHYSICAL / Information on bas or complete informa or complete informa or complete informa	umber: Ir weight AND CH sic phys tion see C:	80 kg 8 ID4,4 EMICAL PROP sical and chemi the product data	r/m ³ (80 g/L) 15 g/mol PERTIES Cal properties asheet. Liqu Visco Chai	id ous Beige racteris -applic	stic		
9.1 In Fo A P A C O O O V B B O V A V A V A V A V A V A V A V A A O O O V A A O O V A A A A	V.O.C. density at Average carbon n Average molecula IN 9: PHYSICAL / Information on base or complete information or complete information or complete information or complete information of comple	umber: ir weight AND CH sic phys ition see C: C: spheric p 0 °C:	80 kg 8 ID4,4 EMICAL PROP sical and chemi the product data	r/m ³ (80 g/L) 5 g/mol ERTIES cal properties asheet. Liqu Visco Chan Non-	id ous Beige racteris -applic °C	stic		
9.1 In Fo A Ph A C C C O O V B O V A V A V A V A	V.O.C. density at Average carbon n Average molecula DN 9: PHYSICAL 4 Information on bas or complete informa Opearance: hysical state at 20 ° ppearance: olour: dour: dour: dour threshold: folatility: oiling point at atmost apour pressure at 20 apour pressure at 20	umber: ir weight AND CH sic phys tion see C: C: spheric p 0 °C: 0 °C:	80 kg 8 ID4,4 EMICAL PROP sical and chemi the product data	i/m ³ (80 g/L) 5 g/mol ERTIES cal properties asheet. Liqu Visco Char Non- 113 2188 1153	id ous Beige racteris -applic •C 8 Pa 31,68 F	stic able * Pa (11,53 kPa)		
9.1 In Fe A PP A Ca O V B B V A V A V A V A V A	V.O.C. density at Average carbon n Average molecula IN 9: PHYSICAL / Information on bas or complete informa Information on bas or complete information Information on bas	AND CH sic phys tion see C: spheric p 0 °C: 0 °C: 0 °C:	80 kg 8 ID4,4 EMICAL PROP sical and chemi the product data	i/m ³ (80 g/L) 5 g/mol ERTIES cal properties asheet. Liqu Visco Char Non- 113 2188 1153	id ous Beige racteris -applic °C 8 Pa	stic able * Pa (11,53 kPa)		
9.1 In Fo A Ph A Ph A Ph C A O O O V A B C O O V A E V A Ph C A Ph C A C A Ph C A C A C A C A C A C A C A Ph C A A Ph C A A Ph C A A Ph C A A Ph C A A Ph C A A A A A A A A A A A A A A A A A A	V.O.C. density at Average carbon n Average molecula DN 9: PHYSICAL 4 Information on bas or complete informat or complete informat o	AND CH sic phys tion see C: spheric p 0 °C: 0 °C: 0 °C:	80 kg 8 ID4,4 EMICAL PROP sical and chemi the product data	I/m ³ (80 g/L) 5 g/mol ERTIES Cal properties asheet. Liqu Visco Chai Non- 113 2188 1153 Non-	id ous Beige racteris -applic °C 8 Pa 31,68 F -applic	stic able * Pa (11,53 kPa) able *		
9.1 II FC A Pł C C O O V BC V BC V V V V V V V V V C D D	V.O.C. density at Average carbon n Average molecula DN 9: PHYSICAL A Information on bas or complete informa ppearance: hysical state at 20 ° ppearance: olour: dour: dour: dour threshold: folatility: oiling point at atmost apour pressure at 20 apour pressure at 20 vaporation rate at 20 roduct description tensity at 20 °C:	umber: r weight AND CH sic phys tion see C: c: spheric p 0 °C: 0 °C: 0 °C: n:	80 kg 8 ID4,4 EMICAL PROP sical and chemi the product data	I/m ³ (80 g/L) IS g/mol IS g/mol IS groperties asheet. Liqu Visco Chai Non- 113 2188 1153 Non- 1090	id ous Beige racteris -applic 8 Pa 31,68 F -applic	stic able * Pa (11,53 kPa) able *		
9.1 In Fe A P A P Ca O O V A Ca O V A Ca Ca Ca Ca Ca Ca Ca Ca Ca Ca Ca Ca Ca	V.O.C. density at Average carbon n Average molecula IN 9: PHYSICAL / Information on bas or complete information or complete information or complete information or complete information of complet	AND CH sic phys tion see C: c: spheric p 0 °C: 0 °C: n: 0 °C:	80 kg 8 ID4,4 EMICAL PROP sical and chemi the product data	I/m ³ (80 g/L) IS g/mol IS g/mol IS GAI properties asheet. Liqu Visco Chai Non- 113 2188 1153 Non- 1090 1,42	id ous Beige racteris -applic 8 Pa 31,68 F -applic 0 kg/m 27	stic able * Pa (11,53 kPa) able *		
9.1 In Fo A P A P C C O O O V B C O O V A E V A C C O O C V A P I D D R A D	V.O.C. density at Average carbon n Average molecula DN 9: PHYSICAL 4 Information on bas or complete informat or complete informat or complete informat pearance: hysical state at 20 ° ppearance: olour: olour: dour threshold: 'olatility: oiling point at atmost apour pressure at 20 apour pressure at 20 apour pressure at 20 apour pressure at 20 apour pressure at 20 vaporation rate at 20 roduct description ensity at 20 °C: elative density at 20 ynamic viscosity at 20	AND CH sic phys tion see C: c: o oC: o oC: o oC: n: o oC: n: o oC: n:	80 kg 8 ID4,4 EMICAL PROP sical and chemi the product data	I/m ³ (80 g/L) ERTIES Cal properties asheet. Liqu Visco Char Non- 113 2188 115: Non- 1090 1,42 2,21	id ous Beige racteris -applic 8 Pa 31,68 F -applic 0 kg/m 27 . cP	stic able * Pa (11,53 kPa) able * 3		
9.1 In Fe A PP A C C O O V B B C O O V S C C O O V S C C O O V S C C O O V S C C O O V S C C O O V S C C O O V S C C O O V S C C O O S S S S S S S S S S S S S S S	V.O.C. density at Average carbon n Average molecula IN 9: PHYSICAL / Information on bas or complete information or complete information or complete information or complete information of complet	AND CH sic phys tion see C: C: spheric p 0 °C: 0 °C: 0 °C: n: 20 °C: 20 °C: 20 °C:	80 kg 8 :: 104,4 IEMICAL PROP sical and chemi the product data	I/m ³ (80 g/L) IS g/mol IS g/mol IS GI properties asheet. Liqu Visco Chan Non- 113 2188 1153 Non- 1090 1,42 2,21 1,55	id ous Beige racteris -applic 8 Pa 31,68 F -applic 0 kg/m 27 . cP 5 mm ² /	stic able * Pa (11,53 kPa) able * 3		



SUPER-T

Printing	19/12/2022 Dat	te of compilation: 02/09/2019	Revised: 24/01/2022	Version: 4 (Replaced 3)
SECT	TION 9: PHYSICAL AI	ND CHEMICAL PROPERTIES	(continued)	
	Kinematic viscosity at	40 °C:	>20,5 mm²/s	
	Concentration:		Non-applicable *	
	pH:		Non-applicable *	
	Vapour density at 20 °	PC:	Non-applicable *	
	Partition coefficient n-o	octanol/water 20 °C:	Non-applicable *	
	Solubility in water at 2	0 °C:	Non-applicable *	
	Solubility properties:		Non-applicable *	
	Decomposition temper	ature:	Non-applicable *	
	Melting point/freezing	point:	Non-applicable *	
	Flammability:			
	Flash Point:		39 °C	
	Flammability (solid, ga	s):	Non-applicable *	
	Autoignition temperatu	ıre:	238 °C	
	Lower flammability lim	it:	Not available	
	Upper flammability lim	it:	Not available	
	Particle characterist	tics:		
	Median equivalent diar	meter:	Non-applicable	
9.2	Other information:			
	Information with re	gard to physical hazard class	ses:	
	Explosive properties:		Non-applicable *	
	Oxidising properties:		Non-applicable *	
	Corrosive to metals:		Non-applicable *	
	Heat of combustion:		Non-applicable *	
	components:	age (by mass) of flammable	Non-applicable *	
	Other safety charac	teristics:		
	Surface tension at 20 G	°C:	Non-applicable *	
	Refraction index:		Non-applicable *	
	*Not relevant due to the na	ature of the product, not providing inform	mation property of its hazards.	

1	Reactivity:								
	No hazardous reactions are expected because the product is stable under recommended storage conditions. See section 7.								
.2	Chemical stability:								
	Chemically stable under the	indicated conditions of	storage, handling and use.						
).3	Possibility of hazardous	reactions:							
	Under the specified conditions, hazardous reactions that lead to excessive temperatures or pressure are not expected.								
	Under the specified condition	ons, hazardous reactions	s that lead to excessive tem	peratures or pressure are	e not expected.				
).4	•	ons, hazardous reactions	s that lead to excessive tem	peratures or pressure are	e not expected.				
).4	•			peratures or pressure ar	e not expected.				
).4	Conditions to avoid:			peratures or pressure an Sunlight	e not expected. Humidity				
).4	Conditions to avoid: Applicable for handling and	storage at room tempe	rature:						
0.4	Conditions to avoid: Applicable for handling and Shock and friction	storage at room tempe Contact with air Not applicable	rature: Increase in temperature	Sunlight	Humidity				
	Conditions to avoid: Applicable for handling and Shock and friction Not applicable	storage at room tempe Contact with air Not applicable	rature: Increase in temperature	Sunlight	Humidity				



SUPER-T

-	12/2022	Date of compilation: 02/09/2019	Revised: 24/01/2022	Version: 4 (Replaced 3)
SECTIO	N 10: STABI	LITY AND REACTIVITY (continued	d)	
		nces highly reactive and can auto-polyr s are extremely shock- and heat-sensiti		peroxide accumulation. The peroxides forme
ECTIO	N 11: TOXIC	OLOGICAL INFORMATION		
1.1 In	formation o	n hazard classes as defined in Regu	lation (EC) No 1272/2008	3:
Th	e experimenta	I information related to the toxicologica	l properties of the product its	elf is not available
tha	at are hazardo	us to the health .	vapours for prolonged period	Is of time due to the possibility of effects
	•	alth implications:		
ad		on health may result, depending on the		recommended occupational exposure limits,
B-	as dangerous	s for consumption. For more information //Irritability: The consumption of a cons	see section 3.	however, it contains substances classified tion in the throat, abdominal pain, nausea
C-	as hazardous - Corrosivity classified as	for inhalation. For more information se	e section 3. e classification criteria are no	However, it contains substances classified t met, as it does not contain substances
D-	- Contact w	ith the skin: Produces skin inflammation ith the eyes: Produces eye damage after (carcinogenicity, mutagenicity and toxic	er contact.	
E-	as dangerous IARC: styre Solvent naph - Mutagenic hazardous fo	s with carcinogenic effects. For more inf ene (2A); Talc (3); 2-butoxyethanol (3); tha (petroleum), light arom., < 0.1 % E ity: Based on available data, the classif r this effect. For more information see s ive toxicity: Suspected of damaging the	ormation see section 3. styrene (2A); Titanium dioxic C 200-753-7 (3); 2,6-di-tert-t ication criteria are not met, as section 3.	However, it contains substances classified de (aerodynamic diameter $\leq 10 \ \mu$ m) (2B); butyl-p-cresol (3) s it does not contain substances classified as
F-	hazardous wi - Skin: Base hazardous fo	y: Based on available data, the classific th sensitising effects. For more informa ed on available data, the classification co r this effect. For more information see s et organ toxicity (STOT) - single exposu	tion see section 3. riteria are not met, as it does section 3.	it does not contain substances classified as not contain substances classified as
G-	this effect. Fo	ilable data, the classification criteria are or more information see section 3. et organ toxicity (STOT)-repeated expos		ain substances classified as hazardous for
H-	including dea - Skin: Base	th, serious functional disorders or more of on available data, the classification of r this effect. For more information see s	hological changes of toxicolog riteria are not met, as it does	
Ot		or more information see section 3.	e not met, as it does not cont	ain substances classified as hazardous for
to	mixtures in po			on as a carcinogen by inhalation applies only e form of or incorporated in particles with



SUPER-T

ng: 19/12/2022	Date of compilation: 02/09/2019	Revised: 24/01/	2022 V	ersion: 4 (Replaced 3)	
CTION 11: TOXI	COLOGICAL INFORMATION (contir	nued)			
Specific toxic	ology information on the substances	5:			
	Identification		A	cute toxicity	Genus
styrene		L	.D50 oral	>2000 mg/kg	
CAS: 100-42-5		L	.D50 dermal	>2000 mg/kg	
EC: 202-851-5		L	.C50 inhalation	12 mg/L (4 h)	Rat
Titanium dioxide (aerodynamic diameter ≤ 10 µm)	L	.D50 oral	10000 mg/kg	Rat
CAS: 13463-67-7		L	.D50 dermal	10000 mg/kg	Rabbit
EC: 236-675-5		L	.C50 inhalation	>5 mg/L	
2-butoxyethanol		L	.D50 oral	1200 mg/kg	Rat
CAS: 111-76-2		L	.D50 dermal	3000 mg/kg	Rabbit
EC: 203-905-0		L	.C50 inhalation	>20 mg/L	
Acute Toxicity	• Estimate (ATE mix):				

	Ingredient(s) of unknown toxicity	
Oral >2000 mg/kg (Calculation method)		Non-applicable
Dermal	>2000 mg/kg (Calculation method)	Non-applicable
Inhalation	64,08 mg/L (4 h) (Calculation method)	0 %

11.2 Information on other hazards:

Endocrine disrupting properties

Endocrine-disrupting properties: The product fails to meet the criteria.

Other information

Non-applicable

SECTION 12: ECOLOGICAL INFORMATION

The experimental information related to the eco-toxicological properties of the product itself is not available

12.1 Toxicity:

Acute toxicity:

Identification		Concentration	Species	Genus
2-butoxyethanol	LC50	1490 mg/L (96 h)	Lepomis macrochirus	Fish
CAS: 111-76-2 EC: 203-905-0		1815 mg/L (48 h)	Daphnia magna	Crustacean
		911 mg/L (72 h)	Pseudokirchneriella subcapitata	Algae

Chronic toxicity:

Identification		Concentration	Species	Genus
2-butoxyethanol	NOEC	100 mg/L	Danio rerio	Fish
CAS: 111-76-2 EC: 203-905-0	NOEC	100 mg/L	Daphnia magna	Crustacean

12.2 Persistence and degradability:

Substance-specific information:

Identification	Degradability		Biodegradability	
2-butoxyethanol	BOD5	0,71 g O2/g	Concentration	100 mg/L
CAS: 111-76-2	COD	2,2 g O2/g	Period	14 days
EC: 203-905-0	BOD5/COD	0,32	% Biodegradable	96 %

12.3 Bioaccumulative potential:

Substance-specific information:

	Identification	Bioaccumulation potential		
	2-butoxyethanol	BCF	3	
	CAS: 111-76-2	Pow Log	0.83	
	EC: 203-905-0	Potential	Low	
12.4	Mobility in soil:			



SUPER-T

Printing: 19/12/2022 Date of compilation: 02/09/2019

Revised: 24/01/2022

Version: 4 (Replaced 3)

SECTION 12: ECOLOGICAL INFORMATION (continued)

Identification	Absorp	Absorption/desorption		Volatility	
styrene	Кос	Non-applicable	Henry	Non-applicable	
CAS: 100-42-5	Conclusion	Non-applicable	Dry soil	Non-applicable	
EC: 202-851-5	Surface tension	3,21E-2 N/m (25 °C)	Moist soil	Non-applicable	
2-butoxyethanol	Кос	8	Henry	1,621E-1 Pa·m ³ /mo	
CAS: 111-76-2	Conclusion	Very High	Dry soil	No	
EC: 203-905-0	Surface tension	2,729E-2 N/m (25 °C)	Moist soil	Yes	

12.5 Results of PBT and vPvB assessment:

Product fails to meet PBT/vPvB criteria

12.6 Endocrine disrupting properties:

Endocrine-disrupting properties: The product fails to meet the criteria.

12.7 Other adverse effects:

Not described

SECTION 13: DISPOSAL CONSIDERATIONS

13.1 Waste treatment methods:

Code	Description	Waste class (Regulation (EU) No 1357/2014)
	waste paint and varnish containing organic solvents or other hazardous substances packaging containing residues of or contaminated by hazardous substances	Dangerous

Type of waste (Regulation (EU) No 1357/2014):

HP3 Flammable, HP5 Specific Target Organ Toxicity (STOT)/Aspiration Toxicity, HP10 Toxic for reproduction, HP4 Irritant — skin irritation and eye damage

Waste management (disposal and evaluation):

Consult the authorized waste service manager on the assessment and disposal operations in accordance with Annex 1 and Annex 2 (Directive 2008/98/EC). As under 15 01 (2014/955/EC) of the code and in case the container has been in direct contact with the product, it will be processed the same way as the actual product. Otherwise, it will be processed as non-dangerous residue. Waste should not be disposed of to drains. See paragraph 6.2.

Regulations related to waste management:

In accordance with Annex II of Regulation (EC) No 1907/2006 (REACH) the community or state provisions related to waste management are stated

Community legislation: Directive 2008/98/EC, 2014/955/EU, Regulation (EU) No 1357/2014

SECTION 14: TRANSPORT INFORMATION

Transport of dangerous goods by land:

With regard to ADR 2021 and RID 2021:

14.1 UN number or ID number: UN3269 POLYESTER RESIN KIT, liquid base material 14.2 UN proper shipping name: 14.3 Transport hazard class(es): 3 Labels: 3 14.4 Packing group: III 14.5 Environmental hazards: No 14.6 Special precautions for user 236, 340 Special regulations: Tunnel restriction code: F Physico-Chemical properties: see section 9 Limited quantities: 5 L 14.7 Maritime transport in bulk Non-applicable according to IMO instruments: Transport of dangerous goods by sea:



SUPER-T

Printing: 19/12/2022	Date	of compilation: 02/09/2019	Revised: 24/01/2022	Version: 4 (Replaced 3)	
SECTION 14: TRAN	SPORT	INFORMATION (continued)			
With regard to	IMDG 40	-20:			
	14.2 14.3 14.4 14.5	UN number or ID number: UN proper shipping name: Transport hazard class(es): Labels: Packing group: Marine pollutant: Special precautions for user	UN3269 POLYESTER RESIN KIT, liqui 3 3 III No	d base material	
		Special regulations: EmS Codes: Physico-Chemical properties: Limited quantities: Segregation group: Maritime transport in bulk	340, 236 F-E, S-D see section 9 5 L Non-applicable Non-applicable		
		according to IMO instruments:			
Transport of	dangero	ous goods by air:			
With regard to	IATA/IC/	AO 2022:			
	14.2 14.3	UN number or ID number: UN proper shipping name: Transport hazard class(es): Labels:	UN3269 POLYESTER RESIN KIT, liqui 3 3	d base material	
3	14.5	Packing group: Environmental hazards: Special precautions for user	III No		
	14.7	Physico-Chemical properties: Maritime transport in bulk according to IMO instruments:	see section 9 Non-applicable		
SECTION 15: REGU	LATOR	INFORMATION			
Candidate subst Substances inclu Regulation (EC) Article 95, REGU	ances for uded in A No 1005 JLATION	vironmental regulations/legisler authorisation under the Regulation nnex XIV of REACH ("Authorisation /2009, about substances that depl (EU) No 528/2012: Non-applicable 19/2012, in relation to the import a	n (EC) No 1907/2006 (REACH n List") and sunset date: Non- ete the ozone layer: Non-appli e): Non-applicable applicable icable ical products: Non-applica	
Section		Description	1	Lower-tier requirements	Upper-tier requirements
Limitations to etc): Shall not be use —ornamental an and ashtrays,	ed in: ticles inte	IQUIDS rcialisation and the use of cert ended to produce light or colour ef			
Specific provis	e or more sions in	participants, or any article intendent terms of protecting people or the information included in this s	the environment:		ecific risk

It is recommended to use the information included in this safety data sheet as a basis for conducting workplace-specific risk assessments in order to establish the necessary risk prevention measures for the handling, use, storage and disposal of this product.



SUPER-T

	ION 15: REGULATORY INFORMATION (continued) Other legislation: The product could be affected by sectorial legislation Chemical safety assessment: The supplier has not carried out evaluation of chemical safety.				
SECT	ION 16: OTHER INFORMATION				
	Legislation related to safety data sheets: The SDS shall be supplied in an official language of the country where the product is placed on the market. This safety data sheet has been designed in accordance with ANNEX II-Guide to the compilation of safety data sheets of Regulation (EC) No 1907/2006 (COMMISSION REGULATION (EU) 2020/878).				
	Modifications related to the previous Safety Data Sheet which concerns the ways of managing risks.: COMMISSION REGULATION (EU) 2020/878 CLP Regulation (EC) No 1272/2008 (SECTION 2, SECTION 16): · Precautionary statements				
	Texts of the legislative phrases mentioned in section 2: H315: Causes skin irritation. H372: Causes damage to organs through prolonged or repeated exposure. H361d: Suspected of damaging the unborn child. H226: Flammable liquid and vapour. H319: Causes serious eye irritation.				
	Texts of the legislative phrases mentioned in section 3: The phrases indicated do not refer to the product itself; they are present merely for informative purposes and refer to the individual components which appear in section 3 CLP Regulation (EC) No 1272/2008:				
	Acute Tox. 4: H302+H332 - Harmful if swallowed or if inhaled. Acute Tox. 4: H332 - Harmful if inhaled. Carc. 2: H351 - Suspected of causing cancer (Inhalation). Eye Irrit. 2: H319 - Causes serious eye irritation. Flam. Liq. 3: H226 - Flammable liquid and vapour. Repr. 2: H361d - Suspected of damaging the unborn child. Skin Irrit. 2: H315 - Causes skin irritation. STOT RE 1: H372 - Causes damage to organs through prolonged or repeated exposure.				
	Classification procedure: Skin Irrit. 2: Calculation method STOT RE 1: Calculation method Repr. 2: Calculation method Flam. Liq. 3: Calculation method (2.6.4.3) Eye Irrit. 2: Calculation method				
	Advice related to training: Training is recommended in order to prevent industrial risks for staff using this product and to facilitate their comprehension and interpretation of this safety data sheet, as well as the label on the product. Principal bibliographical sources:				
	http://echa.europa.eu http://eur-lex.europa.eu				



SUPER-T

Printing: 19/12/2022	Date of compilation: 02/09/2019	Revised: 24/01/2022	Version: 4 (Replaced 3)	
SECTION 16: OTHE	R INFORMATION (continued)			
IMDG: Internatio IATA: Internatio ICAO: Internatio COD: Chemical 0 BOD5: 5day bio BCF: Bioconcent LD50: Lethal Do LC50: Lethal Co EC50: Effective LogPOW: Octan Koc: Partition co UFI: unique forr	use 50 ncentration 50 concentration 50 olwater partition coefficient pefficient of organic carbon	arriage of dangerous goods	by road	

The information contained in this safety data sheet is based on sources, technical knowledge and current legislation at European and state level, without being able to guarantee its accuracy. This information cannot be considered a guarantee of the properties of the product, it is simply a description of the security requirements. The occupational methodology and conditions for users of this product are not within our awareness or control, and it is ultimately the responsibility of the user to take the necessary measures to obtain the legal requirements concerning the manipulation, storage, use and disposal of chemical products. The information on this safety data sheet only refers to this product, which should not be used for needs other than those specified.