

TURBO-T GLAZE

Printing: 19/12/2022

Date of compilation: 31/07/2019

Revised: 17/11/2022

Version: 8 (Replaced 7)

SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

- 1.1 Product identifier:** TURBO-T GLAZE
Other means of identification:
UFI: 1KHV-X0YA-Y008-ANK0
- 1.2 Relevant identified uses of the substance or mixture and uses advised against:**
 Relevant uses: Car repair; filler for joints, cracks, etc.... For professional users only.
 Uses advised against: All uses not specified in this section or in section 7.3
- 1.3 Details of the supplier of the safety data sheet:**
 Troton Sp. z o.o.
 Ząbrowo 14A
 78-120 Gościno - Zachodniopomorskie - Polska
 Phone: +48 94 35 123 94 - Fax: +48 94 35 126 22
 troton@troton.com.pl
 www.troton.pl / www.troton.eu
- 1.4 Emergency telephone number:** (8am-4pm)+48 094 35 123 94; 112

SECTION 2: HAZARDS IDENTIFICATION

- 2.1 Classification of the substance or mixture:**
CLP Regulation (EC) No 1272/2008:
 Classification of this product has been carried out in accordance with CLP Regulation (EC) No 1272/2008.
 Eye Irrit. 2: Eye irritation, Category 2, H319
 Flam. Liq. 3: Flammable liquids, Category 3, H226
 Repr. 2: Reproductive toxicity, Category 2, H361d
 Skin Irrit. 2: Skin irritation, Category 2, H315
 STOT RE 1: Specific target organ toxicity — Repeated exposure, Hazard Category 1, H372

2.2 Label elements:

CLP Regulation (EC) No 1272/2008:

Danger



Hazard statements:

Eye Irrit. 2: H319 - Causes serious eye irritation.
 Flam. Liq. 3: H226 - Flammable liquid and vapour.
 Repr. 2: H361d - Suspected of damaging the unborn child.
 Skin Irrit. 2: H315 - Causes skin irritation.
 STOT RE 1: H372 - Causes damage to organs through prolonged or repeated exposure.

Precautionary statements:

P201: Obtain special instructions before use.
 P210: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
 P280: Wear protective gloves/protective clothing/respiratory protection/eye protection/protective footwear.
 P302+P352: IF ON SKIN: Wash with plenty of water.
 P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
 P308+P313: IF exposed or concerned: Get medical advice/attention.
 P501: Dispose of contents/container in accordance with regulations on hazardous waste or packaging and packaging waste respectively.

Supplementary information:

EUH211: Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.

Substances that contribute to the classification

styrene

2.3 Other hazards:

Safety data sheet

This SDS is an English translation of COMMISSION REGULATION (EU) 2020/878, without any country-specific legislation

TURBO-T GLAZE

Printing: 19/12/2022 Date of compilation: 31/07/2019 Revised: 17/11/2022 Version: 8 (Replaced 7)

SECTION 2: HAZARDS IDENTIFICATION (continued)

Product fails to meet PBT/vPvB criteria
Endocrine-disrupting properties: The product fails to meet the criteria.

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

3.1 Substance:




Non-applicable

3.2 Mixture:

Chemical description: Mixture composed of chemical products

Components:

In accordance with Annex II of Regulation (EC) No 1907/2006 (point 3), the product contains:

Identification	Chemical name/Classification		Concentration
CAS: 100-42-5 EC: 202-851-5 Index: 601-026-00-0 REACH: 01-2119457861-32-XXXX	styrene⁽¹⁾ Regulation 1272/2008	ATP ATP06 Acute Tox. 4: H332; Eye Irrit. 2: H319; Flam. Liq. 3: H226; Repr. 2: H361d; Skin Irrit. 2: H315; STOT RE 1: H372 - Danger	 10 - <25 %
CAS: 13463-67-7 EC: 236-675-5 Index: 022-006-00-2 REACH: 01-2119489379-17-XXXX	Titanium dioxide (aerodynamic diameter ≤ 10 µm)⁽¹⁾ Regulation 1272/2008	ATP ATP14 Carc. 2: H351 - Warning	 1 - <2,5 %
CAS: 111-76-2 EC: 203-905-0 Index: 603-014-00-0 REACH: 01-2119475108-36-XXXX	2-butoxyethanol⁽²⁾ Regulation 1272/2008	ATP ATP15 Acute Tox. 4: H302+H332; Eye Irrit. 2: H319; Skin Irrit. 2: H315 - Warning	 <1 %

⁽¹⁾ Substances presenting a health or environmental hazard which meet criteria laid down in Regulation (EU) No. 2020/878

⁽²⁾ Substance with a Union workplace exposure limit

To obtain more information on the hazards of the substances consult sections 11, 12 and 16.

SECTION 4: FIRST AID MEASURES

4.1 Description of first aid measures:

The symptoms resulting from intoxication can appear after exposure, therefore, in case of doubt, seek medical attention for direct exposure to the chemical product or persistent discomfort, showing the SDS of this product.

By inhalation:

Remove the person affected from the area of exposure, provide with fresh air and keep at rest. In serious cases such as cardiorespiratory failure, artificial resuscitation techniques will be necessary (mouth to mouth resuscitation, cardiac massage, oxygen supply, etc.) requiring immediate medical assistance.

By skin contact:

Remove contaminated clothing and footwear, rinse skin or shower the person affected if appropriate with plenty of cold water and neutral soap. In serious cases see a doctor. If the product causes burns or freezing, clothing should not be removed as this could worsen the injury caused if it is stuck to the skin. If blisters form on the skin, these should never be burst as this will increase the risk of infection.

By eye contact:

Rinse eyes thoroughly with lukewarm water for at least 15 minutes. Do not allow the person affected to rub or close their eyes. If the injured person uses contact lenses, these should be removed unless they are stuck to the eyes, in which case this could cause further damage. In all cases, after cleaning, a doctor should be consulted as quickly as possible with the SDS of the product.

By ingestion/aspiration:

Do not induce vomiting, but if it does happen keep the head down to avoid aspiration. Keep the person affected at rest. Rinse out the mouth and throat, as they may have been affected during ingestion.

4.2 Most important symptoms and effects, both acute and delayed:

Acute and delayed effects are indicated in sections 2 and 11.

4.3 Indication of any immediate medical attention and special treatment needed:

Non-applicable

TURBO-T GLAZE

Printing: 19/12/2022

Date of compilation: 31/07/2019

Revised: 17/11/2022

Version: 8 (Replaced 7)

SECTION 5: FIREFIGHTING MEASURES**5.1 Extinguishing media:****Suitable extinguishing media:**

If possible use polyvalent powder fire extinguishers (ABC powder), alternatively use foam or carbon dioxide extinguishers (CO₂).

Unsuitable extinguishing media:

IT IS RECOMMENDED NOT to use full jet water as an extinguishing agent.

5.2 Special hazards arising from the substance or mixture:

As a result of combustion or thermal decomposition reactive sub-products are created that can become highly toxic and, consequently, can present a serious health risk.

5.3 Advice for firefighters:

Depending on the magnitude of the fire it may be necessary to use full protective clothing and self-contained breathing apparatus (SCBA). Minimum emergency facilities and equipment should be available (fire blankets, portable first aid kit,...) in accordance with Directive 89/654/EC.

Additional provisions:

Act in accordance with the Internal Emergency Plan and the Information Sheets on actions to take after an accident or other emergencies. Eliminate all sources of ignition. In case of fire, cool the storage containers and tanks for products susceptible to combustion, explosion or BLEVE as a result of high temperatures. Avoid spillage of the products used to extinguish the fire into an aqueous medium.

SECTION 6: ACCIDENTAL RELEASE MEASURES**6.1 Personal precautions, protective equipment and emergency procedures:****For non-emergency personnel:**

Isolate leaks provided that there is no additional risk for the people performing this task. Evacuate the area and keep out those without protection. Personal protection equipment must be used against potential contact with the spilt product (See section 8). Above all prevent the formation of any vapour-air flammable mixtures, through either ventilation or the use of an inert medium. Remove any source of ignition. Eliminate electrostatic charges by interconnecting all the conductive surfaces on which static electricity could form, and also ensuring that all surfaces are connected to the ground.

For emergency responders:

Wear protective equipment. Keep unprotected persons away. See section 8.

6.2 Environmental precautions:

This product is not classified as hazardous to the environment. Keep product away from drains, surface and underground water.

6.3 Methods and material for containment and cleaning up:

It is recommended:

Absorb the spillage using sand or inert absorbent and move it to a safe place. Do not absorb in sawdust or other combustible absorbents. For any concern related to disposal consult section 13.

6.4 Reference to other sections:

See sections 8 and 13.

SECTION 7: HANDLING AND STORAGE**7.1 Precautions for safe handling:**

A.- General precautions for safe use

Comply with the current legislation concerning the prevention of industrial risks. Keep containers hermetically sealed. Control spills and residues, destroying them with safe methods (section 6). Avoid leakages from the container. Maintain order and cleanliness where dangerous products are used.

B.- Technical recommendations for the prevention of fires and explosions

Safety data sheet

This SDS is an English translation of COMMISSION REGULATION (EU) 2020/878, without any country-specific legislation

TURBO-T GLAZE

Printing: 19/12/2022

Date of compilation: 31/07/2019

Revised: 17/11/2022

Version: 8 (Replaced 7)

SECTION 7: HANDLING AND STORAGE (continued)

Transfer in well ventilated areas, preferably through localized extraction. Fully control sources of ignition (mobile phones, sparks,...) and ventilate during cleaning operations. Avoid the existence of dangerous atmospheres inside containers, applying inertization systems where possible. Transfer at a slow speed to avoid the creation of electrostatic charges. Against the possibility of electrostatic charges: ensure a perfect equipotential connection, always use groundings, do not wear work clothes made of acrylic fibres, preferably wearing cotton clothing and conductive footwear. Comply with the essential security requirements for equipment and systems defined in Directive 2014/34/EC (ATEX 100) and with the minimum requirements for protecting the security and health of workers under the selection criteria of Directive 1999/92/EC (ATEX 137). Consult section 10 for conditions and materials that should be avoided.

C.- Technical recommendations on general occupational hygiene

PREGNANT WOMEN SHOULD NOT BE EXPOSED TO THIS PRODUCT. Transfer in designated areas that comply with the necessary safety conditions (emergency showers and eyewash stations in close proximity), using personal protection equipment, especially on the hands and face (See section 8). Limit manual transfers to small amounts only. Do not eat or drink during the process, washing hands afterwards with suitable cleaning products.

D.- Technical recommendations to prevent environmental risks

It is recommended to have absorbent material available at close proximity to the product (See subsection 6.3)

7.2 Conditions for safe storage, including any incompatibilities:

A.- Technical measures for storage

- Minimum Temp.: 15 °C
- Maximum Temp.: 25 °C
- Maximum time: 12 Months

B.- General conditions for storage

Avoid sources of heat, radiation, static electricity and contact with food. For additional information see subsection 10.5

7.3 Specific end use(s):

Except for the instructions already specified it is not necessary to provide any special recommendation regarding the uses of this product.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1 Control parameters:

Substances whose occupational exposure limits have to be monitored in the workplace (European OEL, not country-specific legislation):

Directive (EU) 2000/39, Directive 2004/37/EC, Directive (EU) 2006/15, Directive (EU) 2009/161, Directive (EU) 2017/164, Directive (EU) 2019/1831:

Identification	Occupational exposure limits		
	IOELV (8h)	20 ppm	98 mg/m ³
2-butoxyethanol CAS: 111-76-2 EC: 203-905-0	IOELV (STEL)	50 ppm	246 mg/m ³

DNEL (Workers):

Identification		Short exposure		Long exposure	
		Systemic	Local	Systemic	Local
styrene CAS: 100-42-5 EC: 202-851-5	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
	Dermal	Non-applicable	Non-applicable	406 mg/kg	Non-applicable
	Inhalation	289 mg/m ³	306 mg/m ³	85 mg/m ³	Non-applicable
2-butoxyethanol CAS: 111-76-2 EC: 203-905-0	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
	Dermal	89 mg/kg	Non-applicable	125 mg/kg	Non-applicable
	Inhalation	1091 mg/m ³	246 mg/m ³	98 mg/m ³	Non-applicable

DNEL (General population):

Identification		Short exposure		Long exposure	
		Systemic	Local	Systemic	Local
styrene CAS: 100-42-5 EC: 202-851-5	Oral	Non-applicable	Non-applicable	2,1 mg/kg	Non-applicable
	Dermal	Non-applicable	Non-applicable	343 mg/kg	Non-applicable
	Inhalation	174,25 mg/m ³	182,75 mg/m ³	10,2 mg/m ³	Non-applicable

Safety data sheet

This SDS is an English translation of COMMISSION REGULATION (EU) 2020/878, without any country-specific legislation

TURBO-T GLAZE

Printing: 19/12/2022

Date of compilation: 31/07/2019

Revised: 17/11/2022

Version: 8 (Replaced 7)

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION (continued)

Identification		Short exposure		Long exposure	
		Systemic	Local	Systemic	Local
2-butoxyethanol CAS: 111-76-2 EC: 203-905-0	Oral	Non-applicable	Non-applicable	6,3 mg/kg	Non-applicable
	Dermal	89 mg/kg	Non-applicable	75 mg/kg	Non-applicable
	Inhalation	426 mg/m ³	147 mg/m ³	59 mg/m ³	Non-applicable

PNEC:

Identification				
styrene CAS: 100-42-5 EC: 202-851-5	STP	5 mg/L	Fresh water	0,028 mg/L
	Soil	0,2 mg/kg	Marine water	0,014 mg/L
	Intermittent	0,04 mg/L	Sediment (Fresh water)	0,614 mg/kg
	Oral	Non-applicable	Sediment (Marine water)	0,307 mg/kg
2-butoxyethanol CAS: 111-76-2 EC: 203-905-0	STP	463 mg/L	Fresh water	8,8 mg/L
	Soil	2,33 mg/kg	Marine water	0,88 mg/L
	Intermittent	26,4 mg/L	Sediment (Fresh water)	34,6 mg/kg
	Oral	0,02 g/kg	Sediment (Marine water)	3,46 mg/kg



8.2 Exposure controls:

A.- Individual protection measures, such as personal protective equipment



In accordance with the order of importance to control professional exposure (Directive 98/24/EC) it is recommended to use localized extraction in the work area as a collective protection measure to avoid exceeding the occupational exposure limits. In case of using personal protective equipment it should have CE marking in accordance with Directive 2016/425/EC. For more information on Personal Protective Equipment (storage, use, cleaning, maintenance, class of protection,...) consult the information leaflet provided by the manufacturer. For additional information see subsection 7.1.

All information contained herein is a recommendation which needs some specification from the labour risk prevention services as it is not known whether the company has additional measures at its disposal.

B.- Respiratory protection



Pictogram	PPE	Labelling	CEN Standard	Remarks
 Mandatory respiratory tract protection	Filter mask for gases and vapours (Filter type: A)		EN 405:2002+A1:2010	Replace when there is a taste or smell of the contaminant inside the face mask. If the contaminant comes with warnings it is recommended to use isolation equipment.

C.- Specific protection for the hands

Pictogram	PPE	Labelling	CEN Standard	Remarks
 Mandatory hand protection	NON-disposable chemical protective gloves (Material: Nitrile, Breakthrough time: > 480 min, Thickness: 0.4 mm)		EN ISO 374-1:2016+A1:2018 EN 16523-1:2015+A1:2018 EN ISO 21420:2020	The Breakthrough Time indicated by the manufacturer must exceed the period during which the product is being used. Do not use protective creams after the product has come into contact with skin.

As the product is a mixture of several substances, the resistance of the glove material can not be calculated in advance with total reliability and has therefore to be checked prior to the application.

D.- Eye and face protection

Pictogram	PPE	Labelling	CEN Standard	Remarks
 Mandatory face protection	Panoramic glasses against splash/projections.		EN 166:2002 EN ISO 4007:2018	Clean daily and disinfect periodically according to the manufacturer's instructions. Use if there is a risk of splashing.

E.- Body protection

Safety data sheet

This SDS is an English translation of COMMISSION REGULATION (EU) 2020/878, without any country-specific legislation

TURBO-T GLAZE

Printing: 19/12/2022

Date of compilation: 31/07/2019

Revised: 17/11/2022

Version: 8 (Replaced 7)

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION (continued)

Pictogram	PPE	Labelling	CEN Standard	Remarks
 Mandatory complete body protection	Disposable clothing for protection against chemical risks, with antistatic and fireproof properties	 CAT III	EN 1149-1,2,3 EN 13034:2005+A1:2009 EN ISO 13982-1:2004/A1:2010 EN ISO 6529:2013 EN ISO 6530:2005 EN ISO 13688:2013 EN 464:1994	For professional use only. Clean periodically according to the manufacturer's instructions.
 Mandatory foot protection	Safety footwear for protection against chemical risk, with antistatic and heat resistant properties	 CAT III	EN ISO 13287:2020 EN ISO 20345:2011 EN 13832-1:2019	Replace boots at any sign of deterioration.

F.- Additional emergency measures

Emergency measure	Standards	Emergency measure	Standards
 Emergency shower	ANSI Z358-1 ISO 3864-1:2011, ISO 3864-4:2011	 Eyewash stations	DIN 12 899 ISO 3864-1:2011, ISO 3864-4:2011

Environmental exposure controls:

In accordance with the community legislation for the protection of the environment it is recommended to avoid environmental spillage of both the product and its container. For additional information see subsection 7.1.D

Volatile organic compounds:

With regard to Directive 2010/75/EU, this product has the following characteristics:

V.O.C. (Supply):	20,26 % weight
V.O.C. density at 20 °C:	30 kg/m ³ (30 g/L)
Average carbon number:	8
Average molecular weight:	104,48 g/mol

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES **

9.1 Information on basic physical and chemical properties:

For complete information see the product datasheet.

Appearance:

Physical state at 20 °C:	Liquid
Appearance:	Viscous
Colour:	Green
Odour:	Characteristic
Odour threshold:	Non-applicable *

Volatility:

Boiling point at atmospheric pressure:	113 °C
Vapour pressure at 20 °C:	2188 Pa
Vapour pressure at 50 °C:	11530,12 Pa (11,53 kPa)
Evaporation rate at 20 °C:	Non-applicable *

Product description:

Density at 20 °C:	1270 kg/m ³ (DIN 53217)
Relative density at 20 °C:	Non-applicable *
Dynamic viscosity at 20 °C:	2,13 cP

*Not relevant due to the nature of the product, not providing information property of its hazards.

** Changes with regards to the previous version

- CONTINUED ON NEXT PAGE -

Safety data sheet

This SDS is an English translation of COMMISSION REGULATION (EU) 2020/878, without any country-specific legislation

TURBO-T GLAZE

Printing: 19/12/2022

Date of compilation: 31/07/2019

Revised: 17/11/2022

Version: 8 (Replaced 7)

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES ** (continued)

Kinematic viscosity at 20 °C:	1,53 mm ² /s
Kinematic viscosity at 40 °C:	>20,5 mm ² /s
Concentration:	Non-applicable *
pH:	Non-applicable *
Vapour density at 20 °C:	Non-applicable *
Partition coefficient n-octanol/water 20 °C:	Non-applicable *
Solubility in water at 20 °C:	Non-applicable *
Solubility properties:	Non-applicable *
Decomposition temperature:	Non-applicable *
Melting point/freezing point:	Non-applicable *

Flammability:

Flash Point:	39 °C
Flammability (solid, gas):	Non-applicable *
Autoignition temperature:	238 °C
Lower flammability limit:	Not available
Upper flammability limit:	Not available

Particle characteristics:

Median equivalent diameter:	Non-applicable
-----------------------------	----------------

9.2 Other information:

Information with regard to physical hazard classes:

Explosive properties:	Non-applicable *
Oxidising properties:	Non-applicable *
Corrosive to metals:	Non-applicable *
Heat of combustion:	Non-applicable *
Aerosols-total percentage (by mass) of flammable components:	Non-applicable *

Other safety characteristics:

Surface tension at 20 °C:	Non-applicable *
Refraction index:	Non-applicable *

*Not relevant due to the nature of the product, not providing information property of its hazards.

** Changes with regards to the previous version

SECTION 10: STABILITY AND REACTIVITY

10.1 Reactivity:

No hazardous reactions are expected because the product is stable under recommended storage conditions. See section 7.

10.2 Chemical stability:

Chemically stable under the indicated conditions of storage, handling and use.

10.3 Possibility of hazardous reactions:

Under the specified conditions, hazardous reactions that lead to excessive temperatures or pressure are not expected.

10.4 Conditions to avoid:

Applicable for handling and storage at room temperature:

Shock and friction	Contact with air	Increase in temperature	Sunlight	Humidity
Not applicable	Not applicable	Risk of combustion	Avoid direct impact	Not applicable

10.5 Incompatible materials:

Acids	Water	Oxidising materials	Combustible materials	Others
Avoid strong acids	Not applicable	Avoid direct impact	Not applicable	Avoid alkalis or strong bases

- CONTINUED ON NEXT PAGE -

Safety data sheet

This SDS is an English translation of COMMISSION REGULATION (EU) 2020/878, without any country-specific legislation

TURBO-T GLAZE

Printing: 19/12/2022

Date of compilation: 31/07/2019

Revised: 17/11/2022

Version: 8 (Replaced 7)

SECTION 10: STABILITY AND REACTIVITY (continued)**10.6 Hazardous decomposition products:**

Contains substances highly reactive and can auto-polymerize as a result of internal peroxide accumulation. The peroxides formed in these reactions are extremely shock- and heat-sensitive.

SECTION 11: TOXICOLOGICAL INFORMATION**11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008:**

The experimental information related to the toxicological properties of the product itself is not available

Contains glycols. It is recommended not to breathe the vapours for prolonged periods of time due to the possibility of effects that are hazardous to the health .

Dangerous health implications:

In case of exposure that is repetitive, prolonged or at concentrations higher than the recommended occupational exposure limits, adverse effects on health may result, depending on the means of exposure:

A- Ingestion (acute effect):

- Acute toxicity : Based on available data, the classification criteria are not met, however, it contains substances classified as dangerous for consumption. For more information see section 3.
- Corrosivity/Irritability: The consumption of a considerable dose can cause irritation in the throat, abdominal pain, nausea and vomiting.

B- Inhalation (acute effect):

- Acute toxicity : Based on available data, the classification criteria are not met. However, it contains substances classified as hazardous for inhalation. For more information see section 3.
- Corrosivity/Irritability: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.

C- Contact with the skin and the eyes (acute effect):

- Contact with the skin: Produces skin inflammation.
- Contact with the eyes: Produces eye damage after contact.

D- CMR effects (carcinogenicity, mutagenicity and toxicity to reproduction):

- Carcinogenicity: Based on available data, the classification criteria are not met. However, it contains substances classified as dangerous with carcinogenic effects. For more information see section 3.
IARC: styrene (2A); Talc (3); 2-butoxyethanol (3); Solvent naphtha (petroleum), light arom., < 0.1 % EC 200-753-7 (3); 2,6-di-tert-butyl-p-cresol (3); Titanium dioxide (aerodynamic diameter ≤ 10 µm) (2B); styrene (2A)
- Mutagenicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.
- Reproductive toxicity: Suspected of damaging the unborn child.

E- Sensitizing effects:

- Respiratory: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous with sensitising effects. For more information see section 3.
- Skin: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.

F- Specific target organ toxicity (STOT) - single exposure:

Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.

G- Specific target organ toxicity (STOT)-repeated exposure:

- Specific target organ toxicity (STOT)-repeated exposure: Serious health effects in the case of prolonged consumption, including death, serious functional disorders or morphological changes of toxicological importance.
- Skin: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.

H- Aspiration hazard:

Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.

Other information:

Safety data sheet

This SDS is an English translation of COMMISSION REGULATION (EU) 2020/878, without any country-specific legislation

TURBO-T GLAZE

Printing: 19/12/2022

Date of compilation: 31/07/2019

Revised: 17/11/2022

Version: 8 (Replaced 7)

SECTION 11: TOXICOLOGICAL INFORMATION (continued)

CAS 13463-67-7 Titanium dioxide (aerodynamic diameter ≤ 10 µm): The classification as a carcinogen by inhalation applies only to mixtures in powder form containing 1 % or more of titanium dioxide which is in the form of or incorporated in particles with aerodynamic diameter ≤ 10 µm

Specific toxicology information on the substances:

Identification	Acute toxicity		Genus
styrene CAS: 100-42-5 EC: 202-851-5	LD50 oral	>2000 mg/kg	
	LD50 dermal	>2000 mg/kg	
	LC50 inhalation	12 mg/L (4 h)	Rat
Titanium dioxide (aerodynamic diameter ≤ 10 µm) CAS: 13463-67-7 EC: 236-675-5	LD50 oral	10000 mg/kg	Rat
	LD50 dermal	10000 mg/kg	Rabbit
	LC50 inhalation	>5 mg/L	
2-butoxyethanol CAS: 111-76-2 EC: 203-905-0	LD50 oral	1200 mg/kg	Rat
	LD50 dermal	3000 mg/kg	Rabbit
	LC50 inhalation	>20 mg/L	

Acute Toxicity Estimate (ATE mix):

ATE mix		Ingredient(s) of unknown toxicity
Oral	>2000 mg/kg (Calculation method)	Non-applicable
Dermal	>2000 mg/kg (Calculation method)	Non-applicable
Inhalation	60,34 mg/L (4 h) (Calculation method)	0 %

11.2 Information on other hazards:

Endocrine disrupting properties

Endocrine-disrupting properties: The product fails to meet the criteria.

Other information

Non-applicable

SECTION 12: ECOLOGICAL INFORMATION

The experimental information related to the eco-toxicological properties of the product itself is not available

12.1 Toxicity:

Acute toxicity:

Identification	Concentration		Species	Genus
2-butoxyethanol CAS: 111-76-2 EC: 203-905-0	LC50	1490 mg/L (96 h)	Lepomis macrochirus	Fish
	EC50	1815 mg/L (48 h)	Daphnia magna	Crustacean
	EC50	911 mg/L (72 h)	Pseudokirchneriella subcapitata	Algae

Chronic toxicity:

Identification	Concentration		Species	Genus
2-butoxyethanol CAS: 111-76-2 EC: 203-905-0	NOEC	100 mg/L	Danio rerio	Fish
	NOEC	100 mg/L	Daphnia magna	Crustacean

12.2 Persistence and degradability:

Substance-specific information:

Identification	Degradability		Biodegradability	
2-butoxyethanol CAS: 111-76-2 EC: 203-905-0	BOD5	0,71 g O2/g	Concentration	100 mg/L
	COD	2,2 g O2/g	Period	14 days
	BOD5/COD	0,32	% Biodegradable	96 %

12.3 Bioaccumulative potential:

Substance-specific information:

Identification	Bioaccumulation potential	
2-butoxyethanol CAS: 111-76-2 EC: 203-905-0	BCF	3
	Pow Log	0.83
	Potential	Low

- CONTINUED ON NEXT PAGE -

TURBO-T GLAZE

Printing: 19/12/2022

Date of compilation: 31/07/2019

Revised: 17/11/2022

Version: 8 (Replaced 7)

SECTION 12: ECOLOGICAL INFORMATION (continued)

12.4 Mobility in soil:

Identification	Absorption/desorption		Volatility	
	Koc	Non-applicable	Henry	Non-applicable
styrene CAS: 100-42-5 EC: 202-851-5	Conclusion	Non-applicable	Dry soil	Non-applicable
	Surface tension	3,21E-2 N/m (25 °C)	Moist soil	Non-applicable
	Koc	8	Henry	1,621E-1 Pa·m ³ /mol
2-butoxyethanol CAS: 111-76-2 EC: 203-905-0	Conclusion	Very High	Dry soil	No
	Surface tension	2,729E-2 N/m (25 °C)	Moist soil	Yes

12.5 Results of PBT and vPvB assessment:

Product fails to meet PBT/vPvB criteria

12.6 Endocrine disrupting properties:

Endocrine-disrupting properties: The product fails to meet the criteria.

12.7 Other adverse effects:

Not described

SECTION 13: DISPOSAL CONSIDERATIONS

13.1 Waste treatment methods:

Code	Description	Waste class (Regulation (EU) No 1357/2014)
08 01 11* 15 01 10*	waste paint and varnish containing organic solvents or other hazardous substances packaging containing residues of or contaminated by hazardous substances	Dangerous

Type of waste (Regulation (EU) No 1357/2014):

HP3 Flammable, HP5 Specific Target Organ Toxicity (STOT)/Aspiration Toxicity, HP10 Toxic for reproduction, HP4 Irritant — skin irritation and eye damage

Waste management (disposal and evaluation):

Consult the authorized waste service manager on the assessment and disposal operations in accordance with Annex 1 and Annex 2 (Directive 2008/98/EC). As under 15 01 (2014/955/EC) of the code and in case the container has been in direct contact with the product, it will be processed the same way as the actual product. Otherwise, it will be processed as non-dangerous residue. Waste should not be disposed of to drains. See paragraph 6.2.

Regulations related to waste management:

In accordance with Annex II of Regulation (EC) No 1907/2006 (REACH) the community or state provisions related to waste management are stated

Community legislation: Directive 2008/98/EC, 2014/955/EU, Regulation (EU) No 1357/2014

SECTION 14: TRANSPORT INFORMATION

Transport of dangerous goods by land:

With regard to ADR 2021 and RID 2021:



- 14.1 UN number or ID number:** UN3269
- 14.2 UN proper shipping name:** POLYESTER RESIN KIT, liquid base material
- 14.3 Transport hazard class(es):** 3
- Labels: 3
- 14.4 Packing group:** III
- 14.5 Environmental hazards:** No
- 14.6 Special precautions for user**
- Special regulations: 236, 340
- Tunnel restriction code: E
- Physico-Chemical properties: see section 9
- Limited quantities: 5 L
- 14.7 Maritime transport in bulk according to IMO instruments:** Non-applicable

TURBO-T GLAZE

Printing: 19/12/2022

Date of compilation: 31/07/2019

Revised: 17/11/2022

Version: 8 (Replaced 7)

SECTION 14: TRANSPORT INFORMATION (continued)

Transport of dangerous goods by sea:

With regard to IMDG 40-20:



- 14.1 UN number or ID number:** UN3269
- 14.2 UN proper shipping name:** POLYESTER RESIN KIT, liquid base material
- 14.3 Transport hazard class(es):** 3
Labels: 3
- 14.4 Packing group:** III
- 14.5 Marine pollutant:** No
- 14.6 Special precautions for user**
Special regulations: 340, 236
EmS Codes: F-E, S-D
Physico-Chemical properties: see section 9
Limited quantities: 5 L
Segregation group: Non-applicable
- 14.7 Maritime transport in bulk according to IMO instruments:** Non-applicable

Transport of dangerous goods by air:

With regard to IATA/ICAO 2022:



- 14.1 UN number or ID number:** UN3269
- 14.2 UN proper shipping name:** POLYESTER RESIN KIT, liquid base material
- 14.3 Transport hazard class(es):** 3
Labels: 3
- 14.4 Packing group:** III
- 14.5 Environmental hazards:** No
- 14.6 Special precautions for user**
Physico-Chemical properties: see section 9
- 14.7 Maritime transport in bulk according to IMO instruments:** Non-applicable

SECTION 15: REGULATORY INFORMATION

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture:

Candidate substances for authorisation under the Regulation (EC) No 1907/2006 (REACH): Non-applicable
 Substances included in Annex XIV of REACH ("Authorisation List") and sunset date: Non-applicable
 Regulation (EC) No 1005/2009, about substances that deplete the ozone layer: Non-applicable
 Article 95, REGULATION (EU) No 528/2012: Non-applicable
 REGULATION (EU) No 649/2012, in relation to the import and export of hazardous chemical products: Non-applicable

Seveso III:

Section	Description	Lower-tier requirements	Upper-tier requirements
P5c	FLAMMABLE LIQUIDS	5000	50000

Limitations to commercialisation and the use of certain dangerous substances and mixtures (Annex XVII REACH, etc):

Shall not be used in:
 —ornamental articles intended to produce light or colour effects by means of different phases, for example in ornamental lamps and ashtrays,
 —tricks and jokes,
 —games for one or more participants, or any article intended to be used as such, even with ornamental aspects.

Specific provisions in terms of protecting people or the environment:

Safety data sheet

This SDS is an English translation of COMMISSION REGULATION (EU) 2020/878, without any country-specific legislation

TURBO-T GLAZE

Printing: 19/12/2022

Date of compilation: 31/07/2019

Revised: 17/11/2022

Version: 8 (Replaced 7)

SECTION 15: REGULATORY INFORMATION (continued)

It is recommended to use the information included in this safety data sheet as a basis for conducting workplace-specific risk assessments in order to establish the necessary risk prevention measures for the handling, use, storage and disposal of this product.

Other legislation:

The product could be affected by sectorial legislation

15.2 Chemical safety assessment:

The supplier has not carried out evaluation of chemical safety.

SECTION 16: OTHER INFORMATION**Legislation related to safety data sheets:**

The SDS shall be supplied in an official language of the country where the product is placed on the market. This safety data sheet has been designed in accordance with ANNEX II-Guide to the compilation of safety data sheets of Regulation (EC) No 1907/2006 (COMMISSION REGULATION (EU) 2020/878).

Modifications related to the previous Safety Data Sheet which concerns the ways of managing risks.:

COMMISSION REGULATION (EU) 2020/878

Information on basic physical and chemical properties (SECTION 9):

- Flash Point

Texts of the legislative phrases mentioned in section 2:

H315: Causes skin irritation.

H372: Causes damage to organs through prolonged or repeated exposure.

H361d: Suspected of damaging the unborn child.

H226: Flammable liquid and vapour.

H319: Causes serious eye irritation.

Texts of the legislative phrases mentioned in section 3:

The phrases indicated do not refer to the product itself; they are present merely for informative purposes and refer to the individual components which appear in section 3

CLP Regulation (EC) No 1272/2008:

Acute Tox. 4: H302+H332 - Harmful if swallowed or if inhaled.

Acute Tox. 4: H332 - Harmful if inhaled.

Carc. 2: H351 - Suspected of causing cancer (Inhalation).

Eye Irrit. 2: H319 - Causes serious eye irritation.

Flam. Liq. 3: H226 - Flammable liquid and vapour.

Repr. 2: H361d - Suspected of damaging the unborn child.

Skin Irrit. 2: H315 - Causes skin irritation.

STOT RE 1: H372 - Causes damage to organs through prolonged or repeated exposure.

Classification procedure:

Skin Irrit. 2: Calculation method

STOT RE 1: Calculation method

Repr. 2: Calculation method

Flam. Liq. 3: Calculation method (2.6.4.3)

Eye Irrit. 2: Calculation method

Advice related to training:

Training is recommended in order to prevent industrial risks for staff using this product and to facilitate their comprehension and interpretation of this safety data sheet, as well as the label on the product.

Principal bibliographical sources:

<http://echa.europa.eu>

<http://eur-lex.europa.eu>

Abbreviations and acronyms:

Safety data sheet

This SDS is an English translation of COMMISSION REGULATION (EU) 2020/878, without any country-specific legislation

TURBO-T GLAZE

Printing: 19/12/2022

Date of compilation: 31/07/2019

Revised: 17/11/2022

Version: 8 (Replaced 7)

SECTION 16: OTHER INFORMATION (continued)

ADR: European agreement concerning the international carriage of dangerous goods by road
IMDG: International maritime dangerous goods code
IATA: International Air Transport Association
ICAO: International Civil Aviation Organisation
COD: Chemical Oxygen Demand
BOD5: 5day biochemical oxygen demand
BCF: Bioconcentration factor
LD50: Lethal Dose 50
LC50: Lethal Concentration 50
EC50: Effective concentration 50
LogPOW: Octanolwater partition coefficient
Koc: Partition coefficient of organic carbon
UFI: unique formula identifier
IARC: International Agency for Research on Cancer

The information contained in this safety data sheet is based on sources, technical knowledge and current legislation at European and state level, without being able to guarantee its accuracy. This information cannot be considered a guarantee of the properties of the product, it is simply a description of the security requirements. The occupational methodology and conditions for users of this product are not within our awareness or control, and it is ultimately the responsibility of the user to take the necessary measures to obtain the legal requirements concerning the manipulation, storage, use and disposal of chemical products. The information on this safety data sheet only refers to this product, which should not be used for needs other than those specified.

- END OF SAFETY DATA SHEET -