

ULTRALIGHT CARBON

ECT	TION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING	
1		
L	Product identifier: ULTRALIGHT CARBON Other means of identification:	
2	Relevant identified uses of the substance or mixture and uses advised against:	
	Relevant uses: Car repair. For professional users only.	
	Uses advised against: All uses not specified in this section or in section 7.3	
3	Details of the supplier of the safety data sheet: Troton Sp. z o.o.	
	Zabrowo 14A	
	78-120 Gościno - Zachodniopomorskie - Polska	
	Phone: +48 94 35 123 94 - Fax: +48 94 35 126 22 troton@troton.com.pl	
	www.troton.pl / www.troton.eu	
4	Emergency telephone number: (8am-4pm)+48 094 35 123 94; 112	
C	TION 2: HAZARDS IDENTIFICATION	
1	Classification of the substance or mixture:	
	CLP Regulation (EC) No 1272/2008:	
	Classification of this product has been carried out in accordance with CLP Regulation (EC) No 1272/2008.	
_	Eye Irrit. 2: Eye irritation, Category 2, H319 Flam. Liq. 3: Flammable liquids, Category 3, H226 Repr. 2: Reproductive toxicity, Category 2, H361d Skin Irrit. 2: Skin irritation, Category 2, H315 STOT RE 1: Specific target organ toxicity — Repeated exposure, Hazard Category 1, H372	
.2	Label elements:	
	CLP Regulation (EC) No 1272/2008:	
	Danger	
	Hazard statements:	
	Eye Irrit. 2: H319 - Causes serious eye irritation.	
	Flam. Liq. 3: H226 - Flammable liquid and vapour. Repr. 2: H361d - Suspected of damaging the unborn child.	
	Skin Irrit. 2: H315 - Causes skin irritation.	
	STOT RE 1: H372 - Causes damage to organs through prolonged or repeated exposure.	
	Precautionary statements:	
	P201: Obtain special instructions before use. P210: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.	
	P280: Wear protective gloves/protective clothing/respiratory protection/eye protection/protective footwear.	
	P302+P352: IF ON SKIN: Wash with plenty of water. P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy	to
	do. Continue rinsing.	
	P308+P313: IF exposed or concerned: Get medical advice/attention. P501: Dispose of contents/container in accordance with regulations on hazardous waste or packaging and packaging waste respectively.	
	Substances that contribute to the classification	
	styrene	
3	Other hazards:	
	Product fails to meet PBT/vPvB criteria	
	Endocrine-disrupting properties: The product fails to meet the criteria.	

- CONTINUED ON NEXT PAGE -



ULTRALIGHT CARBON

Printing: 19/12/2022 Date of compilation: 26/02/2016 Revised: 13/01/2022 Version: 4 (Replaced 3)

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS **

3.1 Substance:

Non-applicable

3.2 Mixture:

Chemical description: Mixture composed of chemical products

Components:

In accordance with Annex II of Regulation (EC) No 1907/2006 (point 3), the product contains:

	Identification			Concentration	
CAS:		styrene ⁽¹⁾ ATP ATPO			
EC: Index: REACH:	202-851-5 601-026-00-0 01-2119457861-32- XXXX	Regulation 1272/2008	Acute Tox. 4: H332; Eye Irrit. 2: H319; Flam. Liq. 3: H226; Repr. 2: H361d; Skin Irrit. 2: H315; STOT RE 1: H372 - Danger	() 🏟 🚸	25 - <50 %
CAS:	13463-67-7	Titanium dioxide (ae	rodynamic diameter ≤ 10 μm) ⁽¹⁾	ATP ATP14	
	236-675-5 022-006-00-2 01-2119489379-17- XXXX	Regulation 1272/2008	Carc. 2: H351 - Warning		<1 %

⁽¹⁾ Substances presenting a health or environmental hazard which meet criteria laid down in Regulation (EU) No. 2020/878

To obtain more information on the hazards of the substances consult sections 11, 12 and 16.

** Changes with regards to the previous version

SECTION 4: FIRST AID MEASURES

4.1 Description of first aid measures:

The symptoms resulting from intoxication can appear after exposure, therefore, in case of doubt, seek medical attention for direct exposure to the chemical product or persistent discomfort, showing the SDS of this product.

By inhalation:

Remove the person affected from the area of exposure, provide with fresh air and keep at rest. In serious cases such as cardiorespiratory failure, artificial resuscitation techniques will be necessary (mouth to mouth resuscitation, cardiac massage, oxygen supply, etc.) requiring immediate medical assistance.

By skin contact:

Remove contaminated clothing and footwear, rinse skin or shower the person affected if appropriate with plenty of cold water and neutral soap. In serious cases see a doctor. If the product causes burns or freezing, clothing should not be removed as this could worsen the injury caused if it is stuck to the skin. If blisters form on the skin, these should never be burst as this will increase the risk of infection.

By eye contact:

Rinse eyes thoroughly with lukewarm water for at least 15 minutes. Do not allow the person affected to rub or close their eyes. If the injured person uses contact lenses, these should be removed unless they are stuck to the eyes, in which case this could cause further damage. In all cases, after cleaning, a doctor should be consulted as quickly as possible with the SDS of the product.

By ingestion/aspiration:

Do not induce vomiting, but if it does happen keep the head down to avoid aspiration. Keep the person affected at rest. Rinse out the mouth and throat, as they may have been affected during ingestion.

4.2 Most important symptoms and effects, both acute and delayed:

Acute and delayed effects are indicated in sections 2 and 11.

4.3 Indication of any immediate medical attention and special treatment needed:

Non-applicable

SECTION 5: FIREFIGHTING MEASURES

5.1 Extinguishing media:

Suitable extinguishing media:

If possible use polyvalent powder fire extinguishers (ABC powder), alternatively use foam or carbon dioxide extinguishers (CO2).

Unsuitable extinguishing media:



ULTRALIGHT CARBON

Printing: 19/12/2022 Date of compilation: 26/02/2016 Revised: 13/01/2022 Ver

Version: 4 (Replaced 3)

SECTION 5: FIREFIGHTING MEASURES (continued)

IT IS RECOMMENDED NOT to use full jet water as an extinguishing agent.

5.2 Special hazards arising from the substance or mixture:

As a result of combustion or thermal decomposition reactive sub-products are created that can become highly toxic and, consequently, can present a serious health risk.

5.3 Advice for firefighters:

Depending on the magnitude of the fire it may be necessary to use full protective clothing and self-contained breathing apparatus (SCBA). Minimum emergency facilities and equipment should be available (fire blankets, portable first aid kit,...) in accordance with Directive 89/654/EC.

Additional provisions:

Act in accordance with the Internal Emergency Plan and the Information Sheets on actions to take after an accident or other emergencies. Eliminate all sources of ignition. In case of fire, cool the storage containers and tanks for products susceptible to combustion, explosion or BLEVE as a result of high temperatures. Avoid spillage of the products used to extinguish the fire into an aqueous medium.

SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1 Personal precautions, protective equipment and emergency procedures:

For non-emergency personnel:

Isolate leaks provided that there is no additional risk for the people performing this task. Evacuate the area and keep out those without protection. Personal protection equipment must be used against potential contact with the spilt product (See section 8). Above all prevent the formation of any vapour-air flammable mixtures, through either ventilation or the use of an inert medium. Remove any source of ignition. Eliminate electrostatic charges by interconnecting all the conductive surfaces on which static electricity could form, and also ensuring that all surfaces are connected to the ground.

For emergency responders:

Wear protective equipment. Keep unprotected persons away. See section 8.

6.2 Environmental precautions:

This product is not classified as hazardous to the environment. Keep product away from drains, surface and underground water.

6.3 Methods and material for containment and cleaning up:

It is recommended:

Absorb the spillage using sand or inert absorbent and move it to a safe place. Do not absorb in sawdust or other combustible absorbents. For any concern related to disposal consult section 13.

6.4 Reference to other sections:

See sections 8 and 13.

SECTION 7: HANDLING AND STORAGE

7.1 Precautions for safe handling:

A.- General precautions for safe use

Comply with the current legislation concerning the prevention of industrial risks. Keep containers hermetically sealed. Control spills and residues, destroying them with safe methods (section 6). Avoid leakages from the container. Maintain order and cleanliness where dangerous products are used.

B.- Technical recommendations for the prevention of fires and explosions

Transfer in well ventilated areas, preferably through localized extraction. Fully control sources of ignition (mobile phones, sparks,...) and ventilate during cleaning operations. Avoid the existence of dangerous atmospheres inside containers, applying inertization systems where possible. Transfer at a slow speed to avoid the creation of electrostatic charges. Against the possibility of electrostatic charges: ensure a perfect equipotential connection, always use groundings, do not wear work clothes made of acrylic fibres, preferably wearing cotton clothing and conductive footwear. Comply with the essential security requirements for equipment and systems defined in Directive 2014/34/EC (ATEX 100) and with the minimum requirements for protecting the security and health of workers under the selection criteria of Directive 1999/92/EC (ATEX 137). Consult section 10 for conditions and materials that should be avoided.

C.- Technical recommendations on general occupational hygiene



ULTRALIGHT CARBON

	: 19/12/2022 Date of compilation	1. 20/02/2010	Revised: 13/01/202	.2 VEI SIUI	n: 4 (Replaced	/			
ECT	TION 7: HANDLING AND STORAGI	E (continued)							
	PREGNANT WOMEN SHOULD NOT necessary safety conditions (emerged equipment, especially on the hand drink during the process, washing D Technical recommendations to pre	gency showers and ey s and face (See section hands afterwards with	rewash stations in clo on 8). Limit manual t n suitable cleaning p	ose proximity), us ransfers to small	sing personal	protection			
	It is recommended to have absorb			o the product (Se	e subsection	6.3)			
.2	Conditions for safe storage, includ			F (/			
	A Technical measures for storage								
	Minimum Temp.: 15 °C								
	Maximum Temp.: 25 °C								
	Maximum time: 12 Mon	ths							
	B General conditions for storage								
	Avoid sources of heat, radiation, si	tatic electricity and co	ntact with food. For	additional inform	nation see sub	osection 10.5			
.3	Specific end use(s):								
	Except for the instructions already spe product.	cified it is not necess	ary to provide any sp	oecial recomment	dation regardi	ing the uses of this			
		DCONAL DOOTEC							
EC	TION 8: EXPOSURE CONTROLS/PE	RSONAL PROTEC	TION						
1	Control parameters:								
	Substances whose occupational exposure limits have to be monitored in the workplace (European OEL, not country-specific legislation): There are no applicable occupational exposure limits for the substances contained in the product DNEL (Workers) :								
	There are no applicable occupational e	exposure limits for the	substances containe	ed in the product	:				
	5 ,	exposure limits for the				ng exposure			
	There are no applicable occupational e	exposure limits for the		ed in the product exposure Local		ong exposure			
	There are no applicable occupational e	exposure limits for the Oral	Short	exposure	Lo	Local			
	There are no applicable occupational e DNEL (Workers): Identification styrene CAS: 100-42-5	Oral Dermal	Short Systemic Non-applicable Non-applicable	exposure Local Non-applicable Non-applicable	Lo Systemic Non-applicable 406 mg/kg	Local e Non-applicable Non-applicable			
	There are no applicable occupational e DNEL (Workers): Identification styrene CAS: 100-42-5 EC: 202-851-5	Oral	Short Systemic Non-applicable	exposure Local Non-applicable	Lo Systemic Non-applicable	Local e Non-applicable			
	There are no applicable occupational e DNEL (Workers): Identification styrene CAS: 100-42-5	Oral Dermal	Short Systemic Non-applicable Non-applicable 289 mg/m ³	exposure Local Non-applicable Non-applicable 306 mg/m ³	Lo Systemic Non-applicable 406 mg/kg 85 mg/m ³	Local e Non-applicable Non-applicable Non-applicable			
	There are no applicable occupational e DNEL (Workers): Identification styrene CAS: 100-42-5 EC: 202-851-5 DNEL (General population):	Oral Dermal	Short Systemic Non-applicable Non-applicable 289 mg/m ³ Short	exposure Local Non-applicable Non-applicable 306 mg/m ³ exposure	Systemic Non-applicable 406 mg/kg 85 mg/m ³	Local e Non-applicable Non-applicable Non-applicable			
	There are no applicable occupational e DNEL (Workers): Identification styrene CAS: 100-42-5 EC: 202-851-5 DNEL (General population): Identification	Oral Dermal Inhalation	Short Systemic Non-applicable Non-applicable 289 mg/m ³ Short Systemic	exposure Local Non-applicable Non-applicable 306 mg/m ³ exposure Local	Lo Systemic Non-applicable 406 mg/kg 85 mg/m³ Lo Systemic	Local Non-applicable Non-applicable Non-applicable			
	There are no applicable occupational e DNEL (Workers): Identification styrene CAS: 100-42-5 EC: 202-851-5 DNEL (General population): Identification styrene	Oral Dermal Inhalation Oral	Short Systemic Non-applicable 289 mg/m ³ Short Systemic Non-applicable	exposure Local Non-applicable Non-applicable 306 mg/m ³ exposure Local Non-applicable	Lo Systemic Non-applicable 406 mg/kg 85 mg/m ³ Lo Systemic 2,1 mg/kg	Local Local Non-applicable Non-applicable Non-applicable Local Non-applicable Non-applicable			
	There are no applicable occupational e DNEL (Workers): Identification styrene CAS: 100-42-5 EC: 202-851-5 DNEL (General population): Identification	Oral Dermal Inhalation	Short Systemic Non-applicable Non-applicable 289 mg/m ³ Short Systemic	exposure Local Non-applicable Non-applicable 306 mg/m ³ exposure Local	Lo Systemic Non-applicable 406 mg/kg 85 mg/m³ Lo Systemic	Local Non-applicable Non-applicable Non-applicable			
	There are no applicable occupational e DNEL (Workers): Identification styrene CAS: 100-42-5 EC: 202-851-5 DNEL (General population): Identification styrene CAS: 100-42-5	Oral Dermal Inhalation Oral Dermal	Short Systemic Non-applicable Non-applicable 289 mg/m ³ Short Systemic Non-applicable Non-applicable Non-applicable	exposure Local Non-applicable Non-applicable 306 mg/m ³ exposure Local Non-applicable Non-applicable	Lo Systemic Non-applicable 406 mg/kg 85 mg/m ³ 85 mg/m ³ Lo Systemic 2,1 mg/kg 343 mg/kg	Local Local Non-applicable Non-applicable Non-applicable Local Non-applicable Non-applicable Non-applicable Non-applicable Non-applicable			
	There are no applicable occupational e DNEL (Workers): Identification styrene CAS: 100-42-5 EC: 202-851-5 DNEL (General population): Identification styrene CAS: 100-42-5 EC: 202-851-5	Oral Dermal Inhalation Oral Dermal	Short Systemic Non-applicable Non-applicable 289 mg/m ³ Short Systemic Non-applicable Non-applicable Non-applicable	exposure Local Non-applicable Non-applicable 306 mg/m ³ exposure Local Non-applicable Non-applicable	Lo Systemic Non-applicable 406 mg/kg 85 mg/m ³ 85 mg/m ³ Lo Systemic 2,1 mg/kg 343 mg/kg	Local Local Non-applicable Non-applicable Non-applicable Local Non-applicable Non-applicable Non-applicable Non-applicable			
	There are no applicable occupational e DNEL (Workers): Identification styrene CAS: 100-42-5 EC: 202-851-5 DNEL (General population): Identification styrene CAS: 100-42-5 EC: 202-851-5 PNEC:	Oral Dermal Inhalation Oral Dermal	Short Systemic Non-applicable Non-applicable 289 mg/m ³ Short Systemic Non-applicable Non-applicable Non-applicable	exposure Local Non-applicable Non-applicable 306 mg/m ³ exposure Local Non-applicable Non-applicable	Lo Systemic Non-applicable 406 mg/kg 85 mg/m ³ 85 mg/m ³ Lo Systemic 2,1 mg/kg 343 mg/kg	Local Local Non-applicable Non-applicable Non-applicable Local Non-applicable Non-applicable Non-applicable Non-applicable			
	There are no applicable occupational e DNEL (Workers): Identification styrene CAS: 100-42-5 EC: 202-851-5 DNEL (General population): Identification styrene CAS: 100-42-5 EC: 202-851-5 PNEC: Identification	Oral Dermal Inhalation Oral Dermal Inhalation	Short Systemic Non-applicable Non-applicable 289 mg/m³ Short Systemic Non-applicable Non-applicable Non-applicable 174,25 mg/m³ 5 mg/L 0,2 mg/kg	exposure Local Non-applicable Non-applicable 306 mg/m ³ exposure Local Non-applicable Non-applicable 182,75 mg/m ³ Fresh water Fresh water Marine water	Lo Systemic Non-applicable 406 mg/kg 85 mg/m ³ 85 mg/m ³ Lo Systemic 2,1 mg/kg 343 mg/kg 10,2 mg/m ³	Local Local Non-applicable Non-applicable Non-applicable Local Non-applicable Non-applicable Non-applicable Non-applicable Non-applicable O,028 mg/L O,014 mg/L			
	There are no applicable occupational e DNEL (Workers): Identification styrene CAS: 100-42-5 EC: 202-851-5 DNEL (General population): Identification styrene CAS: 100-42-5 EC: 202-851-5 PNEC: Identification styrene	Oral Dermal Inhalation Oral Dermal Inhalation STP Soil Intermitten	Short Systemic Non-applicable Non-applicable 289 mg/m ³ Short Systemic Non-applicable Non-applicable Non-applicable Non-applicable Non-applicable Non-applicable 174,25 mg/m ³ Sing/L 0,2 mg/kg t 0,04 mg/L	exposure Local Non-applicable 306 mg/m ³ attribute Local Non-applicable Local Non-applicable Non-applicable 182,75 mg/m ³ tribute Fresh water Rest water Sediment (Fresh	 Lo Systemic Non-applicable 406 mg/kg 85 mg/m³ 85 mg/m³ Lo Systemic 2,1 mg/kg 343 mg/kg 10,2 mg/m³ 	Local Non-applicable Non-applicable Non-applicable Non-applicable Local Non-applicable Non-applicable Non-applicable Non-applicable 0,028 mg/L 0,014 mg/L 0,614 mg/kg			
	There are no applicable occupational e DNEL (Workers): Identification styrene CAS: 100-42-5 EC: 202-851-5 DNEL (General population): Identification styrene CAS: 100-42-5 EC: 202-851-5 PNEC: Identification styrene CAS: 100-42-5 EC: 202-851-5 EC: 202-851-5	Oral Dermal Inhalation Oral Dermal Inhalation STP Soil	Short Systemic Non-applicable Non-applicable 289 mg/m³ Short Systemic Non-applicable Non-applicable Non-applicable 174,25 mg/m³ 5 mg/L 0,2 mg/kg	exposure Local Non-applicable Non-applicable 306 mg/m ³ exposure Local Non-applicable Non-applicable 182,75 mg/m ³ Fresh water Fresh water Marine water	 Lo Systemic Non-applicable 406 mg/kg 85 mg/m³ 85 mg/m³ Lo Systemic 2,1 mg/kg 343 mg/kg 10,2 mg/m³ 	Local Local Non-applicable Non-applicable Non-applicable Local Non-applicable Non-applicable Non-applicable Non-applicable Non-applicable O,028 mg/L O,014 mg/L			
.2	There are no applicable occupational e DNEL (Workers): Identification styrene CAS: 100-42-5 EC: 202-851-5 DNEL (General population): Identification styrene CAS: 100-42-5 EC: 202-851-5 PNEC: Identification styrene CAS: 100-42-5 EC: 202-851-5	Oral Dermal Inhalation Oral Dermal Inhalation STP Soil Intermitten Oral	Short Systemic Non-applicable Non-applicable 289 mg/m³ Short Short Short Non-applicable Non-applicable Non-applicable Non-applicable 174,25 mg/m³ 5 mg/L 0,2 mg/kg t 0,04 mg/L Non-applicable	exposure Local Non-applicable 306 mg/m ³ attribute Local Non-applicable Local Non-applicable Non-applicable 182,75 mg/m ³	 Lo Systemic Non-applicable 406 mg/kg 85 mg/m³ 85 mg/m³ Lo Systemic 2,1 mg/kg 343 mg/kg 10,2 mg/m³ 	Local Non-applicable Non-applicable Non-applicable Non-applicable Local Non-applicable Non-applicable Non-applicable Non-applicable 0,028 mg/L 0,014 mg/L 0,614 mg/kg			



ULTRALIGHT CARBON

	Pictogram		PPE	Labelling		CEN Standard		Remarks
	Mandatory respiratory tract protection		sk for gases and (Filter type: A)		EN	405:2002+A1:2010	C	place when there is a taste or smell of the ontaminant inside the face mask. If the contaminant comes with warnings it is commended to use isolation equipment.
C	Specific protection for the hands		Labolling					
	Pictogram		PPE	Labelling		CEN Standard		Remarks
	Mandatory hand protection	protective Nitrile, Bre	oosable chemical gloves (Material: akthrough time: > hickness: 0.4 mm)		EN 16	374-1:2016+A1:2018 523-1:2015+A1:2018 I ISO 21420:2020	manufa the p	he Breakthrough Time indicated by the acturer must exceed the period during wh roduct is being used. Do not use protectiv ns after the product has come into conta- with skin.
							rial car	n not be calculated in advance with
_	total reliability an		refore to be che	cked prior to t	he appl	ication.		
D	Eye and face prot	ection	205					
	Pictogram		PPE	Labelling		CEN Standard		Remarks
	Mandatory face protection		c glasses against n/projections.		E	EN 166:2002 N ISO 4007:2018		daily and disinfect periodically according anufacturer´s instructions. Use if there is risk of splashing.
E	Body protection						-	
	Pictogram		PPE	Labelling		CEN Standard	Remarks	
	Mandatory complete body protection	protection risks, wi	ble clothing for against chemical th antistatic and pof properties		E	EN 1149-1,2,3 3034:2005+A1:2009 EN ISO 13982- 1:2004/A1:2010 N ISO 6529:2013 N ISO 6530:2005 I ISO 13688:2013 EN 464:1994		r professional use only. Clean periodically ording to the manufacturer's instructions
	Mandatory foot protection	Safety footwear for protection against chemical risk, with antistatic and heat resistant properties		mical d heat		EN ISO 13287:2020 EN ISO 20345:2011 EN 13832-1:2019		place boots at any sign of deterioration.
	Additional emerge	ency mea	sures					
F	Emergency measure		St	andards		Emergency measu	ire	Standards
F	Emergency mea	Emergency shower		ANSI Z358-1 ISO 3864-1:2011, ISO 3864-4:2011		•	DIN 12 899 ISO 3864-1:2011, ISO 3864-	
F	+	ower)11	Evewash station	s	
	Emergency mer		ISO 3864-1:20)11	Eyewash station:	S	

V.O.C. (Supply):	25,44 % weight
V.O.C. density at 20 °C:	40 kg/m ³ (40 g/L)
Average carbon number:	8
Average molecular weight:	104,2 g/mol

- CONTINUED ON NEXT PAGE -



ULTRALIGHT CARBON

Printing:	19/12/2022	Date of compilation: 26/02/2016	Revised: 13/01/2022	Version: 4 (Replaced 3)
SECT	TION 9: PHYSIC	AL AND CHEMICAL PROPERTIES	5	
9.1	Information or	n basic physical and chemical pro	perties:	
		ormation see the product datasheet.		
	Appearance:			
	Physical state at	20 °C:	Liquid	
	Appearance:		Viscous	
	Colour:		Grey	
	Odour:		Characteristic	
	Odour threshold:		Non-applicable *	
	Volatility:			
	Boiling point at a	tmospheric pressure:	118 °C	
	Vapour pressure	at 20 °C:	2099 Pa	
	Vapour pressure	at 50 °C:	11062,86 Pa (11,06 kPa)	
	Evaporation rate	at 20 °C:	Non-applicable *	
	Product descri	ption:		
	Density at 20 °C	:	970 - 1030 kg/m³	
	Relative density	at 20 ºC:	Non-applicable *	
	Dynamic viscosit	y at 20 °C:	Non-applicable *	
	Kinematic viscos	ity at 20 ºC:	Non-applicable *	
	Kinematic viscos	ity at 40 °C:	>20,5 mm²/s	
	Concentration:		Non-applicable *	
	pH:		Non-applicable *	
	Vapour density a	at 20 ºC:	Non-applicable *	
	Partition coefficie	ent n-octanol/water 20 °C:	Non-applicable *	
	Solubility in wate	er at 20 °C:	Non-applicable *	
	Solubility proper	ties:	Non-applicable *	
	Decomposition to	emperature:	Non-applicable *	
	Melting point/fre	ezing point:	Non-applicable *	
	Flammability:			
	Flash Point:		37 °C	
	Flammability (so	lid, gas):	Non-applicable *	
	Autoignition tem		490 °C	
	Lower flammabil	ity limit:	Not available	
	Upper flammabil	•	Not available	
	Particle charac			
	Median equivaler		Non-applicable	
9.2	Other informat			
		ith regard to physical hazard clas		
	Explosive proper		Non-applicable *	
	Oxidising proper		Non-applicable *	
	Corrosive to met		Non-applicable *	
	Heat of combust		Non-applicable *	
	Aerosols-total pe components: Other safety cl	ercentage (by mass) of flammable	Non-applicable *	
	Surface tension a		Non-applicable *	
		b the nature of the product, not providing infor		
		, the nature of the product, not providing Infor	mation property of its nazarus.	

- CONTINUED ON NEXT PAGE -



ULTRALIGHT CARBON

Printing: 19/12/2022 Date of compilation: 26/02/2016 Revised: 13/01/2022 Version: 4 (Replaced 3) SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES (continued) Refraction index: Non-applicable * *Not relevant due to the nature of the product, not providing information property of its hazards. SECTION 10: STABILITY AND REACTIVITY 10.1 Reactivity: No hazardous reactions are expected because the product is stable under recommended storage conditions. See section 7. 10.2 Chemical stability: Chemically stable under the indicated conditions of storage, handling and use. 10.3 Possibility of hazardous reactions: Under the specified conditions, hazardous reactions that lead to excessive temperatures or pressure are not expected. 10.4 Conditions to avoid: Applicable for handling and storage at room temperature: Humidity Shock and friction Contact with air Increase in temperature Sunlight Not applicable Not applicable Risk of combustion Not applicable Avoid direct impact 10.5 Incompatible materials: Acids Water Oxidising materials Combustible materials Others Avoid strong acids Not applicable Avoid direct impact Not applicable Avoid alkalis or strong bases 10.6 Hazardous decomposition products: Contains susbstances highly reactive and can auto-polymerize as a result of internal peroxide accumulation. The peroxides formed in these reactions are extremely shock- and heat-sensitive. SECTION 11: TOXICOLOGICAL INFORMATION ** 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008: The experimental information related to the toxicological properties of the product itself is not available

Dangerous health implications:

In case of exposure that is repetitive, prolonged or at concentrations higher than the recommended occupational exposure limits, adverse effects on health may result, depending on the means of exposure: A- Ingestion (acute effect):

- Acute toxicity : Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for consumption. For more information see section 3

- Corrosivity/Irritability: The consumption of a considerable dose can cause irritation in the throat, abdominal pain, nausea and vomiting.

- B- Inhalation (acute effect):
 - Acute toxicity : Based on available data, the classification criteria are not met. However, it contains substances classified as hazardous for inhalation. For more information see section 3.
 - Corrosivity/Irritability: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.
- C- Contact with the skin and the eyes (acute effect):
 - Contact with the skin: Produces skin inflammation.
 - Contact with the eyes: Produces eye damage after contact.
- D- CMR effects (carcinogenicity, mutagenicity and toxicity to reproduction):
 - Carcinogenicity: Based on available data, the classification criteria are not met. However, it contains substances classified as dangerous with carcinogenic effects. For more information see section 3.
 - IARC: styrene (2A); Talc (3); Titanium dioxide (aerodynamic diameter \leq 10 µm) (2B)

- Mutagenicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.

Reproductive toxicity: Suspected of damaging the unborn child.

** Changes with regards to the previous version

- CONTINUED ON NEXT PAGE -



ULTRALIGHT CARBON

Printing:	19/12/2022	Date of compilat	ion: 26/02/2016	Revised: 13/01	/2022	Vers	sion: 4 (Replaced 3)				
SECT	TON 11: TOXICO	DLOGICAL INFC	RMATION ** (con	tinued)							
	E- Sensitizing eff	ects:									
	 Respiratory hazardous witi Skin: Based hazardous for F- Specific target Based on avail this effect. For G- Specific target Specific target Specific target Specific target Skin: Based hazardous for H- Aspiration haz Based on avail 	Based on available h sensitising effect d on available data this effect. For mo organ toxicity (ST able data, the class more information organ toxicity (ST get organ toxicity h, serious function d on available data this effect. For mo ard: able data, the class more information	s. For more information , the classification crit ore information see see (OT) - single exposure satification criteria are a see section 3. (OT)-repeated exposu (STOT)-repeated exposu (STOT)-repeated exposu (STOT)-repeated exposu (STOT)-repeated exposu al disorders or morph , the classification crit ore information see see satification criteria are a	on see section 3. eria are not met, ction 3. e: not met, as it doe re: osure: Serious hea ological changes o eria are not met, ction 3.	as it does no s not contair alth effects ir of toxicologic as it does no	n subst n the ca cal imp ot conta	ot contain substances ain substances classifie cances classified as haz ase of prolonged consu ortance. ain substances classifie cances classified as haz	ed as zardous for umption, ed as			
	to mixtures in pov aerodynamic diam	Other information: CAS 13463-67-7 Titanium dioxide (aerodynamic diameter $\leq 10 \ \mu$ m): The classification as a carcinogen by inhalation applies only to mixtures in powder form containing 1 % or more of titanium dioxide which is in the form of or incorporated in particles with aerodynamic diameter $\leq 10 \ \mu$ m Specific toxicology information on the substances:									
		Iden	tification			Acute	e toxicity	Genus			
	styrene				LD50 oral		>2000 mg/kg				
	CAS: 100-42-5				LD50 dermal		>2000 mg/kg				
	EC: 202-851-5		10		LC50 inhalation		12 mg/L (4 h)	Rat			
	Titanium dioxide (aer CAS: 13463-67-7	rodynamic diameter ≤	10 µm)		LD50 oral LD50 dermal		10000 mg/kg 10000 mg/kg	Rat Rabbit			
	EC: 236-675-5				LC50 inhalation		>5 mg/L	Kabbit			
	Į	stimate (ATE mi	ix):								
			ATE mix				Ingredient(s) of unknown	toxicity			
	Oral		>2000 mg/kg (Calculation	n method)		Non-app	plicable				
	Dermal		>2000 mg/kg (Calculation	n method)		Non-app	plicable				
	Inhalation		47,17 mg/L (4 h) (Calcula	ation method)		0 %					
	Information on Endocrine disru Endocrine-disrupti Other information Non-applicable ages with regards to	pting properties ing properties: The on	e product fails to mee	t the criteria.							
Chang											
	TON 12: ECOLO										
	•	ation related to the	e eco-toxicological pro	perties of the pro	duct itself is	not av	railable				
12.1	Toxicity:										
	Not available										
12.2	Persistence and	degradability:									
	Not available										
12.3	Bioaccumulative	e potential:									

Not available

12.4 Mobility in soil:



ULTRALIGHT CARBON

		Identification	Absorp	tion/desorption		Volatility							
st	tyrene		Кос	Non-applicable	Henry	Non-applicable	e						
C/	CAS: 100-42-5		Conclusion	Non-applicable	Dry soil	Non-applicable	e						
EC	C: 202-851-5		Surface tension	3,21E-2 N/m (25 °C)	Moist soil	Non-applicable	Non-applicable						
5 R	Results of PBT and vPvB assessment:												
Pr	Product fails to meet PBT/vPvB criteria												
6 Er	ndocrine di	srupting properties:											
Fr	ndocrine-disi	upting properties: The product fail	s to meet the cri	Endocrine-disrupting properties: The product fails to meet the criteria.									
7 01	ther advers												
7 01													
7 O	ther advers												
7 Ot	ot described	se effects:											
7 Ot	ot described												
7 Ot No	other adversion of the secribed	POSAL CONSIDERATIONS											
7 Ot No	other adversion of the secribed	se effects:											
7 Ot No	other adversion of the secribed	POSAL CONSIDERATIONS	Description			Waste class (Regulation (1357/2014)	EU) I						
7 Ot No	ON 13: DIS Vaste treatu 08 01 11*	Se effects: POSAL CONSIDERATIONS nent methods: waste paint and varnish containing organ	Description ic solvents or other	nazardous substances		1357/2014)	EU) I						
7 Ot No	ot described	se effects: POSAL CONSIDERATIONS nent methods:	Description ic solvents or other	nazardous substances			EU)						
7 Ori No CTIO 1 W	other adversion described on 13: DIS Vaste treats Code 08 01 11* 15 01 10*	Se effects: POSAL CONSIDERATIONS ment methods: waste paint and varnish containing orgar packaging containing residues of or cont	Description ic solvents or other aminated by hazardo	nazardous substances		1357/2014)	EU)						
7 Ot No 1 W	ON 13: DIS Vaste treatu 08 01 11* 15 01 10*	Se effects: POSAL CONSIDERATIONS nent methods: waste paint and varnish containing orgar packaging containing residues of or cont ce (Regulation (EU) No 1357/2	Description bic solvents or other aminated by hazardo	nazardous substances us substances		1357/2014) ` Dangerous	. ,						
7 01 No 2TIO 1 W Ty HF	other adversion described on 13: DIS Vaste treats Code 08 01 11* 15 01 10* 09 00 wasi P3 Flammab	Se effects: POSAL CONSIDERATIONS ment methods: waste paint and varnish containing orgar packaging containing residues of or cont	Description bic solvents or other aminated by hazardo	nazardous substances us substances	ute Toxicity, I	1357/2014) ` Dangerous							

the product, it will be processed the same way as the actual product. Otherwise, it will be processed as non-dangerous residue. Waste should not be disposed of to drains. See paragraph 6.2.

Regulations related to waste management:

In accordance with Annex II of Regulation (EC) No 1907/2006 (REACH) the community or state provisions related to waste management are stated

Community legislation: Directive 2008/98/EC, 2014/955/EU, Regulation (EU) No 1357/2014

SECTION 14: TRANSPORT INFORMATION

Transport of dangerous goods by land:

With regard to ADR 2021 and RID 2021:

	14.1	UN number or ID number:	UN3269
	14.2	UN proper shipping name:	POLYESTER RESIN KIT, liquid base material
	14.3	Transport hazard class(es):	3
$\langle \simeq \rangle$		Labels:	3
	14.4	Packing group:	III
3	14.5	Environmental hazards:	No
·	14.6	Special precautions for user	
		Special regulations:	236, 340
		Tunnel restriction code:	E
		Physico-Chemical properties:	see section 9
		Limited quantities:	5 L
	14.7	Maritime transport in bulk according to IMO instruments:	Non-applicable
Transport of da	angero	us goods by sea:	
With regard to II	MDG 40	-20:	



ULTRALIGHT CARBON

Printing: 19/12/2022	Date o	of compilation: 26/02/2016	Revised: 13/01/2022	Version: 4 (Replaced 3)
SECTION 14: TRANSP	ORT	INFORMATION (continued)		
	14.2	UN number or ID number: UN proper shipping name: Transport hazard class(es): Labels:	UN3269 POLYESTER RESIN KIT, liqu 3 3	uid base material
3	14.4 14.5 14.6	· · · · · · · · · · · · · · · · · · ·	III No	
	14.0	Special regulations: EmS Codes: Physico-Chemical properties: Limited quantities:	340, 236 F-E, S-D see section 9 5 L	
	14.7	Segregation group: Maritime transport in bulk according to IMO instruments:	Non-applicable Non-applicable	
Transport of da	ngero	us goods by air:		
With regard to IA	TA/ICA	NO 2022:		
3	14.2 14.3 14.4	UN number or ID number: UN proper shipping name: Transport hazard class(es): Labels: Packing group: Environmental hazards:	UN3269 POLYESTER RESIN KIT, liqu 3 3 III No	id base material
	14.6	Special precautions for user		
	14.7	Physico-Chemical properties: Maritime transport in bulk according to IMO instruments:	see section 9 Non-applicable	

SECTION 15: REGULATORY INFORMATION

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture:

Candidate substances for authorisation under the Regulation (EC) No 1907/2006 (REACH): Non-applicable

Substances included in Annex XIV of REACH ("Authorisation List") and sunset date: Non-applicable

Regulation (EC) No 1005/2009, about substances that deplete the ozone layer: Non-applicable

Article 95, REGULATION (EU) No 528/2012: Non-applicable

REGULATION (EU) No 649/2012, in relation to the import and export of hazardous chemical products: Non-applicable

Seveso III:

Se	ection	Description	Lower-tier requirements	Upper-tier requirements
	P5c	FLAMMABLE LIQUIDS	5000	50000

Limitations to commercialisation and the use of certain dangerous substances and mixtures (Annex XVII REACH, etc):

Shall not be used in:

—ornamental articles intended to produce light or colour effects by means of different phases, for example in ornamental lamps and ashtrays,

-tricks and jokes,

-games for one or more participants, or any article intended to be used as such, even with ornamental aspects.

Occupational exposure to respirable crystalline silica must be controlled pursuant to Directive (EU) 2019/130.

Specific provisions in terms of protecting people or the environment:

It is recommended to use the information included in this safety data sheet as a basis for conducting workplace-specific risk assessments in order to establish the necessary risk prevention measures for the handling, use, storage and disposal of this product.



ULTRALIGHT CARBON

	TION 15: REGULATORY INFORMATION (continued)						
	Other legislation:						
	The product could be affected by sectorial legislation						
5.2	Chemical safety assessment:						
	The supplier has not carried out evaluation of chemical safety.						
ECT	TION 16: OTHER INFORMATION						
	Legislation related to safety data sheets:						
	Legislation related to safety data sheets: The SDS shall be supplied in an official language of the country where the product is placed on the market. This safety data sheet has been designed in accordance with ANNEX II-Guide to the compilation of safety data sheets of Regulation (EC) No 1907/2006 (COMMISSION REGULATION (EU) 2020/878).						
	Modifications related to the previous Safety Data Sheet which concerns the ways of managing risks.:						
	COMMISSION REGULATION (EU) 2020/878						
	COMPOSITION/INFORMATION ON INGREDIENTS (SECTION 3, SECTION 11): · New declared substances						
	Titanium dioxide (aerodynamic diameter $\leq 10 \ \mu$ m) (13463-67-7)						
	Texts of the legislative phrases mentioned in section 2:						
	H315: Causes skin irritation.						
	H372: Causes damage to organs through prolonged or repeated exposure.						
	H361d: Suspected of damaging the unborn child.						
	H226: Flammable liquid and vapour. H319: Causes serious eye irritation.						
	Texts of the legislative phrases mentioned in section 3:						
	The phrases indicated do not refer to the product itself; they are present merely for informative purposes and refer to the individual components which appear in section 3						
	CLP Regulation (EC) No 1272/2008:						
	Acute Tox. 4: H332 - Harmful if inhaled.						
	Carc. 2: H351 - Suspected of causing cancer (Inhalation). Eye Irrit. 2: H319 - Causes serious eye irritation.						
	Flam. Liq. 3: H226 - Flammable liquid and vapour.						
	Repr. 2: H361d - Suspected of damaging the unborn child.						
	Skin Irrit. 2: H315 - Causes skin irritation.						
	STOT RE 1: H372 - Causes damage to organs through prolonged or repeated exposure.						
	Classification procedure: Skin Irrit, 2: Calculation method						
	STOT RE 1: Calculation method						
	Repr. 2: Calculation method						
	Flam. Liq. 3: Calculation method (2.6.4.3)						
	Eye Irrit. 2: Calculation method						
	Advice related to training: Training is recommended in order to prevent industrial risks for staff using this product and to facilitate their comprehension ar						
	interpretation of this safety data sheet, as well as the label on the product.						
	Principal bibliographical sources: http://echa.europa.eu						
	http://eur-lex.europa.eu						
	Abbreviations and acronyms:						



ULTRALIGHT CARBON

Printing: 19/12/2022	Date of compilation: 26/02/2016	Revised: 13/01/2022	Version: 4 (Replaced 3)	
SECTION 16: OTHER INFORMATION (continued)				
ADR: European agreement concerning the international carriage of dangerous goods by road IMDG: International maritime dangerous goods code IATA: International Air Transport Association ICAO: International Civil Aviation Organisation COD: Chemical Oxygen Demand BOD5: 5day biochemical oxygen demand BCF: Bioconcentration factor LD50: Lethal Dose 50 LC50: Lethal Concentration 50 EC50: Effective concentration 50 EC50: Effective concentration 50 LogPOW: Octanolwater partition coefficient Koc: Partition coefficient of organic carbon UFI: unique formula identifier IARC: International Agency for Research on Cancer				

The information contained in this safety data sheet is based on sources, technical knowledge and current legislation at European and state level, without being able to guarantee its accuracy. This information cannot be considered a guarantee of the properties of the product, it is simply a description of the security requirements. The occupational methodology and conditions for users of this product are not within our awareness or control, and it is ultimately the responsibility of the user to take the necessary measures to obtain the legal requirements concerning the manipulation, storage, use and disposal of chemical products. The information on this safety data sheet only refers to this product, which should not be used for needs other than those specified.