ER

This SDS is an English translation of COMMISSION REGULATION (EU) 2020/878, without any country-specific legislation

V2012 4:1

ECT	TION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING
.1	Product identifier: V2012 4:1
	Other means of identification:
2	UFI: 7K0N-90PX-Q005-251W
.2	Relevant identified uses of the substance or mixture and uses advised against:
	Relevant uses: Car repair; base for coatings. For professional users only.
2	Uses advised against: All uses not specified in this section or in section 7.3
.3	Details of the supplier of the safety data sheet:
	Troton Sp. z o.o. Ząbrowo 14A 78-120 Gościno - Zachodniopomorskie - Polska Phone: +48 94 35 123 94 - Fax: +48 94 35 126 22 troton@troton.com.pl www.troton.pl / www.troton.eu
.4	Emergency telephone number: (8am-4pm)+48 094 35 123 94; 112
FCT	TION 2: HAZARDS IDENTIFICATION
.1	Classification of the substance or mixture:
-	CLP Regulation (EC) No 1272/2008:
	Classification of this product has been carried out in accordance with CLP Regulation (EC) No 1272/2008.
	Aquatic Chronic 3: Hazardous to the aquatic environment, long-term hazard, Category 3, H412
	Asp. Tox. 1: Aspiration hazard, Category 1, H304 Eye Irrit. 2: Eye irritation, Category 2, H319 Flam. Liq. 3: Flammable liquids, Category 3, H226 Skin Irrit. 2: Skin irritation, Category 2, H315 STOT RE 2: Specific target organ toxicity — Repeated exposure, Hazard Category 2 (Oral), H373
.2	Label elements:
	CLP Regulation (EC) No 1272/2008:
	Danger
	Hazard statements:
	Aquatic Chronic 3: H412 - Harmful to aquatic life with long lasting effects. Asp. Tox. 1: H304 - May be fatal if swallowed and enters airways. Eye Irrit. 2: H319 - Causes serious eye irritation. Flam. Liq. 3: H226 - Flammable liquid and vapour. Skin Irrit. 2: H315 - Causes skin irritation.
	STOT RE 2: H373 - May cause damage to organs through prolonged or repeated exposure (Oral).
	Precautionary statements:
	 P210: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P280: Wear protective gloves/protective clothing/respiratory protection/eye protection/protective footwear. P301+P310: IF SWALLOWED: Immediately call a POISON CENTER/doctor. P302+P352: IF ON SKIN: Wash with plenty of water. P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy do. Continue rinsing. P403+P235: Store in a well-ventilated place. Keep cool. P501: Dispose of contents/container in accordance with regulations on hazardous waste or packaging and packaging waste respectively.
	Supplementary information:
	EUH211: Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.
	Substances that contribute to the classification
	Xylene



СТ	TON 2	: HAZARDS IDE	ENTIFICATION (cor	ntinued)				
;	Other	hazards:						
		t fails to meet PE	T/vPvB critoria					
			operties: The product	fails to meet t	he criteria.			
СТ	ION 3	: COMPOSITIO	N/INFORMATION (ON INGREDI	ENTS			
	Subst	ance:						
		pplicable						
	Mixtu							
	Chem	ical description	: Mixture composed c	of chemical pro	oducts			
	Comp	onents:						
	In acc	ordance with Ann	ex II of Regulation (EC	C) No 1907/20	06 (point 3), the prod	uct contains:		
		Identification			Chemical name/Classificati	on		Concentrati
	CAS: EC:	1330-20-7	Xylene ⁽¹⁾				Self-classified	
	Index:	215-535-7 601-022-00-9 01-2119488216-32- XXXX	Regulation 1272/2008			12; Asp. Tox. 1: H304; Eye Irrit. STOT RE 2: H373; STOT SE 3:	>>>>>>>>>>>>>>>>>>>>>>>>>>>>>>>>>>>	10 - <25 9
	CAS: EC:	123-86-4 204-658-1	N-butyl acetate ⁽¹⁾				ATP CLP00	
	Index:	607-025-00-1 01-2119485493-29- XXXX	Regulation 1272/2008	Flam. Liq. 3: H226;	STOT SE 3: H336; EUH066 -	Warning	(Ì) 🏟	5 - <10 %
	CAS:	13463-67-7	Titanium dioxide (aero	odynamic diam	eter ≤ 10 µm) ⁽¹⁾		ATP ATP14	
		236-675-5 022-006-00-2 01-2119489379-17- XXXX	Regulation 1272/2008	Carc. 2: H351 - Wa	rning		٨	5 - <10 %
	CAS:	108-65-6	2-methoxy-1-methyle	ethyl acetate ⁽²⁾			ATP ATP01	
		203-603-9 607-195-00-7 01-2119475791-29- XXXX	Regulation 1272/2008	Flam. Liq. 3: H226 -	· Warning			5 - <10 %
	CAS:	7779-90-0	trizinc bis(orthophosp	hate) ⁽¹⁾			ATP CLP00	
		231-944-3 Non-applicable 01-2119485044-40- XXXX	Regulation 1272/2008	Aquatic Acute 1: H4	00; Aquatic Chronic 1: H410	Warning		1 - <2,5 %
	CAS:	100-41-4	Ethylbenzene ⁽²⁾				ATP ATP06	
		202-849-4 601-023-00-4 01-2119489370-35- XXXX	D 11: 1070/0000	Acute Tox. 4: H332; Danger	Asp. Tox. 1: H304; Flam. Liq	2: H225; STOT RE 2: H373 -	>>>>>>>>>>>>>>>>>>>>>>>>>>>>>>>>>>>	<1 %
	CAS:	141-32-2	n-butyl acrylate ⁽²⁾				Self-classified	
		205-480-7 607-062-00-3 01-2119453155-43- XXXX			Aquatic Chronic 3: H412; Eye Skin Sens. 1B: H317; STOT SI	e Irrit. 2: H319; Flam. Liq. 3: H22 3: H335 - Warning	26; (1) 🚯	<1 %
	CAS:	80-62-6	Methyl methacrylate ⁽²	2)			ATP CLP00	
		201-297-1 607-035-00-6 01-2119452498-28- XXXX	Regulation 1272/2008	Flam. Liq. 2: H225;	Skin Irrit. 2: H315; Skin Sens	1: H317; STOT SE 3: H335 - Da	anger 🔃 🔕	<1 %
	CAS: EC:	111-76-2 203-905-0	2-butoxyethanol ⁽²⁾				ATP ATP15	
	Index:	603-014-00-0 01-2119475108-36- XXXX	Regulation 1272/2008	Acute Tox. 4: H302	+H332; Eye Irrit. 2: H319; Sk	n Irrit. 2: H315 - Warning		<1 %
	CAS:	108-88-3	Toluene ⁽²⁾				Self-classified	
		203-625-9 601-021-00-3 01-2119471310-51- XXXX			H412; Asp. Tox. 1: H304; Flan STOT RE 2: H373; STOT SE 3	n. Liq. 2: H225; Repr. 2: H361d; : H336 - Danger	(!) (ð) (\$	<1 %

To obtain more information on the hazards of the substances consult sections 11, 12 and 16.



V2012 4:1

inting:	03/01/2023	Date of compilation: 26/06/2011	Revised: 15/09/2022	Version: 6 (Replaced 5)
SECT	TON 4: FIRST	AID MEASURES		
4.1	Description o	f first aid measures:		
		resulting from intoxication can appear af e to the chemical product or persistent dis		
		rson affected from the area of exposure,		ntoxication symptoms it is recommended to rest. Request medical attention if symptoms
	and neutral soa	ap. In serious cases see a doctor. If the p he injury caused if it is stuck to the skin.	roduct causes burns or freezi	ed if appropriate with plenty of cold water ing, clothing should not be removed as this hese should never be burst as this will
	By eye conta	ct:		
	unless they are		I could cause further damage	contact lenses, these should be removed e. In all cases, after cleaning, a doctor should
	By ingestion/	aspiration:		
4.2	the head down doctor. Rinse o		f consciousness do not admir ve been affected during inge	duce vomiting, but if it does happen keep nister anything orally unless supervised by a stion. Keep the person affected at rest.
4.2	•	•••	-	
		yed effects are indicated in sections 2 and		
4.3	Indication of	any immediate medical attention an	id special treatment need	ed:
	Non-applicable			
SECT	TON 5: FIREF	IGHTING MEASURES		
5.1	Extinguishing	media:		
	Suitable extin	iguishing media:		
	If possible use	polyvalent powder fire extinguishers (ABC	powder), alternatively use f	oam or carbon dioxide extinguishers (CO2).
		tinguishing media:		
		ENDED NOT to use full jet water as an ex	tinguishing agent.	
5.2		ds arising from the substance or mix		
	As a result of co	ombustion or thermal decomposition reac an present a serious health risk.		d that can become highly toxic and,
5.3	Advice for fire			
		um emergency facilities and equipment sl 9/654/EC.		thing and self-contained breathing apparatus ets, portable first aid kit,) in accordance

Additional provisions:

Act in accordance with the Internal Emergency Plan and the Information Sheets on actions to take after an accident or other emergencies. Eliminate all sources of ignition. In case of fire, cool the storage containers and tanks for products susceptible to combustion, explosion or BLEVE as a result of high temperatures. Avoid spillage of the products used to extinguish the fire into an aqueous medium.

SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1 Personal precautions, protective equipment and emergency procedures:

For non-emergency personnel:



V2012 4:1

Printing: 03/01/2023 Date of compilation: 26/06/2011 Revised: 15/09/2022 Version: 6 (Replaced 5) SECTION 6: ACCIDENTAL RELEASE MEASURES (continued) Isolate leaks provided that there is no additional risk for the people performing this task. Evacuate the area and keep out those without protection. Personal protection equipment must be used against potential contact with the spilt product (See section 8). Above all prevent the formation of any vapour-air flammable mixtures, through either ventilation or the use of an inert medium. Remove any source of ignition. Eliminate electrostatic charges by interconnecting all the conductive surfaces on which static electricity could form, and also ensuring that all surfaces are connected to the ground. For emergency responders: Wear protective equipment. Keep unprotected persons away. See section 8. 6.2 **Environmental precautions:** Avoid at all cost any type of spillage into an aqueous medium. Contain the product absorbed appropriately in hermetically sealed containers. Notify the relevant authority in case of exposure to the general public or the environment. 6.3 Methods and material for containment and cleaning up: It is recommended: Absorb the spillage using sand or inert absorbent and move it to a safe place. Do not absorb in sawdust or other combustible absorbents. For any concern related to disposal consult section 13. Reference to other sections: 6.4 See sections 8 and 13. SECTION 7: HANDLING AND STORAGE Precautions for safe handling: 7.1 A.- General precautions for safe use Comply with the current legislation concerning the prevention of industrial risks. Keep containers hermetically sealed. Control spills and residues, destroying them with safe methods (section 6). Avoid leakages from the container. Maintain order and cleanliness where dangerous products are used. B.- Technical recommendations for the prevention of fires and explosions Transfer in well ventilated areas, preferably through localized extraction. Fully control sources of ignition (mobile phones, sparks,...) and ventilate during cleaning operations. Avoid the existence of dangerous atmospheres inside containers, applying inertization systems where possible. Transfer at a slow speed to avoid the creation of electrostatic charges. Against the possibility of electrostatic charges: ensure a perfect equipotential connection, always use groundings, do not wear work clothes made of acrylic fibres, preferably wearing cotton clothing and conductive footwear. Comply with the essential security requirements for equipment and systems defined in Directive 2014/34/EC (ATEX 100) and with the minimum requirements for protecting the security and health of workers under the selection criteria of Directive 1999/92/EC (ATEX 137). Consult section 10 for conditions and materials that should be avoided. C.- Technical recommendations on general occupational hygiene Do not eat or drink during the process, washing hands afterwards with suitable cleaning products. D.- Technical recommendations to prevent environmental risks Due to the danger of this product for the environment it is recommended to use it within an area containing contamination control barriers in case of spillage, as well as having absorbent material in close proximity. Conditions for safe storage, including any incompatibilities: 7.2 A.- Technical measures for storage Minimum Temp.: 15 °C Maximum Temp.: 25 °C Maximum time: 12 Months

B.- General conditions for storage

Avoid sources of heat, radiation, static electricity and contact with food. For additional information see subsection 10.5

7.3 Specific end use(s):

Except for the instructions already specified it is not necessary to provide any special recommendation regarding the uses of this product.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1 **Control parameters:**



V2012 4:1

Printing: 03/01/2023 Date of compilation: 26/06/2011 Revised: 15/09/2022 Versi

Version: 6 (Replaced 5)

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION (continued)

Substances whose occupational exposure limits have to be monitored in the workplace (European OEL, not country-specific legislation):

Directive (EU) 2000/39, Directive 2004/37/EC, Directive (EU) 2006/15, Directive (EU) 2009/161, Directive (EU) 2017/164, Directive (EU) 2019/1831:

Identification	Occ	cupational exposu	ire limits
Xylene	IOELV (8h)	50 ppm	221 mg/m ³
CAS: 1330-20-7 EC: 215-535-7	IOELV (STEL)	100 ppm	442 mg/m ³
N-butyl acetate	IOELV (8h)	50 ppm	241 mg/m ³
CAS: 123-86-4 EC: 204-658-1	IOELV (STEL)	150 ppm	723 mg/m ³
2-methoxy-1-methylethyl acetate	IOELV (8h)	50 ppm	275 mg/m ³
CAS: 108-65-6 EC: 203-603-9	IOELV (STEL)	100 ppm	550 mg/m ³
Ethylbenzene	IOELV (8h)	100 ppm	442 mg/m ³
CAS: 100-41-4 EC: 202-849-4	IOELV (STEL)	200 ppm	884 mg/m ³
n-butyl acrylate	IOELV (8h)	2 ppm	11 mg/m ³
CAS: 141-32-2 EC: 205-480-7	IOELV (STEL)	10 ppm	53 mg/m ³
Methyl methacrylate	IOELV (8h)	50 ppm	
CAS: 80-62-6 EC: 201-297-1	IOELV (STEL)	100 ppm	
2-butoxyethanol	IOELV (8h)	20 ppm	98 mg/m ³
CAS: 111-76-2 EC: 203-905-0	IOELV (STEL)	50 ppm	246 mg/m ³
Toluene	IOELV (8h)	50 ppm	192 mg/m ³
CAS: 108-88-3 EC: 203-625-9	IOELV (STEL)	100 ppm	384 mg/m ³

DNEL (Workers):

		Short	exposure	Long	exposure
Identification		Systemic	Local	Systemic	Local
Xylene	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
CAS: 1330-20-7	Dermal	Non-applicable	Non-applicable	212 mg/kg	Non-applicable
EC: 215-535-7	Inhalation	442 mg/m ³	442 mg/m ³	221 mg/m ³	221 mg/m ³
N-butyl acetate	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
CAS: 123-86-4	Dermal	11 mg/kg	Non-applicable	11 mg/kg	Non-applicable
EC: 204-658-1	Inhalation	600 mg/m ³	600 mg/m ³	300 mg/m ³	300 mg/m ³
2-methoxy-1-methylethyl acetate	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
CAS: 108-65-6	Dermal	Non-applicable	Non-applicable	796 mg/kg	Non-applicable
EC: 203-603-9	Inhalation	Non-applicable	550 mg/m ³	275 mg/m ³	Non-applicable
trizinc bis(orthophosphate)	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
CAS: 7779-90-0	Dermal	Non-applicable	Non-applicable	83 mg/kg	Non-applicable
EC: 231-944-3	Inhalation	Non-applicable	Non-applicable	5 mg/m ³	Non-applicable
Ethylbenzene	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
CAS: 100-41-4	Dermal	Non-applicable	Non-applicable	180 mg/kg	Non-applicable
EC: 202-849-4	Inhalation	Non-applicable	293 mg/m ³	77 mg/m ³	Non-applicable
n-butyl acrylate	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
CAS: 141-32-2	Dermal	Non-applicable	Non-applicable	Non-applicable	Non-applicable
EC: 205-480-7	Inhalation	Non-applicable	Non-applicable	Non-applicable	11 mg/m ³
Methyl methacrylate	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
CAS: 80-62-6	Dermal	Non-applicable	Non-applicable	13,67 mg/kg	Non-applicable
EC: 201-297-1	Inhalation	Non-applicable	416 mg/m ³	348,4 mg/m ³	208 mg/m ³
2-butoxyethanol	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
CAS: 111-76-2	Dermal	89 mg/kg	Non-applicable	125 mg/kg	Non-applicable
EC: 203-905-0	Inhalation	1091 mg/m ³	246 mg/m ³	98 mg/m ³	Non-applicable
Toluene	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
CAS: 108-88-3	Dermal	Non-applicable	Non-applicable	384 mg/kg	Non-applicable
EC: 203-625-9	Inhalation	384 mg/m ³	384 mg/m ³	192 mg/m ³	192 mg/m ³



Printing: 03/01/2023

Date of compilation: 26/06/2011

Revised: 15/09/2022

Version: 6 (Replaced 5)

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION (continued)

		Short	exposure	Long	exposure
Identification		Systemic	Local	Systemic	Local
Xylene	Oral	Non-applicable	Non-applicable	12,5 mg/kg	Non-applicable
CAS: 1330-20-7	Dermal	Non-applicable	Non-applicable	125 mg/kg	Non-applicable
EC: 215-535-7	Inhalation	260 mg/m ³	260 mg/m ³	65,3 mg/m ³	65,3 mg/m ³
N-butyl acetate	Oral	2 mg/kg	Non-applicable	2 mg/kg	Non-applicable
CAS: 123-86-4	Dermal	6 mg/kg	Non-applicable	6 mg/kg	Non-applicable
EC: 204-658-1	Inhalation	300 mg/m ³	300 mg/m ³	35,7 mg/m ³	35,7 mg/m ³
2-methoxy-1-methylethyl acetate	Oral	Non-applicable	Non-applicable	36 mg/kg	Non-applicable
CAS: 108-65-6	Dermal	Non-applicable	Non-applicable	320 mg/kg	Non-applicable
EC: 203-603-9	Inhalation	Non-applicable	Non-applicable	33 mg/m ³	33 mg/m ³
trizinc bis(orthophosphate)	Oral	Non-applicable	Non-applicable	0,83 mg/kg	Non-applicable
CAS: 7779-90-0	Dermal	Non-applicable	Non-applicable	83 mg/kg	Non-applicable
EC: 231-944-3	Inhalation	Non-applicable	Non-applicable	2,5 mg/m ³	Non-applicable
Ethylbenzene	Oral	Non-applicable	Non-applicable	1,6 mg/kg	Non-applicable
CAS: 100-41-4	Dermal	Non-applicable	Non-applicable	Non-applicable	Non-applicable
EC: 202-849-4	Inhalation	Non-applicable	Non-applicable	15 mg/m ³	Non-applicable
Methyl methacrylate	Oral	Non-applicable	Non-applicable	8,2 mg/kg	Non-applicable
CAS: 80-62-6	Dermal	Non-applicable	Non-applicable	8,2 mg/kg	Non-applicable
EC: 201-297-1	Inhalation	Non-applicable	208 mg/m ³	74,3 mg/m ³	104 mg/m ³
2-butoxyethanol	Oral	Non-applicable	Non-applicable	6,3 mg/kg	Non-applicable
CAS: 111-76-2	Dermal	89 mg/kg	Non-applicable	75 mg/kg	Non-applicable
EC: 203-905-0	Inhalation	426 mg/m ³	147 mg/m ³	59 mg/m ³	Non-applicable
Toluene	Oral	Non-applicable	Non-applicable	8,13 mg/kg	Non-applicable
CAS: 108-88-3	Dermal	Non-applicable	Non-applicable	226 mg/kg	Non-applicable
EC: 203-625-9	Inhalation	226 mg/m ³	226 mg/m ³	56,5 mg/m ³	56,5 mg/m ³

PNEC:

Identification				
Xylene	STP	6,58 mg/L	Fresh water	0,327 mg/L
CAS: 1330-20-7	Soil	2,31 mg/kg	Marine water	0,327 mg/L
EC: 215-535-7	Intermittent	0,327 mg/L	Sediment (Fresh water)	12,46 mg/kg
	Oral	Non-applicable	Sediment (Marine water)	12,46 mg/kg
N-butyl acetate	STP	35,6 mg/L	Fresh water	0,18 mg/L
CAS: 123-86-4	Soil	0,09 mg/kg	Marine water	0,018 mg/L
EC: 204-658-1	Intermittent	0,36 mg/L	Sediment (Fresh water)	0,981 mg/kg
	Oral	Non-applicable	Sediment (Marine water)	0,098 mg/kg
2-methoxy-1-methylethyl acetate	STP	100 mg/L	Fresh water	0,635 mg/L
CAS: 108-65-6	Soil	0,29 mg/kg	Marine water	0,064 mg/L
EC: 203-603-9	Intermittent	6,35 mg/L	Sediment (Fresh water)	3,29 mg/kg
	Oral	Non-applicable	Sediment (Marine water)	0,329 mg/kg
trizinc bis(orthophosphate)	STP	0,1 mg/L	Fresh water	0,0206 mg/L
CAS: 7779-90-0	Soil	35,6 mg/kg	Marine water	0,0061 mg/L
EC: 231-944-3	Intermittent	Non-applicable	Sediment (Fresh water)	117,8 mg/kg
	Oral	Non-applicable	Sediment (Marine water)	56,5 mg/kg
Ethylbenzene	STP	9,6 mg/L	Fresh water	0,1 mg/L
CAS: 100-41-4	Soil	2,68 mg/kg	Marine water	0,01 mg/L
EC: 202-849-4	Intermittent	0,1 mg/L	Sediment (Fresh water)	13,7 mg/kg
	Oral	0,02 g/kg	Sediment (Marine water)	1,37 mg/kg
n-butyl acrylate	STP	3,5 mg/L	Fresh water	0,003 mg/L
CAS: 141-32-2	Soil	1 mg/kg	Marine water	0 mg/L
EC: 205-480-7	Intermittent	0,011 mg/L	Sediment (Fresh water)	0,034 mg/kg
	Oral	Non-applicable	Sediment (Marine water)	0,003 mg/kg



Printing: 03/01/2023 Date of compilation: 26/06/2011

Revised: 15/09/2022

Version: 6 (Replaced 5)

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION (continued)

Identification				
Methyl methacrylate	STP	10 mg/L	Fresh water	0,94 mg/L
CAS: 80-62-6	Soil	1,48 mg/kg	Marine water	0,094 mg/L
EC: 201-297-1	Intermittent	0,94 mg/L	Sediment (Fresh water)	10,2 mg/kg
	Oral	Non-applicable	Sediment (Marine water)	0,102 mg/kg
2-butoxyethanol	STP	463 mg/L	Fresh water	8,8 mg/L
CAS: 111-76-2	Soil	2,33 mg/kg	Marine water	0,88 mg/L
EC: 203-905-0	Intermittent	26,4 mg/L	Sediment (Fresh water)	34,6 mg/kg
	Oral	0,02 g/kg	Sediment (Marine water)	3,46 mg/kg
Toluene	STP	13,61 mg/L	Fresh water	0,68 mg/L
CAS: 108-88-3	Soil	2,89 mg/kg	Marine water	0,68 mg/L
EC: 203-625-9	Intermittent	0,68 mg/L	Sediment (Fresh water)	16,39 mg/kg
	Oral	Non-applicable	Sediment (Marine water)	16,39 mg/kg

8.2 Exposure controls:

A.- Individual protection measures, such as personal protective equipment

As a preventative measure it is recommended to use basic Personal Protective Equipment, with the corresponding <<CE marking>> in accordance with Regulation (EU) 2016/425. For more information on Personal Protective Equipment (storage, use, cleaning, maintenance, class of protection,...) consult the information leaflet provided by the manufacturer. For more information see subsection 7.1. All information contained herein is a recommendation which needs some specification from the labour risk prevention services as it is not known whether the company has additional measures at its disposal.

B.- Respiratory protection

Pictogram	PPE	Labelling	CEN Standard	Remarks
Mandatory respiratory tract protection	Filter mask for gases and vapours (Filter type: A)		EN 405:2002+A1:2010	Replace when there is a taste or smell of the contaminant inside the face mask. If the contaminant comes with warnings it is recommended to use isolation equipment.

C.- Specific protection for the hands

Pictogram	PPE	Labelling	CEN Standard	Remarks
	NON-disposable chemical protective gloves (Material: Nitrile, Breakthrough time: > 480 min, Thickness: 0.4 mm)		EN ISO 374-1:2016+A1:2018 EN 16523-1:2015+A1:2018 EN ISO 21420:2020	The Breakthrough Time indicated by the manufacturer must exceed the period during which the product is being used. Do not use protective creams after the product has come into contact with skin.

As the product is a mixture of several substances, the resistance of the glove material can not be calculated in advance with total reliability and has therefore to be checked prior to the application.

D.- Eye and face protection

1	Distagram	PPE	Labelling	CEN Standard	Remarks
	Pictogram	PPL	Labelling	CEN Stanuaru	Refindings
	Mandatory face protection	Panoramic glasses against splash/projections.		EN 166:2002 EN ISO 4007:2018	Clean daily and disinfect periodically according to the manufacturer's instructions. Use if there is a risk of splashing.
E]	Body protection				
	Pictogram	PPE	Labelling	CEN Standard	Remarks
	Mandatory complete body protection	Disposable clothing for protection against chemical risks, with antistatic and fireproof properties		EN 1149-1,2,3 EN 13034:2005+A1:2009 EN ISO 13982- 1:2004/A1:2010 EN ISO 6529:2013 EN ISO 6530:2005 EN ISO 13688:2013	For professional use only. Clean periodically according to the manufacturer's instructions.



V2012 4:1

				ON (continued)		
Pictogram		PPE	Labelling	CEN Standard		Remarks
Mandatory foot protection	protection risk, with a	footwear for against chemical ntistatic and heat nt properties	CAT III	EN ISO 13287:2020 EN ISO 20345:2011 EN 13832-1:2019	Re	eplace boots at any sign of deterioratio
F Additional emer	rgency meas	ures				
Emergency n	neasure	St	andards	Emergency measu	ure	Standards
Emergency	shower		SI Z358-1 11, ISO 3864-4:201	.1 Eyewash station	IS	DIN 12 899 ISO 3864-1:2011, ISO 3864-4:20
Environmental ex	xposure co	ntrols:				
spillage of both the Volatile organic of	e product and compounds	d its container.	For additional in	formation see subsection		nmended to avoid environment
-				owing characteristics:		
V.O.C. (Supply)		-) % weight			
V.O.C. density a Average carbon		6,87	cg/m³ (510 g/L))		
Average molecu			91 g/mol			
Information on h	acie nhveid	al and chomi	PERTIES	•		
Information on b For complete inform			cal properties	:		
Information on b For complete inform Appearance:			cal properties	:		
For complete inform	mation see th		cal properties			
For complete inform Appearance:	mation see th		cal properties asheet.			
For complete inform Appearance: Physical state at 20	mation see th		cal properties asheet. Liquid Fluid		the pa	ckage
For complete inform Appearance: Physical state at 20 Appearance:	mation see th		cal properties asheet. Liquic Fluid Accor	1	the pa	ckage
For complete inform Appearance: Physical state at 20 Appearance: Colour:	mation see th		cal properties asheet. Liquic Fluid Accor Chara	d ding to the markings on	the pa	ckage
For complete inform Appearance: Physical state at 20 Appearance: Colour: Odour:	mation see th		cal properties asheet. Liquic Fluid Accor Chara	d ding to the markings on acteristic	the pa	ckage
For complete inform Appearance: Physical state at 20 Appearance: Colour: Odour: Odour threshold:	mation see th	ne product data	cal properties asheet. Liquic Fluid Accor Chara	d ding to the markings on acteristic applicable *	the pa	ckage
For complete inform Appearance: Physical state at 20 Appearance: Colour: Odour: Odour threshold: Volatility: Boiling point at atm Vapour pressure at	mation see th) °C: nospheric pre	ne product data	ical properties asheet. Fluid Accor Chara Non-a 135 º 933 F	d rding to the markings on acteristic applicable * YC	the pa	ckage
For complete inform Appearance: Physical state at 20 Appearance: Colour: Odour: Odour threshold: Volatility: Boiling point at atm Vapour pressure at Vapour pressure at	mation see th) °C: nospheric pre : 20 °C: : 50 °C:	ne product data	cal properties asheet. Fluid Accor Chara Non-a 135 º 933 P 4905,	d rding to the markings on acteristic applicable * PC Pa .03 Pa (4,91 kPa)	the par	ckage
For complete inform Appearance: Physical state at 20 Appearance: Colour: Odour: Odour threshold: Volatility: Boiling point at atm Vapour pressure at Vapour pressure at Evaporation rate at	nospheric pre 20 °C: 20 °C: 50 °C: 50 °C: 220 °C:	ne product data	cal properties asheet. Fluid Accor Chara Non-a 135 º 933 P 4905,	d rding to the markings on acteristic applicable * YC	the pa	ckage
For complete inform Appearance: Physical state at 20 Appearance: Colour: Odour: Odour threshold: Volatility: Boiling point at atm Vapour pressure at Vapour pressure at Evaporation rate at Product description	nospheric pre 20 °C: 20 °C: 50 °C: 50 °C: 220 °C:	ne product data	ical properties asheet. Fluid Accor Chara Non-a 135 º 933 F 4905, Non-a	d rding to the markings on acteristic applicable * PC Pa ,03 Pa (4,91 kPa) applicable *	the par	ckage
For complete inform Appearance: Physical state at 20 Appearance: Colour: Odour: Odour threshold: Volatility: Boiling point at atm Vapour pressure at Vapour pressure at Evaporation rate at Product descripti Density at 20 °C:	mation see th) °C: : 20 °C: : 50 °C: : 20 °C: t 20 °C: ion:	ne product data	cal properties asheet. Fluid Accor Chara Non-a 135 º 933 F 4905, Non-a 1550	d rding to the markings on acteristic applicable * PC 2a .03 Pa (4,91 kPa) applicable * kg/m ³	the pa	ckage
For complete inform Appearance: Physical state at 20 Appearance: Colour: Odour: Odour threshold: Volatility: Boiling point at atm Vapour pressure at Evaporation rate at Product descripti Density at 20 °C: Relative density at	mation see th 0 °C: 20 °C: 50 °C: 50 °C: 50 °C: 50 °C: 50 °C: 50 °C:	ne product data	ical properties asheet. Fluid Accor Chara Non-a 135 º 933 F 4905, Non-a 1550 Non-a	d ding to the markings on acteristic applicable * C Pa ,03 Pa (4,91 kPa) applicable * kg/m ³ applicable *	the pa	ckage
For complete inform Appearance: Physical state at 20 Appearance: Colour: Odour: Odour threshold: Volatility: Boiling point at atm Vapour pressure at Vapour pressure at Evaporation rate at Product descripti Density at 20 °C: Relative density at Dynamic viscosity at	mation see th 0 °C: 20 °C: 50 °C: 50 °C: 20 °C: ion: 20 °C: at 20 °C:	ne product data	ical properties asheet. Fluid Accor Chara Non-a 135 º 933 F 4905, Non-a 1550 Non-a Non-a	d rding to the markings on acteristic applicable * PC Pa .03 Pa (4,91 kPa) applicable * kg/m ³ applicable * applicable *	the par	ckage
For complete inform Appearance: Physical state at 20 Appearance: Colour: Odour: Odour threshold: Volatility: Boiling point at atm Vapour pressure at Vapour pressure at Evaporation rate at Product descripti Density at 20 °C: Relative density at Dynamic viscosity at Kinematic viscosity	mation see th 0 °C: 20 °C: 50 °C: 50 °C: 50 °C: 100: 20 °C: 100: 20 °C: 100: 20 °C: 100: 100: 100: 100: 100: 100: 100: 10	ne product data	ical properties asheet. Fluid Accor Chara Non-a 135 ° 933 F 4905, Non-a 1550 Non-a Non-a Non-a	d rding to the markings on acteristic applicable * 'C 'a ,03 Pa (4,91 kPa) applicable * kg/m ³ applicable * applicable * applicable *	the par	ckage
For complete inform Appearance: Physical state at 20 Appearance: Colour: Odour: Odour threshold: Volatility: Boiling point at atm Vapour pressure at Vapour pressure at Evaporation rate at Product descripti Density at 20 °C: Relative density at Dynamic viscosity Kinematic viscosity	mation see th 0 °C: 20 °C: 50 °C: 50 °C: 50 °C: 100: 20 °C: 100: 20 °C: 100: 20 °C: 100: 100: 100: 100: 100: 100: 100: 10	ne product data	ical properties asheet. Liquid Fluid Accor Chara Non-a 135 º 933 F 4905, Non-a 1550 Non-a Non-a Non-a	d ding to the markings on acteristic applicable * C Pa 03 Pa (4,91 kPa) applicable * kg/m ³ applicable * applicable * applicable * applicable *	the par	ckage
For complete inform Appearance: Physical state at 20 Appearance: Colour: Odour threshold: Volatility: Boiling point at atm Vapour pressure at Vapour pressure at Evaporation rate at Product descripti Density at 20 °C: Relative density at Dynamic viscosity at Kinematic viscosity Concentration:	mation see th 0 °C: 20 °C: 50 °C: 50 °C: 50 °C: 100: 20 °C: 100: 20 °C: 100: 20 °C: 100: 100: 100: 100: 100: 100: 100: 10	ne product data	ical properties asheet. Liquid Fluid Accor Chara Non-a 135 º 933 F 4905, Non-a 1550 Non-a Non-a Non-a Non-a Non-a	d rding to the markings on acteristic applicable * PC Pa ,03 Pa (4,91 kPa) applicable * applicable * applicable * applicable * applicable * applicable * 5 mm ² /s applicable *	the par	ckage
For complete inform Appearance: Physical state at 20 Appearance: Colour: Odour: Odour threshold: Volatility: Boiling point at atm Vapour pressure at Evaporation rate at Product descripti Density at 20 °C: Relative density at Dynamic viscosity Kinematic viscosity Concentration: pH:	mation see th 0 °C: 20 °C: 50 °C: 50 °C: 50 °C: 50 °C: ion: 20 °C: at 20 °C: at 20 °C: at 20 °C: at 20 °C: at 20 °C:	ne product data	ical properties asheet. Liquid Fluid Accor Chara Non-a 135 ° 933 F 4905, Non-a 1550 Non-a Non-a <20,5 Non-a Non-a Non-a	d rding to the markings on acteristic applicable * PC Pa 03 Pa (4,91 kPa) applicable * applicable * applicable * applicable * applicable * applicable * applicable * applicable * applicable *	the par	ckage
For complete inform Appearance: Physical state at 20 Appearance: Colour: Odour : Odour threshold: Volatility: Boiling point at atm Vapour pressure at Vapour pressure at Evaporation rate at Product descripti Density at 20 °C: Relative density at Dynamic viscosity at Kinematic viscosity Concentration:	mation see th 0 °C: 20 °C: 50	essure:	ical properties asheet. Liquid Fluid Accor Chara Non-a 135 º 933 F 4905, Non-a 1550 Non-a Non-a Non-a Non-a Non-a Non-a Non-a Non-a	d rding to the markings on acteristic applicable * PC Pa ,03 Pa (4,91 kPa) applicable * applicable * applicable * applicable * applicable * applicable * 5 mm ² /s applicable *	the par	ckage



V2012 4:1

Printing:	03/01/2023	Date of compilation: 26/06/2011	Revised: 15/09/2022	Version: 6 (Replaced 5)
SECT	TION 9: PHYSIC	AL AND CHEMICAL PROPERTIE	S (continued)	
	Solubility in wate	er at 20 ºC:	Non-applicable *	
	Solubility propert	ies:	Non-applicable *	
	Decomposition te	emperature:	Non-applicable *	
	Melting point/free	ezing point:	Non-applicable *	
	Flammability:			
	Flash Point:		32 °C	
	Flammability (sol	lid, gas):	Non-applicable *	
	Autoignition temp	perature:	238 °C	
	Lower flammabili	ity limit:	Not available	
	Upper flammabili	ity limit:	Not available	
	Particle charac	teristics:		
	Median equivaler	nt diameter:	Non-applicable	
9.2	Other informat	ion:		
	Information wi	ith regard to physical hazard clas	sses:	
	Explosive propert	ties:	Non-applicable *	
	Oxidising propert	ties:	Non-applicable *	
	Corrosive to meta	als:	Non-applicable *	
	Heat of combusti	ion:	Non-applicable *	
	Aerosols-total pe components:	rcentage (by mass) of flammable	Non-applicable *	
	Other safety ch	naracteristics:		
	Surface tension a	at 20 °C:	Non-applicable *	
	Refraction index:		Non-applicable *	
	*Not relevant due to	the nature of the product, not providing info	rmation property of its hazards.	

SECTION 10: STABILITY AND REACTIVITY

10.1 Reactivity:

No hazardous reactions are expected because the product is stable under recommended storage conditions. See section 7.

10.2 Chemical stability:

Chemically stable under the indicated conditions of storage, handling and use.

10.3 Possibility of hazardous reactions:

Under the specified conditions, hazardous reactions that lead to excessive temperatures or pressure are not expected.

10.4 Conditions to avoid:

Applicable for handling and storage at room temperature:

Shock and friction	Contact with air	Increase in temperature	Sunlight	Humidity
Not applicable	Not applicable	Risk of combustion	Avoid direct impact	Not applicable

10.5 Incompatible materials:

Acids	Water	Oxidising materials	Combustible materials	Others
Avoid strong acids	Not applicable	Avoid direct impact	Not applicable	Avoid alkalis or strong bases

10.6 Hazardous decomposition products:

See subsection 10.3, 10.4 and 10.5 to find out the specific decomposition products. Depending on the decomposition conditions, complex mixtures of chemical substances can be released: carbon dioxide (CO₂), carbon monoxide and other organic compounds.

SECTION 11: TOXICOLOGICAL INFORMATION

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008:



V2012 4:1

: 03/01/2023	Date of compilation: 26/06/2011	Revised: 15/09/2022	Version: 6 (Replaced 5)
TION 11: TC	XICOLOGICAL INFORMATION (continu	ied)	
The experim	ental information related to the toxicological p	properties of the product itse	elf is not available
that are haz	cols. It is recommended not to breathe the vandous to the health . health implications:	apours for prolonged periods	s of time due to the possibility of effects
adverse effe	posure that is repetitive, prolonged or at con- cts on health may result, depending on the m (acute effect):		recommended occupational exposure lim
as dange	toxicity : Based on available data, the classif rous for consumption. For more information s ivity/Irritability: The consumption of a consid ting.	ee section 3.	
B- Inhalatio	n (acute effect):		
as hazaro - Corros classified	toxicity : Based on available data, the classif lous for inhalation. For more information see sivity/Irritability: Based on available data, the as hazardous for inhalation. For more inform with the skin and the eyes (acute effect):	section 3. classification criteria are not	
	ct with the skin: Produces skin inflammation. ct with the eyes: Produces eye damage after	contact	
	cts (carcinogenicity, mutagenicity and toxicity		
as dange IARC: (2B); Tal (3); Titar - Mutag hazardou - Repro	ogenicity: Based on available data, the classif rous with carcinogenic effects. For more infor Ethylbenzene (2B); n-butyl acrylate (3); 2-eth c (3); Hydrocarbons, C9-C12, n-alkanes, isoal nium dioxide (aerodynamic diameter \leq 10 µm enicity: Based on available data, the classifica s for this effect. For more information see see ductive toxicity: Based on available data, the as hazardous for this effect. For more inform	mation see section 3. ylhexyl acrylate (2B); Methy kanes, cyclics, aromatics (2-) (2B) ation criteria are not met, as ction 3. classification criteria are not	l methacrylate (3); Xylene (3); Carbon b 25%) (3); 2-butoxyethanol (3); Toluene it does not contain substances classified
E- Sensitizir	g effects:		
hazardou - Skin: dangerou	atory: Based on available data, the classificat s with sensitising effects. For more informatic Based on available data, the classification crit is with sensitising effects. For more informatic	on see section 3. eria are not met. However, i on see section 3.	
Based or	arget organ toxicity (STOT) - single exposure available data, the classification criteria are r		ns substances classified as hazardous for
	 h. For more information see section 3. arget organ toxicity (STOT)-repeated exposure 	re:	
- Specif nervous consciou - Skin:	ic target organ toxicity (STOT)-repeated expo system causing headache, dizziness, vertigo, h	sure: Exposure in high conce nausea, vomiting, confusion, eria are not met. However, i	, and in serious cases, loss of it does contain substances which are
H- Aspiratio			
	umption of a considerable dose can cause pu	Imonary damage.	
Other infor	mation:		
to mixtures i	7-7 Titanium dioxide (aerodynamic diameter n powder form containing 1 % or more of tita diameter \leq 10 µm		



: 03/01/2023	Date of compilation: 26/06/2011	Revised: 15/0	5,2022 1	ersion: 6 (Replaced 5)	
TION 11: TOXIC	COLOGICAL INFORMATION (contir	nued)			
	Identification		A	cute toxicity	Ge
N-butyl acetate			LD50 oral	12789 mg/kg	R
CAS: 123-86-4			LD50 dermal	14112 mg/kg	Ra
EC: 204-658-1			LC50 inhalation	23,4 mg/L (4 h)	R
Xylene			LD50 oral	2100 mg/kg	R
CAS: 1330-20-7			LD50 dermal	1100 mg/kg	R
EC: 215-535-7			LC50 inhalation	11 mg/L (ATEi)	
2-methoxy-1-meth	ylethyl acetate		LD50 oral	8532 mg/kg	R
CAS: 108-65-6			LD50 dermal	5100 mg/kg	R
EC: 203-603-9			LC50 inhalation	30 mg/L (4 h)	R
trizinc bis(orthopho	osphate)		LD50 oral	>2000 mg/kg	
CAS: 7779-90-0			LD50 dermal	>2000 mg/kg	
EC: 231-944-3			LC50 inhalation	>5 mg/L	
Titanium dioxide (a	aerodynamic diameter ≤ 10 µm)		LD50 oral	10000 mg/kg	F
CAS: 13463-67-7			LD50 dermal	10000 mg/kg	Ra
EC: 236-675-5			LC50 inhalation	>5 mg/L	
Ethylbenzene			LD50 oral	3500 mg/kg	F
CAS: 100-41-4			LD50 dermal	15354 mg/kg	Ra
EC: 202-849-4			LC50 inhalation	17,2 mg/L (4 h)	F
n-butyl acrylate			LD50 oral	4000 mg/kg	
CAS: 141-32-2			LD50 dermal	>2000 mg/kg	
EC: 205-480-7			LC50 inhalation	>20 mg/L	
Methyl methacrylat	te		LD50 oral	>2000 mg/kg	
CAS: 80-62-6			LD50 dermal	>2000 mg/kg	
EC: 201-297-1			LC50 inhalation	>20 mg/L	
2-butoxyethanol			LD50 oral	1200 mg/kg	F
CAS: 111-76-2			LD50 dermal	3000 mg/kg	Ra
EC: 203-905-0			LC50 inhalation	>20 mg/L	
Toluene			LD50 oral	5580 mg/kg	F
CAS: 108-88-3			LD50 dermal	12124 mg/kg	F
EC: 203-625-9			LC50 inhalation	28,1 mg/L (4 h)	F

Acute Toxicity Estimate (ATE mix):

ATE mix		Ingredient(s) of unknown toxicity
Oral	>2000 mg/kg (Calculation method)	Non-applicable
Dermal	9927,08 mg/kg (Calculation method)	0 %
Inhalation		

11.2 Information on other hazards:

Endocrine disrupting properties

Endocrine-disrupting properties: The product fails to meet the criteria.

Other information

Non-applicable

SECTION 12: ECOLOGICAL INFORMATION

The experimental information related to the eco-toxicological properties of the product itself is not available

12.1 Toxicity:

Acute toxicity:

Identification	Concentration		Species	Genus
Xylene	LC50	>10 - 100 mg/L (96 h)		Fish
CAS: 1330-20-7	EC50	>10 - 100 mg/L (48 h)		Crustacean
EC: 215-535-7	EC50	>10 - 100 mg/L (72 h)		Algae



Printing: 03/01/2023 Date of compilation: 26/06/2011

06/2011 Revis

Revised: 15/09/2022

Version: 6 (Replaced 5)

Identification		Concentration	Species	Ge
N-butyl acetate	LC50	Non-applicable		
CAS: 123-86-4	EC50	Non-applicable		
EC: 204-658-1	EC50	675 mg/L (72 h)	Scenedesmus subspicatus	A
2-methoxy-1-methylethyl acetate	LC50	161 mg/L (96 h)	Pimephales promelas	F
CAS: 108-65-6	EC50	481 mg/L (48 h)	Daphnia sp.	Crus
EC: 203-603-9	EC50	Non-applicable		
trizinc bis(orthophosphate)	LC50	>0.1 - 1 mg/L (96 h)		F
CAS: 7779-90-0	EC50	>0.1 - 1 mg/L (48 h)		Crus
EC: 231-944-3	EC50	>0.1 - 1 mg/L (72 h)		A
Ethylbenzene	LC50	42,3 mg/L (96 h)	Pimephales promelas	F
CAS: 100-41-4	EC50	75 mg/L (48 h)	Daphnia magna	Crus
EC: 202-849-4	EC50	63 mg/L (3 h)	Chlorella vulgaris	Al
n-butyl acrylate	LC50	5,2 mg/L (96 h)	Salmo gairdneri	F
CAS: 141-32-2	EC50	230 mg/L (24 h)	Daphnia magna	Crus
EC: 205-480-7	EC50	5,5 mg/L (96 h)	Selenastrum capricornutum	Al
Methyl methacrylate	LC50	191 mg/L (96 h)	Lepomis macrochirus	F
CAS: 80-62-6	EC50	69 mg/L (48 h)	Daphnia magna	Crus
EC: 201-297-1	EC50	170 mg/L (96 h)	Selenastrum capricornutum	Al
2-butoxyethanol	LC50	1490 mg/L (96 h)	Lepomis macrochirus	F
CAS: 111-76-2	EC50	1815 mg/L (48 h)	Daphnia magna	Crus
EC: 203-905-0	EC50	911 mg/L (72 h)	Pseudokirchneriella subcapitata	A
Toluene	LC50	13 mg/L (96 h)	Carassius auratus	F
CAS: 108-88-3	EC50	11,5 mg/L (48 h)	Daphnia magna	Crus
EC: 203-625-9	EC50	Non-applicable		

Chronic toxicity:

Identification		Concentration	Species	Genus
Xylene	NOEC	1,3 mg/L	Oncorhynchus mykiss	Fish
CAS: 1330-20-7 EC: 215-535-7	NOEC	1,17 mg/L	Ceriodaphnia dubia	Crustacean
N-butyl acetate	NOEC	Non-applicable		
CAS: 123-86-4 EC: 204-658-1	NOEC	23,2 mg/L	Daphnia magna	Crustacean
2-methoxy-1-methylethyl acetate	NOEC	47,5 mg/L	Oryzias latipes	Fish
CAS: 108-65-6 EC: 203-603-9	NOEC	100 mg/L	Daphnia magna	Crustacean
Ethylbenzene	NOEC	Non-applicable		
CAS: 100-41-4 EC: 202-849-4	NOEC	0,96 mg/L	Ceriodaphnia dubia	Crustacean
n-butyl acrylate	NOEC	Non-applicable		
CAS: 141-32-2 EC: 205-480-7	NOEC	0,136 mg/L	Daphnia magna	Crustacean
Methyl methacrylate	NOEC	9,4 mg/L	Danio rerio	Fish
CAS: 80-62-6 EC: 201-297-1	NOEC	37 mg/L	Daphnia magna	Crustacean
2-butoxyethanol	NOEC	100 mg/L	Danio rerio	Fish
CAS: 111-76-2 EC: 203-905-0	NOEC	100 mg/L	Daphnia magna	Crustacean

12.2 Persistence and degradability:

Substance-specific information:

Identification	Degradability		Biodegradability	
Xylene	BOD5	Non-applicable	Concentration	Non-applicable
CAS: 1330-20-7	COD	Non-applicable	Period	28 days
EC: 215-535-7	BOD5/COD	Non-applicable	% Biodegradable	88 %
N-butyl acetate	BOD5	Non-applicable	Concentration	Non-applicable
CAS: 123-86-4	COD	Non-applicable	Period	5 days
EC: 204-658-1	BOD5/COD	Non-applicable	% Biodegradable	84 %



Printing: 03/01/2023 Date of compilation: 26/06/2011

11 Revised: 15/09/2022

Version: 6 (Replaced 5)

SECTION 12: ECOLOGICAL INFORMATION (continued)

Identification	De	gradability	Biode	gradability
2-methoxy-1-methylethyl acetate	BOD5	Non-applicable	Concentration	785 mg/L
CAS: 108-65-6	COD	Non-applicable	Period	8 days
EC: 203-603-9	BOD5/COD	Non-applicable	% Biodegradable	100 %
Ethylbenzene	BOD5	Non-applicable	Concentration	100 mg/L
CAS: 100-41-4	COD	Non-applicable	Period	14 days
EC: 202-849-4	BOD5/COD	Non-applicable	% Biodegradable	90 %
n-butyl acrylate	BOD5	Non-applicable	Concentration	100 mg/L
CAS: 141-32-2	COD	Non-applicable	Period	14 days
EC: 205-480-7	BOD5/COD	Non-applicable	% Biodegradable	61,3 %
Methyl methacrylate	BOD5	Non-applicable	Concentration	100 mg/L
CAS: 80-62-6	COD	Non-applicable	Period	14 days
EC: 201-297-1	BOD5/COD	Non-applicable	% Biodegradable	94,3 %
2-butoxyethanol	BOD5	0,71 g O2/g	Concentration	100 mg/L
CAS: 111-76-2	COD	2,2 g O2/g	Period	14 days
EC: 203-905-0	BOD5/COD	0,32	% Biodegradable	96 %
Toluene	BOD5	2,5 g O2/g	Concentration	100 mg/L
CAS: 108-88-3	COD	Non-applicable	Period	14 days
EC: 203-625-9	BOD5/COD	Non-applicable	% Biodegradable	100 %

12.3 Bioaccumulative potential:

Substance-specific information:

Identification	Bioa	accumulation potential
Xylene	BCF	9
CAS: 1330-20-7	Pow Log	2.77
EC: 215-535-7	Potential	Low
N-butyl acetate	BCF	4
CAS: 123-86-4	Pow Log	1.78
EC: 204-658-1	Potential	Low
2-methoxy-1-methylethyl acetate	BCF	1
CAS: 108-65-6	Pow Log	0.43
EC: 203-603-9	Potential	Low
Ethylbenzene	BCF	1
AS: 100-41-4	Pow Log	3.15
EC: 202-849-4	Potential	Low
n-butyl acrylate	BCF	37
CAS: 141-32-2	Pow Log	2.36
EC: 205-480-7	Potential	Moderate
Methyl methacrylate	BCF	7
CAS: 80-62-6	Pow Log	1.38
EC: 201-297-1	Potential	Low
2-butoxyethanol	BCF	3
CAS: 111-76-2	Pow Log	0.83
EC: 203-905-0	Potential	Low
Toluene	BCF	90
CAS: 108-88-3	Pow Log	2.73
EC: 203-625-9	Potential	Moderate

12.4 Mobility in soil:

Identification	Absorption/desorption		Volatility	
Xylene	Кос	202	Henry	524,86 Pa·m³/mol
CAS: 1330-20-7	Conclusion	Moderate	Dry soil	Yes
EC: 215-535-7	Surface tension	Non-applicable	Moist soil	Yes



Printing: 03/01/2023 Date of compilation: 26/06/2011

Revised: 15/09/2022

Version: 6 (Replaced 5)

SECTION 12: ECOLOGICAL INFORMATION (continued)

Identification	Absor	Absorption/desorption		Volatility	
N-butyl acetate	Кос	Non-applicable	Henry	Non-applicable	
CAS: 123-86-4	Conclusion	Non-applicable	Dry soil	Non-applicable	
EC: 204-658-1	Surface tension	2,478E-2 N/m (25 °C)	Moist soil	Non-applicable	
Ethylbenzene	Кос	520	Henry	798,44 Pa·m³/mc	
CAS: 100-41-4	Conclusion	Moderate	Dry soil	Yes	
EC: 202-849-4	Surface tension	2,859E-2 N/m (25 °C)	Moist soil	Yes	
n-butyl acrylate	Кос	Non-applicable	Henry	Non-applicable	
CAS: 141-32-2	Conclusion	Non-applicable	Dry soil	Non-applicable	
EC: 205-480-7	Surface tension	2,598E-2 N/m (25 °C)	Moist soil	Non-applicable	
Methyl methacrylate	Кос	Non-applicable	Henry	Non-applicable	
CAS: 80-62-6	Conclusion	Non-applicable	Dry soil	Non-applicable	
EC: 201-297-1	Surface tension	2,551E-2 N/m (25 °C)	Moist soil	Non-applicable	
2-butoxyethanol	Кос	8	Henry	1,621E-1 Pa·m ³ /r	
CAS: 111-76-2	Conclusion	Very High	Dry soil	No	
EC: 203-905-0	Surface tension	2,729E-2 N/m (25 °C)	Moist soil	Yes	
Toluene	Кос	178	Henry	672,8 Pa·m ³ /mol	
CAS: 108-88-3	Conclusion	Moderate	Dry soil	Yes	
EC: 203-625-9	Surface tension	2,793E-2 N/m (25 °C)	Moist soil	Yes	

12.5 Results of PBT and vPvB assessment:

Product fails to meet PBT/vPvB criteria

12.6 Endocrine disrupting properties:

Endocrine-disrupting properties: The product fails to meet the criteria.

12.7 Other adverse effects:

Not described

SECTION 13: DISPOSAL CONSIDERATIONS

13.1 Waste treatment methods:

Code	Description	Waste class (Regulation (EU) No 1357/2014)
08 01 11* 15 01 10*	waste paint and varnish containing organic solvents or other hazardous substances packaging containing residues of or contaminated by hazardous substances	Dangerous

Type of waste (Regulation (EU) No 1357/2014):

HP14 Ecotoxic, HP5 Specific Target Organ Toxicity (STOT)/Aspiration Toxicity, HP3 Flammable, HP4 Irritant — skin irritation and eye damage

Waste management (disposal and evaluation):

Consult the authorized waste service manager on the assessment and disposal operations in accordance with Annex 1 and Annex 2 (Directive 2008/98/EC). As under 15 01 (2014/955/EC) of the code and in case the container has been in direct contact with the product, it will be processed the same way as the actual product. Otherwise, it will be processed as non-dangerous residue. Waste should not be disposed of to drains. See paragraph 6.2.

Regulations related to waste management:

In accordance with Annex II of Regulation (EC) No 1907/2006 (REACH) the community or state provisions related to waste management are stated

Community legislation: Directive 2008/98/EC, 2014/955/EU, Regulation (EU) No 1357/2014

SECTION 14: TRANSPORT INFORMATION

Transport of dangerous goods by land:

With regard to ADR 2021 and RID 2021:

V2012 4:1

Printing: 03/01/2023	Date o	of compilation: 26/06/2011	Revised: 15/09/2022	Version: 6 (Replaced 5)
SECTION 14: TRANSF	PORT	INFORMATION (continued)		
	14.2	UN number or ID number: UN proper shipping name: Transport hazard class(es): Labels:	UN1263 PAINT 3 3	
		Packing group:	III	
		Environmental hazards:	No	
	14.6	Special precautions for user Special regulations: Tunnel restriction code: Physico-Chemical properties: Limited quantities:	163, 367, 650 D/E see section 9 5 L	
	14.7	Maritime transport in bulk according to IMO instruments:	Non-applicable	
Transport of da	ngero	us goods by sea:		
With regard to IN	1DG 40	-20:		
		UN number or ID number:	UN1263	
		UN proper shipping name:	PAINT	
Je.	14.3	Transport hazard class(es):	3	
	144	Labels:	3	
		Packing group: Marine pollutant:	III No	
3		Special precautions for user	NO	
•	14.0	Special regulations:	223, 955, 163, 367	
		EmS Codes:	F-E, S-E	
		Physico-Chemical properties:	see section 9	
		Limited quantities:	5 L	
		Segregation group:	Non-applicable	
	14.7	Maritime transport in bulk according to IMO instruments:	Non-applicable	
Transport of da	ngero	us goods by air:		
With regard to IA	-			
		UN number or ID number:	UN1263	
*		UN proper shipping name:	PAINT	
$\langle - \rangle$	14.3	Transport hazard class(es):	3	
		Labels:	3	
		Packing group: Environmental hazards:	III	
		Special precautions for user	No	
	14.0	Physico-Chemical properties:	see section 9	
	14.7	Maritime transport in bulk according to IMO instruments:	Non-applicable	

SECTION 15: REGULATORY INFORMATION

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture: Candidate substances for authorisation under the Regulation (EC) No 1907/2006 (REACH): Non-applicable Substances included in Annex XIV of REACH ("Authorisation List") and sunset date: Non-applicable

Regulation (EC) No 1005/2009, about substances that deplete the ozone layer: Non-applicable

Article 95, REGULATION (EU) No 528/2012: Non-applicable



Safety data sheet

This SDS is an English translation of COMMISSION REGULATION (EU) 2020/878, without any country-specific legislation

V2012 4:1

Printing: 03/01/2023 Date of compilation: 26/06/2011 Revised: 15/09/2022 Version: 6 (Replaced 5) SECTION 15: REGULATORY INFORMATION (continued) REGULATION (EU) No 649/2012, in relation to the import and export of hazardous chemical products: Non-applicable Seveso III: Lower-tier Upper-tier Section Description requirements requirements P5c FLAMMABLE LIQUIDS 5000 50000 Limitations to commercialisation and the use of certain dangerous substances and mixtures (Annex XVII REACH, etc): Shall not be used in: and ashtravs. -tricks and jokes, -games for one or more participants, or any article intended to be used as such, even with ornamental aspects. Occupational exposure to respirable crystalline silica must be controlled pursuant to Directive (EU) 2019/130. Specific provisions in terms of protecting people or the environment: It is recommended to use the information included in this safety data sheet as a basis for conducting workplace-specific risk assessments in order to establish the necessary risk prevention measures for the handling, use, storage and disposal of this product. Other legislation: The product could be affected by sectorial legislation 15.2 Chemical safety assessment: The supplier has not carried out evaluation of chemical safety.

SECTION 16: OTHER INFORMATION

Legislation related to safety data sheets:

The SDS shall be supplied in an official language of the country where the product is placed on the market. This safety data sheet has been designed in accordance with ANNEX II-Guide to the compilation of safety data sheets of Regulation (EC) No 1907/2006 (COMMISSION REGULATION (EU) 2020/878).

Modifications related to the previous Safety Data Sheet which concerns the ways of managing risks.: Non-applicable

Texts of the legislative phrases mentioned in section 2:

H315: Causes skin irritation.

H412: Harmful to aquatic life with long lasting effects.

H373: May cause damage to organs through prolonged or repeated exposure (Oral).

H304: May be fatal if swallowed and enters airways.

H226: Flammable liquid and vapour.

H319: Causes serious eye irritation.

Texts of the legislative phrases mentioned in section 3:

The phrases indicated do not refer to the product itself; they are present merely for informative purposes and refer to the individual components which appear in section 3

CLP Regulation (EC) No 1272/2008:

Safety data sheet

This SDS is an English translation of COMMISSION REGULATION (EU) 2020/878, without any country-specific legislation

V2012 4:1

Printing: 03/01/2023	Date of compilation: 26/06/2011	Revised: 15/09/2022	Version: 6 (Replaced 5)
SECTION 16: OTHE	ER INFORMATION (continued)		
Acute Tox. 4: H Acute Tox. 4: H Aquatic Acute 1 Aquatic Acute 1 Aquatic Chronic Asp. Tox. 1: H3 Carc. 2: H351 - Eye Irrit. 2: H3 Flam. Liq. 2: H3 Flam. Liq. 3: H3 Skin Sens. 1: H Skin Sens. 11: H Skin Sens. 11: H Skin Sens. 11: H Stor RE 2: H3 STOT RE 2: H3 STOT RE 2: H3	 H302+H332 - Harmful if swallowed or if H312+H332 - Harmful in contact with sk H332 - Harmful if inhaled. H400 - Very toxic to aquatic life. H410 - Very toxic to aquatic life with H412 - Harmful to aquatic life with G4 - May be fatal if swallowed and enter Suspected of causing cancer (Inhalation Highly flammable liquid and vapour. Suspected of damaging the unborn ch Causes skin irritation. Causes skin irritation. - May cause an allergic skin reaction H317 - May cause an allergic skin reaction H317 - May cause damage to organs throw Anay cause damage to organs throw - May cause respiratory irritation. 	in or if inhaled. h long lasting effects. long lasting effects. ers airways. m). ur. hild. in. igh prolonged or repeated expo ugh prolonged or repeated expo	
STOT SE 3: H3	36 - May cause drowsiness or dizziness.		
Aquatic Chronic STOT RE 2: Cal Asp. Tox. 1: Ca Flam. Liq. 3: Ca	Iculation method 2 3: Calculation method 1 culation method 1 culation method 1 culation method 2 culation method 1 culation method		
Advice related	-		
	mmended in order to prevent industrial of this safety data sheet, as well as the la		t and to facilitate their comprehension and
Principal bibli	iographical sources:		
http://echa.eur http://eur-lex.e			
	s and acronyms:		
IMDG: Internat IATA: Internation ICAO: Internation COD: Chemical BOD5: 5day bion BCF: Bioconcen LD50: Lethal Do LC50: Lethal Co EC50: Effective LogPOW: Octar	ose 50 oncentration 50 concentration 50 nolwater partition coefficient oefficient of organic carbon	i carriage of dangerous goods b	y Toau
	onal Agency for Research on Cancer		

The information contained in this safety data sheet is based on sources, technical knowledge and current legislation at European and state level, without being able to guarantee its accuracy. This information cannot be considered a guarantee of the properties of the product, it is simply a description of the security requirements. The occupational methodology and conditions for users of this product are not within our awareness or control, and it is ultimately the responsibility of the user to take the necessary measures to obtain the legal requirements concerning the manipulation, storage, use and disposal of chemical products. The information on this safety data sheet only refers to this product, which should not be used for needs other than those specified.

