

Safety data sheet

This SDS is an English translation of COMMISSION REGULATION (EU) 2020/878, without any country-specific legislation

## **CLEAR COAT GLOSS**

ECT	TION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING
.1	Product identifier: CLEAR COAT GLOSS
	Other means of identification:
•	UFI: 3YFV-62WW-Y00T-HM03
.2	Relevant identified uses of the substance or mixture and uses advised against:
	Relevant uses: Car repair; spray paint. For professional users only.
2	Uses advised against: All uses not specified in this section or in section 7.3
.3	Details of the supplier of the safety data sheet:
	Troton Sp. z o.o. Ząbrowo 14A 78-120 Gościno - Zachodniopomorskie - Polska Phone: +48 94 35 123 94 - Fax: +48 94 35 126 22 troton@troton.com.pl www.troton.pl / www.troton.eu
.4	Emergency telephone number: (8am-4pm)+48 094 35 123 94; 112
FCT	TION 2: HAZARDS IDENTIFICATION
.1	Classification of the substance or mixture:
• #	
	CLP Regulation (EC) No 1272/2008:
	Classification of this product has been carried out in accordance with CLP Regulation (EC) No 1272/2008.
	Aerosol 1: Pressurised container: May burst if heated., H229 Aerosol 1: Flammable aerosols, Category 1, H222
	Aquatic Chronic 3: Hazardous to the aquatic environment, long-term hazard, Category 3, H412
	Eye Irrit. 2: Eye irritation, Category 2, H319 STOT SE 3: Specific toxicity causing drowsiness and dizziness, single exposure, Category 3, H336
.2	Label elements:
	CLP Regulation (EC) No 1272/2008:
	Danger
	Hazard statements:
	Aerosol 1: H229 - Pressurised container: May burst if heated. Aerosol 1: H222 - Extremely flammable aerosol.
	Aquatic Chronic 3: H412 - Harmful to aquatic life with long lasting effects. Eye Irrit. 2: H319 - Causes serious eye irritation. STOT SE 3: H336 - May cause drowsiness or dizziness.
	Precautionary statements:
	P210: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P211: Do not spray on an open flame or other ignition source. P251: Do not pierce or burn, even after use.
	P280: Wear protective gloves/protective clothing/respiratory protection/eye protection/protective footwear.
	P304+P340: IF INHALED: Remove person to fresh air and keep comfortable for breathing. P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy
	do. Continue rinsing.
	P410+P412: Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122°F P501: Dispose of contents/container in accordance with regulations on hazardous waste or packaging and packaging waste respectively.
	Supplementary information:
	EUH066: Repeated exposure may cause skin dryness or cracking.
	Substances that contribute to the classification
	acetone; Hydrocarbons, C9, aromatics; N-butyl acetate
.3	Other hazards:



Safety data sheet

This SDS is an English translation of COMMISSION REGULATION (EU) 2020/878, without any country-specific legislation

# **CLEAR COAT GLOSS**

-	20/01/20		of compilation: 18/0	·	Revised: 18/02/2022	Version: 2 (R	eplaced 1)			
DECT	Product	: fails to meet PB	NTIFICATION (cc I/vPvB criteria perties: The product		the criteria.					
SECT	ION 3:	COMPOSITIO	N/INFORMATION	ON INGREE	DIENTS					
3.1	Substa	ince:								
	Non-ap	plicable								
3.2	Mixtur	e:								
	Chemi	cal description:	Mixture composed	of chemical p	products					
	Compo	onents:								
	In accordance with Annex II of Regulation (EC) No 1907/2006 (point 3), the product contains:									
	]	Identification			Chemical name/Classification			Concentratio		
		115-10-6	Dimethyl ether(1)				ATP CLP00			
	Index: 6 REACH: 0	204-065-8 503-019-00-8 01-2119472128-37- XXXX	Regulation 1272/2008	Flam. Gas 1A: H2	20; Press. Gas: H280 - Danger		۵ ٦	50 - <75 %		
		57-64-1 200-662-2	acetone <sup>(2)</sup>	-			ATP CLP00			
	Index: 6 REACH: 0	200-662-2 506-001-00-8 )1-2119471330-49- (XXX	Regulation 1272/2008	Eye Irrit. 2: H319	; Flam. Liq. 2: H225; STOT SE 3: H33	6; EUH066 - Danger	(1) (1)	10 - <25 %		
		128601-23-0	Hydrocarbons, C9, a	romatics <sup>(2)</sup>			Self-classified			
	Index: N REACH: 0	918-668-5 Non-applicable I: 01-2119455851-35- XXXX	Regulation 1272/2008		: H411; Asp. Tox. 1: H304; Flam. Liq. : H336; EUH066 - Danger	3: H226; STOT SE 3:	(!) (a) (b) (b)	10 - <25 %		
		111-76-2	2-butoxyethanol <sup>(2)</sup>				ATP ATP18			
	Index: 6 REACH: 0	203-905-0 503-014-00-0 01-2119475108-36- XXXX	Regulation 1272/2008	Acute Tox. 3: H33	31; Acute Tox. 4: H302; Eye Irrit. 2: H	1319; Skin Irrit. 2: H315	- Danger 🛛 🛞	2,5 - <5 %		
		123-86-4	N-butyl acetate <sup>(2)</sup>				ATP CLP00			
	Index: 6 REACH: 0	204-658-1 507-025-00-1 01-2119485493-29- XXXX	Regulation 1272/2008	Flam. Liq. 3: H220	6; STOT SE 3: H336; EUH066 - Warni	ng	() ()	1 - <2,5 %		
		1330-20-7	Xylene <sup>(2)</sup>				ATP CLP00			
	Index: 6 REACH: 0	215-535-7 501-022-00-9 01-2119488216-32- XXXX	Regulation 1272/2008	Acute Tox. 4: H31	12+H332; Flam. Liq. 3: H226; Skin Irr	it. 2: H315 - Warning		1 - <2,5 %		

<sup>(1)</sup> Substance with a Union workplace exposure limit <sup>(2)</sup> Substances presenting a health or environmental hazard which meet criteria laid down in Regulation (EU) No. 2020/878

To obtain more information on the hazards of the substances consult sections 11, 12 and 16.

### SECTION 4: FIRST AID MEASURES

### 4.1 Description of first aid measures:

The symptoms resulting from intoxication can appear after exposure, therefore, in case of doubt, seek medical attention for direct exposure to the chemical product or persistent discomfort, showing the SDS of this product. **By inhalation:** 

Remove the person affected from the area of exposure, provide with fresh air and keep at rest. In serious cases such as cardiorespiratory failure, artificial resuscitation techniques will be necessary (mouth to mouth resuscitation, cardiac massage, oxygen supply, etc.) requiring immediate medical assistance.

#### By skin contact:

Remove contaminated clothing and footwear, rinse skin or shower the person affected if appropriate with plenty of cold water and neutral soap. In serious cases see a doctor. If the product causes burns or freezing, clothing should not be removed as this could worsen the injury caused if it is stuck to the skin. If blisters form on the skin, these should never be burst as this will increase the risk of infection.

### By eye contact:



# **CLEAR COAT GLOSS**

rinting	: 20/01/2023 Date of compilation: 18/04/2019 Revised: 18/02/2022 Version: 2 (Replaced 1)						
SEC	TION 4: FIRST AID MEASURES (continued)						
Rinse eyes thoroughly with lukewarm water for at least 15 minutes. Do not allow the person affected to rub or close their eyes. If the injured person uses contact lenses, these should be removed unless they are stuck to the eyes, in which case this could cause further damage. In all cases, after cleaning, a doctor should be consulted as quickly as possible with the SDS of the product. By ingestion/aspiration:							
<ul> <li>Do not induce vomiting, but if it does happen keep the head down to avoid aspiration. Keep the person affected at rest. Rinse out the mouth and throat, as they may have been affected during ingestion.</li> <li>4.2 Most important symptoms and effects, both acute and delayed:</li> </ul>							
	Acute and delayed effects are indicated in sections 2 and 11.						
4.3	Indication of any immediate medical attention and special treatment needed: Non-applicable						
SEC	TION 5: FIREFIGHTING MEASURES						
5.1	Extinguishing media:						
5.1							
5.1	Extinguishing media:						
5.1	Extinguishing media: Suitable extinguishing media:						
5.1	<b>Extinguishing media:</b> <b>Suitable extinguishing media:</b> If possible use polyvalent powder fire extinguishers (ABC powder), alternatively use foam or carbon dioxide extinguishers (CO <sub>2</sub> ).						
5.1	Extinguishing media: Suitable extinguishing media: If possible use polyvalent powder fire extinguishers (ABC powder), alternatively use foam or carbon dioxide extinguishers (CO <sub>2</sub> ). Unsuitable extinguishing media:						

#### 5.3 Advice for firefighters:

Depending on the magnitude of the fire it may be necessary to use full protective clothing and self-contained breathing apparatus (SCBA). Minimum emergency facilities and equipment should be available (fire blankets, portable first aid kit,...) in accordance with Directive 89/654/EC.

#### Additional provisions:

Act in accordance with the Internal Emergency Plan and the Information Sheets on actions to take after an accident or other emergencies. Eliminate all sources of ignition. In case of fire, cool the storage containers and tanks for products susceptible to combustion, explosion or BLEVE as a result of high temperatures. Avoid spillage of the products used to extinguish the fire into an aqueous medium.

### SECTION 6: ACCIDENTAL RELEASE MEASURES

### 6.1 Personal precautions, protective equipment and emergency procedures:

#### For non-emergency personnel:

Isolate leaks provided that there is no additional risk for the people performing this task. Evacuate the area and keep out those without protection. Personal protection equipment must be used against potential contact with the spilt product (See section 8). Above all prevent the formation of any vapour-air flammable mixtures, through either ventilation or the use of an inert medium. Remove any source of ignition. Eliminate electrostatic charges by interconnecting all the conductive surfaces on which static electricity could form, and also ensuring that all surfaces are connected to the ground.

### For emergency responders:

Wear protective equipment. Keep unprotected persons away. See section 8.

### 6.2 Environmental precautions:

Avoid at all cost any type of spillage into an aqueous medium. Contain the product absorbed appropriately in hermetically sealed containers. Notify the relevant authority in case of exposure to the general public or the environment.

### 6.3 Methods and material for containment and cleaning up:

#### It is recommended:

Absorb the spillage using sand or inert absorbent and move it to a safe place. Do not absorb in sawdust or other combustible absorbents. For any concern related to disposal consult section 13.

### 6.4 Reference to other sections:

See sections 8 and 13.



# **CLEAR COAT GLOSS**

Printing: 20/01/2023 Date of compilation: 18/04/2019

Revised: 18/02/2022

Version: 2 (Replaced 1)

### SECTION 7: HANDLING AND STORAGE

#### 7.1 Precautions for safe handling:

A.- General precautions for safe use

Comply with the current legislation concerning the prevention of industrial risks. Keep containers hermetically sealed. Control spills and residues, destroying them with safe methods (section 6). Avoid leakages from the container. Maintain order and cleanliness where dangerous products are used.

B.- Technical recommendations for the prevention of fires and explosions

Avoid the evaporation of the product as it contains flammable substances, which could form flammable vapour/air mixtures in the presence of sources of ignition. Control sources of ignition (mobile phones, sparks,...) and transfer at slow speeds to avoid the creation of electrostatic charges. Consult section 10 for conditions and materials that should be avoided.

C.- Technical recommendations on general occupational hygiene

Do not eat or drink during the process, washing hands afterwards with suitable cleaning products.

D.- Technical recommendations to prevent environmental risks

Due to the danger of this product for the environment it is recommended to use it within an area containing contamination control barriers in case of spillage, as well as having absorbent material in close proximity.

#### Conditions for safe storage, including any incompatibilities:

A.- Technical measures for storage

Maximum Temp.: 25 °C

B.- General conditions for storage

Avoid sources of heat, radiation, static electricity and contact with food. For additional information see subsection 10.5

#### 7.3 Specific end use(s):

7.2

Except for the instructions already specified it is not necessary to provide any special recommendation regarding the uses of this product.

### SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

#### 8.1 Control parameters:

Substances whose occupational exposure limits have to be monitored in the workplace (European OEL, not country-specific legislation):

Directive (EU) 2000/39, Directive 2004/37/EC, Directive (EU) 2006/15, Directive (EU) 2009/161, Directive (EU) 2017/164, Directive (EU) 2019/1831:

Identification	Осси	Occupational exposure limits				
Dimethyl ether	IOELV (8h)	1000 ppm	1920 mg/m <sup>3</sup>			
CAS: 115-10-6 EC: 204-065-8	IOELV (STEL)					
acetone	IOELV (8h)	500 ppm	1210 mg/m <sup>3</sup>			
CAS: 67-64-1 EC: 200-662-2	IOELV (STEL)					
2-butoxyethanol	IOELV (8h)	20 ppm	98 mg/m <sup>3</sup>			
CAS: 111-76-2 EC: 203-905-0	IOELV (STEL)	50 ppm	246 mg/m <sup>3</sup>			
N-butyl acetate	IOELV (8h)	50 ppm	241 mg/m <sup>3</sup>			
CAS: 123-86-4 EC: 204-658-1	IOELV (STEL)	150 ppm	723 mg/m <sup>3</sup>			
Xylene	IOELV (8h)	50 ppm	221 mg/m <sup>3</sup>			
CAS: 1330-20-7 EC: 215-535-7	IOELV (STEL)	100 ppm	442 mg/m <sup>3</sup>			

#### DNEL (Workers):

	Short e	xposure	Long exposure		
Identification	Systemic	Local	Systemic	Local	
Dimethyl ether	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
CAS: 115-10-6	Dermal	Non-applicable	Non-applicable	Non-applicable	Non-applicable
EC: 204-065-8	Inhalation	Non-applicable	Non-applicable	1894 mg/m <sup>3</sup>	Non-applicable
acetone	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
CAS: 67-64-1	Dermal	Non-applicable	Non-applicable	186 mg/kg	Non-applicable
EC: 200-662-2	Inhalation	Non-applicable	2420 mg/m <sup>3</sup>	1210 mg/m <sup>3</sup>	Non-applicable

# **CLEAR COAT GLOSS**

# Printing: 20/01/2023 Date

Date of compilation: 18/04/2019

Revised: 18/02/2022

Version: 2 (Replaced 1)

# SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION (continued)

	Short	exposure	Long exposure		
Identification	Systemic	Local	Systemic	Local	
Hydrocarbons, C9, aromatics	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
CAS: 128601-23-0	Dermal	Non-applicable	Non-applicable	25 mg/kg	Non-applicable
EC: 918-668-5	Inhalation	Non-applicable	Non-applicable	150 mg/m <sup>3</sup>	Non-applicable
2-butoxyethanol	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
CAS: 111-76-2	Dermal	89 mg/kg	Non-applicable	125 mg/kg	Non-applicable
EC: 203-905-0	Inhalation	1091 mg/m <sup>3</sup>	246 mg/m <sup>3</sup>	98 mg/m <sup>3</sup>	Non-applicable
N-butyl acetate	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
CAS: 123-86-4	Dermal	11 mg/kg	Non-applicable	11 mg/kg	Non-applicable
EC: 204-658-1	Inhalation	600 mg/m <sup>3</sup>	600 mg/m <sup>3</sup>	300 mg/m <sup>3</sup>	300 mg/m <sup>3</sup>
Xylene	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
CAS: 1330-20-7	Dermal	Non-applicable	Non-applicable	212 mg/kg	Non-applicable
EC: 215-535-7	Inhalation	442 mg/m <sup>3</sup>	442 mg/m <sup>3</sup>	221 mg/m <sup>3</sup>	221 mg/m <sup>3</sup>

### DNEL (General population):

	Short e	exposure	Long exposure		
Identification		Systemic	Local	Systemic	Local
Dimethyl ether	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
CAS: 115-10-6	Dermal	Non-applicable	Non-applicable	Non-applicable	Non-applicable
EC: 204-065-8	Inhalation	Non-applicable	Non-applicable	471 mg/m³	Non-applicable
acetone	Oral	Non-applicable	Non-applicable	62 mg/kg	Non-applicable
CAS: 67-64-1	Dermal	Non-applicable	Non-applicable	62 mg/kg	Non-applicable
EC: 200-662-2	Inhalation	Non-applicable	Non-applicable	200 mg/m <sup>3</sup>	Non-applicable
Hydrocarbons, C9, aromatics	Oral	Non-applicable	Non-applicable	11 mg/kg	Non-applicable
CAS: 128601-23-0	Dermal	Non-applicable	Non-applicable	11 mg/kg	Non-applicable
EC: 918-668-5	Inhalation	Non-applicable	Non-applicable	32 mg/m <sup>3</sup>	Non-applicable
2-butoxyethanol	Oral	Non-applicable	Non-applicable	6,3 mg/kg	Non-applicable
CAS: 111-76-2	Dermal	89 mg/kg	Non-applicable	75 mg/kg	Non-applicable
EC: 203-905-0	Inhalation	426 mg/m <sup>3</sup>	147 mg/m <sup>3</sup>	59 mg/m <sup>3</sup>	Non-applicable
N-butyl acetate	Oral	2 mg/kg	Non-applicable	2 mg/kg	Non-applicable
CAS: 123-86-4	Dermal	6 mg/kg	Non-applicable	6 mg/kg	Non-applicable
EC: 204-658-1	Inhalation	300 mg/m <sup>3</sup>	300 mg/m <sup>3</sup>	35,7 mg/m <sup>3</sup>	35,7 mg/m <sup>3</sup>
Xylene	Oral	Non-applicable	Non-applicable	12,5 mg/kg	Non-applicable
CAS: 1330-20-7	Dermal	Non-applicable	Non-applicable	125 mg/kg	Non-applicable
EC: 215-535-7	Inhalation	260 mg/m <sup>3</sup>	260 mg/m <sup>3</sup>	65,3 mg/m <sup>3</sup>	65,3 mg/m <sup>3</sup>

### PNEC:

Identification				
Dimethyl ether	STP	160 mg/L	Fresh water	0,155 mg/L
CAS: 115-10-6	Soil	0,045 mg/kg	Marine water	0,016 mg/L
EC: 204-065-8	Intermittent	1,549 mg/L	Sediment (Fresh water)	0,681 mg/kg
	Oral	Non-applicable	Sediment (Marine water)	0,069 mg/kg
acetone	STP	100 mg/L	Fresh water	10,6 mg/L
CAS: 67-64-1	Soil	29,5 mg/kg	Marine water	1,06 mg/L
EC: 200-662-2	Intermittent	21 mg/L	Sediment (Fresh water)	30,4 mg/kg
	Oral	Non-applicable	Sediment (Marine water)	3,04 mg/kg
2-butoxyethanol	STP	463 mg/L	Fresh water	8,8 mg/L
CAS: 111-76-2	Soil	2,33 mg/kg	Marine water	0,88 mg/L
EC: 203-905-0	Intermittent	26,4 mg/L	Sediment (Fresh water)	34,6 mg/kg
	Oral	0,02 g/kg	Sediment (Marine water)	3,46 mg/kg
N-butyl acetate	STP	35,6 mg/L	Fresh water	0,18 mg/L
CAS: 123-86-4	Soil	0,09 mg/kg	Marine water	0,018 mg/L
EC: 204-658-1	Intermittent	0,36 mg/L	Sediment (Fresh water)	0,981 mg/kg
	Oral	Non-applicable	Sediment (Marine water)	0,098 mg/kg



# **CLEAR COAT GLOSS**

		8: EXPOSURE	CONTROL	S/PERSON/	AL PROTECT	10N (	continued)				
		Id	lentification								
	Xyle	ene			STP	6	,58 mg/L	Fresh	h water		0,327 mg/L
		AS: 1330-20-7		Soil		,31 mg/kg		ne wate		0,327 mg/L	
	EC:	215-535-7			Intermittent		,327 mg/L			resh water)	12,46 mg/kg
					Oral	Ν	on-applicable	Sedir	ment (№	larine water)	12,46 mg/kg
2	-	osure controls: Individual protect		es, such as pe	ersonal protecti	ive eau	lipment				
		marking>> in acc use, cleaning, ma	cordance wit intenance, c ubsection 7. evention ser	h Regulation lass of protection 1. All information	(EU) 2016/425 ction,) consul ation contained	5. For r It the i I herei	nore informati nformation lea n is a recomm	ion on aflet pr iendati	Perso ovideo on wh	nal Protective by the manu ich needs sor	responding < <ce Equipment (stora ufacturer. For more ne specification fro its disposal.</ce 
		Pictogram	P	PE	Labelling		CEN Standard			R	emarks
		Mandatory respiratory tract protection		for gases and liter type: A)	CAT III	EN	405:2002+A1:2(	010	C	ontaminant insid contaminant con	is a taste or smell of i the the face mask. If the nes with warnings it is use isolation equipmen
	C	Specific protection	n for the har	nds							
		Pictogram	P	PE	Labelling		CEN Standard			R	emarks
		Madata	protective glo Nitrile, Breakt	able chemical oves (Material: hrough time: >	CE		O 374-1:2016+A1 6523-1:2015+A1		manufa		Time indicated by the ed the period during
		Mandatory hand protection As the product is		kness: 0.4 mm) several subs			N ISO 21420:202	20	crear	· wi	duct has come into cor ith skin.
		protection As the product is total reliability and Eye and face prot	a mixture of d has theref ection	several subs	tances, the res	sistanc	e of the glove	20	crear	not be calcu	duct has come into cor ith skin.
		protection As the product is total reliability and	a mixture of d has theref ection	several subs ore to be che	tances, the res	sistanc	e of the glove lication.	20	crear	not be calcu	duct has come into cor ith skin. lated in advance v
	D	protection As the product is total reliability and Eye and face prot Pictogram Mandatory face protection	a mixture of d has thereficection	several subs ore to be che	tances, the res	sistanc he app	e of the glove lication.	20 mater	crear ial car Clean	a not be calcu R daily and disinfe	duct has come into cor ith skin. lated in advance v
	D	Protection As the product is total reliability and Eye and face prot Pictogram	a mixture of d has thereficection	several subs ore to be che PE	tances, the restricted prior to the Labelling	sistanc he app	e of the glove lication. CEN Standard EN 166:2002	20 mater	crear ial car Clean	a not be calcu R daily and disinfe	duct has come into cor ith skin. lated in advance v emarks ect periodically accordi istructions. Use if them
	D	protection As the product is total reliability and Eye and face prot Pictogram Mandatory face protection	a mixture of d has thereficection Panoramic g splash/p	several subs ore to be che PE	tances, the restricted prior to the Labelling	sistanc he app	e of the glove lication. CEN Standard EN 166:2002	20 mater	crear ial car Clean	daily and disinfe risk of	duct has come into cor ith skin. lated in advance v emarks ect periodically accordi istructions. Use if them
	D	protection As the product is total reliability and Eye and face prot Pictogram Pictogram Mandatory face protection Body protection	a mixture of d has thereficection Panoramic g splash/p Disposable protection ag risks, with a	several subs ore to be che PE lasses against rojections.	Labelling	EN :	e of the glove lication. CEN Standard EN 166:2002 EN ISO 4007:201:	20 mater 8 2009 3 5	crear ial car Clean the m	a not be calcu R daily and disinfe nanufacturer's ir risk of R R	duct has come into cor ith skin. lated in advance v emarks ect periodically accordi istructions. Use if there f splashing.
	D	protection As the product is total reliability and Eye and face prot Pictogram Mandatory face protection Body protection Pictogram	a mixture of d has theref ection Panoramic g splash/p Disposable protection ag risks, with a fireproof Safety fo protection ag risk, with anti	several subsore to be che PE lasses against rojections. PE clothing for ainst chemical antistatic and	Labelling Labelling Labelling Labelling	EN :	e of the glove lication. CEN Standard EN 166:2002 EN ISO 4007:2013 CEN Standard EN 1149-1,2,3 13034:2005+A1:2 EN ISO 13982- 1:2004/A1:2010 EN ISO 6529:2013 EN ISO 6530:200 N ISO 13688:201	20 mater 8 2009 3 5 13 20 11	Clean the m	daily and disinfe daily and disinfe nanufacturer's in risk of R r professional us ording to the ma	duct has come into cor ith skin. lated in advance v emarks ect periodically accordi istructions. Use if there f splashing. emarks e only. Clean periodica
	D	protection As the product is total reliability and Eye and face prot Pictogram Mandatory face protection Pictogram Mandatory complete body protection	a mixture of d has thereficection Panoramic g splash/p Disposable protection ag risks, with a fireproof Safety fo protection ag risk, with anti- resistant	several subsore to be che         PE         lasses against rojections.         PE         clothing for antistatic and properties         otwear for anist chemical static and heat properties	Labelling Labelling Labelling Labelling Labelling	EN :	e of the glove lication. CEN Standard EN 166:2002 EN ISO 4007:201: CEN Standard EN 1149-1,2,3 13034:2005+A1:2 EN ISO 13982- 1:2004/A1:2010 EN ISO 6529:201: EN ISO 6530:200 N ISO 13688:201 EN 464:1994 N ISO 13287:202 N ISO 20345:201	20 mater 8 2009 3 5 13 20 11	Clean the m	anot be calcu R daily and disinfe nanufacturer's in risk of R r professional us ording to the ma	duct has come into cor ith skin. lated in advance v emarks ect periodically accordi istructions. Use if there istructions. Use if there f splashing. emarks e only. Clean periodica nufacturer's instructio
	D	protection As the product is total reliability and Eye and face prot Pictogram Mandatory face protection Pictogram Pictogram Mandatory complete body protection	a mixture of d has theref ection Panoramic g splash/p Disposable protection ag risks, with a fireproof Safety fo protection ag risk, with anti resistant	several subsore to be che         PE         lasses against rojections.         PE         clothing for lainst chemical antistatic and properties         otwear for lainst chemical static and heat properties         es	Labelling Labelling Labelling Labelling Labelling	EN :	e of the glove lication. CEN Standard EN 166:2002 EN ISO 4007:201: CEN Standard EN 1149-1,2,3 13034:2005+A1:2 EN ISO 13982- 1:2004/A1:2010 EN ISO 6529:201: EN ISO 6530:200 N ISO 13688:201 EN 464:1994 N ISO 13287:202 N ISO 20345:201	20 mater 8 2009 3 5 13 20 11 9	crear ial car Clean the m	anot be calcu R daily and disinfe nanufacturer's in risk of R r professional us ording to the ma	duct has come into cor ith skin. lated in advance v emarks ect periodically accordi istructions. Use if there istructions. Use if there f splashing. emarks e only. Clean periodica nufacturer's instructio



# **CLEAR COAT GLOSS**

	20/01/2023 Date of compilation: 18/04/20	
ECI	TION 8: EXPOSURE CONTROLS/PERSONAL	PROTECTION (continued)
	Environmental exposure controls:	
	In accordance with the community legislation for spillage of both the product and its container. For	the protection of the environment it is recommended to avoid environmental
	spinage of both the product and its container. For	
·ECT	TION 9: PHYSICAL AND CHEMICAL PROPER	
.1	Information on basic physical and chemica	
	For complete information see the product datash	eet.
	Appearance:	
	Physical state at 20 °C:	Aerosol
	Appearance:	Not available
	Colour:	Colourless
	Odour:	Characteristic
	Odour threshold:	Non-applicable *
	Volatility:	
	Boiling point at atmospheric pressure:	Non-applicable *
	Vapour pressure at 20 °C:	400002 Pa
	Vapour pressure at 50 °C:	<300000 Pa (300 kPa)
	Evaporation rate at 20 °C:	Non-applicable *
	Product description:	
	Density at 20 °C:	780 kg/m <sup>3</sup>
	Relative density at 20 °C:	Non-applicable *
	Dynamic viscosity at 20 °C:	Non-applicable *
	Kinematic viscosity at 20 °C:	Non-applicable *
	Kinematic viscosity at 40 °C:	Non-applicable *
	Concentration:	Non-applicable *
	pH:	Non-applicable *
	Vapour density at 20 °C:	Non-applicable *
	Partition coefficient n-octanol/water 20 °C:	Non-applicable *
	Solubility in water at 20 °C:	Non-applicable *
	Solubility properties:	Non-applicable *
	Decomposition temperature:	Non-applicable *
	Melting point/freezing point:	Non-applicable *
	Recipient pressure:	Non-applicable *
	Flammability:	
	Flash Point:	Non-applicable
	Flammability (solid, gas):	Non-applicable *
	Autoignition temperature:	240 °C (Propellant)
	Lower flammability limit:	Non-applicable *
	Upper flammability limit:	Non-applicable *
	Particle characteristics:	
-	Median equivalent diameter:	Non-applicable
.2	Other information:	
	Information with regard to physical hazard	
	Explosive properties:	Non-applicable *



# **CLEAR COAT GLOSS**

Printing: 20/01/2023	Date of compilation: 18/04/2019	Revised: 18/02/2022	Version: 2 (Replaced 1)
SECTION 9: PHYSI	CAL AND CHEMICAL PROPERTIES	6 (continued)	
Oxidising prope	erties:	Non-applicable *	
Corrosive to me	etals:	Non-applicable *	
Heat of combus	Heat of combustion:		
components:	ercentage (by mass) of flammable	Non-applicable *	
Surface tension		Non-applicable *	
Refraction inde	x:	Non-applicable *	
*Not relevant due	to the nature of the product, not providing infor	mation property of its hazards.	

CECTION	10: STABILITY AND REACTIVITY	/
SECTION		Y .

#### 10.1 Reactivity:

No hazardous reactions are expected because the product is stable under recommended storage conditions. See section 7.

#### 10.2 Chemical stability:

Chemically stable under the indicated conditions of storage, handling and use.

#### 10.3 Possibility of hazardous reactions:

Under the specified conditions, hazardous reactions that lead to excessive temperatures or pressure are not expected.

#### **10.4** Conditions to avoid:

Applicable for handling and storage at room temperature:

Shock and friction	Contact with air	Increase in temperature	Sunlight	Humidity
Not applicable	Not applicable	Risk of combustion	Avoid direct impact	Not applicable

#### 10.5 Incompatible materials:

-				
Acids	Water	Oxidising materials	Combustible materials	Others
Avoid strong acids	Not applicable	Avoid direct impact	Not applicable	Avoid alkalis or strong bases

#### 10.6 Hazardous decomposition products:

See subsection 10.3, 10.4 and 10.5 to find out the specific decomposition products. Depending on the decomposition conditions, complex mixtures of chemical substances can be released: carbon dioxide (CO<sub>2</sub>), carbon monoxide and other organic compounds.

#### SECTION 11: TOXICOLOGICAL INFORMATION

#### 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008:

The experimental information related to the toxicological properties of the product itself is not available

Contains glycols. It is recommended not to breathe the vapours for prolonged periods of time due to the possibility of effects that are hazardous to the health .

### Dangerous health implications:

In case of exposure that is repetitive, prolonged or at concentrations higher than the recommended occupational exposure limits, adverse effects on health may result, depending on the means of exposure:

A- Ingestion (acute effect):

- Acute toxicity : Based on available data, the classification criteria are not met, however, it contains substances classified as dangerous for consumption. For more information see section 3.
- Corrosivity/Irritability: Based on available data, the classification criteria are not met. However, it does contain substances classified as hazardous for this effect. For more information see section 3.
- B- Inhalation (acute effect):
  - Acute toxicity : Based on available data, the classification criteria are not met. However, it contains substances classified as hazardous for inhalation. For more information see section 3.
  - Corrosivity/Irritability: Based on available data, the classification criteria are not met. However, it contains substances classified as hazardous for inhalation. For more information see section 3.
- C- Contact with the skin and the eyes (acute effect):



# **CLEAR COAT GLOSS**

20/01/2023	Date of compilation: 18/04/2019	Revised: 18/02/2022	Version: 2 (Replaced 1)	
ION 11: TOXI	COLOGICAL INFORMATION (contin	ued)		
classified as - Contact v	with the skin: Based on available data, the hazardous for skin contact. For more info with the eyes: Produces eye damage after (carcinogenicity, mutagenicity and toxicit	ormation see section 3. r contact.	met. However, it contains	substances
as hazardou IARC: 2-b - Mutageni hazardous fo - Reproduc	enicity: Based on available data, the class is for the effects mentioned. For more info utoxyethanol (3); Xylene (3); Hydrocarbo icity: Based on available data, the classific or this effect. For more information see se tive toxicity: Based on available data, the hazardous for this effect. For more infor effects:	ormation see section 3. ons, C9, aromatics (3) cation criteria are not met, as i ection 3. e classification criteria are not r	t does not contain substan	ces classified
hazardous w - Skin: Bas hazardous fe	bry: Based on available data, the classification with sensitising effects. For more informat sed on available data, the classification cri- for this effect. For more information see se	ion see section 3. iteria are not met, as it does ne ection 3.		
	jet organ toxicity (STOT) - single exposur			
vomiting, co	high concentration can interfere with the onfusion, and in serious cases, loss of con get organ toxicity (STOT)-repeated exposi	sciousness.	ig headache, dizziness, ver	tigo, nausea,
- Specific t it does not d	arget organ toxicity (STOT)-repeated exp contain substances classified as hazardous seated exposure may cause skin dryness	osure: Based on available data s for this effect. For more infor		are not met,
<ul> <li>Specific t it does not o</li> <li>Skin: Rep</li> <li>H- Aspiration h</li> <li>Based on av</li> <li>for this effect</li> </ul>	arget organ toxicity (STOT)-repeated exp contain substances classified as hazardous beated exposure may cause skin dryness azard: railable data, the classification criteria are ct. For more information see section 3.	osure: Based on available data s for this effect. For more infor or cracking	mation see section 3.	
<ul> <li>Specific t it does not o</li> <li>Skin: Rep H- Aspiration h Based on av for this effec</li> <li>Other information</li> </ul>	arget organ toxicity (STOT)-repeated exp contain substances classified as hazardous beated exposure may cause skin dryness azard: railable data, the classification criteria are ct. For more information see section 3.	osure: Based on available data s for this effect. For more infor or cracking	mation see section 3.	
<ul> <li>Specific t it does not o</li> <li>Skin: Rep H- Aspiration h Based on av for this effec</li> <li>Other information</li> <li>Non-applicable</li> </ul>	arget organ toxicity (STOT)-repeated exp contain substances classified as hazardous beated exposure may cause skin dryness azard: vailable data, the classification criteria are ct. For more information see section 3.	oosure: Based on available data s for this effect. For more infor or cracking not met. However, it does co	mation see section 3.	
<ul> <li>Specific t it does not o</li> <li>Skin: Rep H- Aspiration h Based on av for this effec</li> <li>Other information</li> <li>Non-applicable</li> </ul>	arget organ toxicity (STOT)-repeated exp contain substances classified as hazardous beated exposure may cause skin dryness azard: railable data, the classification criteria are ct. For more information see section 3. ation:	oosure: Based on available data s for this effect. For more infor or cracking not met. However, it does co	mation see section 3.	as hazardou:
<ul> <li>Specific to it does not of a skin: Rep</li> <li>H- Aspiration h</li> <li>Based on av for this effect</li> <li>Other information</li> <li>Non-applicable</li> </ul>	arget organ toxicity (STOT)-repeated exp contain substances classified as hazardous beated exposure may cause skin dryness azard: vailable data, the classification criteria are ct. For more information see section 3.	oosure: Based on available data s for this effect. For more infor or cracking not met. However, it does con	ntain substances classified	
<ul> <li>Specific to it does not of a skin: Rep</li> <li>Skin: Rep</li> <li>H- Aspiration h</li> <li>Based on av for this effect</li> <li>Other information</li> <li>Non-applicable</li> <li>Specific toxico</li> <li>Dimethyl ether</li> </ul>	arget organ toxicity (STOT)-repeated exp contain substances classified as hazardous beated exposure may cause skin dryness azard: railable data, the classification criteria are ct. For more information see section 3. ation:	oosure: Based on available data s for this effect. For more infor or cracking not met. However, it does con : LD50 oral	Acute toxicity >2000 mg/kg	as hazardous
<ul> <li>Specific to it does not of a skin: Rep</li> <li>Skin: Rep</li> <li>H- Aspiration h</li> <li>Based on aw for this effect</li> <li>Other information</li> <li>Non-applicable</li> <li>Specific toxico</li> <li>Dimethyl ether</li> <li>CAS: 115-10-6</li> </ul>	arget organ toxicity (STOT)-repeated exp contain substances classified as hazardous beated exposure may cause skin dryness azard: railable data, the classification criteria are ct. For more information see section 3. ation:	oosure: Based on available data s for this effect. For more infor or cracking not met. However, it does con : LD50 oral LD50 dermal	Acute toxicity >2000 mg/kg >2000 mg/kg	as hazardous
<ul> <li>Specific to it does not of a skin: Rep</li> <li>H- Aspiration h</li> <li>Based on av for this effect</li> <li>Other information</li> <li>Non-applicable</li> <li>Specific toxico</li> <li>Dimethyl ether</li> <li>CAS: 115-10-6</li> <li>EC: 204-065-8</li> </ul>	arget organ toxicity (STOT)-repeated exp contain substances classified as hazardous beated exposure may cause skin dryness azard: railable data, the classification criteria are ct. For more information see section 3. ation:	oosure: Based on available data s for this effect. For more infor or cracking not met. However, it does con LD50 oral LD50 dermal LC50 inhalatio	Acute toxicity >2000 mg/kg n 308,5 mg/L (4 h)	as hazardous
<ul> <li>Specific to it does not of a skin: Rep.</li> <li>H- Aspiration h Based on aw for this effect</li> <li>Other information</li> <li>Non-applicable</li> <li>Specific toxico</li> <li>Dimethyl ether</li> <li>CAS: 115-10-6</li> <li>EC: 204-065-8</li> <li>acetone</li> </ul>	arget organ toxicity (STOT)-repeated exp contain substances classified as hazardous beated exposure may cause skin dryness azard: railable data, the classification criteria are ct. For more information see section 3. ation:	oosure: Based on available data s for this effect. For more infor or cracking not met. However, it does col LD50 oral LD50 dermal LD50 oral LD50 oral	Acute toxicity >2000 mg/kg >2000 mg/kg n 308,5 mg/L (4 h) 5800 mg/kg	as hazardou Genus Rat Rat
<ul> <li>Specific to it does not of Skin: Rep H- Aspiration h Based on av for this effect</li> <li>Other information</li> <li>Non-applicable</li> <li>Specific toxico</li> <li>Dimethyl ether</li> <li>CAS: 115-10-6</li> <li>EC: 204-065-8</li> <li>acetone</li> <li>CAS: 67-64-1</li> </ul>	arget organ toxicity (STOT)-repeated exp contain substances classified as hazardous beated exposure may cause skin dryness azard: railable data, the classification criteria are ct. For more information see section 3. ation:	s for this effect. For more infor or cracking not met. However, it does con LD50 oral LD50 oral LD50 oral LD50 oral LD50 oral LD50 oral LD50 dermal	Acute toxicity >2000 mg/kg >2000 mg/kg >2000 mg/kg 100 mg/kg >2000 mg/kg 100 mg/kg 100 mg/kg 100 mg/kg 100 mg/kg 100 mg/kg	as hazardou Genus Rat Rat Rabit
<ul> <li>Specific to it does not of a skin: Rep.</li> <li>H- Aspiration h Based on aw for this effect</li> <li>Other information</li> <li>Non-applicable</li> <li>Specific toxico</li> <li>Dimethyl ether</li> <li>CAS: 115-10-6</li> <li>EC: 204-065-8</li> <li>acetone</li> </ul>	arget organ toxicity (STOT)-repeated exp contain substances classified as hazardous beated exposure may cause skin dryness azard: railable data, the classification criteria are ct. For more information see section 3. ation:	s for this effect. For more infor or cracking not met. However, it does con LD50 oral LD50 oral LD50 dermal LD50 dermal LD50 dermal LD50 dermal LC50 inhalatio	Acute toxicity >2000 mg/kg >2000 mg/kg >2000 mg/kg 100 mg/kg 2000 mg/kg	as hazardou Genus Arrow Rat Rat Rabit Rat
<ul> <li>Specific to it does not of a skin: Rep</li> <li>Skin: Rep</li> <li>H- Aspiration h</li> <li>Based on aw for this effect</li> <li>Other information</li> <li>Non-applicable</li> <li>Specific toxico</li> <li>Dimethyl ether</li> <li>CAS: 115-10-6</li> <li>EC: 204-065-8</li> <li>acetone</li> <li>CAS: 67-64-1</li> <li>EC: 200-662-2</li> <li>2-butoxyethanol</li> </ul>	arget organ toxicity (STOT)-repeated exp contain substances classified as hazardous beated exposure may cause skin dryness azard: railable data, the classification criteria are ct. For more information see section 3. ation:	oosure: Based on available data s for this effect. For more infor or cracking not met. However, it does con LD50 oral LD50 dermal LD50 dermal LD50 dermal LD50 dermal LD50 dermal LD50 dermal LD50 oral	Acute toxicity >2000 mg/kg >2000 mg/kg >2000 mg/kg n 308,5 mg/L (4 h) 5800 mg/kg n 7426 mg/kg n 76 mg/L (4 h) 1200 mg/kg	as hazardou Genus Rat Rat Rabbit Rat Rat
<ul> <li>Specific to it does not of Skin: Rep H- Aspiration h Based on av for this effect</li> <li>Other information</li> <li>Non-applicable</li> <li>Specific toxico</li> <li>Dimethyl ether</li> <li>CAS: 115-10-6</li> <li>EC: 204-065-8</li> <li>acetone</li> <li>CAS: 67-64-1</li> <li>EC: 200-662-2</li> <li>2-butoxyethanol</li> <li>CAS: 111-76-2</li> </ul>	arget organ toxicity (STOT)-repeated exp contain substances classified as hazardous beated exposure may cause skin dryness azard: railable data, the classification criteria are ct. For more information see section 3. ation:	oosure: Based on available data s for this effect. For more infor or cracking not met. However, it does con LD50 oral LD50 dermal LD50 dermal LD50 dermal LD50 dermal LD50 dermal LD50 dermal	Acute toxicity >2000 mg/kg >2000 mg/kg >2000 mg/kg n 308,5 mg/L (4 h) 5800 mg/kg 7426 mg/kg n 76 mg/L (4 h) 1200 mg/kg 3000 mg/kg	as hazardou Genus Rat Rat Rabbit Rat Rat
<ul> <li>Specific to it does not of a skin: Rep</li> <li>Skin: Rep</li> <li>H- Aspiration h</li> <li>Based on aw for this effect</li> <li>Other information</li> <li>Non-applicable</li> <li>Specific toxico</li> <li>Dimethyl ether</li> <li>CAS: 115-10-6</li> <li>EC: 204-065-8</li> <li>acetone</li> <li>CAS: 67-64-1</li> <li>EC: 200-662-2</li> <li>2-butoxyethanol</li> </ul>	arget organ toxicity (STOT)-repeated exp contain substances classified as hazardous beated exposure may cause skin dryness azard: railable data, the classification criteria are ct. For more information see section 3. ation:	oosure: Based on available data s for this effect. For more infor or cracking not met. However, it does con LD50 oral LD50 dermal LD50 dermal LD50 dermal LD50 dermal LD50 dermal LD50 dermal LD50 oral	Acute toxicity >2000 mg/kg >2000 mg/kg >2000 mg/kg n 308,5 mg/L (4 h) 5800 mg/kg 7426 mg/kg n 76 mg/L (4 h) 1200 mg/kg 3000 mg/kg	as hazardous Genus A Rat Rat Rabbit Rat
<ul> <li>Specific to it does not of Skin: Rep H- Aspiration h Based on av for this effect</li> <li>Other information</li> <li>Non-applicable</li> <li>Specific toxico</li> <li>Dimethyl ether</li> <li>CAS: 115-10-6</li> <li>EC: 204-065-8</li> <li>acetone</li> <li>CAS: 67-64-1</li> <li>EC: 200-662-2</li> <li>2-butoxyethanol</li> <li>CAS: 111-76-2</li> </ul>	arget organ toxicity (STOT)-repeated exp contain substances classified as hazardous beated exposure may cause skin dryness azard: railable data, the classification criteria are ct. For more information see section 3. ation:	oosure: Based on available data s for this effect. For more infor or cracking not met. However, it does con LD50 oral LD50 dermal LD50 dermal LD50 dermal LD50 dermal LD50 dermal LD50 dermal	Acute toxicity >2000 mg/kg >2000 mg/kg >2000 mg/kg >2000 mg/kg 1200 mg/kg 12789 mg/kg	as hazardous Genus A Genus A Rat A Rat A Rat A Rat A Rat A Rat
<ul> <li>Specific to it does not of Skin: Rep H- Aspiration h Based on aw for this effect</li> <li>Other information</li> <li>Non-applicable</li> <li>Specific toxico</li> <li>Dimethyl ether</li> <li>CAS: 115-10-6</li> <li>EC: 204-065-8</li> <li>acetone</li> <li>CAS: 67-64-1</li> <li>EC: 200-662-2</li> <li>2-butoxyethanol</li> <li>CAS: 111-76-2</li> <li>EC: 203-905-0</li> </ul>	arget organ toxicity (STOT)-repeated exp contain substances classified as hazardous beated exposure may cause skin dryness azard: railable data, the classification criteria are ct. For more information see section 3. ation:	e not met. However, it does con s for this effect. For more infor or cracking not met. However, it does con LD50 oral LD50 dermal LC50 inhalatio LD50 dermal LC50 inhalatio LD50 dermal LC50 inhalatio	Acute toxicity >2000 mg/kg >2000 mg/kg >2000 mg/kg n 308,5 mg/L (4 h) 5800 mg/kg 7426 mg/kg n 76 mg/L (4 h) 1200 mg/kg a 3000 mg/kg n 3 mg/L (ATEi)	as hazardous Genus Rat Rat Rabbit Rat Rabbit
<ul> <li>Specific to it does not of Skin: Rep H- Aspiration h Based on av for this effect</li> <li>Other information</li> <li>Non-applicable</li> <li>Specific toxico</li> <li>Dimethyl ether</li> <li>CAS: 115-10-6</li> <li>EC: 204-065-8</li> <li>acetone</li> <li>CAS: 67-64-1</li> <li>EC: 200-662-2</li> <li>2-butoxyethanol</li> <li>CAS: 111-76-2</li> <li>EC: 203-905-0</li> <li>N-butyl acetate</li> </ul>	arget organ toxicity (STOT)-repeated exp contain substances classified as hazardous beated exposure may cause skin dryness azard: railable data, the classification criteria are ct. For more information see section 3. ation:	e not met. However, it does con s for this effect. For more infor or cracking not met. However, it does con LD50 oral LD50 dermal LC50 inhalatio LD50 dermal LC50 inhalatio LD50 dermal LC50 inhalatio LD50 dermal LC50 inhalatio LD50 dermal LC50 inhalatio LD50 dermal LD50 dermal LC50 inhalatio	Acute toxicity           >2000 mg/kg           >2000 mg/kg           >2000 mg/kg           >2000 mg/kg           >2000 mg/kg           7426 mg/kg           7426 mg/kg           76 mg/L (4 h)           1200 mg/kg           3000 mg/kg           1200 mg/kg	as hazar

ATE mix

40000 mg/kg (Calculation method)

52380,95 mg/kg (Calculation method)

LD50 oral

LD50 oral

LD50 dermal

LC50 inhalation

0 %

0 %

LD50 dermal

LC50 inhalation

3523 mg/kg

1100 mg/kg

11 mg/L (ATEi)

>2000 mg/kg

>2000 mg/kg

Ingredient(s) of unknown toxicity

>20 mg/L

Xylene

CAS: 1330-20-7

EC: 215-535-7

EC: 918-668-5

Oral

Dermal

CAS: 128601-23-0

Hydrocarbons, C9, aromatics

Acute Toxicity Estimate (ATE mix):

Rat



# **CLEAR COAT GLOSS**

Printing: 20/01/2023	Date of compilation: 18/04/2019	Revised: 18/02/2022	Version: 2 (Replaced 1)					
SECTION 11: TOXICOLOGICAL INFORMATION (continued)								
Inhalation	83,97 mg/L (4 h) (Calcu	lation method)	0 %					
11.2 Information o	n other hazards:							

### Endocrine disrupting properties

Endocrine-disrupting properties: The product fails to meet the criteria.

### Other information

Non-applicable

# SECTION 12: ECOLOGICAL INFORMATION

The experimental information related to the eco-toxicological properties of the product itself is not available

### 12.1 Toxicity:

#### Acute toxicity:

Identification		Concentration	Species	Genus
acetone	LC50	5540 mg/L (96 h)	Oncorhynchus mykiss	Fish
CAS: 67-64-1	EC50	8800 mg/L (48 h)	Daphnia pulex	Crustacean
EC: 200-662-2	EC50	3400 mg/L (48 h)	Chlorella pyrenoidosa	Algae
Hydrocarbons, C9, aromatics	LC50	>1 - 10 mg/L (96 h)		Fish
CAS: 128601-23-0	EC50	>1 - 10 mg/L (48 h)		Crustacean
EC: 918-668-5	EC50	>1 - 10 mg/L (72 h)		Algae
2-butoxyethanol	LC50	1490 mg/L (96 h)	Lepomis macrochirus	Fish
CAS: 111-76-2	EC50	1815 mg/L (48 h)	Daphnia magna	Crustacean
EC: 203-905-0	EC50	911 mg/L (72 h)	Pseudokirchneriella subcapitata	Algae
N-butyl acetate	LC50	Non-applicable		
CAS: 123-86-4	EC50	Non-applicable		
EC: 204-658-1	EC50	675 mg/L (72 h)	Scenedesmus subspicatus	Algae

#### Chronic toxicity:

Identification		Concentration	Species	Genus
acetone	NOEC	Non-applicable		
CAS: 67-64-1 EC: 200-662-2	NOEC	2212 mg/L	Daphnia magna	Crustacean
2-butoxyethanol	NOEC	100 mg/L	Danio rerio	Fish
CAS: 111-76-2 EC: 203-905-0	NOEC	100 mg/L	Daphnia magna	Crustacean
N-butyl acetate	NOEC	Non-applicable		
CAS: 123-86-4 EC: 204-658-1	NOEC	23,2 mg/L	Daphnia magna	Crustacean
Xylene	NOEC	1,3 mg/L	Oncorhynchus mykiss	Fish
CAS: 1330-20-7 EC: 215-535-7	NOEC	1,17 mg/L	Ceriodaphnia dubia	Crustacean

# 12.2 Persistence and degradability:

#### Substance-specific information:

Identification	Degi	adability	Biodegradal	oility
acetone	BOD5	Non-applicable	Concentration	100 mg/L
CAS: 67-64-1	COD	Non-applicable	Period	28 days
EC: 200-662-2	BOD5/COD	Non-applicable	% Biodegradable	96 %
2-butoxyethanol	BOD5	0,71 g O2/g	Concentration	100 mg/L
CAS: 111-76-2	COD	2,2 g O2/g	Period	14 days
EC: 203-905-0	BOD5/COD	0,32	% Biodegradable	96 %
N-butyl acetate	BOD5	Non-applicable	Concentration	Non-applicable
CAS: 123-86-4	COD	Non-applicable	Period	5 days
EC: 204-658-1	BOD5/COD	Non-applicable	% Biodegradable	84 %
Xylene	BOD5	Non-applicable	Concentration	Non-applicable
CAS: 1330-20-7	COD	Non-applicable	Period	28 days
EC: 215-535-7	BOD5/COD	Non-applicable	% Biodegradable	88 %

12.3 Bioaccumulative potential:



# **CLEAR COAT GLOSS**

	cific information:				
	Identificatio	n		Bioaccu	umulation potential
acetone				BCF	1
CAS: 67-64-1			-	Pow Log	-0.24
EC: 200-662-2				Potential	Low
2-butoxyethanol				BCF	3
CAS: 111-76-2			-	Pow Log	0.83
EC: 203-905-0				Potential	Low
N-butyl acetate				BCF	4
CAS: 123-86-4			-	Pow Log	1.78
EC: 204-658-1				Potential	Low
Xylene				BCF	9
CAS: 1330-20-7			-	Pow Log	2.77
EC: 215-535-7				Potential	Low
.4 Mobility in soil:					
	Identification	Absor	ption/desorption		Volatility
Dimethyl ether		17.00			
		Koc	Non-applicable	Henry	Non-applicable
CAS: 115-10-6		KOC Conclusion	Non-applicable Non-applicable	Henry Dry soil	Non-applicable Non-applicable
CAS: 115-10-6 EC: 204-065-8				Dry soil	
		Conclusion	Non-applicable	Dry soil	Non-applicable
EC: 204-065-8		Conclusion Surface tension	Non-applicable       1,136E-2 N/m (25 °C)       1       Very High	Dry soil Moist soil Henry Dry soil	Non-applicable Non-applicable
EC: 204-065-8 acetone		Conclusion Surface tension Koc	Non-applicable           1,136E-2 N/m (25 °C)           1	Dry soil Moist soil Henry Dry soil	Non-applicable           Non-applicable           2,93 Pa·m³/mol
EC: 204-065-8 acetone CAS: 67-64-1		Conclusion Surface tension Koc Conclusion Surface tension Koc	Non-applicable       1,136E-2 N/m (25 °C)       1       Very High	Dry soil Moist soil Henry Dry soil	Non-applicable       Non-applicable       2,93 Pa·m³/mol       Yes       Yes
EC: 204-065-8 acetone CAS: 67-64-1 EC: 200-662-2 2-butoxyethanol CAS: 111-76-2		Conclusion Surface tension Koc Conclusion Surface tension	Non-applicable           1,136E-2 N/m (25 °C)           1           Very High           2,304E-2 N/m (25 °C)           8           Very High	Dry soil Moist soil Henry Dry soil Moist soil Henry Dry soil	Non-applicable       Non-applicable       2,93 Pa·m³/mol       Yes       Yes       1,621E-1 Pa·m³/mi       No
EC: 204-065-8 acetone CAS: 67-64-1 EC: 200-662-2 2-butoxyethanol		Conclusion Surface tension Koc Conclusion Surface tension Koc	Non-applicable           1,136E-2 N/m (25 °C)           1           Very High           2,304E-2 N/m (25 °C)           8           Very High           2,729E-2 N/m (25 °C)	Dry soil Moist soil Henry Dry soil Moist soil Henry Dry soil	Non-applicable         Non-applicable         2,93 Pa·m³/mol         Yes         Yes         1,621E-1 Pa·m³/mol         No         Yes
EC: 204-065-8 acetone CAS: 67-64-1 EC: 200-662-2 2-butoxyethanol CAS: 111-76-2		Conclusion Surface tension Koc Conclusion Surface tension Koc Conclusion Surface tension Koc	Non-applicable           1,136E-2 N/m (25 °C)           1           Very High           2,304E-2 N/m (25 °C)           8           Very High	Dry soil Moist soil Henry Dry soil Moist soil Henry Dry soil	Non-applicable       Non-applicable       2,93 Pa·m³/mol       Yes       Yes       1,621E-1 Pa·m³/mi       No
EC: 204-065-8 acetone CAS: 67-64-1 EC: 200-662-2 2-butoxyethanol CAS: 111-76-2 EC: 203-905-0 N-butyl acetate CAS: 123-86-4		Conclusion Surface tension Koc Conclusion Surface tension Koc Conclusion Koc Conclusion	Non-applicable           1,136E-2 N/m (25 °C)           1           Very High           2,304E-2 N/m (25 °C)           8           Very High           2,729E-2 N/m (25 °C)           Non-applicable           Non-applicable	Dry soilMoist soilHenryDry soilMoist soilHenryDry soilMoist soilHenryDry soilMoist soilHenryDry soilDry soil	Non-applicable         Non-applicable         2,93 Pa·m³/mol         Yes         1,621E-1 Pa·m³/m         No         Yes         No         Yes         No         Yes         No-applicable         Non-applicable         Non-applicable         Non-applicable
EC: 204-065-8 acetone CAS: 67-64-1 EC: 200-662-2 2-butoxyethanol CAS: 111-76-2 EC: 203-905-0 N-butyl acetate		Conclusion Surface tension Koc Conclusion Surface tension Koc Conclusion Surface tension Koc	Non-applicable           1,136E-2 N/m (25 °C)           1           Very High           2,304E-2 N/m (25 °C)           8           Very High           2,729E-2 N/m (25 °C)           Non-applicable           Non-applicable           2,478E-2 N/m (25 °C)	Dry soilMoist soilHenryDry soilMoist soilHenryDry soilMoist soilHenryDry soilMoist soilHenryDry soilDry soil	Non-applicable         Non-applicable         2,93 Pa·m³/mol         Yes         1,621E-1 Pa·m³/m         No         Yes         No         Yes         Non-applicable         Non-applicable         Non-applicable         Non-applicable
EC: 204-065-8 acetone CAS: 67-64-1 EC: 200-662-2 2-butoxyethanol CAS: 111-76-2 EC: 203-905-0 N-butyl acetate CAS: 123-86-4 EC: 204-658-1 Xylene		Conclusion Surface tension Koc Conclusion Surface tension Koc Conclusion Surface tension Koc Conclusion Surface tension Surface tension	Non-applicable           1,136E-2 N/m (25 °C)           1           Very High           2,304E-2 N/m (25 °C)           8           Very High           2,729E-2 N/m (25 °C)           Non-applicable           Non-applicable           2,478E-2 N/m (25 °C)           202	Dry soilMoist soilHenryDry soilMoist soilHenryDry soilMoist soilHenryDry soilHenryDry soilHenryHenryHenryHenryHenryHenryHenryHenryHenryHenry	Non-applicable         Non-applicable         2,93 Pa·m³/mol         Yes         Yes         1,621E-1 Pa·m³/mol         No         Yes         No         Yes         Non-applicable         Non-applicable         Non-applicable         S24,86 Pa·m³/mol
EC: 204-065-8 acetone CAS: 67-64-1 EC: 200-662-2 2-butoxyethanol CAS: 111-76-2 EC: 203-905-0 N-butyl acetate CAS: 123-86-4 EC: 204-658-1		Conclusion Surface tension Koc Conclusion Surface tension Koc Conclusion Surface tension Koc Conclusion Surface tension	Non-applicable           1,136E-2 N/m (25 °C)           1           Very High           2,304E-2 N/m (25 °C)           8           Very High           2,729E-2 N/m (25 °C)           Non-applicable           Non-applicable           2,478E-2 N/m (25 °C)	Dry soilMoist soilHenryDry soilMoist soilHenryDry soilMoist soilHenryDry soilMoist soilHenryDry soilMoist soil	Non-applicable         Non-applicable         2,93 Pa·m³/mol         Yes         Yes         1,621E-1 Pa·m³/mol         No         Yes         No         Yes         Non-applicable         Non-applicable         Non-applicable         Non-applicable

#### **12.7** Other adverse effects:

Not described

# SECTION 13: DISPOSAL CONSIDERATIONS

#### **13.1** Waste treatment methods:

Code	Description	Waste class (Regulation (EU) No 1357/2014)
16 05 04*	gases in pressure containers (including halons) containing hazardous substances	Dangerous

### Type of waste (Regulation (EU) No 1357/2014):

HP14 Ecotoxic, HP3 Flammable, HP4 Irritant — skin irritation and eye damage

#### Waste management (disposal and evaluation):

Consult the authorized waste service manager on the assessment and disposal operations in accordance with Annex 1 and Annex 2 (Directive 2008/98/EC). As under 15 01 (2014/955/EC) of the code and in case the container has been in direct contact with the product, it will be processed the same way as the actual product. Otherwise, it will be processed as non-dangerous residue. Waste should not be disposed of to drains. See paragraph 6.2.



# **CLEAR COAT GLOSS**

rinting: 20/01/2023	Date o	of compilation: 18/04/2019	Revised: 18/02/2022	Version: 2 (Replaced 1)
SECTION 13: DISPC	osal CC	NSIDERATIONS (continued)		
Regulations re	lated to	waste management:		
-		-	006 (REACH) the community	or state provisions related to waste
management are				F
Community legis	lation: D	irective 2008/98/EC, 2014/955/EU	, Regulation (EU) No 1357/20	014
SECTION 14: TRANS	SPORT	INFORMATION		
Transport of	dangero	us goods by land:		
_	-	1 and RID 2021:		
		UN number or ID number:	UN1950	
	14.2	UN proper shipping name:	AEROSOLS	
***		Transport hazard class(es):	2	
$\langle \simeq \rangle$	•	Labels:	2.1	
		Packing group:	N/A	
		Environmental hazards:	No	
	14.6	Special precautions for user		
		Special regulations:	190, 327, 344, 625	
		Tunnel restriction code: Physico-Chemical properties:	D see section 9	
		Limited quantities:	1 L	
	14 7	Maritime transport in bulk		
	14.7	according to IMO instruments:	Non-applicable	
Transport of o	dangero	us goods by sea:		
With regard to	IMDG 40	-20:		
5		UN number or ID number:	UN1950	
		UN proper shipping name:	AEROSOLS	
		Transport hazard class(es):	2	
	_	Labels:	2.1	
	14.4	Packing group:	N/A	
2	14.5	Marine pollutant:	No	
	14.6	Special precautions for user		
		Special regulations:	63, 959, 190, 277, 327, 344	ł
		EmS Codes:	F-D, S-U	
		Physico-Chemical properties:	see section 9	
		Limited quantities:	1L New genetice block	
		Segregation group:	Non-applicable	
	14.7	Maritime transport in bulk according to IMO instruments:	Non-applicable	
Transport of e	dangero	us goods by air:		
With regard to	-			
		UN number or ID number:	UN1950	
JAL .		UN proper shipping name:	AEROSOLS	
	14.3	Transport hazard class(es):	2	
		Labels:	2.1	
2		Packing group:	N/A	
Ť		Environmental hazards:	No	
	14.6	Special precautions for user		
		Physico-Chemical properties:	see section 9	
	14.7	Maritime transport in bulk according to IMO instruments:	Non-applicable	



# **CLEAR COAT GLOSS**

Printing: 20/01/2023 Date of compilation: 18/04/2019 Revised: 18/02/2022 Version: 2 (Replaced 1) SECTION 15: REGULATORY INFORMATION 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture: Candidate substances for authorisation under the Regulation (EC) No 1907/2006 (REACH): Non-applicable Substances included in Annex XIV of REACH ("Authorisation List") and sunset date: Non-applicable Regulation (EC) No 1005/2009, about substances that deplete the ozone layer: Non-applicable Article 95, REGULATION (EU) No 528/2012: Non-applicable REGULATION (EU) No 649/2012, in relation to the import and export of hazardous chemical products: Non-applicable Seveso III: Lower-tier Upper-tier Section Description requirements requirements P3a FLAMMABLE AEROSOLS 150 500 Limitations to commercialisation and the use of certain dangerous substances and mixtures (Annex XVII REACH, etc ....): Regulation (EU) 2019/1148 on the marketing and use of explosives precursors: Contains acetone. Product under the provisions of

Article 9. However, products that contain explosives precursors only to such a small extent and in such complex mixtures that the extraction of the explosives precursors is technically extremely difficult should be excluded from the scope of this Regulation. Shall not be used in:

—ornamental articles intended to produce light or colour effects by means of different phases, for example in ornamental lamps and ashtrays,

-tricks and jokes,

-games for one or more participants, or any article intended to be used as such, even with ornamental aspects.

#### Specific provisions in terms of protecting people or the environment:

It is recommended to use the information included in this safety data sheet as a basis for conducting workplace-specific risk assessments in order to establish the necessary risk prevention measures for the handling, use, storage and disposal of this product.

#### Other legislation:

The product could be affected by sectorial legislation

Council Directive 75/324/EEC of 20 May 1975 on the approximation of the laws of the Member States relating to aerosol dispensers

Commission Directive 94/1/EC of 6 January 1994 adapting some technicalities of Council Directive 75/324/EEC on the approximation of the laws of the relating Member States to aerosol dispensers

Commission Directive 2008/47/EC of 8 April 2008 amending, for the purposes of adapting to technical progress, Council Directive 75/324/EEC on the approximation of the laws of the Member States relating to aerosol dispensers

Commission Directive 2013/10/EU of 19 March 2013 amending Council Directive 75/324/EEC on the approximation of the laws of the Member States relating to aerosol dispensers in order to adapt its labelling provisions to Regulation (EC) No 1272/2008 of the European Parliament and of the Council on classification, labelling and packaging of substances and mixtures

COMMISSION DIRECTIVE (EU) 2016/2037 of 21 November 2016 amending Council Directive 75/324/EEC as regards the maximum allowable pressure of aerosol dispensers and to adapt its labelling provisions to Regulation (EC) No 1272/2008 of the European Parliament and of the Council on classification, labelling and packaging of substances and mixtures

### **15.2** Chemical safety assessment:

The supplier has not carried out evaluation of chemical safety.

### SECTION 16: OTHER INFORMATION

#### Legislation related to safety data sheets:

The SDS shall be supplied in an official language of the country where the product is placed on the market. This safety data sheet has been designed in accordance with ANNEX II-Guide to the compilation of safety data sheets of Regulation (EC) No 1907/2006 (COMMISSION REGULATION (EU) 2020/878).

# Modifications related to the previous Safety Data Sheet which concerns the ways of managing risks.:

COMMISSION REGULATION (EU) 2020/878

## Texts of the legislative phrases mentioned in section 2:

### H319: Causes serious eye irritation.

H336: May cause drowsiness or dizziness.

H412: Harmful to aquatic life with long lasting effects.

H229: Pressurised container: May burst if heated.

H222: Extremely flammable aerosol.

#### Texts of the legislative phrases mentioned in section 3:

-adds-

Safety data sheet

This SDS is an English translation of COMMISSION REGULATION (EU) 2020/878, without any country-specific legislation

# **CLEAR COAT GLOSS**

Printing: 20/01/2023	Date of compilation: 18/04/2019	Revised: 18/02/2022	Version: 2 (Replaced 1)
SECTION 16: OTHE	R INFORMATION (continued)		
individual compo <b>CLP Regulatio</b> Acute Tox. 3: H Acute Tox. 4: H Acute Tox. 4: H Aquatic Chronic Asp. Tox. 1: H30 Eye Irrit. 2: H31 Flam. Gas 1A: H Flam. Liq. 2: H22 Flam. Liq. 3: H22 Press. Gas: H28 Skin Irrit. 2: H33 STOT SE 3: H33 STOT SE 3: H33	licated do not refer to the product itself; t onents which appear in section 3 <b>on (EC) No 1272/2008:</b> 331 - Toxic if inhaled. 302 - Harmful if swallowed. 312+H332 - Harmful in contact with skin 2: H411 - Toxic to aquatic life with long 04 - May be fatal if swallowed and enters 19 - Causes serious eye irritation. 1220 - Extremely flammable gas. 225 - Highly flammable liquid and vapour. 226 - Flammable liquid and vapour. 20 - Contains gas under pressure, may ex 15 - Causes skin irritation. 36 - May cause drowsiness or dizziness.	or if inhaled. lasting effects. airways.	nformative purposes and refer to the
Classification Eye Irrit. 2: Calo STOT SE 3: Calo Aquatic Chronic Aerosol 1: Calcu Aerosol 1: Calcu	culation method culation method 3: Calculation method Ilation method		
Advice related			
	nmended in order to prevent industrial ris f this safety data sheet, as well as the lab		t and to facilitate their comprehension and
-	ographical sources:		
http://echa.euro http://eur-lex.eu			
	and acronyms:		
IMDG: Internati IATA: Internatio ICAO: Internatio COD: Chemical BOD5: 5day bio BCF: Bioconcent LD50: Lethal Do LC50: Lethal Co EC50: Effective LogPOW: Octan	ose 50 ncentration 50 concentration 50 olwater partition coefficient pefficient of organic carbon		by road
IARC: Internatio	onal Agency for Research on Cancer		

The information contained in this safety data sheet is based on sources, technical knowledge and current legislation at European and state level, without being able to guarantee its accuracy. This information cannot be considered a guarantee of the properties of the product, it is simply a description of the security requirements. The occupational methodology and conditions for users of this product are not within our awareness or control, and it is ultimately the responsibility of the user to take the necessary measures to obtain the legal requirements concerning the manipulation, storage, use and disposal of chemical products. The information on this safety data sheet only refers to this product, which should not be used for needs other than those specified.