adds



This SDS is an English translation of COMMISSION REGULATION (EU) 2020/878, without any country-specific legislation

CLEAR COAT MAT

Printing: 20/01/2023 Date of compilation: 18/04/2019 Revised: 18/01/2023 Version: 3 (Replaced 2)

SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1 Product identifier: CLEAR COAT MAT

Other means of identification:

UFI: 82F5-K3JR-100R-2AF2

1.2 Relevant identified uses of the substance or mixture and uses advised against:

Relevant uses: Car repair; spray paint. For professional users only.

Uses advised against: All uses not specified in this section or in section 7.3

1.3 Details of the supplier of the safety data sheet:

Troton Sp. z o.o. Ząbrowo 14A

78-120 Gościno - Zachodniopomorskie - Polska Phone: +48 94 35 123 94 - Fax: +48 94 35 126 22

troton@troton.com.pl www.troton.pl / www.troton.eu

1.4 Emergency telephone number: (8am-4pm)+48 094 35 123 94; 112

SECTION 2: HAZARDS IDENTIFICATION

2.1 Classification of the substance or mixture:

CLP Regulation (EC) No 1272/2008:

Classification of this product has been carried out in accordance with CLP Regulation (EC) No 1272/2008.

Aerosol 1: Pressurised container: May burst if heated., H229

Aerosol 1: Flammable aerosols, Category 1, H222 Eye Irrit. 2: Eye irritation, Category 2, H319

STOT SE 3: Specific toxicity causing drowsiness and dizziness, single exposure, Category 3, H336

2.2 Label elements:

CLP Regulation (EC) No 1272/2008:

Danger





Hazard statements:

Aerosol 1: H229 - Pressurised container: May burst if heated.

Aerosol 1: H222 - Extremely flammable aerosol. Eye Irrit. 2: H319 - Causes serious eye irritation. STOT SE 3: H336 - May cause drowsiness or dizziness.

Precautionary statements:

P210: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P211: Do not spray on an open flame or other ignition source.

P251: Do not pierce or burn, even after use.

P280: Wear protective gloves/face protection/protective clothing/respiratory protection/protective footwear.

P304+P340: IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P410+P412: Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122°F

P501: Dispose of contents/container in accordance with regulations on hazardous waste or packaging and packaging waste respectively.

Supplementary information:

EUH066: Repeated exposure may cause skin dryness or cracking.

Substances that contribute to the classification

acetone; Ethyl acetate; N-butyl acetate; 2-methoxy-1-methylethyl acetate

2.3 Other hazards:

Safety data sheet

This SDS is an English translation of COMMISSION REGULATION (EU) 2020/878, without any country-specific legislation

CLEAR COAT MAT

Printing: 20/01/2023 Date of compilation: 18/04/2019 Revised: 18/01/2023 Version: 3 (Replaced 2)

SECTION 2: HAZARDS IDENTIFICATION (continued)

Product fails to meet PBT/vPvB criteria

Endocrine-disrupting properties: The product fails to meet the criteria.

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS **

3.1 Substance:

Non-applicable

3.2 Mixture:

Chemical description: Mixture composed of chemical products

Components:

In accordance with Annex II of Regulation (EC) No 1907/2006 (point 3), the product contains:

| | Identification | | Chemical name/Classification | | Concentration | |
|------|--|--|--|-----------------|---------------|--|
| CAS: | 67-64-1 | acetone(1) | | ATP CLP00 | | |
| | 200-662-2 606-001-00-8 01-2119471330-49- XXXX | Regulation 1272/2008 | Eye Irrit. 2: H319; Flam. Liq. 2: H225; STOT SE 3: H336; EUH066 - Danger | 1 4 | 25 - <50 % | |
| CAS: | 115-10-6 | Dimethyl ether(2) | | ATP CLP00 | | |
| | 204-065-8 603-019-00-8 01-2119472128-37- XXXX | Regulation 1272/2008 | Flam. Gas 1A: H220; Press. Gas: H280 - Danger | * | 10 - <25 % | |
| CAS: | | | | ATP CLP00 | | |
| | 205-500-4 607-022-00-5 01-2119475103-46- XXXX | Regulation 1272/2008 | Eye Irrit. 2: H319; Flam. Liq. 2: H225; STOT SE 3: H336; EUH066 - Danger | (1) (b) | 10 - <25 % | |
| CAS: | 123-86-4 | N-butyl acetate(1) | | ATP CLP00 | | |
| | 204-658-1 607-025-00-1 01-2119485493-29- XXXX | Regulation 1272/2008 | Flam. Liq. 3: H226; STOT SE 3: H336; EUH066 - Warning | <u>(1)</u> | 5 - <10 % | |
| CAS: | 74-98-6 | Propane ⁽³⁾ | | ATP CLP00 | | |
| | 200-827-9 601-003-00-5 01-2119486944-21- XXXX | 4-21- Regulation 1272/2008 Flam. Gas 1A: H220; Press. Gas: H280 - Danger | | * | 5 - <10 % | |
| CAS: | 106-97-8 | Butane ⁽³⁾ | | ATP CLP00 | | |
| | 203-448-7 601-004-00-0 01-2119474691-32- XXXX | Regulation 1272/2008 | Flam. Gas 1A: H220; Press. Gas: H280 - Danger | * 0 | 5 - <10 % | |
| CAS: | 75-28-5 | Isobutane(3) | | ATP CLP00 | | |
| | 200-857-2 601-004-00-0 01-2119485395-27- XXXX | Regulation 1272/2008 | Flam. Gas 1A: H220; Press. Gas: H280 - Danger | * | 5 - <10 % | |
| CAS: | 108-65-6 | 2-methoxy-1-methy | ethyl acetate ⁽¹⁾ | Self-classified | | |
| | 203-603-9 607-195-00-7 01-2119475791-29- XXXX | Regulation 1272/2008 | Flam. Liq. 3: H226; STOT SE 3: H336 - Warning | (1) | 2,5 - <5 % | |
| CAS: | 71-36-3 | butan-1-ol ⁽¹⁾ | | ATP CLP00 | | |
| | 200-751-6 603-004-00-6 01-2119484630-38- XXXX | Regulation 1272/2008 | Acute Tox. 4: H302; Eye Dam. 1: H318; Flam. Liq. 3: H226; Skin Irrit. 2: H315; STOT SE 3: H335; STOT SE 3: H336 - Danger | (1) (2) (A) | 1 - <2,5 % | |

⁽¹⁾ Substances presenting a health or environmental hazard which meet criteria laid down in Regulation (EU) No. 2020/878

To obtain more information on the hazards of the substances consult sections 11, 12 and 16.

SECTION 4: FIRST AID MEASURES

4.1 Description of first aid measures:

⁽²⁾ Substance with a Union workplace exposure limit

⁽³⁾ Voluntarily-listed substance failing to meet any of the criteria set out in Regulation (EU) No. 2020/878

^{**} Changes with regards to the previous version

-adds-

This SDS is an English translation of COMMISSION REGULATION (EU) 2020/878, without any country-specific legislation

CLEAR COAT MAT

Printing: 20/01/2023 Date of compilation: 18/04/2019 Revised: 18/01/2023 Version: 3 (Replaced 2)

SECTION 4: FIRST AID MEASURES (continued)

The symptoms resulting from intoxication can appear after exposure, therefore, in case of doubt, seek medical attention for direct exposure to the chemical product or persistent discomfort, showing the SDS of this product.

By inhalation:

Remove the person affected from the area of exposure, provide with fresh air and keep at rest. In serious cases such as cardiorespiratory failure, artificial resuscitation techniques will be necessary (mouth to mouth resuscitation, cardiac massage, oxygen supply, etc.) requiring immediate medical assistance.

By skin contact:

Remove contaminated clothing and footwear, rinse skin or shower the person affected if appropriate with plenty of cold water and neutral soap. In serious cases see a doctor. If the product causes burns or freezing, clothing should not be removed as this could worsen the injury caused if it is stuck to the skin. If blisters form on the skin, these should never be burst as this will increase the risk of infection.

By eye contact:

Rinse eyes thoroughly with lukewarm water for at least 15 minutes. Do not allow the person affected to rub or close their eyes. If the injured person uses contact lenses, these should be removed unless they are stuck to the eyes, in which case this could cause further damage. In all cases, after cleaning, a doctor should be consulted as quickly as possible with the SDS of the product.

By ingestion/aspiration:

Do not induce vomiting, but if it does happen keep the head down to avoid aspiration. Keep the person affected at rest. Rinse out the mouth and throat, as they may have been affected during ingestion.

4.2 Most important symptoms and effects, both acute and delayed:

Acute and delayed effects are indicated in sections 2 and 11.

4.3 Indication of any immediate medical attention and special treatment needed:

Non-applicable

SECTION 5: FIREFIGHTING MEASURES

5.1 Extinguishing media:

Suitable extinguishing media:

If possible use polyvalent powder fire extinguishers (ABC powder), alternatively use foam or carbon dioxide extinguishers (CO2).

Unsuitable extinguishing media:

IT IS RECOMMENDED NOT to use full jet water as an extinguishing agent.

5.2 Special hazards arising from the substance or mixture:

As a result of combustion or thermal decomposition reactive sub-products are created that can become highly toxic and, consequently, can present a serious health risk.

5.3 Advice for firefighters:

Depending on the magnitude of the fire it may be necessary to use full protective clothing and self-contained breathing apparatus (SCBA). Minimum emergency facilities and equipment should be available (fire blankets, portable first aid kit,...) in accordance with Directive 89/654/EC.

Additional provisions:

Act in accordance with the Internal Emergency Plan and the Information Sheets on actions to take after an accident or other emergencies. Eliminate all sources of ignition. In case of fire, cool the storage containers and tanks for products susceptible to combustion, explosion or BLEVE as a result of high temperatures. Avoid spillage of the products used to extinguish the fire into an aqueous medium.

SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1 Personal precautions, protective equipment and emergency procedures:

For non-emergency personnel:

Isolate leaks provided that there is no additional risk for the people performing this task. Evacuate the area and keep out those without protection. Personal protection equipment must be used against potential contact with the spilt product (See section 8). Above all prevent the formation of any vapour-air flammable mixtures, through either ventilation or the use of an inert medium. Remove any source of ignition. Eliminate electrostatic charges by interconnecting all the conductive surfaces on which static electricity could form, and also ensuring that all surfaces are connected to the ground.

This SDS is an English translation of COMMISSION REGULATION (EU) 2020/878, without any country-specific legislation





CLEAR COAT MAT

Printing: 20/01/2023 Date of compilation: 18/04/2019 Revised: 18/01/2023 Version: 3 (Replaced 2)

SECTION 6: ACCIDENTAL RELEASE MEASURES (continued)

For emergency responders:

Wear protective equipment. Keep unprotected persons away. See section 8.

Environmental precautions:

This product is not classified as hazardous to the environment. Keep product away from drains, surface and ground water.

Methods and material for containment and cleaning up:

It is recommended:

Absorb the spillage using sand or inert absorbent and move it to a safe place. Do not absorb in sawdust or other combustible absorbents. For any concern related to disposal consult section 13.

Reference to other sections:

See sections 8 and 13.

SECTION 7: HANDLING AND STORAGE

7.1 Precautions for safe handling:

A.- General precautions for safe use

Comply with the current legislation concerning the prevention of industrial risks. Keep containers hermetically sealed. Control spills and residues, destroying them with safe methods (section 6). Avoid leakages from the container. Maintain order and cleanliness where dangerous products are used.

B.- Technical recommendations for the prevention of fires and explosions

Avoid the evaporation of the product as it contains flammable substances, which could form flammable vapour/air mixtures in the presence of sources of ignition. Control sources of ignition (mobile phones, sparks,...) and transfer at slow speeds to avoid the creation of electrostatic charges. Consult section 10 for conditions and materials that should be avoided.

C.- Technical recommendations on general occupational hygiene

Do not eat or drink during the process, washing hands afterwards with suitable cleaning products.

D.- Technical recommendations to prevent environmental risks

It is recommended to have absorbent material available at close proximity to the product (See subsection 6.3)

7.2 Conditions for safe storage, including any incompatibilities:

A.- Technical measures for storage

Maximum Temp.:

B.- General conditions for storage

Avoid sources of heat, radiation, static electricity and contact with food. For additional information see subsection 10.5

7.3 Specific end use(s):

Except for the instructions already specified it is not necessary to provide any special recommendation regarding the uses of this product.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1 **Control parameters:**

Substances whose occupational exposure limits have to be monitored in the workplace (European OEL, not country-specific

Directive (EU) 2000/39, Directive 2004/37/EC, Directive (EU) 2006/15, Directive (EU) 2009/161, Directive (EU) 2017/164, Directive (EU) 2019/1831:

| | Identification | Occ | Occupational exposure limits | | |
|-----------------|------------------|--------------|------------------------------|------------------------|--|
| acetone | | IOELV (8h) | 500 ppm | 1210 mg/m ³ | |
| CAS: 67-64-1 | EC: 200-662-2 | IOELV (STEL) | | | |
| Dimethyl ether | | IOELV (8h) | 1000 ppm | 1920 mg/m ³ | |
| CAS: 115-10-6 | EC: 204-065-8 | IOELV (STEL) | | | |
| Ethyl acetate | | IOELV (8h) | 200 ppm | 734 mg/m ³ | |
| CAS: 141-78-6 | EC: 205-500-4 | IOELV (STEL) | 400 ppm | 1468 mg/m ³ | |
| N-butyl acetate | | IOELV (8h) | 50 ppm | 241 mg/m ³ | |
| CAS: 123-86-4 | EC: 204-658-1 | IOELV (STEL) | 150 ppm | 723 mg/m ³ | |
| 2-methoxy-1-met | hylethyl acetate | IOELV (8h) | 50 ppm | 275 mg/m ³ | |

Safety data sheet

This SDS is an English translation of COMMISSION REGULATION (EU) 2020/878, without any country-specific legislation

CLEAR COAT MAT

Printing: 20/01/2023 Date of compilation: 18/04/2019 Revised: 18/01/2023 Version: 3 (Replaced 2)

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION (continued)

Directive (EU) 2000/39, Directive 2004/37/EC, Directive (EU) 2006/15, Directive (EU) 2009/161, Directive (EU) 2017/164, Directive (EU) 2019/1831:

| | Identification | Occupational exposure limits | | |
|---------------|----------------|------------------------------|---------|-----------------------|
| CAS: 108-65-6 | EC: 203-603-9 | IOELV (STEL) | 100 ppm | 550 mg/m ³ |

DNEL (Workers):

| | | Short e | exposure | Long exposure | |
|---------------------------------|----------------|------------------------|------------------------|------------------------|-----------------------|
| Identification | Identification | | Local | Systemic | Local |
| acetone | Oral | Non-applicable | Non-applicable | Non-applicable | Non-applicable |
| CAS: 67-64-1 | Dermal | Non-applicable | Non-applicable | 186 mg/kg | Non-applicable |
| EC: 200-662-2 | Inhalation | Non-applicable | 2420 mg/m ³ | 1210 mg/m ³ | Non-applicable |
| Dimethyl ether | Oral | Non-applicable | Non-applicable | Non-applicable | Non-applicable |
| CAS: 115-10-6 | Dermal | Non-applicable | Non-applicable | Non-applicable | Non-applicable |
| EC: 204-065-8 | Inhalation | Non-applicable | Non-applicable | 1894 mg/m ³ | Non-applicable |
| Ethyl acetate | Oral | Non-applicable | Non-applicable | Non-applicable | Non-applicable |
| CAS: 141-78-6 | Dermal | Non-applicable | Non-applicable | 63 mg/kg | Non-applicable |
| EC: 205-500-4 | Inhalation | 1468 mg/m ³ | 1468 mg/m ³ | 734 mg/m ³ | 734 mg/m ³ |
| N-butyl acetate | Oral | Non-applicable | Non-applicable | Non-applicable | Non-applicable |
| CAS: 123-86-4 | Dermal | 11 mg/kg | Non-applicable | 11 mg/kg | Non-applicable |
| EC: 204-658-1 | Inhalation | 600 mg/m ³ | 600 mg/m ³ | 300 mg/m ³ | 300 mg/m ³ |
| 2-methoxy-1-methylethyl acetate | Oral | Non-applicable | Non-applicable | Non-applicable | Non-applicable |
| CAS: 108-65-6 | Dermal | Non-applicable | Non-applicable | 796 mg/kg | Non-applicable |
| EC: 203-603-9 | Inhalation | Non-applicable | 550 mg/m ³ | 275 mg/m ³ | Non-applicable |
| butan-1-ol | Oral | Non-applicable | Non-applicable | Non-applicable | Non-applicable |
| CAS: 71-36-3 | Dermal | Non-applicable | Non-applicable | Non-applicable | Non-applicable |
| EC: 200-751-6 | Inhalation | Non-applicable | Non-applicable | Non-applicable | 310 mg/m ³ |

DNEL (General population):

| | | Short e | exposure Long exposure | | exposure |
|---------------------------------|------------|-----------------------|------------------------|--------------------------|------------------------|
| Identification | | Systemic | Local | Systemic | Local |
| acetone | Oral | Non-applicable | Non-applicable | 62 mg/kg | Non-applicable |
| CAS: 67-64-1 | Dermal | Non-applicable | Non-applicable | 62 mg/kg | Non-applicable |
| EC: 200-662-2 | Inhalation | Non-applicable | Non-applicable | 200 mg/m ³ | Non-applicable |
| Dimethyl ether | Oral | Non-applicable | Non-applicable | Non-applicable | Non-applicable |
| CAS: 115-10-6 | Dermal | Non-applicable | Non-applicable | Non-applicable | Non-applicable |
| EC: 204-065-8 | Inhalation | Non-applicable | Non-applicable | 471 mg/m ³ | Non-applicable |
| Ethyl acetate | Oral | Non-applicable | Non-applicable | 4,5 mg/kg | Non-applicable |
| CAS: 141-78-6 | Dermal | Non-applicable | Non-applicable | 37 mg/kg | Non-applicable |
| EC: 205-500-4 | Inhalation | 734 mg/m ³ | 734 mg/m ³ | 367 mg/m ³ | 367 mg/m ³ |
| N-butyl acetate | Oral | 2 mg/kg | Non-applicable | 2 mg/kg | Non-applicable |
| CAS: 123-86-4 | Dermal | 6 mg/kg | Non-applicable | 6 mg/kg | Non-applicable |
| EC: 204-658-1 | Inhalation | 300 mg/m ³ | 300 mg/m ³ | 35,7 mg/m ³ | 35,7 mg/m ³ |
| 2-methoxy-1-methylethyl acetate | Oral | Non-applicable | Non-applicable | 36 mg/kg | Non-applicable |
| CAS: 108-65-6 | Dermal | Non-applicable | Non-applicable | 320 mg/kg | Non-applicable |
| EC: 203-603-9 | Inhalation | Non-applicable | Non-applicable | 33 mg/m ³ | 33 mg/m ³ |
| butan-1-ol | Oral | Non-applicable | Non-applicable | 1,562 mg/kg | Non-applicable |
| CAS: 71-36-3 | Dermal | Non-applicable | Non-applicable | 3,125 mg/kg | Non-applicable |
| EC: 200-751-6 | Inhalation | Non-applicable | Non-applicable | 55,357 mg/m ³ | 155 mg/m ³ |

PNEC:

| Identification | | | | |
|----------------|--------------|----------------|-------------------------|------------|
| acetone | STP | 100 mg/L | Fresh water | 10,6 mg/L |
| CAS: 67-64-1 | Soil | 29,5 mg/kg | Marine water | 1,06 mg/L |
| EC: 200-662-2 | Intermittent | 21 mg/L | Sediment (Fresh water) | 30,4 mg/kg |
| | Oral | Non-applicable | Sediment (Marine water) | 3,04 mg/kg |

This SDS is an English translation of COMMISSION REGULATION (EU) 2020/878, without any country-specific legislation

CLEAR COAT MAT

Printing: 20/01/2023 Date of compilation: 18/04/2019 Revised: 18/01/2023 Version: 3 (Replaced 2)

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION (continued)

| Identification | | | | |
|---------------------------------|--------------|----------------|-------------------------|-------------|
| Dimethyl ether | STP | 160 mg/L | Fresh water | 0,155 mg/L |
| CAS: 115-10-6 | Soil | 0,045 mg/kg | Marine water | 0,016 mg/L |
| EC: 204-065-8 | Intermittent | 1,549 mg/L | Sediment (Fresh water) | 0,681 mg/kg |
| | Oral | Non-applicable | Sediment (Marine water) | 0,069 mg/kg |
| Ethyl acetate | STP | 650 mg/L | Fresh water | 0,24 mg/L |
| CAS: 141-78-6 | Soil | 0,148 mg/kg | Marine water | 0,024 mg/L |
| EC: 205-500-4 | Intermittent | 1,65 mg/L | Sediment (Fresh water) | 1,15 mg/kg |
| | Oral | 0,2 g/kg | Sediment (Marine water) | 0,115 mg/kg |
| N-butyl acetate | STP | 35,6 mg/L | Fresh water | 0,18 mg/L |
| CAS: 123-86-4 | Soil | 0,09 mg/kg | Marine water | 0,018 mg/L |
| EC: 204-658-1 | Intermittent | 0,36 mg/L | Sediment (Fresh water) | 0,981 mg/kg |
| | Oral | Non-applicable | Sediment (Marine water) | 0,098 mg/kg |
| 2-methoxy-1-methylethyl acetate | STP | 100 mg/L | Fresh water | 0,635 mg/L |
| CAS: 108-65-6 | Soil | 0,29 mg/kg | Marine water | 0,064 mg/L |
| EC: 203-603-9 | Intermittent | 6,35 mg/L | Sediment (Fresh water) | 3,29 mg/kg |
| | Oral | Non-applicable | Sediment (Marine water) | 0,329 mg/kg |
| butan-1-ol | STP | 2476 mg/L | Fresh water | 0,082 mg/L |
| CAS: 71-36-3 | Soil | 0,017 mg/kg | Marine water | 0,008 mg/L |
| EC: 200-751-6 | Intermittent | 2,25 mg/L | Sediment (Fresh water) | 0,324 mg/kg |
| | Oral | Non-applicable | Sediment (Marine water) | 0,032 mg/kg |

8.2 Exposure controls:

A.- Individual protection measures, such as personal protective equipment

As a preventative measure it is recommended to use basic Personal Protective Equipment, with the corresponding <<CE marking>> in accordance with Regulation (EU) 2016/425. For more information on Personal Protective Equipment (storage, use, cleaning, maintenance, class of protection,...) consult the information leaflet provided by the manufacturer. For more information see subsection 7.1. All information contained herein is a recommendation which needs some specification from the labour risk prevention services as it is not known whether the company has additional measures at its disposal.

B.- Respiratory protection

| Pictogram | PPE | Labelling | CEN Standard | Remarks |
|--|---|-----------|---|---|
| Mandatory respiratory tract protection | Filter mask for gases, vapours and particles | CAT III | EN 149:2001+A1:2009 EN 405:2002+A1:2010 EN ISO 136:1998 | Replace when an increase in resistence to breathing is observed and/or a smell or taste of the contaminant is detected. |

C.- Specific protection for the hands

| Pictogram | PPE | Labelling | CEN Standard | Remarks |
|---------------------------|---|-----------|-------------------|--|
| Mandatory hand protection | Chemical protective gloves (Material: Linear low-density polyethylene (LLDPE), Breakthrough time: > 480 min, Thickness: 0.062 mm) | CAT III | EN ISO 21420:2020 | Replace the gloves at any sign of deterioration. |

As the product is a mixture of several substances, the resistance of the glove material can not be calculated in advance with total reliability and has therefore to be checked prior to the application.

D.- Eye and face protection

| Pictogram | PPE | Labelling | CEN Standard | Remarks |
|---------------------------|-------------|-----------|---|---|
| Mandatory face protection | Face shield | CATII | EN 166:2002 EN 167:2002 EN 168:2002 EN ISO 4007:2018 | Clean daily and disinfect periodically according to the manufacturer's instructions. Use if there is a risk of splashing. |

E.- Body protection



-addsTROTON®

This SDS is an English translation of COMMISSION REGULATION (EU) 2020/878, without any country-specific legislation

CLEAR COAT MAT

Printing: 20/01/2023 Date of compilation: 18/04/2019 Revised: 18/01/2023 Version: 3 (Replaced 2)

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION (continued)

| Pictogram | PPE | Labelling | CEN Standard | Remarks |
|------------------------------------|--|-----------|---|---|
| Mandatory complete body protection | Disposable clothing for protection against chemical risks, with antistatic and fireproof properties | CAT III | EN 1149-1,2,3 EN 13034:2005+A1:2009 EN ISO 13982- 1:2004/A1:2010 EN ISO 6529:2013 EN ISO 6530:2005 EN ISO 13688:2013 EN 464:1994 | For professional use only. Clean periodically according to the manufacturer's instructions. |
| Mandatory foot protection | Safety footwear for protection against chemical risk, with antistatic and heat resistant properties | CAT III | EN ISO 13287:2020 EN ISO 20345:2011 EN 13832-1:2019 | Replace boots at any sign of deterioration. |

F.- Additional emergency measures

| Emergency measure | Standards | Emergency measure | Standards |
|-------------------|---|-------------------|--|
| • | ANSI Z358-1 ISO 3864-1:2011, ISO 3864-4:2011 | - ∰ | DIN 12 899 ISO 3864-1:2011, ISO 3864-4:2011 |
| Emergency shower | | Eyewash stations | |

Environmental exposure controls:

In accordance with the community legislation for the protection of the environment it is recommended to avoid environmental spillage of both the product and its container. For additional information see subsection 7.1.D

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1 Information on basic physical and chemical properties:

For complete information see the product datasheet.

Appearance:

Physical state at 20 °C:

Appearance:

Colour:

Colour:

Characteristic

Odour threshold:

Aerosol

Volatile

Colourless

Characteristic

Volatility:

Boiling point at atmospheric pressure: -25 °C (Propellant)

Vapour pressure at 20 °C: 400002 Pa

Vapour pressure at 50 °C: <300000 Pa (300 kPa)

Evaporation rate at 20 °C: Non-applicable *

Product description:

Density at 20 °C: Non-applicable * Relative density at 20 °C: Non-applicable * Dynamic viscosity at 20 °C: Non-applicable * Kinematic viscosity at 20 °C: Non-applicable * Kinematic viscosity at 40 °C: Non-applicable * Concentration: Non-applicable * pH: Non-applicable * Vapour density at 20 °C: Non-applicable * Partition coefficient n-octanol/water 20 °C: Non-applicable * Solubility in water at 20 °C: Non-applicable * *Not relevant due to the nature of the product, not providing information property of its hazards.

adds

Safety data sheet

This SDS is an English translation of COMMISSION REGULATION (EU) 2020/878, without any country-specific legislation

CLEAR COAT MAT

Printing: 20/01/2023 Date of compilation: 18/04/2019 Revised: 18/01/2023 Version: 3 (Replaced 2)

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES (continued)

Solubility properties:

Decomposition temperature:

Melting point/freezing point:

Recipient pressure:

Non-applicable *

Non-applicable *

Flammability:

Flash Point:

Flammability (solid, gas):

Autoignition temperature:

Lower flammability limit:

Upper flammability limit:

Non-applicable *

Non-applicable *

Particle characteristics:

Median equivalent diameter: Non-applicable

9.2 Other information:

Information with regard to physical hazard classes:

Explosive properties:

Oxidising properties:

Corrosive to metals:

Heat of combustion:

Aerosols-total percentage (by mass) of flammable

Non-applicable *

Non-applicable *

Non-applicable *

Non-applicable *

components:

Other safety characteristics:

Surface tension at 20 °C:

Refraction index:

Non-applicable *

Non-applicable *

*Not relevant due to the nature of the product, not providing information property of its hazards.

SECTION 10: STABILITY AND REACTIVITY

10.1 Reactivity:

No hazardous reactions are expected because the product is stable under recommended storage conditions. See section 7.

10.2 Chemical stability:

Chemically stable under the indicated conditions of storage, handling and use.

10.3 Possibility of hazardous reactions:

Under the specified conditions, hazardous reactions that lead to excessive temperatures or pressure are not expected.

10.4 Conditions to avoid:

Applicable for handling and storage at room temperature:

| Shock and friction | Contact with air | Increase in temperature | Sunlight | Humidity |
|--------------------|------------------|-------------------------|---------------------|----------------|
| Not applicable | Not applicable | Risk of combustion | Avoid direct impact | Not applicable |

10.5 Incompatible materials:

| Acids | Water | Oxidising materials | Combustible materials | Others |
|--------------------|----------------|---------------------|-----------------------|-------------------------------|
| Avoid strong acids | Not applicable | Avoid direct impact | Not applicable | Avoid alkalis or strong bases |

10.6 Hazardous decomposition products:

See subsection 10.3, 10.4 and 10.5 to find out the specific decomposition products. Depending on the decomposition conditions, complex mixtures of chemical substances can be released: carbon dioxide (CO₂), carbon monoxide and other organic compounds.

SECTION 11: TOXICOLOGICAL INFORMATION **

^{**} Changes with regards to the previous version





CLEAR COAT MAT

Printing: 20/01/2023 Date of compilation: 18/04/2019 Revised: 18/01/2023 Version: 3 (Replaced 2)

SECTION 11: TOXICOLOGICAL INFORMATION ** (continued)

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008:

The experimental information related to the toxicological properties of the product itself is not available

Contains glycols. It is recommended not to breathe the vapours for prolonged periods of time due to the possibility of effects that are hazardous to the health .

Dangerous health implications:

In case of exposure that is repetitive, prolonged or at concentrations higher than the recommended occupational exposure limits, adverse effects on health may result, depending on the means of exposure:

- A- Ingestion (acute effect):
 - Acute toxicity: Based on available data, the classification criteria are not met, however, it contains substances classified as dangerous for consumption. For more information see section 3.
 - Corrosivity/Irritability: Based on available data, the classification criteria are not met. However, it does contain substances classified as hazardous for this effect. For more information see section 3.
- B- Inhalation (acute effect):
 - Acute toxicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for inhalation. For more information see section 3.
 - Corrosivity/Irritability: Based on available data, the classification criteria are not met. However, it contains substances classified as hazardous for inhalation. For more information see section 3.
- C- Contact with the skin and the eyes (acute effect):
 - Contact with the skin: Based on available data, the classification criteria are not met. However, it contains substances classified as hazardous for skin contact. For more information see section 3.
 - Contact with the eyes: Produces eye damage after contact.
- D- CMR effects (carcinogenicity, mutagenicity and toxicity to reproduction):
 - Carcinogenicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for the effects mentioned. For more information see section 3.

 IARC: propan-2-ol (3)
 - Mutagenicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.
 - Reproductive toxicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.
- E- Sensitizing effects:
 - Respiratory: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous with sensitising effects. For more information see section 3.
 - Skin: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.
- F- Specific target organ toxicity (STOT) single exposure:

Exposure in high concentration can interfere with the central nervous system causing headache, dizziness, vertigo, nausea, vomiting, confusion, and in serious cases, loss of consciousness.

- $\mbox{G-}$ Specific target organ toxicity (STOT)-repeated exposure:
 - Specific target organ toxicity (STOT)-repeated exposure: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.
 - Skin: Repeated exposure may cause skin dryness or cracking
- H- Aspiration hazard:

Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.

Other information:

Non-applicable

Specific toxicology information on the substances:

| Identification | Acute toxicity | | Genus |
|----------------|-----------------|------------------|-------|
| Dimethyl ether | LD50 oral | >2000 mg/kg | |
| CAS: 115-10-6 | LD50 dermal | >2000 mg/kg | |
| EC: 204-065-8 | LC50 inhalation | 308,5 mg/L (4 h) | Rat |

^{**} Changes with regards to the previous version

Safety data sheet

This SDS is an English translation of COMMISSION REGULATION (EU) 2020/878, without any country-specific legislation

CLEAR COAT MAT

Printing: 20/01/2023 Date of compilation: 18/04/2019 Revised: 18/01/2023 Version: 3 (Replaced 2)

SECTION 11: TOXICOLOGICAL INFORMATION ** (continued)

| Identification | A | cute toxicity | Genus |
|---------------------------------|-----------------|------------------|--------|
| acetone | LD50 oral | 5800 mg/kg | Rat |
| CAS: 67-64-1 | LD50 dermal | 7426 mg/kg | Rabbit |
| EC: 200-662-2 | LC50 inhalation | 76 mg/L (4 h) | Rat |
| N-butyl acetate | LD50 oral | 12789 mg/kg | Rat |
| CAS: 123-86-4 | LD50 dermal | 14112 mg/kg | Rabbit |
| EC: 204-658-1 | LC50 inhalation | 23,4 mg/L (4 h) | Rat |
| Propane | LD50 oral | >2000 mg/kg | |
| CAS: 74-98-6 | LD50 dermal | >2000 mg/kg | |
| EC: 200-827-9 | LC50 inhalation | >5 mg/L | |
| Ethyl acetate | LD50 oral | 4100 mg/kg | Rat |
| CAS: 141-78-6 | LD50 dermal | 20000 mg/kg | Rabbit |
| EC: 205-500-4 | LC50 inhalation | >20 mg/L | |
| Butane | LD50 oral | >2000 mg/kg | |
| CAS: 106-97-8 | LD50 dermal | >2000 mg/kg | |
| EC: 203-448-7 | LC50 inhalation | 658 mg/L (4 h) | Rat |
| Isobutane | LD50 oral | >2000 mg/kg | |
| CAS: 75-28-5 | LD50 dermal | >2000 mg/kg | |
| EC: 200-857-2 | LC50 inhalation | >5 mg/L | |
| 2-methoxy-1-methylethyl acetate | LD50 oral | 8532 mg/kg | Rat |
| CAS: 108-65-6 | LD50 dermal | >5000 mg/kg | Rat |
| EC: 203-603-9 | LC50 inhalation | 30 mg/L (4 h) | Rat |
| butan-1-ol | LD50 oral | 800 mg/kg | Rat |
| CAS: 71-36-3 | LD50 dermal | 3430 mg/kg | Rabbit |
| EC: 200-751-6 | LC50 inhalation | 24,66 mg/L (4 h) | Rat |

Acute Toxicity Estimate (ATE mix):

| ATE mix | | Ingredient(s) of unknown toxicity |
|---------------------------------------|-------------------------------------|-----------------------------------|
| Oral 40000 mg/kg (Calculation method) | | 0 % |
| Dermal | >2000 mg/kg (Calculation method) | Non-applicable |
| Inhalation | >20 mg/L (4 h) (Calculation method) | Non-applicable |

11.2 Information on other hazards:

Endocrine disrupting properties

Endocrine-disrupting properties: The product fails to meet the criteria.

Other information

Non-applicable

SECTION 12: ECOLOGICAL INFORMATION **

The experimental information related to the eco-toxicological properties of the product itself is not available

12.1 Toxicity:

Acute toxicity:

| Identification | Concentration | | Species | Genus |
|----------------|---------------|------------------|-------------------------|------------|
| acetone | LC50 | 5540 mg/L (96 h) | Oncorhynchus mykiss | Fish |
| CAS: 67-64-1 | EC50 | 8800 mg/L (48 h) | Daphnia pulex | Crustacean |
| EC: 200-662-2 | EC50 | 3400 mg/L (48 h) | Chlorella pyrenoidosa | Algae |
| Ethyl acetate | LC50 | 230 mg/L (96 h) | Pimephales promelas | Fish |
| CAS: 141-78-6 | EC50 | 717 mg/L (48 h) | Daphnia magna | Crustacean |
| EC: 205-500-4 | EC50 | 3300 mg/L (48 h) | Scenedesmus subspicatus | Algae |

^{**} Changes with regards to the previous version

^{**} Changes with regards to the previous version

Safety data sheet

This SDS is an English translation of COMMISSION REGULATION (EU) 2020/878, without any country-specific legislation

CLEAR COAT MAT

Printing: 20/01/2023 Date of compilation: 18/04/2019 Revised: 18/01/2023 Version: 3 (Replaced 2)

SECTION 12: ECOLOGICAL INFORMATION ** (continued)

| Identification | | Concentration | Species | Genus |
|---------------------------------|------|------------------|-------------------------|------------|
| N-butyl acetate | LC50 | Non-applicable | | |
| CAS: 123-86-4 | EC50 | Non-applicable | | |
| EC: 204-658-1 | EC50 | 675 mg/L (72 h) | Scenedesmus subspicatus | Algae |
| 2-methoxy-1-methylethyl acetate | LC50 | 161 mg/L (96 h) | Pimephales promelas | Fish |
| CAS: 108-65-6 | EC50 | 481 mg/L (48 h) | Daphnia sp. | Crustacean |
| EC: 203-603-9 | EC50 | Non-applicable | | |
| butan-1-ol | LC50 | 1740 mg/L (96 h) | Pimephales promelas | Fish |
| CAS: 71-36-3 | EC50 | 1983 mg/L (48 h) | Daphnia magna | Crustacean |
| EC: 200-751-6 | EC50 | 500 mg/L (96 h) | Scenedesmus subspicatus | Algae |

Chronic toxicity:

| Identification | | Concentration | Species | Genus |
|---------------------------------|------|----------------|---------------------|------------|
| acetone | NOEC | Non-applicable | | |
| CAS: 67-64-1 EC: 200-662-2 | NOEC | 2212 mg/L | Daphnia magna | Crustacean |
| Ethyl acetate | NOEC | 9,65 mg/L | Pimephales promelas | Fish |
| CAS: 141-78-6 EC: 205-500-4 | NOEC | 2,4 mg/L | Daphnia magna | Crustacean |
| N-butyl acetate | NOEC | Non-applicable | | |
| CAS: 123-86-4 EC: 204-658-1 | NOEC | 23,2 mg/L | Daphnia magna | Crustacean |
| 2-methoxy-1-methylethyl acetate | NOEC | 47,5 mg/L | Oryzias latipes | Fish |
| CAS: 108-65-6 EC: 203-603-9 | NOEC | 100 mg/L | Daphnia magna | Crustacean |
| butan-1-ol | NOEC | Non-applicable | | |
| CAS: 71-36-3 EC: 200-751-6 | NOEC | 4,1 mg/L | Daphnia magna | Crustacean |

12.2 Persistence and degradability:

Substance-specific information:

| Identification | Degradability | | Biodegradab | oility |
|---------------------------------|---------------|----------------|-----------------|----------------|
| acetone | BOD5 | Non-applicable | Concentration | 100 mg/L |
| CAS: 67-64-1 | COD | Non-applicable | Period | 28 days |
| EC: 200-662-2 | BOD5/COD | Non-applicable | % Biodegradable | 96 % |
| Ethyl acetate | BOD5 | 1,36 g O2/g | Concentration | 100 mg/L |
| CAS: 141-78-6 | COD | 1,69 g O2/g | Period | 14 days |
| EC: 205-500-4 | BOD5/COD | 0,8 | % Biodegradable | 83 % |
| N-butyl acetate | BOD5 | Non-applicable | Concentration | Non-applicable |
| CAS: 123-86-4 | COD | Non-applicable | Period | 5 days |
| EC: 204-658-1 | BOD5/COD | Non-applicable | % Biodegradable | 84 % |
| 2-methoxy-1-methylethyl acetate | BOD5 | Non-applicable | Concentration | 785 mg/L |
| CAS: 108-65-6 | COD | Non-applicable | Period | 8 days |
| EC: 203-603-9 | BOD5/COD | Non-applicable | % Biodegradable | 100 % |
| butan-1-ol | BOD5 | 1,71 g O2/g | Concentration | Non-applicable |
| CAS: 71-36-3 | COD | 2,46 g O2/g | Period | 19 days |
| EC: 200-751-6 | BOD5/COD | 0,7 | % Biodegradable | 98 % |

12.3 Bioaccumulative potential:

Substance-specific information:

| Identification | Bioaccumulation potential | | |
|----------------|---------------------------|----------|--|
| acetone | BCF | 1 | |
| CAS: 67-64-1 | Pow Log | -0.24 | |
| EC: 200-662-2 | Potential | Low | |
| Ethyl acetate | BCF | 30 | |
| CAS: 141-78-6 | Pow Log | 0.73 | |
| EC: 205-500-4 | Potential | Moderate | |

^{**} Changes with regards to the previous version

Safety data sheet

This SDS is an English translation of COMMISSION REGULATION (EU) 2020/878, without any country-specific legislation

CLEAR COAT MAT

Printing: 20/01/2023 Date of compilation: 18/04/2019 Revised: 18/01/2023 Version: 3 (Replaced 2)

SECTION 12: ECOLOGICAL INFORMATION ** (continued)

| Identification | | Bioaccui | mulation potential |
|---------------------------------|--|-----------|--------------------|
| N-butyl acetate | | BCF | 4 |
| AS: 123-86-4 | | Pow Log | 1.78 |
| EC: 204-658-1 | | Potential | Low |
| Propane | | BCF | 13 |
| CAS: 74-98-6 | | Pow Log | 2.86 |
| EC: 200-827-9 | | Potential | Low |
| Butane | | BCF | 33 |
| CAS: 106-97-8 | | Pow Log | 2.89 |
| EC: 203-448-7 | | Potential | Moderate |
| Isobutane | | BCF | 27 |
| CAS: 75-28-5 | | Pow Log | 2.76 |
| EC: 200-857-2 | | Potential | Low |
| 2-methoxy-1-methylethyl acetate | | BCF | 1 |
| CAS: 108-65-6 | | Pow Log | 0.43 |
| EC: 203-603-9 | | Potential | Low |
| butan-1-ol | | BCF | 1 |
| CAS: 71-36-3 EC: 200-751-6 | | Pow Log | 0.88 |
| | | Potential | Low |

12.4 Mobility in soil:

| Identification | Absorp | tion/desorption | Volat | ility |
|-----------------|-----------------|----------------------|------------|---------------------|
| acetone | Koc | 1 | Henry | 2,93 Pa·m³/mol |
| CAS: 67-64-1 | Conclusion | Very High | Dry soil | Yes |
| EC: 200-662-2 | Surface tension | 2,304E-2 N/m (25 °C) | Moist soil | Yes |
| Dimethyl ether | Koc | Non-applicable | Henry | Non-applicable |
| CAS: 115-10-6 | Conclusion | Non-applicable | Dry soil | Non-applicable |
| EC: 204-065-8 | Surface tension | 1,136E-2 N/m (25 °C) | Moist soil | Non-applicable |
| Ethyl acetate | Koc | 59 | Henry | 13,58 Pa·m³/mol |
| CAS: 141-78-6 | Conclusion | Very High | Dry soil | Yes |
| EC: 205-500-4 | Surface tension | 2,324E-2 N/m (25 °C) | Moist soil | Yes |
| N-butyl acetate | Koc | Non-applicable | Henry | Non-applicable |
| CAS: 123-86-4 | Conclusion | Non-applicable | Dry soil | Non-applicable |
| EC: 204-658-1 | Surface tension | 2,478E-2 N/m (25 °C) | Moist soil | Non-applicable |
| Propane | Koc | 460 | Henry | 71636,78 Pa·m³/mol |
| CAS: 74-98-6 | Conclusion | Moderate | Dry soil | Yes |
| EC: 200-827-9 | Surface tension | 7,02E-3 N/m (25 °C) | Moist soil | Yes |
| Butane | Koc | 900 | Henry | 96258,75 Pa·m³/mol |
| CAS: 106-97-8 | Conclusion | Low | Dry soil | Yes |
| EC: 203-448-7 | Surface tension | 1,187E-2 N/m (25 °C) | Moist soil | Yes |
| Isobutane | Koc | 35 | Henry | 120576,75 Pa·m³/mol |
| CAS: 75-28-5 | Conclusion | Very High | Dry soil | Yes |
| EC: 200-857-2 | Surface tension | 9,84E-3 N/m (25 °C) | Moist soil | Yes |
| butan-1-ol | Koc | 2.44 | Henry | 5,39E-2 Pa·m³/mol |
| CAS: 71-36-3 | Conclusion | Very High | Dry soil | Yes |
| EC: 200-751-6 | Surface tension | 2,567E-2 N/m (25 °C) | Moist soil | Yes |

12.5 Results of PBT and vPvB assessment:

Product fails to meet PBT/vPvB criteria

12.6 Endocrine disrupting properties:

Endocrine-disrupting properties: The product fails to meet the criteria.

12.7 Other adverse effects:

Not described

^{**} Changes with regards to the previous version

This SDS is an English translation of COMMISSION REGULATION (EU) 2020/878, without any country-specific legislation

CLEAR COAT MAT

Printing: 20/01/2023 Date of compilation: 18/04/2019 Revised: 18/01/2023 Version: 3 (Replaced 2)

SECTION 13: DISPOSAL CONSIDERATIONS

13.1 Waste treatment methods:

| Code | Description | Waste class (Regulation (EU) No 1357/2014) | |
|-----------|---|---|--|
| 16 05 04* | gases in pressure containers (including halons) containing hazardous substances | Dangerous | |

Type of waste (Regulation (EU) No 1357/2014):

HP3 Flammable, HP5 Specific Target Organ Toxicity (STOT)/Aspiration Toxicity, HP4 Irritant — skin irritation and eye damage

Waste management (disposal and evaluation):

Consult the authorized waste service manager on the assessment and disposal operations in accordance with Annex 1 and Annex 2 (Directive 2008/98/EC). As under 15 01 (2014/955/EC) of the code and in case the container has been in direct contact with the product, it will be processed the same way as the actual product. Otherwise, it will be processed as non-dangerous residue. Waste should not be disposed of to drains. See paragraph 6.2.

Regulations related to waste management:

In accordance with Annex II of Regulation (EC) No 1907/2006 (REACH) the community or state provisions related to waste management are stated

2

Community legislation: Directive 2008/98/EC, 2014/955/EU, Regulation (EU) No 1357/2014

SECTION 14: TRANSPORT INFORMATION

Transport of dangerous goods by land:

With regard to ADR 2021 and RID 2021:



14.1 UN number or ID number: UN1950 **AEROSOLS** 14.2 UN proper shipping name:

14.3 Transport hazard class(es): Labels: 2.1 14.4 Packing group: N/A 14.5 Environmental hazards: No 14.6 Special precautions for user

> Special regulations: 190, 327, 344, 625

Tunnel restriction code:

Physico-Chemical properties: see section 9

Limited quantities: 1 L

14.7 Maritime transport in bulk according to IMO

instruments:

Non-applicable

Transport of dangerous goods by sea:

With regard to IMDG 40-20:



14.1 UN number or ID number: UN1950 14.2 UN proper shipping name: **AEROSOLS**

14.3 Transport hazard class(es): Labels: 2.1

14.4 Packing group: N/A 14.5 Marine pollutant: Nο

14.6 Special precautions for user

Special regulations: 63, 959, 190, 277, 327, 344

F-D, S-U FmS Codes: Physico-Chemical properties: see section 9

Limited quantities: 1 L

Segregation group: Non-applicable 14.7 Maritime transport in bulk Non-applicable according to IMO

instruments: Transport of dangerous goods by air:

With regard to IATA/ICAO 2023:

adds

adds

Safety data sheet

This SDS is an English translation of COMMISSION REGULATION (EU) 2020/878, without any country-specific legislation

CLEAR COAT MAT

Printing: 20/01/2023 Date of compilation: 18/04/2019 Revised: 18/01/2023 Version: 3 (Replaced 2)

SECTION 14: TRANSPORT INFORMATION (continued)



14.1 UN number or ID number: UN1950 14.2 UN proper shipping name: AFROSOLS

14.3 Transport hazard class(es): 2

Labels: 2.1 N/A 14.4 Packing group: 14.5 Environmental hazards: Nο

14.6 Special precautions for user

Physico-Chemical properties: see section 9 14.7 Maritime transport in bulk

according to IMO instruments:

Non-applicable

SECTION 15: REGULATORY INFORMATION

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture:

Candidate substances for authorisation under the Regulation (EC) No 1907/2006 (REACH): Non-applicable

Substances included in Annex XIV of REACH ("Authorisation List") and sunset date: Non-applicable

Regulation (EC) No 1005/2009, about substances that deplete the ozone layer: Non-applicable

Article 95, REGULATION (EU) No 528/2012: Non-applicable

REGULATION (EU) No 649/2012, in relation to the import and export of hazardous chemical products: Non-applicable

Seveso III:

| | Section | Description | Lower-tier requirements | Upper-tier requirements |
|--|---------|--------------------|-------------------------|-------------------------|
| | P3a | FLAMMABLE AEROSOLS | 150 | 500 |

Limitations to commercialisation and the use of certain dangerous substances and mixtures (Annex XVII REACH,

Regulation (EU) 2019/1148 on the marketing and use of explosives precursors: Contains acetone. Product under the provisions of Article 9. However, products that contain explosives precursors only to such a small extent and in such complex mixtures that the extraction of the explosives precursors is technically extremely difficult should be excluded from the scope of this Regulation. Shall not be used in:

- —ornamental articles intended to produce light or colour effects by means of different phases, for example in ornamental lamps and ashtravs.
- -tricks and jokes,
- —games for one or more participants, or any article intended to be used as such, even with ornamental aspects.

Specific provisions in terms of protecting people or the environment:

It is recommended to use the information included in this safety data sheet as a basis for conducting workplace-specific risk assessments in order to establish the necessary risk prevention measures for the handling, use, storage and disposal of this product.

Other legislation:

The product could be affected by sectorial legislation

Council Directive 75/324/EEC of 20 May 1975 on the approximation of the laws of the Member States relating to aerosol

Commission Directive 94/1/EC of 6 January 1994 adapting some technicalities of Council Directive 75/324/EEC on the approximation of the laws of the relating Member States to aerosol dispensers

Commission Directive 2008/47/EC of 8 April 2008 amending, for the purposes of adapting to technical progress, Council Directive 75/324/EEC on the approximation of the laws of the Member States relating to aerosol dispensers

Commission Directive 2013/10/EU of 19 March 2013 amending Council Directive 75/324/EEC on the approximation of the laws of the Member States relating to aerosol dispensers in order to adapt its labelling provisions to Regulation (EC) No 1272/2008 of the European Parliament and of the Council on classification, labelling and packaging of substances and mixtures

COMMISSION DIRECTIVE (EU) 2016/2037 of 21 November 2016 amending Council Directive 75/324/EEC as regards the maximum allowable pressure of aerosol dispensers and to adapt its labelling provisions to Regulation (EC) No 1272/2008 of the European Parliament and of the Council on classification, labelling and packaging of substances and mixtures

15.2 Chemical safety assessment:

The supplier has not carried out evaluation of chemical safety.

Safety data sheet

This SDS is an English translation of COMMISSION REGULATION (EU) 2020/878, without any country-specific legislation

CLEAR COAT MAT

Printing: 20/01/2023 Date of compilation: 18/04/2019 Revised: 18/01/2023 Version: 3 (Replaced 2)

SECTION 16: OTHER INFORMATION

Legislation related to safety data sheets:

The SDS shall be supplied in an official language of the country where the product is placed on the market. This safety data sheet has been designed in accordance with ANNEX II-Guide to the compilation of safety data sheets of Regulation (EC) No 1907/2006 (COMMISSION REGULATION (EU) 2020/878).

Modifications related to the previous Safety Data Sheet which concerns the ways of managing risks.:

COMMISSION REGULATION (EU) 2020/878

COMPOSITION/INFORMATION ON INGREDIENTS (SECTION 3, SECTION 11, SECTION 12):

New declared substances

Butane (106-97-8)

Isobutane (75-28-5)

Propane (74-98-6)

Texts of the legislative phrases mentioned in section 2:

H319: Causes serious eye irritation.

H336: May cause drowsiness or dizziness.

H229: Pressurised container: May burst if heated.

H222: Extremely flammable aerosol.

Texts of the legislative phrases mentioned in section 3:

The phrases indicated do not refer to the product itself; they are present merely for informative purposes and refer to the individual components which appear in section 3

CLP Regulation (EC) No 1272/2008:

Acute Tox. 4: H302 - Harmful if swallowed.

Eye Dam. 1: H318 - Causes serious eye damage.

Eye Irrit. 2: H319 - Causes serious eye irritation.

Flam. Gas 1A: H220 - Extremely flammable gas.

Flam. Liq. 2: H225 - Highly flammable liquid and vapour.

Flam. Liq. 3: H226 - Flammable liquid and vapour.

Press. Gas: H280 - Contains gas under pressure, may explode if heated.

Skin Irrit. 2: H315 - Causes skin irritation.

STOT SE 3: H335 - May cause respiratory irritation.

STOT SE 3: H336 - May cause drowsiness or dizziness.

Classification procedure:

Eye Irrit. 2: Calculation method

STOT SE 3: Calculation method

Aerosol 1: Calculation method

Aerosol 1: Calculation method

Advice related to training:

Training is recommended in order to prevent industrial risks for staff using this product and to facilitate their comprehension and interpretation of this safety data sheet, as well as the label on the product.

Principal bibliographical sources:

http://echa.europa.eu

http://eur-lex.europa.eu

Abbreviations and acronyms:

ADR: European agreement concerning the international carriage of dangerous goods by road

IMDG: International maritime dangerous goods code

IATA: International Air Transport Association

ICAO: International Civil Aviation Organisation

COD: Chemical Oxygen Demand

BOD5: 5day biochemical oxygen demand

BCF: Bioconcentration factor

LD50: Lethal Dose 50

LC50: Lethal Concentration 50

EC50: Effective concentration 50 LogPOW: Octanolwater partition coefficient

Koc: Partition coefficient of organic carbon

UFI: unique formula identifier

IARC: International Agency for Research on Cancer

The information contained in this safety data sheet is based on sources, technical knowledge and current legislation at European and state level, without being able to guarantee its accuracy. This information cannot be considered a guarantee of the properties of the product, it is simply a description of the security requirements. The occupational methodology and conditions for users of this product are not within our awareness or control, and it is ultimately the responsibility of the user to take the necessary measures to obtain the legal requirements concerning the manipulation, storage, use and disposal of chemical products. The information on this safety data sheet only refers to this product, which should not be used for needs other than those specified.