

TECHNICAL INFORMATION

FOR PROFESSIONAL USE ONLY

MATTING PASTE		
PRODUCT DESCRIPTION		
<p>Product designed for matting the surface before painting, increasing its adhesion and helping to create a smooth even substrate. Paste also cleans and degreases the surface. Allows you to reach hard-to-reach areas e.g. doorjamb and sills, drip channel, door lock, handles etc. Suitable for use also on plastic.</p> <p>Water-based product, environmentally friendly.</p> <p>Intended to use with the Abrasive non-woven fabric.</p>		
PHYSICAL AND CHEMICAL PROPERTIES		
<p>Apperance : paste Capacity: 500 g Color: beige pH in 20°C : 9,5 Density in 20°C: 1,31 g/cm³</p>		
USAGE		
<ul style="list-style-type: none"> • Before use, shake the bottle for 2 – 3 minutes to mix the paste thoroughly. • Using clean water saturate the non-woven pad and apply a small amount of paste. • Using medium to firm pressure abrade the surface to create the cleaning foam . • Wipe until thoroughly clean and desired matt finish is obtained. • For matting larger surface areas the process. • All pretreated areas must be wiped down thoroughly with a damp cloth or sponge to completely remove Any remaining paste. • Surface must be dried prior to paint application. <p>Caution: For safety reasons always comply with information provided in the Material Safety Data Sheet.</p>		
STORAGE		
The product should be stored in dry, cool and ventilated places. Recommended storage temperature: 5 – 25°C. Protect from frost.		
WARRANTY PERIOD		
addsTROTON MATTING PASTE 500 g	2 years from the date of production.	
PRODUCT		Art. No.
addsTROTON MATTING PASTE 500 g		300010363
LIMITATION OF LIABILITY		
<p>The information contained in this TDS sheet is up-to-date and correct on the day the information is released. Because TROTON cannot control or predict the conditions under which a product will be used, each user should review the information in the specific context of the intended usage. To the maximum extent permitted by applicable law, TROTON shall not be liable for damages of any kind arising from the use or reliance on information contained in this TDS.</p> <p>Given the variety of factors that can affect the usage and application of the TROTON product, some of which are only within the user's knowledge and control range, it is essential that the user evaluate the TROTON product to determine if the product is fit for a particular purpose and whether the product is suitable for the user's usage.</p> <p>Under no circumstances shall TROTON be liable to the user or any third party for any indirect, derivative, incidental, special or punitive damages, including loss of profits resulting from the use of products manufactured by TROTON and / or TROTON's services.</p> <p>All information is based on meticulous laboratory tests and many years of experience. An established position on the market does not release us from continuous quality control of our products. However, we are not responsible for the final effects of improper storage or use of our products and for work that is not in line with good craftsmanship.</p>		
		TROTON Sp. z o.o. Ząbrowo, Poland