

## TECHNICAL INFORMATION

### addsTROTON MASKING TAPES



#### PRODUCT DESCRIPTION

High-quality masking tape for industry and automotive, characterized by very good adhesion on irregular surfaces, easy to remove without leave any adhesive residue. Resistant and compatible with most common paints.

#### PRODUCT TECHNICAL DATA

<b>Backing:</b>	58g/m <sup>2</sup> yellow saturated crepes paper
<b>Adhesive:</b>	Natural rubber and resins solvent based
<b>Total thickness:</b>	0.125 mm
<b>Adhesion to steel:</b>	4.3. N/25 mm
<b>Tensile strength:</b>	85 N/ 25 mm
<b>Elongation at break:</b>	7,5%
<b>Temperature resistance:</b>	80 <sup>0</sup> C (1 hour)
<b>Width:</b>	19 mm, 25 mm, 30 mm, 38 mm, 50 mm
<b>Roll length:</b>	50 m

#### STORAGE

Masking tapes technical features remain at their best for 12 months from production date when stored in temperature between +15 and +25<sup>0</sup>C and humidity level below 65%. It is the best not to expose the product to direct sunlight and heat sources, avoid quick and sudden temperature changes and high levels of humidity. When temperatures are lower than suggested, it is always required to recondition the tape at normal temperature before use.