

TECHNICAL INFORMATION

FOR PROFESSIONAL USE ONLY

adds TROTON SPRAY PLASTIC PRIMER



PRODUCT DESCRIPTION

High quality primer designed to use on treated and untreated surfaces made of plastics. Primer improves the adhesion ability of acrylics and polyurethanes to the several types of plastic. Easy to use and very efficient, fast dry.

PHYSICAL AND CHEMICAL PROPERTIES

- Color: transparent
- Base: polyolefine resin
- Volume: 400 ml
- Efficiency: $2 \div 3 \text{ m}^2$
- Re-sprayable: after 10 to 15 minutes

VOC CONTENT

VOC = 701,1 [g/l].

The product fulfils the requirements of the European Directive (2004/42/WE), which defines the volatile components content for that products category (cat..B/5) at the level of 840[g/l] for the ready product.

SUBSTRATE AND SURFACE PREPARATION

The product has very good adherence to various substrates. The surface should be degreased, dulled with the abrasive cloth. Next the surface should be again degreased, wash by water and dry.

CAUTION: Primer do not improve adhesion to polyethylene surface!

APPLICATION PROCESS

- Best processing temperature 15 – 25⁰C.
- Shake before using for 2 minutes and try it on cardboard.
- During lacquering hold aerosol in 25÷30 cm distance from the surface.
- Apply spray in maximum two thin layer interval 5÷10minutes.
- **Clean the spray nozzle after use!** – Holding the can with the valve pointing downward, press the button emptying the content for about 5 seconds.
- After drying, without sanding, re-sprayable with all lacquer systems.

Caution: For safety reasons always comply with information provided in the Material Safety Data Sheet

STORAGE

Store the product components in sealed container, in dry and cool places, away from heat sources, as well as direct sunlight.

EXPIRY DATE

5 years from the production date.

All information are based upon the precise laboratory studies and many years of experience. The good market position does not release us from the constant supervision of our products quality. However we are not responsible for the final effects of the improper storage or application of our products, as well as for work inconsistent with the good craft practice.

TROTON Sp. z o.o.
Ząbrowo, Poland