

TECHNICAL INFORMATION

FOR PROFESSIONAL USE ONLY

addsTROTON FINE LINE TAPE FLEXIBLE



PRODUCT DESCRIPTION

Fine line masking tape designer for specific application in automotive and general industry. High flexibility of the backing material allows good conformance to multi-dimensional surfaces. Is very thin, conforms to the dimensional changes during over-drying or UV drying. Doesn't leave residue after removal, is water-repellent. Suitable also for waterbased lacquer and plastic parts. Not recommended for outdoor use

TECHNICAL INFORMATIONS

Color:	blue
Carrier:	PVC
Adhesive	rubber
Total thickness:	0,14 mm
Adhesive strength:	4,1 N/25mm
Tensile strength:	65,6 N/25 mm
Elongation:	100 %
Temperature resistance:	+5°C to +138°C (to 45 min.)
Width:	3 mm, 6 mm, 9 mm, 12 mm
Roll length:	55 m

USAGE

- Recommended work temperature: +15°C do +50°C
- Surface must be free from dust and degreased, thoroughly cleaned and dried.
- Avoid to touch the exposed surface of the adhesive tape because it reduces product performance.
- Pressure sensitive adhesive must be applied with a maximum of pressure in order to achieve maximum pressure level.
- Maximum level of performance well be reached after total bonding period ie. 24 h. in temp. +23°C.

STORAGE AND WARRANTY PERIOD

Clean and dry in a well ventilated area, preferably at a temperature between +10°C and +30°C. Stored under these conditions shelf life will be a minimum of two years.