

TECHNICAL INFORMATION

FOR PROFESSIONAL USE ONLY

adds TROTON SPRAY REMOVER



PRODUCT DESCRIPTION

Remover spray is designed for cleaning spray guns, paint cabins, tools, machines and others application devices.

PHYSICAL AND CHEMICAL PROPERTIES

- Colour: transparent
- Scent: characteristic
- Volume: 400 ml.
- Yield: approx 0,8 m²
- Density: 0,903 g/cm³

VOC CONTENT

VOC for mixture= 821,7 [g/l].

The product fulfils the requirements of the European Directive (2004/42/WE), which defines the volatile components content for that products category (cat..B/5) at the level of 840[g/l] for the ready product.

USAGE

- Shake well before use.
- Make sure the distance between the spray nozzle and the surface is 20 - 25 cm.
- Leave for 5 – 15 min.
- Rinse the surface with solvent, silicone remover or strong stream of hot water.
- **Clean the spray nozzle after use!** – Holding the can with the valve pointing downward, press the button emptying the content for about 5 seconds.

Caution: To maintain safety, always follow the instructions given in the Safety Data Sheet for the given product.

PRECAUTIONS

- Apply only outdoors or in well ventilated area.
- Before applying on the cleaned surface protect the surroundings from splashes.
- Do not apply the product on hot surfaces and near open flames due to the low boiling point components. Use at 5 – 25°C.
- Avoid contact with amines, aluminum powder, magnesium, sodium, potassium. The reaction of these compounds are formed dangerous products.
- Do not use on plastics.
- Substance very aggressive! Protect respiratory tract, eyes, hands

Warning: Fumes are more heavy than air.

STORAGE

Product should be stored in dry, cool, ventilated place, away from fire and direct sunlight.

EXPIRY DATE

3 years from the production date.

Important Information:

The information contained in this document corresponds to our present knowledge and is a guide to our products and their uses.

Read all directions and warnings prior to using Troton products - Safety Data Sheets can be found online at www.troton.com.pl or will be sent according to your request: troton@troton.com.pl

Technical Information: The technical information, recommendations and other statements contained in this document are based upon tests or experience that Troton believes are reliable, but the accuracy or completeness of such information is not guaranteed.

Many factors beyond Troton's control and uniquely within user's knowledge and control can affect the use and performance of a Troton product in a particular application. Given the variety of factors that can affect the use and performance of a Troton product, user is solely responsible for evaluating the Troton product and determining whether it is fit for a particular purpose and suitable for user's method of application.

Limitation of Liability: Except where prohibited by law, Troton will not be liable for any loss or damage arising from the Troton product, whether direct, indirect, special, incidental or consequential, regardless of the legal theory asserted, including warranty, contract, negligence or strict liability. If used as instructed, this product is designed to comply with the European Volatile Organic Compound (VOC) Emission Standard for Automotive Refinish Coatings. Confirm compliance with your country, state and local air quality rules before use. The data on this sheet represent typical values. Since application variables are a major factor in product performance, this information should serve only as a general guide. Troton assumes no obligation or liability for use of this information.

TROTON Sp. z o.o.
Ząbrowo, Poland

TROTON Sp. z o.o

Address: Ząbrowo 14A, 78-120 Gościno, Poland, Tel: +48 94 35 123 94

Tel/Fax: +48 94 35 126 22 Website: www.troton.com.pl Email: troton@troton.com.pl