

TECHNICAL INFORMATION

FOR PROFESSIONAL USE ONLY

addsTROTON SPRAY RUST CONTROL 4 in 1



PRODUCT DESCRIPTION

Active corrosion protection coating system through effective 4 in 1 system - primer, corrosion protect, paint, finish. Quick-drying and efficient varnish, with excellent adhesion to many kind of surfaces like : iron, steel sheet, tinplate, copper, brass, aluminum, wood, stone, glass, fiberglass elements. It can be applied directly into rust and old layers of paint. Do not apply to lack with synthetic resin

PHYSICAL AND CHEMICAL PROPERTIES

- Color: white (RAL 9010), black (RAL 9005), clear grey (RAL 7035), silver (RAL 9006),
- Glass grade; semi mat
- Volume: 400 ml
- Density: 0,94 g/cm³
- Temperature resistance: up to 80°C
- Efficiency: approx. 2 – 3 m²

Drying time*

- Dust dry: after approx. 20 min
- Dry to touch: after approx. 2 hours
- Ready to lacquer: after approx. 24 hours

*drying time depends on the ambient temperature, air humidity and film thickness

VOLATILE COMPONENTS CONTENT

VOC = 627 [g/l]

The product fulfils the requirements of the European Directive (2004/42/WE), which defines the volatile components content for that products category (cat. B/5) at the level of 840[g/l] for the ready product.

USAGE

- Remove loose particles of rust with wire brush. Slightly grind surfaces free of corrosion with abrasive paper.
- The substrate must be dry, free of dirt and grease.
- On plastic elements apply primer for plastics.
- Shake container before use for at least 3 minutes and try it on cardboard.
- Before operation cover surfaces which should not to be lacquered.
- Spray from the distance approximately 25 cm.
- **Clean the spray nozzle after use!** – Holding the can with the valve pointing downward, press the button emptying the content for about 5 seconds.

Caution: To maintain safety, always follow the instructions given in the Safety Data Sheet for the given product.

STORAGE

Store the product components in a sealed container, in dry and cool places, away from fire and heat sources, as well as direct sunlight.

EXPIRY DATE

5 years from the production date.

All information are based upon the precise laboratory studies and many years of experience. The good market position does not release us from the constant supervision of our products quality. However we are not responsible for the final effects of the improper storage or application of our products, as well as for work inconsistent with the good craft practice.

TROTON Sp. z o.o.
Ząbrowo, Poland