

TECHNICAL INFORMATION

FOR PROFESSIONAL USE ONLY

addsTROTON SEAM SEALANT brushable



PRODUCT DESCRIPTION

Fast-drying product designed for sealing seams, joints and welds in the parts of car-body. Provides a flexible sealing ensuring excellent protection against water, moisture, dirt and dust. After curing doesn't crack and creates smooth layer, which can be painted with all lacquer systems*. Can be applied by nylon brush or putty knife.

PHYSICAL AND CHEMICAL PROPERTIES

- Color: light grey
- Capacity: 1 kg
- Base: synthetic rubber and resins
- Appearance: thixotropic paste
- Skin time: 3 – 4 min. (in 25°C)
- Specific gravity: 1,20 ± 0,02 g/cm³
- Drying time**: 24 h. (in 25°C, thickness 1 mm)
- Overpaintable: after fully dry (24 h.)
- Ambient temperature: 15 ÷ 35°C

*due to lots of paints and varnishes on the market compatibility test is recommended.

** Drying time depends on air temperature, humidity and thickness of the layer.

CONTENT OF VOLATILE MATTER

VOC =348 [g/l].

This product satisfies requirements of the European Union Directive (2004/42/WE), which for this product category (B/5) gives the limit value of content of volatile matter at the level of 840 [g/l] of the ready-for-use product.

USAGE

- Covered surface must be clean, dry, dedusted, degreased.
- Recommended is to pretreat surfaces with suitable primer
- Product should be applied on the surface in required thickness.
- Formed layer should be left untouched until complete drying. Therefore further forming is not required.

Caution: For safety reasons always comply with information provided in the Material Safety Data Sheet for the given product.

STORAGE

Store the product in a sealed container, in dry and cool places, away from fire and heat sources, as well as direct sunlight. Storage temperature 15-30°C.

EXPIRY DATE

18 months from the production date.

Important Information:

The information contained in this document corresponds to our present knowledge and is a guide to our products and their uses.

Read all directions and warnings prior to using Troton products - Safety Data Sheets can be found online at www.troton.com.pl or will be sent according to your request: troton@troton.com.pl

Technical Information: The technical information, recommendations and other statements contained in this document are based upon tests or experience that Troton believes are reliable, but the accuracy or completeness of such information is not guaranteed.

Many factors beyond Troton's control and uniquely within user's knowledge and control can affect the use and performance of a Troton product in a particular application. Given the variety of factors that can affect the use and performance of a Troton product, user is solely responsible for evaluating the Troton product and determining whether it is fit for a particular purpose and suitable for user's method of application.

Limitation of Liability: Except where prohibited by law, Troton will not be liable for any loss or damage arising from the Troton product, whether direct, indirect, special, incidental or consequential, regardless of the legal theory asserted, including warranty, contract, negligence or strict liability. If used as instructed, this product is designed to comply with the European Volatile Organic Compound (VOC) Emission Standard for Automotive Refinish Coatings. Confirm compliance with your country, state and local air quality rules before use. The data on this sheet represent typical values. Since application variables are a major factor in product performance, this information should serve only as a general guide. Troton assumes no obligation or liability for use of this information.

TROTON Sp. z o.o.
Ząbrowo, Poland