

TECHNICAL INFORMATION

FOR PROFESSIONAL USE ONLY

addsTROTON SPRAY SILVER CHROME acryl



PRODUCT DESCRIPTION

Fast-drying, lead-free, acrylic based, spray lacquer providing high gloss effect. It imparts chrome effect; resistant to adverse weather conditions; purposed for small car body parts, decoration, etc. Any other paint should not be apply, not resistant to attrition.

PHYSICAL AND CHEMICAL PROPERTIES

Color:	silver chrome
Glass grade:	high gloss
Capacity:	400 ml
Density:	0,87 kg/l
Efficiency:	approx. 1m ² / 400 ml
Drying time in 20°C*:	
- dust dry:	after approx. 5 – 15 minutes
- dry:	after approx. 24 hours

*drying time depends on the temperature, humidity and thickness of the coating.

CONTENT OF VOLATILE MATTER

VOC = 796 [g/l]

This product satisfies requirements of the European Union Directive (2004/42/WE), which for this product category (B/5) gives the limit value of content of volatile matter at the level of 840 [g/l] of the ready-for-use product.

SUBSTRATE AND PREPARING THE SURFACE

Spray can be apply on coversine and ancoversine to wood, metal, aluminums, glass, stone and equal type of plastic surface. First clear the surface carefully, dry and degrease. Old clear coat and rust, must be remove before grind off, face should be covering by filler. On plastic it is recommended to hold it at temperature of 50°C, with is useful to remove silicon from surface.

USAGE

- Best use temperature 15÷25 °C
- Shake before using for 2 minutes and try it on cardboard.
- **Do not connect with clear coat colourless and synthetic lacquer!**
- During lacquering hold aerosol in 25÷30 cm distance for metal surface.
- Apply spray thin layer interval 5÷10 minutes.
- **After use clean aerosol's outlets** – hold down aerosol's valve, push the bottom and release contents for 5 seconds.

Caution: To maintain safety, always follow the instructions given in the Safety Data Sheet for the given product.

STORAGE

Store the product components in a sealed container, in dry and cool places, away from fire and heat sources, as well as direct sunlight.

EXPIRY DATE

3 years from production date.

Important Information:

The information contained in this document corresponds to our present knowledge and is a guide to our products and their uses.

Read all directions and warnings prior to using Troton products - Safety Data Sheets can be found online at www.troton.com.pl or will be sent according to your request: troton@troton.com.pl

Technical Information: The technical information, recommendations and other statements contained in this document are based upon tests or experience that Troton believes are reliable, but the accuracy or completeness of such information is not guaranteed.

Many factors beyond Troton's control and uniquely within user's knowledge and control can affect the use and performance of a Troton product in a particular application. Given the variety of factors that can affect the use and performance of a Troton product, user is solely responsible for evaluating the Troton product and determining whether it is fit for a particular purpose and suitable for user's method of application.

Limitation of Liability: Except where prohibited by law, Troton will not be liable for any loss or damage arising from the Troton product, whether direct, indirect, special, incidental or consequential, regardless of the legal theory asserted, including warranty, contract, negligence or strict liability. If used as instructed, this product is designed to comply with the European Volatile Organic Compound (VOC) Emission Standard for Automotive Refinish Coatings. Confirm compliance with your country, state and local air quality rules before use. The data on this sheet represent typical values. Since application variables are a major factor in product performance, this information should serve only as a general guide. Troton assumes no obligation or liability for use of this information.

TROTON Sp. z o.o.
Ząbrowo, Poland