

TECHNICAL INFORMATION

FOR PROFESSIONAL USE ONLY

PRE – FILL CONVERTER SPRAY

PRODUCT DESCRIPTION

Pre – fill spray filled with propellant gas, organic thinner and special converter to converts 2K chemically curing products to 1K physically curing paint (cured due to thinner evaporation). A new innovative technology and special type of nozzle ensures perfect atomization to obtain the best results.

Caution:

Can be filled only using professional equipment.

Can be used for all 2k Acrylic Lacquers.

Cannot be used for polyurethane.

PCHYSICAL AND CHEMICAL PROPERTIES

Nozzle connector:	female
Base :	acrylic resin
Color:	depending on filling (content in colorless, does not affect the color of the paint used to fill)
Smell:	solvent
Capacity:	max. volume of 2K paint (without thinner) to fill : 100 ml max. can volume : 400 ml (content 300 ml. + paint 100 ml)
Efficiency:	depending on color and consistence of filling
VOC:	214,7 g./l. (approx.)
Drying time:	depend on filling (refer to information of the paint producer), thickness of coating, ambient temperature and air humidity.

USAGE

- Surface to be processed should be dry, cleaned and degreased.
- Preparation of the surface and adhesion to the substrate depends on the used filling.
- Larger bare surface must be pre-primed with the primer recommended by manufacturer of paint used to fill the cans.
- Fill can with paint (max. 100 ml) using a suitable applicator.
- Shake before use for about 2 minutes.
- Carry out spray test.
- It's recommended to use product after filling within max. 5 days (refer to information of the paint producer).
- **Clean the spray nozzle after use!** – Holding the can with the valve pointing downward, press the button emptying the content for about 5 seconds.

Caution: For safety reasons always comply with information provided in the Material Safety Data Sheet.

STORAGE

Store the product components in sealed container, in dry and cool places, away from heat sources, as well as direct sunlight.

EXPIRY DATE

Empty cans : 5 years from production date.

Important Information:

The information contained in this document corresponds to our present knowledge and is a guide to our products and their uses.

Read all directions and warnings prior to using Troton products - Safety Data Sheets can be found online at www.troton.com.pl or will be sent according to your request: troton@troton.com.pl

Technical Information: The technical information, recommendations and other statements contained in this document are based upon tests or experience that Troton believes are reliable, but the accuracy or completeness of such information is not guaranteed.

Many factors beyond Troton's control and uniquely within user's knowledge and control can affect the use and performance of a Troton product in a particular application. Given the variety of factors that can affect the use and performance of a Troton product, user is solely responsible for evaluating the Troton product and determining whether it is fit for a particular purpose and suitable for user's method of application.

Limitation of Liability: Except where prohibited by law, Troton will not be liable for any loss or damage arising from the Troton product, whether direct, indirect, special, incidental or consequential, regardless of the legal theory asserted, including warranty, contract, negligence or strict liability.

If used as instructed, this product is designed to comply with the European Volatile Organic Compound (VOC) Emission Standard for Automotive Refinish Coatings. Confirm compliance with your country, state and local air quality rules before use. The data on this sheet represent typical values. Since application variables are a major factor in product performance, this information should serve only as a general guide. Troton assumes no obligation or liability for use of this information.

TROTON Sp. z o.o.
Ząbrowo, Poland