-adds-

Safety data sheet

This SDS is an English translation of COMMISSION REGULATION (EU) 2020/878, without any country-specific legislation

# ZINC ALUMINIUM

FCT	TION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING						
.1	Product identifier: ZINC ALUMINIUM						
	Other means of identification:						
	<b>UFI:</b> M3FV-520X-W00V-W65F						
.2	Relevant identified uses of the substance or mixture and uses advised against:						
	Relevant uses: Car repair; spray paint. For professional users only.						
	Uses advised against: All uses not specified in this section or in section 7.3						
.3	Details of the supplier of the safety data sheet:						
	Troton Sp. z o.o.						
	Ząbrowo 14A 78-120 Gościno - Zachodniopomorskie - Polska						
	Phone: +48 94 35 123 94 - Fax: +48 94 35 126 22						
	troton@troton.com.pl www.troton.pl / www.troton.eu						
.4	Emergency telephone number: (8am-4pm)+48 094 35 123 94; 112						
ECT	TION 2: HAZARDS IDENTIFICATION						
.1	Classification of the substance or mixture:						
	CLP Regulation (EC) No 1272/2008:						
	Classification of this product has been carried out in accordance with CLP Regulation (EC) No 1272/2008.						
	Aerosol 1: Pressurised container: May burst if heated., H229 Aerosol 1: Flammable aerosols, Category 1, H222						
	Aquatic Chronic 2: Hazardous to the aquatic environment, long-term hazard, Category 2, H411						
	Eye Irrit. 2: Eye irritation, Category 2, H319						
.2	STOT SE 3: Specific toxicity causing drowsiness and dizziness, single exposure, Category 3, H336 Label elements:						
	CLP Regulation (EC) No 1272/2008:						
	Danger						
	Hazard statements:						
	Aerosol 1: H229 - Pressurised container: May burst if heated. Aerosol 1: H222 - Extremely flammable aerosol.						
	Aquatic Chronic 2: H411 - Toxic to aquatic life with long lasting effects.						
	Eye Irrit. 2: H319 - Causes serious eye irritation.						
	STOT SE 3: H336 - May cause drowsiness or dizziness. Precautionary statements:						
	P210: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.						
	P251: Do not pierce or burn, even after use.						
	P280: Wear protective gloves/protective clothing/respiratory protection/eye protection/protective footwear.						
	P304+P340: IF INHALED: Remove person to fresh air and keep comfortable for breathing. P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to						
	do. Continue rinsing.						
	P403+P233: Store in a well-ventilated place. Keep container tightly closed. P410+P412: Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122°F						
	P501: Dispose of contents/container in accordance with regulations on hazardous waste or packaging and packaging waste						
	respectively.						
	Supplementary information:						
	EUH066: Repeated exposure may cause skin dryness or cracking.						
	Substances that contribute to the classification						
2	acetone; Hydrocarbons, C9, aromatics; butan-1-ol						
.3	Other hazards:						



This SDS is an English translation of COMMISSION REGULATION (EU) 2020/878, without any country-specific legislation

# ZINC ALUMINIUM

			ENTIFICATION (co	ontinued)						
		ct fails to meet PE rine-disrupting pr	3T/vPvB criteria operties: The product	t fails to meet t	he criteria.					
ECT	FION 3	: COMPOSITIO	N/INFORMATION	ON INGRED	IENTS					
1		ance:								
	Non-applicable									
2	Mixture:									
	Chemical description: Mixture composed of chemical products									
	Components:									
	In accordance with Annex II of Regulation (EC) No 1907/2006 (point 3), the product contains:									
		Identification			Chemical name/Classification			Concentratio		
	CAS: EC:	67-64-1 200-662-2	acetone <sup>(1)</sup>				ATP CLP00			
	Index:	606-001-00-8 01-2119471330-49- XXXX	Regulation 1272/2008	Eye Irrit. 2: H319; I	Flam. Liq. 2: H225; STOT SE 3: H336;	EUH066 - Danger		25 - <50 9		
	CAS:	106-97-8	Butane <sup>(1)</sup>				ATP CLP00			
	EC: 203-448-7 Index: 601-004-00-0 REACH: 01-2119474691-32- XXXX	Regulation 1272/2008	Flam. Gas 1A: H220	); Press. Gas: H280 - Danger		۲	10 - <25 %			
	CAS:	74-98-6	Propane <sup>(1)</sup>				ATP CLP00			
	EC: 200-827-9 Index: 601-003-00-5 REACH: 01-2119486944-21- XXXX		Regulation 1272/2008	Flam. Gas 1A: H220	); Press. Gas: H280 - Danger		۲	10 - <25 9		
	CAS:	128601-23-0	Hydrocarbons, C9, a	romatics <sup>(2)</sup>			Self-classified			
		918-668-5 Non-applicable 01-2119455851-35- XXXX	Regulation 1272/2008		H411; Asp. Tox. 1: H304; Flam. Liq. 3 H336; EUH066 - Danger	: H226; STOT SE 3:		5 - <10 %		
	CAS:	75-28-5	Isobutane <sup>(1)</sup>				ATP CLP00			
		200-857-2 601-004-00-0 01-2119485395-27- XXXX	Regulation 1272/2008	Flam. Gas 1A: H220	); Press. Gas: H280 - Danger		۲	5 - <10 %		
	CAS:	7440-66-6	Zinc powder - zinc di	ust (stabilised)(1	)		ATP CLP00			
		231-175-3 030-002-00-7 01-2119467174-37- XXXX	Regulation 1272/2008	Aquatic Acute 1: H4	100; Aquatic Chronic 1: H410 - Warnir	ng		1 - <2,5 %		
	CAS:	71-36-3	butan-1-ol <sup>(1)</sup>				ATP CLP00			
		200-751-6 603-004-00-6 01-2119484630-38- XXXX	Regulation 1272/2008	Acute Tox. 4: H302 STOT SE 3: H335; 9	; Eye Dam. 1: H318; Flam. Liq. 3: H22 STOT SE 3: H336 - Danger	26; Skin Irrit. 2: H315;	(1)	1 - <2,5 %		
	CAS:	7779-90-0	trizinc bis(orthophos	sphate) <sup>(1)</sup>			ATP CLP00			
		231-944-3 Non-applicable 01-2119485044-40- XXXX	Regulation 1272/2008	Aquatic Acute 1: H4	100; Aquatic Chronic 1: H410 - Warnir	ıg	Ł	<1 %		
	CAS:	1314-13-2	zinc oxide <sup>(1)</sup>				ATP CLP00			
		215-222-5 030-013-00-7 01-2119463881-32-	Regulation 1272/2008	Aquatic Acute 1: H4	100; Aquatic Chronic 1: H410 - Warnir	ng		<1 %		

<sup>(1)</sup> Voluntarily-listed substance failing to meet any of the criteria set out in Regulation (EU) No. 2020/878
 <sup>(2)</sup> Substances presenting a health or environmental hazard which meet criteria laid down in Regulation (EU) No. 2020/878

To obtain more information on the hazards of the substances consult sections 11, 12 and 16.

### SECTION 4: FIRST AID MEASURES

#### 4.1 Description of first aid measures:

The symptoms resulting from intoxication can appear after exposure, therefore, in case of doubt, seek medical attention for direct exposure to the chemical product or persistent discomfort, showing the SDS of this product.

Safety data sheet This SDS is an English translation of COMMISSION REGULATION (EU) 2020/878, without any country-specific legislation

# ZINC ALUMINIUM

<ul> <li>By inhalation:</li> <li>Remove the person affected from the area of exposure, provide with fresh air and keep at rest. In serious cases such as cardiorespiratory failure, artificial resuscitation techniques will be necessary (mouth to mouth resuscitation, cardiac massag oxygen supply, etc.) requiring immediate medical assistance.</li> <li>By skin contact:</li> <li>Remove contaminated clothing and footwear, rinse skin or shower the person affected if appropriate with plenty of cold wal and neutral soap. In serious cases see a doctor. If the product causes burns or freezing, clothing should not be removed as could worsen the injury caused if it is stuck to the skin. If blisters form on the skin, these should never be burst as this will increase the risk of infection.</li> </ul>							
Rinse eyes thoroughly with lukewarm water for at least 15 minutes. Do not allow the person affected to rub or close th If the injured person uses contact lenses, these should be removed unless they are stuck to the eyes, in which case this cause further damage. In all cases, after cleaning, a doctor should be consulted as quickly as possible with the SDS of product.							
	By ingestion/aspiration:						
4.2	Do not induce vomiting, but i out the mouth and throat, as <b>Most important symptom</b>	they may have been affect	ted during ingestion.	h. Keep the person affected at rest. Rinse			
7.2	Acute and delayed effects are	•	•				
4.3	Indication of any immedia			-di			
т.Э	•		iu speciai creatilient lieeu	Ξ.			
	Non-applicable						

If possible use polyvalent powder fire extinguishers (ABC powder), alternatively use foam or carbon dioxide extinguishers (CO2).

### Unsuitable extinguishing media:

IT IS RECOMMENDED NOT to use full jet water as an extinguishing agent.

#### 5.2 Special hazards arising from the substance or mixture:

As a result of combustion or thermal decomposition reactive sub-products are created that can become highly toxic and, consequently, can present a serious health risk.

### 5.3 Advice for firefighters:

Depending on the magnitude of the fire it may be necessary to use full protective clothing and self-contained breathing apparatus (SCBA). Minimum emergency facilities and equipment should be available (fire blankets, portable first aid kit,...) in accordance with Directive 89/654/EC.

#### Additional provisions:

Act in accordance with the Internal Emergency Plan and the Information Sheets on actions to take after an accident or other emergencies. Eliminate all sources of ignition. In case of fire, cool the storage containers and tanks for products susceptible to combustion, explosion or BLEVE as a result of high temperatures. Avoid spillage of the products used to extinguish the fire into an aqueous medium.

### SECTION 6: ACCIDENTAL RELEASE MEASURES

### 6.1 Personal precautions, protective equipment and emergency procedures:

### For non-emergency personnel:

Isolate leaks provided that there is no additional risk for the people performing this task. Evacuate the area and keep out those without protection. Personal protection equipment must be used against potential contact with the spilt product (See section 8). Above all prevent the formation of any vapour-air flammable mixtures, through either ventilation or the use of an inert medium. Remove any source of ignition. Eliminate electrostatic charges by interconnecting all the conductive surfaces on which static electricity could form, and also ensuring that all surfaces are connected to the ground.

### For emergency responders:

Wear protective equipment. Keep unprotected persons away. See section 8.



This SDS is an English translation of COMMISSION REGULATION (EU) 2020/878, without any country-specific legislation

# ZINC ALUMINIUM

Printing	: 26/01/2023	Date of compilation: 13/05/2020	Revised: 14/06/2022	Version: 3 (Replaced 2)				
SEC	SECTION 6: ACCIDENTAL RELEASE MEASURES (continued)							
6.2	Avoid at all cost any type of spillage into an aqueous medium. Contain the product absorbed appropriately in hermetically sealed containers. Notify the relevant authority in case of exposure to the general public or the environment.							
6.3								
	It is recommended:							
6.4	absorb in sawdust or other combustible							
	See sections 8 and 13.							
L								
SEC	SECTION 7: HANDLING AND STORAGE							

#### 7.1 Precautions for safe handling:

A.- General precautions for safe use

Comply with the current legislation concerning the prevention of industrial risks. Keep containers hermetically sealed. Control spills and residues, destroying them with safe methods (section 6). Avoid leakages from the container. Maintain order and cleanliness where dangerous products are used.

B.- Technical recommendations for the prevention of fires and explosions

Avoid the evaporation of the product as it contains flammable substances, which could form flammable vapour/air mixtures in the presence of sources of ignition. Control sources of ignition (mobile phones, sparks,...) and transfer at slow speeds to avoid the creation of electrostatic charges. Consult section 10 for conditions and materials that should be avoided.

C.- Technical recommendations on general occupational hygiene

Do not eat or drink during the process, washing hands afterwards with suitable cleaning products.

D.- Technical recommendations to prevent environmental risks

Due to the danger of this product for the environment it is recommended to use it within an area containing contamination control barriers in case of spillage, as well as having absorbent material in close proximity.

### 7.2 Conditions for safe storage, including any incompatibilities:

A.- Technical measures for storage

Maximum Temp.: 25 °C

B.- General conditions for storage

Avoid sources of heat, radiation, static electricity and contact with food. For additional information see subsection 10.5

### 7.3 Specific end use(s):

Except for the instructions already specified it is not necessary to provide any special recommendation regarding the uses of this product.

### SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

#### 8.1 Control parameters:

Substances whose occupational exposure limits have to be monitored in the workplace (European OEL, not country-specific legislation):

Directive (EU) 2000/39, Directive 2004/37/EC, Directive (EU) 2006/15, Directive (EU) 2009/161, Directive (EU) 2017/164, Directive (EU) 2019/1831:

		Identification	Occupational exposure limits			
a	acetone		IOELV (8h)	500 ppm	1210 mg/m <sup>3</sup>	
(	CAS: 67-64-1	EC: 200-662-2	IOELV (STEL)			

#### DNEL (Workers):

	Short e	xposure	Long exposure		
Identification		Systemic	Local	Systemic	Local
acetone	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
CAS: 67-64-1	Dermal	Non-applicable	Non-applicable	186 mg/kg	Non-applicable
EC: 200-662-2	Inhalation	Non-applicable	2420 mg/m <sup>3</sup>	1210 mg/m <sup>3</sup>	Non-applicable

- CONTINUED ON NEXT PAGE -



### Printing: 26/01/2023 Date of comp

Date of compilation: 13/05/2020

Revised: 14/06/2022

Version: 3 (Replaced 2)

# SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION (continued)

		Short	Short exposure		exposure
Identification		Systemic	Local	Systemic	Local
Hydrocarbons, C9, aromatics	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
CAS: 128601-23-0	Dermal	Non-applicable	Non-applicable	25 mg/kg	Non-applicable
EC: 918-668-5	Inhalation	Non-applicable	Non-applicable	150 mg/m <sup>3</sup>	Non-applicable
Zinc powder - zinc dust (stabilised)	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
CAS: 7440-66-6	Dermal	Non-applicable	Non-applicable	83 mg/kg	Non-applicable
EC: 231-175-3	Inhalation	Non-applicable	Non-applicable	5 mg/m <sup>3</sup>	Non-applicable
butan-1-ol	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
CAS: 71-36-3	Dermal	Non-applicable	Non-applicable	Non-applicable	Non-applicable
EC: 200-751-6	Inhalation	Non-applicable	Non-applicable	Non-applicable	310 mg/m <sup>3</sup>
trizinc bis(orthophosphate)	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
CAS: 7779-90-0	Dermal	Non-applicable	Non-applicable	83 mg/kg	Non-applicable
EC: 231-944-3	Inhalation	Non-applicable	Non-applicable	5 mg/m <sup>3</sup>	Non-applicable
zinc oxide	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
CAS: 1314-13-2	Dermal	Non-applicable	Non-applicable	83 mg/kg	Non-applicable
EC: 215-222-5	Inhalation	Non-applicable	Non-applicable	5 mg/m <sup>3</sup>	0,5 mg/m <sup>3</sup>

### DNEL (General population):

		Short e	exposure	Long exposure	
Identification		Systemic	Local	Systemic	Local
acetone	Oral	Non-applicable	Non-applicable	62 mg/kg	Non-applicable
CAS: 67-64-1	Dermal	Non-applicable	Non-applicable	62 mg/kg	Non-applicable
EC: 200-662-2	Inhalation	Non-applicable	Non-applicable	200 mg/m <sup>3</sup>	Non-applicable
Hydrocarbons, C9, aromatics	Oral	Non-applicable	Non-applicable	11 mg/kg	Non-applicable
CAS: 128601-23-0	Dermal	Non-applicable	Non-applicable	11 mg/kg	Non-applicable
EC: 918-668-5	Inhalation	Non-applicable	Non-applicable	32 mg/m <sup>3</sup>	Non-applicable
Zinc powder - zinc dust (stabilised)	Oral	Non-applicable	Non-applicable	0,83 mg/kg	Non-applicable
CAS: 7440-66-6	Dermal	Non-applicable	Non-applicable	83 mg/kg	Non-applicable
EC: 231-175-3	Inhalation	Non-applicable	Non-applicable	2,5 mg/m <sup>3</sup>	Non-applicable
butan-1-ol	Oral	Non-applicable	Non-applicable	1,562 mg/kg	Non-applicable
CAS: 71-36-3	Dermal	Non-applicable	Non-applicable	3,125 mg/kg	Non-applicable
EC: 200-751-6	Inhalation	Non-applicable	Non-applicable	55,357 mg/m <sup>3</sup>	155 mg/m <sup>3</sup>
trizinc bis(orthophosphate)	Oral	Non-applicable	Non-applicable	0,83 mg/kg	Non-applicable
CAS: 7779-90-0	Dermal	Non-applicable	Non-applicable	83 mg/kg	Non-applicable
EC: 231-944-3	Inhalation	Non-applicable	Non-applicable	2,5 mg/m <sup>3</sup>	Non-applicable
zinc oxide	Oral	Non-applicable	Non-applicable	0,83 mg/kg	Non-applicable
CAS: 1314-13-2	Dermal	Non-applicable	Non-applicable	83 mg/kg	Non-applicable
EC: 215-222-5	Inhalation	Non-applicable	Non-applicable	2,5 mg/m <sup>3</sup>	Non-applicable

PNEC:

Identification				
acetone	STP	100 mg/L	Fresh water	10,6 mg/L
CAS: 67-64-1	Soil	29,5 mg/kg	Marine water	1,06 mg/L
EC: 200-662-2	Intermittent	21 mg/L	Sediment (Fresh water)	30,4 mg/kg
	Oral	Non-applicable	Sediment (Marine water)	3,04 mg/kg
Zinc powder - zinc dust (stabilised)	STP	0,1 mg/L	Fresh water	0,0206 mg/L
CAS: 7440-66-6	Soil	106,8 mg/kg	Marine water	0,0061 mg/L
EC: 231-175-3	Intermittent	Non-applicable	Sediment (Fresh water)	235,6 mg/kg
	Oral	Non-applicable	Sediment (Marine water)	121 mg/kg
butan-1-ol	STP	2476 mg/L	Fresh water	0,082 mg/L
CAS: 71-36-3	Soil	0,017 mg/kg	Marine water	0,008 mg/L
EC: 200-751-6	Intermittent	2,25 mg/L	Sediment (Fresh water)	0,324 mg/kg
	Oral	Non-applicable	Sediment (Marine water)	0,032 mg/kg

- CONTINUED ON NEXT PAGE -



_	on 8: exposure c					
	Iden	tification				
t	rizinc bis(orthophosphate)		STP	0,1 mg/L	Fresh water	0,0206 mg/L
C	CAS: 7779-90-0		Soil	35,6 mg/kg	Marine water	0,0061 mg/L
E	EC: 231-944-3		Intermittent	Non-applicable	Sediment (Fresh water)	117,8 mg/kg
			Oral	Non-applicable	Sediment (Marine water)	56,5 mg/kg
z	zinc oxide		STP	0,1 mg/L	Fresh water	0,0206 mg/L
C	CAS: 1314-13-2		Soil	35,6 mg/kg	Marine water	0,0061 mg/L
E	EC: 215-222-5		Intermittent	Non-applicable	Sediment (Fresh water)	117,8 mg/kg
			Oral	Non-applicable	Sediment (Marine water)	56,5 mg/kg
<ul> <li>A Individual protection measures, such as personal protective equipment</li> <li>As a preventative measure it is recommended to use basic Personal Protective Equipment, with the corresponding &lt;<cl marking="">&gt; in accordance with Regulation (EU) 2016/425. For more information on Personal Protective Equipment (stor use, cleaning, maintenance, class of protection,) consult the information leaflet provided by the manufacturer. For mo information see subsection 7.1. All information contained herein is a recommendation which needs some specification f the labour risk prevention services as it is not known whether the company has additional measures at its disposal.</cl></li> <li>B Respiratory protection</li> </ul>						
В	marking>> in accor use, cleaning, main information see sub the labour risk prev	neasure it is recommend rdance with Regulation tenance, class of protect section 7.1. All informa ention services as it is r	led to use basic (EU) 2016/425. tion,) consult tion contained l	Personal Protective For more informati the information lea nerein is a recomm	on on Personal Protective flet provided by the manu endation which needs son	Equipment (storage ifacturer. For more ne specification fro
В	marking>> in accor use, cleaning, main information see sub the labour risk prev	neasure it is recommend rdance with Regulation tenance, class of protect section 7.1. All informa ention services as it is r	led to use basic (EU) 2016/425. tion,) consult tion contained l	Personal Protective For more informati the information lea nerein is a recomm	on on Personal Protective flet provided by the manu endation which needs sor as additional measures at	Equipment (storage ifacturer. For more ne specification fro

C.- Specific protection for the hands

Pictogram	PPE	Labelling	CEN Standard	Remarks
Mandatory hand protection	NON-disposable chemical protective gloves (Material: Latex (natural rubber), Breakthrough time: > 480 min, Thickness: 0.4 mm)		EN ISO 374-1:2016+A1:2018 EN 16523-1:2015+A1:2018 EN ISO 21420:2020	The Breakthrough Time indicated by the manufacturer must exceed the period during which the product is being used. Do not use protective creams after the product has come into contact with skin.

As the product is a mixture of several substances, the resistance of the glove material can not be calculated in advance with total reliability and has therefore to be checked prior to the application.

D.- Eye and face protection

Pictogram	PPE	Labelling	CEN Standard	Remarks
Mandatory face protection	Panoramic glasses against splash/projections.	CAT II	EN 166:2002 EN ISO 4007:2018	Clean daily and disinfect periodically according to the manufacturer's instructions. Use if there is a risk of splashing.

E.- Body protection

Pictogram	PPE	Labelling	CEN Standard	Remarks
Mandatory complete body protection	Disposable clothing for protection against chemical risks, with antistatic and fireproof properties		EN 1149-1,2,3 EN 13034:2005+A1:2009 EN ISO 13982- 1:2004/A1:2010 EN ISO 6529:2013 EN ISO 6530:2005 EN ISO 13688:2013 EN 464:1994	For professional use only. Clean periodically according to the manufacturer's instructions.
Mandatory foot protection	Safety footwear for protection against chemical risk, with antistatic and heat resistant properties		EN ISO 13287:2020 EN ISO 20345:2011 EN 13832-1:2019	Replace boots at any sign of deterioration.

-adds-

Safety data sheet

This SDS is an English translation of COMMISSION REGULATION (EU) 2020/878, without any country-specific legislation

# ZINC ALUMINIUM

ION 8: EXPOSURE CONTROLS,	FERSONAL FROTECTION		-					
Emergency measure	Standards	Emergency measure	Standards					
	ANSI Z358-1 50 3864-1:2011, ISO 3864-4:2011	<b>●</b> + <b>▼</b>	DIN 12 899 ISO 3864-1:2011, ISO 3864-4:20					
Emergency shower	_	Eyewash stations						
Environmental exposure contro		• • • • • • •						
In accordance with the community spillage of both the product and its	legislation for the protection container. For additional info	of the environment it is rec rmation see subsection 7.1.	ommended to avoid environment D					
Volatile organic compounds:								
With regard to Directive 2010/75/E		ving characteristics:						
V.O.C. (Supply):	92,6 % weight							
,	.O.C. density at 20 °C: 746 kg/m <sup>3</sup> (746 g/L)							
Average carbon number:								
Average molecular weight:	69,18 g/mol							
TON 9: PHYSICAL AND CHEMI	CAL PROPERTIES							
Information on basic physical a	and chemical properties:							
For complete information see the p	roduct datasheet.							
Appearance:								
Physical state at 20 °C:	Aerosol							
Appearance:	Volatile							
Colour:	Silv	ver						
Odour:	Charact	eristic						
Odour threshold:	Non-ap	plicable *						
Volatility:								
Boiling point at atmospheric pressu	re: -44 °C	(Propellant)						
Vapour pressure at 20 °C:	830000	Ра						
Vapour pressure at 50 °C:	<30000	00 Pa (300 kPa)						
Evaporation rate at 20 °C:	Non-ap	plicable *						
Product description:								
Density at 20 °C:	711 kg/	′m³						
Relative density at 20 °C:	Non-ap	plicable *						
Dynamic viscosity at 20 °C:	Non-ap	Non-applicable *						
Kinematic viscosity at 20 °C:	Non-ap	Non-applicable *						
Kinematic viscosity at 40 °C:	Non-ap	Non-applicable *						
Concentration:	Non-ap	Non-applicable *						
pH:	Non-ap	Non-applicable *						
Vapour density at 20 °C:	Non-ap	Non-applicable *						
Partition coefficient n-octanol/wate	r 20 °C: Non-ap	plicable *						
Solubility in water at 20 °C:	Non-ap	plicable *						
Solubility properties:	Non-ap	plicable *						
Decomposition temperature:	Non-ap	plicable *						
Melting point/freezing point:	Non-ap	plicable *						
Recipient pressure:	Non-ap	plicable *						



Printing	: 26/01/2023	Date of compilation: 13/05/2020	Revised: 14/06/2022	Version: 3 (Replaced 2)
SECT	TION 9: PHYSIC	AL AND CHEMICAL PROPERTIE	S (continued)	
	Flash Point:		Non-applicable	
	Flammability (sol	id, gas):	Non-applicable *	
	Autoignition temp	perature:	365 °C (Propellant)	
	Lower flammabili	ity limit:	0,7 % Volume	
	Upper flammabili	ty limit:	13 % Volume	
	Particle charac	teristics:		
	Median equivaler	nt diameter:	Non-applicable	
9.2	Other informat	ion:		
	Information wi	ith regard to physical hazard clas	sses:	
	Explosive propert	ties:	Non-applicable *	
	Oxidising propert	ies:	Non-applicable *	
	Corrosive to meta	als:	Non-applicable *	
	Heat of combusti	ion:	Non-applicable *	
	Aerosols-total pe components:	rcentage (by mass) of flammable	Non-applicable *	
	Other safety ch	naracteristics:		
	Surface tension a	at 20 °C:	Non-applicable *	
	Refraction index:		Non-applicable *	
	*Not relevant due to	the nature of the product, not providing info	rmation property of its hazards.	

SECTION 10: STABILITY AND REACTIVITY

### 10.1 Reactivity:

No hazardous reactions are expected because the product is stable under recommended storage conditions. See section 7.

#### 10.2 Chemical stability:

Chemically stable under the indicated conditions of storage, handling and use.

#### 10.3 Possibility of hazardous reactions:

Under the specified conditions, hazardous reactions that lead to excessive temperatures or pressure are not expected.

#### **10.4** Conditions to avoid:

Applicable for handling and storage at room temperature:

Shock and friction	Contact with air	Increase in temperature	Sunlight	Humidity
Not applicable	Not applicable	Risk of combustion	Avoid direct impact	Not applicable

#### 10.5 Incompatible materials:

Acids	Water	Oxidising materials	Combustible materials	Others
Avoid strong acids	Not applicable	Avoid direct impact	Not applicable	Avoid alkalis or strong bases

### 10.6 Hazardous decomposition products:

See subsection 10.3, 10.4 and 10.5 to find out the specific decomposition products. Depending on the decomposition conditions, complex mixtures of chemical substances can be released: carbon dioxide (CO<sub>2</sub>), carbon monoxide and other organic compounds.

#### SECTION 11: TOXICOLOGICAL INFORMATION

#### 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008:

The experimental information related to the toxicological properties of the product itself is not available

#### Dangerous health implications:

In case of exposure that is repetitive, prolonged or at concentrations higher than the recommended occupational exposure limits, adverse effects on health may result, depending on the means of exposure:

A- Ingestion (acute effect):



This SDS is an English translation of COMMISSION REGULATION (EU) 2020/878, without any country-specific legislation

# ZINC ALUMINIUM

rinting: 26/01/2023	Date of compilation: 13/05/2020	Revised: 14/06	5/2022 Ver	sion: 3 (Replaced 2)	
SECTION 11: TOXIC	OLOGICAL INFORMATION (continu	ued)			
- Acute toxic as dangerous - Corrosivity	city : Based on available data, the classi for consumption. For more information r/Irritability: Based on available data, the nazardous for this effect. For more inform	fication criteria are see section 3.	eria are not met. H		
as hazardous - Corrosivity classified as h	city : Based on available data, the classif for inhalation. For more information see /Irritability: Based on available data, the nazardous for inhalation. For more inform the skin and the eyes (acute effect):	section 3. classification crite	eria are not met. H		
classified as h - Contact wi	ith the skin: Based on available data, the nazardous for skin contact. For more info ith the eyes: Produces eye damage after (carcinogenicity, mutagenicity and toxicit	rmation see section contact.	on 3.	However, it contains sub	ostances
as hazardous IARC: Hydr - Mutagenic hazardous for - Reproduct	nicity: Based on available data, the classi for the effects mentioned. For more info ocarbons, C9, aromatics (3) ity: Based on available data, the classific r this effect. For more information see se ive toxicity: Based on available data, the nazardous for this effect. For more inform fects:	ormation see section ation criteria are r action 3. classification crite	on 3. not met, as it does eria are not met, as	not contain substances	classified as
hazardous wi - Skin: Base hazardous fo	<ul> <li>Respiratory: Based on available data, the classification criteria are not met, as it does not contain substances classified hazardous with sensitising effects. For more information see section 3.</li> <li>Skin: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.</li> <li>F- Specific target organ toxicity (STOT) - single exposure:</li> </ul>				
vomiting, con	high concentration can interfere with the Ifusion, and in serious cases, loss of cons at organ toxicity (STOT)-repeated exposu	sciousness.	ystem causing head	dache, dizziness, vertig	o, nausea,
it does not co	rget organ toxicity (STOT)-repeated expo ontain substances classified as hazardous eated exposure may cause skin dryness c zard:	for this effect. Fo			not met, as
	ilable data, the classification criteria are For more information see section 3. .ion:	not met. Howeve	r, it does contain s	ubstances classified as	hazardous
Non-applicable					
Specific toxicol	logy information on the substances:				
	Identification		Acut	te toxicity	Genus
acetone			LD50 oral	5800 mg/kg	Rat
CAS: 67-64-1			LD50 dermal	7426 mg/kg	Rabbit
EC: 200-662-2			LC50 inhalation	76 mg/L (4 h)	Rat
Butane			LD50 oral	>2000 mg/kg	
CAS: 106-97-8			LD50 dermal	>2000 mg/kg	
EC: 203-448-7			LC50 inhalation	658 mg/L (4 h)	Rat
Propane			LD50 oral	>2000 mg/kg	
CAS: 74-98-6			LD50 dermal	>2000 mg/kg	
EC: 200-827-9			LC50 inhalation	>5 mg/L	
Zinc powder - zinc c	lust (stabilised)		LD50 oral	>2000 mg/kg	
CAS: 7440-66-6			LD50 dermal	>2000 mg/kg	
EC: 231-175-3			LC50 inhalation	>5 mg/L	



Printing: 26/01/2023	Date of compilation: 13/05/2020	Revised: 14/06/2022	V
----------------------	---------------------------------	---------------------	---

Version: 3 (Replaced 2)

# SECTION 11: TOXICOLOGICAL INFORMATION (continued)

Identification	А	cute toxicity	Genu
Hydrocarbons, C9, aromatics	LD50 oral	>2000 mg/kg	
CAS: 128601-23-0	LD50 dermal	>2000 mg/kg	
EC: 918-668-5	LC50 inhalation	>20 mg/L	
Isobutane	LD50 oral	>2000 mg/kg	
CAS: 75-28-5	LD50 dermal	>2000 mg/kg	
EC: 200-857-2	LC50 inhalation	>5 mg/L	
butan-1-ol	LD50 oral	800 mg/kg	Rat
CAS: 71-36-3	LD50 dermal	3430 mg/kg	Rabb
EC: 200-751-6	LC50 inhalation	24,66 mg/L (4 h)	Rat
trizinc bis(orthophosphate)	LD50 oral	>2000 mg/kg	
CAS: 7779-90-0	LD50 dermal	>2000 mg/kg	
EC: 231-944-3	LC50 inhalation	>5 mg/L	
zinc oxide	LD50 oral	7950 mg/kg	Mous
CAS: 1314-13-2	LD50 dermal	>2000 mg/kg	
EC: 215-222-5	LC50 inhalation	>5 mg/L	

### Acute Toxicity Estimate (ATE mix):

ATE mix		Ingredient(s) of unknown toxicity
Oral 40000 mg/kg (Calculation method)		0 %
Dermal	>2000 mg/kg (Calculation method)	Non-applicable
Inhalation	>20 mg/L (4 h) (Calculation method)	Non-applicable

# **11.2** Information on other hazards:

### Endocrine disrupting properties

Endocrine-disrupting properties: The product fails to meet the criteria.

#### **Other information**

Non-applicable

## SECTION 12: ECOLOGICAL INFORMATION

The experimental information related to the eco-toxicological properties of the product itself is not available

### 12.1 Toxicity:

### Acute toxicity:

Identification		Concentration	Species	Genus
acetone	LC50	5540 mg/L (96 h)	Oncorhynchus mykiss	Fish
CAS: 67-64-1	EC50	8800 mg/L (48 h)	Daphnia pulex	Crustacean
EC: 200-662-2	EC50	3400 mg/L (48 h)	Chlorella pyrenoidosa	Algae
Hydrocarbons, C9, aromatics	LC50	>1 - 10 mg/L (96 h)		Fish
CAS: 128601-23-0	EC50	>1 - 10 mg/L (48 h)		Crustacean
EC: 918-668-5	EC50	>1 - 10 mg/L (72 h)		Algae
Zinc powder - zinc dust (stabilised)	LC50	0,31 mg/L (96 h)	N/A	Fish
CAS: 7440-66-6	EC50	1,22 mg/L (48 h)	Daphnia magna	Crustacean
EC: 231-175-3	EC50	Non-applicable		
butan-1-ol	LC50	1740 mg/L (96 h)	Pimephales promelas	Fish
CAS: 71-36-3	EC50	1983 mg/L (48 h)	Daphnia magna	Crustacean
EC: 200-751-6	EC50	500 mg/L (96 h)	Scenedesmus subspicatus	Algae
trizinc bis(orthophosphate)	LC50	>0.1 - 1 mg/L (96 h)		Fish
CAS: 7779-90-0	EC50	>0.1 - 1 mg/L (48 h)		Crustacean
EC: 231-944-3	EC50	>0.1 - 1 mg/L (72 h)		Algae
zinc oxide	LC50	0,82 mg/L (96 h)	Oncorhynchus kisutch	Fish
CAS: 1314-13-2	EC50	3,4 mg/L (48 h)	Daphnia magna	Crustacean
EC: 215-222-5	EC50	Non-applicable		

- CONTINUED ON NEXT PAGE -



	ION 12: ECOLOGICAL INFORMATION	l (continued	J)					
	Chronic toxicity:							
	Identification			Concentration		Specie	es	Genus
	acetone	1	NOEC	Non-applicable				
	CAS: 67-64-1 EC: 200-662-2	T I I I I I I I I I I I I I I I I I I I		2212 mg/L		Daphnia n	nagna	Crustacea
	Zinc powder - zinc dust (stabilised)			0,44 mg/L		Oncorhynchu	-	s Fish
	CAS: 7440-66-6 EC: 231-175-3	-		0,031 mg/L		Daphnia n	,	Crustacea
	butan-1-ol	1	NOEC	Non-applicable			-	
	CAS: 71-36-3 EC: 200-751-6	Ī		4,1 mg/L		Daphnia n	naqna	Crustacea
	zinc oxide	r		0,44 mg/L		Oncorhynchu	-	s Fish
	CAS: 1314-13-2 EC: 215-222-5	-		0,031 mg/L		Daphnia n	,	Crustacea
.2	Persistence and degradability:			, 5,			5	
	Substance-specific information:							
	Substance-specific information.				_			
	Identification		Deg	radability		Biod	egradabi	ility
	acetone	BOD5		Non-applicable		entration		100 mg/L
	CAS: 67-64-1	COD		Non-applicable	Perio			28 days
	EC: 200-662-2	BOD5/0	COD	Non-applicable	% Bio	odegradable		96 %
	butan-1-ol	BOD5		1,71 g O2/g	Conce	entration		Non-applicable
	CAS: 71-36-3	COD		2,46 g O2/g	Perio	d		19 days
	EC: 200-751-6	BOD5/0	COD	0,7	% Bio	odegradable		98 %
.3	Bioaccumulative potential:							
	Substance-specific information:							
	Identif	cation				Bioaccumulation potenti		potential
	acetone				BC		1	potential
	CAS: 67-64-1					w Log	-0.24	
	EC: 200-662-2					tential	Low	
	Butane				BC		33	
	CAS: 106-97-8					w Log	2.89	
	EC: 203-448-7					tential	Modera	ate
					_			
					BC	E	12	
	Propane				BC		13 2.86	
	CAS: 74-98-6				Po	w Log	2.86	
	CAS: 74-98-6 EC: 200-827-9				Por	w Log tential	2.86 Low	
	CAS: 74-98-6 EC: 200-827-9 Isobutane				Por Por BC	w Log tential F	2.86 Low 27	
	CAS: 74-98-6 EC: 200-827-9 Isobutane CAS: 75-28-5				Por Por BC	w Log tential F w Log	2.86 Low 27 2.76	
	CAS: 74-98-6 EC: 200-827-9 Isobutane CAS: 75-28-5 EC: 200-857-2				Por Por BC Por	w Log cential F w Log cential	2.86 Low 27 2.76 Low	
	CAS: 74-98-6 EC: 200-827-9 Isobutane CAS: 75-28-5 EC: 200-857-2 butan-1-ol				Por Por Por Por BC	w Log tential F w Log tential F	2.86 Low 27 2.76 Low 1	
	CAS: 74-98-6 EC: 200-827-9 Isobutane CAS: 75-28-5 EC: 200-857-2 butan-1-ol CAS: 71-36-3				Por Por Por Por BC Por	w Log tential F w Log tential F w Log	2.86 Low 27 2.76 Low 1 0.88	
A	CAS: 74-98-6 EC: 200-827-9 Isobutane CAS: 75-28-5 EC: 200-857-2 butan-1-ol CAS: 71-36-3 EC: 200-751-6				Por Por Por Por BC Por	w Log tential F w Log tential F	2.86 Low 27 2.76 Low 1	
.4	CAS: 74-98-6 EC: 200-827-9 Isobutane CAS: 75-28-5 EC: 200-857-2 butan-1-ol CAS: 71-36-3 EC: 200-751-6 <b>Mobility in soil:</b>				Por Por Por Por BC Por	w Log tential F w Log tential F w Log	2.86 Low 27 2.76 Low 1 0.88 Low	
.4	CAS: 74-98-6 EC: 200-827-9 Isobutane CAS: 75-28-5 EC: 200-857-2 butan-1-ol CAS: 71-36-3 EC: 200-751-6		Absor	rption/desorption	Por Por Por Por BC Por	w Log tential F w Log tential F w Log	2.86 Low 27 2.76 Low 1 0.88 Low	
.4	CAS: 74-98-6 EC: 200-827-9 Isobutane CAS: 75-28-5 EC: 200-857-2 butan-1-ol CAS: 71-36-3 EC: 200-751-6 <b>Mobility in soil:</b> Identification acetone	Кос		1	Por Por Por Por BC Por	w Log tential F w Log tential F w Log tential Henry	2.86 Low 27 2.76 Low 1 0.88 Low	2,93 Pa·m <sup>3</sup> /mol
.4	CAS: 74-98-6 EC: 200-827-9 Isobutane CAS: 75-28-5 EC: 200-857-2 butan-1-ol CAS: 71-36-3 EC: 200-751-6 <b>Mobility in soil:</b> Identification acetone CAS: 67-64-1	Conclus	sion	1 Very High	Por Por Por Por Por Por	w Log tential F w Log tential F w Log tential Henry Dry soil	2.86 Low 27 2.76 Low 1 0.88 Low Volati	2,93 Pa·m <sup>3</sup> /mol Yes
.4	CAS: 74-98-6 EC: 200-827-9 Isobutane CAS: 75-28-5 EC: 200-857-2 butan-1-ol CAS: 71-36-3 EC: 200-751-6 <b>Mobility in soil:</b> Identification acetone	Conclus		1	Por Por Por Por Por Por	w Log tential F w Log tential F w Log tential Henry	2.86 Low 27 2.76 Low 1 0.88 Low Volati	2,93 Pa·m³/mol Yes Yes
.4	CAS: 74-98-6 EC: 200-827-9 Isobutane CAS: 75-28-5 EC: 200-857-2 butan-1-ol CAS: 71-36-3 EC: 200-751-6 <b>Mobility in soil:</b> Identification acetone CAS: 67-64-1	Conclus Surface Koc	sion e tension	1 Very High	Por Por Por Por Por Por	w Log tential F w Log tential F w Log tential Henry Dry soil	2.86 Low 27 2.76 Low 1 0.88 Low Volati	2,93 Pa·m <sup>3</sup> /mol Yes
.4	CAS: 74-98-6 EC: 200-827-9 Isobutane CAS: 75-28-5 EC: 200-857-2 butan-1-ol CAS: 71-36-3 EC: 200-751-6 <b>Mobility in soil:</b> Identification acetone CAS: 67-64-1 EC: 200-662-2 Butane CAS: 106-97-8	Conclus	sion e tension	1 Very High 2,304E-2 N/m (2	Por Por Por Por Por Por	w Log tential F w Log tential F w Log tential Henry Dry soil Moist soil	2.86 Low 27 2.76 Low 1 0.88 Low Volatil	2,93 Pa·m³/mol Yes Yes
.4	CAS: 74-98-6 EC: 200-827-9 Isobutane CAS: 75-28-5 EC: 200-857-2 butan-1-ol CAS: 71-36-3 EC: 200-751-6 <b>Mobility in soil:</b> Identification acetone CAS: 67-64-1 EC: 200-662-2 Butane	Conclus Surface Koc Conclus	sion e tension	1 Very High 2,304E-2 N/m (2 900	Por Por Por Por Por Por Por	w Log tential F w Log tential F w Log tential tential Henry Dry soil Moist soil Henry	2.86 Low 27 2.76 Low 1 0.88 Low Volatil	2,93 Pa·m³/mol Yes Yes 96258,75 Pa·m³/m
.4	CAS: 74-98-6 EC: 200-827-9 Isobutane CAS: 75-28-5 EC: 200-857-2 butan-1-ol CAS: 71-36-3 EC: 200-751-6 <b>Mobility in soil:</b> Identification acetone CAS: 67-64-1 EC: 200-662-2 Butane CAS: 106-97-8	Conclus Surface Koc Conclus	sion e tension sion	1 Very High 2,304E-2 N/m (2 900 Low	Por Por Por Por Por Por Por	w Log tential F w Log tential F w Log tential F w Log tential T tential Dry soil Henry Dry soil Henry Dry soil	2.86 Low 27 2.76 Low 1 0.88 Low Volatil	2,93 Pa·m³/mol Yes Yes 96258,75 Pa·m³/m Yes
.4	CAS: 74-98-6 EC: 200-827-9 Isobutane CAS: 75-28-5 EC: 200-857-2 butan-1-ol CAS: 71-36-3 EC: 200-751-6 <b>Mobility in soil:</b> CAS: 67-64-1 EC: 200-662-2 Butane CAS: 106-97-8 EC: 203-448-7	Conclus Surface Koc Conclus Surface	sion e tension sion e tension	1 Very High 2,304E-2 N/m (2 900 Low 1,187E-2 N/m (2	Por Por Por Por Por Por Por	w Log tential F w Log tential F w Log tential Henry Dry soil Henry Dry soil Henry Dry soil Moist soil	2.86 Low 27 2.76 Low 1 0.88 Low Volatil	2,93 Pa·m³/mol Yes Yes 96258,75 Pa·m³/m Yes Yes
.4	CAS: 74-98-6 EC: 200-827-9 Isobutane CAS: 75-28-5 EC: 200-857-2 butan-1-ol CAS: 71-36-3 EC: 200-751-6 <b>Mobility in soil:</b> CAS: 67-64-1 EC: 200-662-2 Butane CAS: 106-97-8 EC: 203-448-7 Propane	Conclus Surface Koc Conclus Surface Koc Conclus	sion e tension sion e tension	1           Very High           2,304E-2 N/m (2           900           Low           1,187E-2 N/m (2           460	Po Po Po Po Po Po Po Po Po Po Po	w Log tential F w Log tential F w Log tential F w Log tential Wog tential Henry Dry soil Henry Dry soil Henry Dry soil Henry Henry	2.86 Low 27 2.76 Low 1 0.88 Low Volatil	2,93 Pa·m³/mol Yes 96258,75 Pa·m³/m Yes Yes 71636,78 Pa·m³/m
.4	CAS: 74-98-6 EC: 200-827-9 Isobutane CAS: 75-28-5 EC: 200-857-2 butan-1-ol CAS: 71-36-3 EC: 200-751-6 <b>Mobility in soil:</b> Identification acetone CAS: 67-64-1 EC: 200-662-2 Butane CAS: 106-97-8 EC: 203-448-7 Propane CAS: 74-98-6	Conclus Surface Koc Conclus Surface Koc Conclus	sion e tension sion e tension sion	1           Very High           2,304E-2 N/m (2           900           Low           1,187E-2 N/m (2           460           Moderate	Po Po Po Po Po Po Po Po Po Po Po	w Log tential F w Log tential F w Log tential F w Log tential F w Log tential Moist soil Henry Dry soil Henry Dry soil Henry Dry soil Henry Dry soil Henry Dry soil	2.86 Low 27 2.76 Low 1 0.88 Low Volatil Volatil Volatil	2,93 Pa·m³/mol Yes 96258,75 Pa·m³/m Yes Yes 71636,78 Pa·m³/m Yes

- CONTINUED ON NEXT PAGE -



This SDS is an English translation of COMMISSION REGULATION (EU) 2020/878, without any country-specific legislation

## ZINC ALUMINIUM

Printing: 26/01/2023 Date of compilation: 13/05/2020		20 Revise	ed: 14/06/2022	Version: 3 (Replaced	12)	
SECT	ION 12: ECOLOGI	CAL INFORMATION (cont	tinued)			
	I	dentification	Absorpti	ion/desorption	Volat	ility
	butan-1-ol		Кос	2.44	Henry	5,39E-2 Pa·m <sup>3</sup> /mol
	CAS: 71-36-3		Conclusion	Very High	Dry soil	Yes
	EC: 200-751-6		Surface tension	2,567E-2 N/m (25 °C)	Moist soil	Yes
12.5	Results of PBT and	d vPvB assessment:				
	Product fails to meet	c PBT/vPvB criteria				
12.6	Endocrine disrupt	ing properties:				
	Endocrine-disrupting properties: The product fails to meet the criteria.					
12.7						

# SECTION 13: DISPOSAL CONSIDERATIONS

### **13.1 Waste treatment methods:**

Code	Description	Waste class (Regulation (EU) No 1357/2014)
16 05 04	gases in pressure containers (including halons) containing hazardous substances	Dangerous

#### Type of waste (Regulation (EU) No 1357/2014):

HP14 Ecotoxic, HP3 Flammable, HP5 Specific Target Organ Toxicity (STOT)/Aspiration Toxicity, HP4 Irritant — skin irritation and eye damage

### Waste management (disposal and evaluation):

Consult the authorized waste service manager on the assessment and disposal operations in accordance with Annex 1 and Annex 2 (Directive 2008/98/EC). As under 15 01 (2014/955/EC) of the code and in case the container has been in direct contact with the product, it will be processed the same way as the actual product. Otherwise, it will be processed as non-dangerous residue. Waste should not be disposed of to drains. See paragraph 6.2.

#### **Regulations related to waste management:**

In accordance with Annex II of Regulation (EC) No 1907/2006 (REACH) the community or state provisions related to waste management are stated

Community legislation: Directive 2008/98/EC, 2014/955/EU, Regulation (EU) No 1357/2014

# SECTION 14: TRANSPORT INFORMATION

### Transport of dangerous goods by land:

With regard to ADR 2021 and RID 2021:

	4.2	UN number or ID number: UN proper shipping name: Transport hazard class(es): Labels:	UN1950 AEROSOLS 2 2.1	
14	4.4	Packing group:	N/A	
14	4.5	Environmental hazards:	Yes	
14	4.6	Special precautions for user		
		Special regulations:	190, 327, 344, 625	
		Tunnel restriction code:	D	
		Physico-Chemical properties:	see section 9	
		Limited quantities:	1 L	
14	.4.7	Maritime transport in bulk according to IMO instruments:	Non-applicable	
Transport of dangerous goods by sea:				
With regard to IMDG 40-20:				

Safety data sheet

This SDS is an English translation of COMMISSION REGULATION (EU) 2020/878, without any country-specific legislation

### ZINC ALUMINIUM

Printing: 26/01/2023	Date c	of compilation: 13/05/2020	Revised: 14/06/2022	Version: 3 (Replaced 2)	
SECTION 14: TRANSPC	SECTION 14: TRANSPORT INFORMATION (continued)				
	14.2 14.3 14.4	UN number or ID number: UN proper shipping name: Transport hazard class(es): Labels: Packing group: Marine pollutant:	UN1950 AEROSOLS 2 2.1 N/A Yes		
		Special precautions for user Special regulations: EmS Codes: Physico-Chemical properties: Limited quantities: Segregation group:	63, 959, 190, 277, 327, 344 F-D, S-U see section 9 1 L Non-applicable		
1	14.7	Maritime transport in bulk according to IMO instruments:	Non-applicable		
Transport of dan	gero	us goods by air:			
With regard to IAT	A/ICA	O 2023:			
	14.2 14.3 14.4	UN number or ID number: UN proper shipping name: Transport hazard class(es): Labels: Packing group: Environmental hazards:	UN1950 AEROSOLS 2 2.1 N/A Yes		
-		Special precautions for user			
		Physico-Chemical properties:	see section 9		
1	14.7	Maritime transport in bulk according to IMO instruments:	Non-applicable		

SECTION 15: REGULATORY INFORMATION

### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture:

Candidate substances for authorisation under the Regulation (EC) No 1907/2006 (REACH): Non-applicable

Substances included in Annex XIV of REACH ("Authorisation List") and sunset date: Non-applicable

Regulation (EC) No 1005/2009, about substances that deplete the ozone layer: Non-applicable

Article 95, REGULATION (EU) No 528/2012: Non-applicable

REGULATION (EU) No 649/2012, in relation to the import and export of hazardous chemical products: Non-applicable

### Seveso III:

Section	Description	Lower-tier requirements	Upper-tier requirements
P3a	FLAMMABLE AEROSOLS	150	500
E2	ENVIRONMENTAL HAZARDS	200	500

Limitations to commercialisation and the use of certain dangerous substances and mixtures (Annex XVII REACH, etc ....):

Regulation (EU) 2019/1148 on the marketing and use of explosives precursors: Contains acetone. Product under the provisions of Article 9. However, products that contain explosives precursors only to such a small extent and in such complex mixtures that the extraction of the explosives precursors is technically extremely difficult should be excluded from the scope of this Regulation. Shall not be used in:

—ornamental articles intended to produce light or colour effects by means of different phases, for example in ornamental lamps and ashtrays,

-tricks and jokes,

-games for one or more participants, or any article intended to be used as such, even with ornamental aspects.

Specific provisions in terms of protecting people or the environment:



Version: 3 (Replaced 2)

Safety data sheet This SDS is an English translation of COMMISSION REGULATION (EU) 2020/878, without any country-specific legislation

# ZINC ALUMINIUM

Revised: 14/06/2022

Date of compilation: 13/05/2020

Printing: 26/01/2023

SECT	
5201	ION 15: REGULATORY INFORMATION (continued)
	It is recommended to use the information included in this safety data sheet as a basis for conducting workplace-specific risk assessments in order to establish the necessary risk prevention measures for the handling, use, storage and disposal of this product.
	Other legislation:
	The product could be affected by sectorial legislation
	Council Directive 75/324/EEC of 20 May 1975 on the approximation of the laws of the Member States relating to aerosol dispensers
15.2	Commission Directive 94/1/EC of 6 January 1994 adapting some technicalities of Council Directive 75/324/EEC on the approximation of the laws of the relating Member States to aerosol dispensers Commission Directive 2008/47/EC of 8 April 2008 amending, for the purposes of adapting to technical progress, Council Directive 75/324/EEC on the approximation of the laws of the Member States relating to aerosol dispensers Commission Directive 2013/10/EU of 19 March 2013 amending Council Directive 75/324/EEC on the approximation of the laws of the Member States relating provisions to Regulation (EC) No 1272/2008 of the European Parliament and of the Council on classification, labelling and packaging of substances and mixtures COMMISSION DIRECTIVE (EU) 2016/2037 of 21 November 2016 amending Council Directive 75/324/EEC as regards the maximum allowable pressure of aerosol dispensers and to adapt its labelling provisions to Regulation (EC) No 1272/2008 of the European Parliament and of the Council on classification, labelling and packaging of substances and mixtures <b>COMMISSION DIRECTIVE (EU)</b> 2016/2037 of 21 November 2016 amending Council Directive 75/324/EEC as regards the maximum allowable pressure of aerosol dispensers and to adapt its labelling provisions to Regulation (EC) No 1272/2008 of the European Parliament and of the Council on classification, labelling and packaging of substances and mixtures <b>COMMISSION DIRECTIVE (EU)</b> 2016/2037 of 21 November 2016 amending Council Directive 75/324/EEC as regards the maximum allowable pressure of aerosol dispensers and to adapt its labelling provisions to Regulation (EC) No 1272/2008 of the European Parliament and of the Council on classification, labelling and packaging of substances and mixtures <b>Chemical safety assessment:</b>
	The supplier has not carried out evaluation of chemical safety.
SECT	ION 16: OTHER INFORMATION
	Legislation related to safety data sheets:
	The SDS shall be supplied in an official language of the country where the product is placed on the market. This safety data sheet has been designed in accordance with ANNEX II-Guide to the compilation of safety data sheets of Regulation (EC) No 1907/2006 (COMMISSION REGULATION (EU) 2020/878).
	Modifications related to the previous Safety Data Sheet which concerns the ways of managing risks.: COMMISSION REGULATION (EU) 2020/878
	Texts of the legislative phrases mentioned in section 2:
	H319: Causes serious eye irritation.
	H336: May cause drowsiness or dizziness.
	H411: Toxic to aquatic life with long lasting effects. H229: Pressurised container: May burst if heated.
	H222: Extremely flammable aerosol.
	Texts of the legislative phrases mentioned in section 3:
	The phrases indicated do not refer to the product itself; they are present merely for informative purposes and refer to the individual components which appear in section 3
	CLP Regulation (EC) No 1272/2008:
	Acute Tox. 4: H302 - Harmful if swallowed.
	Aquatic Acute 1: H400 - Very toxic to aquatic life. Aquatic Chronic 1: H410 - Very toxic to aquatic life with long lasting effects.
	Aquatic Chronic 2: H411 - Toxic to aquatic life with long lasting effects.
	Asp. Tox. 1: H304 - May be fatal if swallowed and enters airways.
	Eye Dam. 1: H318 - Causes serious eye damage. Eye Irrit. 2: H319 - Causes serious eye irritation.
	Flam. Gas 1A: H220 - Extremely flammable gas.
	Flam. Liq. 2: H225 - Highly flammable liquid and vapour.
	Flam. Liq. 3: H226 - Flammable liquid and vapour. Press. Gas: H280 - Contains gas under pressure, may explode if heated.
	Skin Irrit. 2: H315 - Causes skin irritation.
	STOT SE 3: H335 - May cause respiratory irritation. STOT SE 3: H336 - May cause drowsiness or dizziness.
	Classification procedure:
	Eye Irrit. 2: Calculation method
	STOT SE 3: Calculation method
	Aquatic Chronic 2: Calculation method Aerosol 1: Calculation method
	Aerosol 1: Calculation method
	Advice related to training:
	- CONTINUED ON NEXT PAGE -
	Page 14/



This SDS is an English translation of COMMISSION REGULATION (EU) 2020/878, without any country-specific legislation

# ZINC ALUMINIUM

Printing: 26/01/2023	Date of compilation: 13/05/2020	Revised: 14/06/2022	Version: 3 (Replaced 2)		
SECTION 16: OTHE	ER INFORMATION (continued)				
Training is recommended in order to prevent industrial risks for staff using this product and to facilitate their comprehension and interpretation of this safety data sheet, as well as the label on the product. <b>Principal bibliographical sources:</b> http://echa.europa.eu					
http://eur-lex.e	s and acronyms:				
ADR: European IMDG: Internati IATA: Internatio ICAO: Internatio COD: Chemical BOD5: 5day bio BCF: Bioconcen LD50: Lethal Do LC50: Lethal Co EC50: Effective LogPOW: Octar Koc: Partition co UFI: unique for	agreement concerning the international c tional maritime dangerous goods code onal Air Transport Association ional Civil Aviation Organisation Oxygen Demand ochemical oxygen demand atration factor ose 50 oncentration 50 concentration 50 nolwater partition coefficient oefficient of organic carbon	arriage of dangerous goods	by road		

The information contained in this safety data sheet is based on sources, technical knowledge and current legislation at European and state level, without being able to guarantee its accuracy. This information cannot be considered a guarantee of the properties of the product, it is simply a description of the security requirements. The occupational methodology and conditions for users of this product are not within our awareness or control, and it is ultimately the responsibility of the user to take the necessary measures to obtain the legal requirements concerning the manipulation, storage, use and disposal of chemical products. The information on this safety data sheet only refers to this product, which should not be used for needs other than those specified.