


TECHNICAL INFORMATION

FOR PROFESSIONAL USE ONLY

ANTICORROSIVE EPOXY PRIMER SPRAY		
PRODUCT DESCRIPTION		
<p>1K primer designed to preparing the surface for the top coating. Product has excellent anticorrosion properties and guarantees very good insulation from moisture. Is perfect to the spot repairs, may be covered by water-based or solvent-based systems*. Can be applied directly on steel, galvanized steel, stainless steel, aluminum and old paint coatings, also can be applied wet-on-wet.</p> <p>*due to lots of paints and varnishes on the market compatibility test is recommended.</p>		
PHYSICAL AND CHEMICAL PROPERTIES		
BASE :	epoxy resin	
CAPACITY :	400 ml	
COLOUR:	grey	
DENSITY:	0,802 g/cm³ / 20°C	
CURING TIME:	10 – 15 min / 20°C	
VOLATILE ORGANIC COMPOUNDS		
VOC = 683,4 [g/l]		
This product satisfies requirements of the European Union Directive (2004/42/WE), which for this product category (B/5) gives the limit value of content of volatile matter at the level of 840 [g/l] of the ready-for-use product.		
USAGE		
<ul style="list-style-type: none">• Surface should be dry sanded, degreased, cleaned and dry.• Before using shake aerosol can for 2 minutes and try it on cardboard.• Apply 2-3 layers of the primer for the prepared surface• After use clean aerosol's outlets – hold down aerosol's valve, push the bottom and release contents for 5 seconds.		
Caution: For safety reasons always comply with information provided in the Material Safety Data Sheet		
STORAGE		
Store the product components in sealed container, in dry and cool places, away from heat sources, as well as direct sunlight.		
WARRANTY PERIOD		
MF ANTICORROSIVE EPOXY PRIMER		- 5 years from the date of production
PRODUCT	Art. No.	
MF ANTICORROSIVE EPOXY PRIMER	300006522 (400ml)	
<p>Important Information: The information contained in this document corresponds to our present knowledge and is a guide to our products and their uses. Read all directions and warnings prior to using Troton products - Safety Data Sheets can be found online at www.troton.com.pl or will be sent according to your request: troton@troton.com.pl</p> <p>Technical Information: The technical information, recommendations and other statements contained in this document are based upon tests or experience that Troton believes are reliable, but the accuracy or completeness of such information is not guaranteed. Many factors beyond Troton's control and uniquely within user's knowledge and control can affect the use and performance of a Troton product in a particular application. Given the variety of factors that can affect the use and performance of a Troton product, user is solely responsible for evaluating the Troton product and determining whether it is fit for a particular purpose and suitable for user's method of application.</p> <p>Limitation of Liability: Except where prohibited by law, Troton will not be liable for any loss or damage arising from the Troton product, whether direct, indirect, special, incidental or consequential, regardless of the legal theory asserted, including warranty, contract, negligence or strict liability.</p> <p>If used as instructed, this product is designed to comply with the European Volatile Organic Compound (VOC) Emission Standard for Automotive Refinish Coatings. Confirm compliance with your country, state and local air quality rules before use. The data on this sheet represent typical values. Since application variables are a major factor in product performance, this information should serve only as a general guide. Troton assumes no obligation or liability for use of this information.</p>		
TROTON Sp. z o.o. Ząbrowo, Poland.		