


TECHNICAL INFORMATION

FOR PROFESSIONAL USE ONLY

<p>RUST FILLER RUST REMOVER AND PRIMER</p>	
<p>PRODUCT DESCRIPTION</p> <p>RUST FILLER is a water – based primer and rust converter in one. It stops and neutralizes the corrosion process. Formed the primer coat with adhesion for following treatment with putty and clear coat. The product is characterized by quick drying time, very good solvent – resistance and is easy to apply. Recommended to use in automotive, industry, metal processing etc. Can be mixed with water.</p>	

PHYSICAL AND CHEMICAL PROPERTIES
<p>COLOUR: beige SMELL: slight DENSITY*: approx. 1.02 g/cm³ VISCOSITY*: 10 – 16 sec (Ford Cup no.4) CAPACITY: 100 ml PH VALUE*: 1.50 EFFICIENCY FOR 100 ML: 2m² DRYING TIME*: 6 – 8 h</p> <p>*at temp. 20°C and relative humidity of 50%</p>
VOLATILE ORGANIC COMPOUNDS
Product does not contain VOC.
USAGE
<ul style="list-style-type: none"> Remove rust, fat, dirt and paint flakes which are infiltrated by corrosion. Use brush if it is necessary. Shake well bottle before use. Apply product evenly on the rusty surface. Depending on degree of corrosion is recommended to apply 3 – 4 layers. Wait until the end of reaction – surface change color for dark blue. Protected and dry area cover with primer or lacquer. <p>Warning: Use only in well ventilated area or outdoors. Caution: To maintain safety, always follow the instructions given in the MSDS for the product.</p>
STORAGE
Store in temp. 10 – 25°C and relative air humidity 60%. Protect from freeze and direct sunlight.
WARRANTY PERIOD
5 years from production date in the original packaging.

PRODUCT	NR ART
MF RUST FILLER 100 ml	300005730

Important Information: The information contained in this document corresponds to our present knowledge and is a guide to our products and their uses. Read all directions and warnings prior to using Troton products - Safety Data Sheets can be found online at www.troton.com.pl or will be sent according to your request: troton@troton.com.pl

Technical Information: The technical information, recommendations and other statements contained in this document are based upon tests or experience that Troton believes are reliable, but the accuracy or completeness of such information is not guaranteed. Many factors beyond Troton’s control and uniquely within user’s knowledge and control can affect the use and performance of a Troton product in a particular application. Given the variety of factors that can affect the use and performance of a Troton product, user is solely responsible for evaluating the Troton product and determining whether it is fit for a particular purpose and suitable for user’s method of application.

Limitation of Liability: Except where prohibited by law, Troton will not be liable for any loss or damage arising from the Troton product, whether direct, indirect, special, incidental or consequential, regardless of the legal theory asserted, including warranty, contract, negligence or strict liability.

If used as instructed, this product is designed to comply with the European Volatile Organic Compound (VOC) Emission Standard for Automotive Refinish Coatings. Confirm compliance with your country, state and local air quality rules before use. The data on this sheet represent typical values. Since application variables are a major factor in product performance, this information should serve only as a general guide. Troton assumes no obligation or liability for use of this information.

TROTON Sp. z o.o.
Ząbrowo, Poland.