

TECHNICAL INFORMATION

FOR PROFESSIONAL USE ONLY

U - PRIMER



PRODUCT DESCRIPTION

The primer facilitating adhesion the polyurethane adhesive for automobile windscreen. In addition, provides protection against UV radiation, which can lead to degradation of the adhesive. It is ideal base layer for the first installation of automobile windscreen as well as during other repairs.

PHYSICAL AND CHEMICAL PROPERTIES

- Color: black
- Capacity: 30 ml
- Specific gravity: 0,95 g/cm²
- Consistency: liquid
- Application temperature: 10⁰C to 35⁰C
- Minimum drying time*: 5 minutes
- Maksimum drying time*: 24 hours

*In temp. 23⁰C and r.h. 50%

VOC CONTENT

VOC = 588 [g/l]

The product fulfils the requirements of the European Directive (2004/42/WE), which defines the volatile components content for that products category (cat..B/5) at the level of 840[g/l] for the ready product.

USAGE

TROTON Sp. z.o.o

Address: Zabrowo 14A, 78-120 Gościno, Poland, Tel: +48 94 35 123 94
Tel/Fax: +48 94 35 126 22 Website: www.troton.com.pl Email: troton@troton.com.pl

- Surface to be treated must be clean, dry and degreased.
- Before application shake bottle for minimum 1 minutes.
- Using applicator apply thin layer of product on parts which has to be sealed.
- Remove useless part of product with solvent for nitrocellulose or acrylic products. .
- After use immediately close the bottle tightly (product evaporates very quickly).

Caution: For safety reasons always comply with information provided in the Material Safety Data Sheet.

STORAGE

Store product in a sealed container in dry and cool places, away from the heat sources , as well as direct sunlight. The product is flammable.

Best storage temperature: 5 ÷ 25⁰C.

WARRANTY PERIOD

12 months from production date.

Important Information:

The information contained in this document corresponds to our present knowledge and is a guide to our products and their uses.

Read all directions and warnings prior to using Troton products - Safety Data Sheets can be found online at www.troton.com.pl or will be sent according to your request: troton@troton.com.pl

Technical Information: The technical information, recommendations and other statements contained in this document are based upon tests or experience that Troton believes are reliable, but the accuracy or completeness of such information is not guaranteed.

Many factors beyond Troton's control and uniquely within user's knowledge and control can affect the use and performance of a Troton product in a particular application. Given the variety of factors that can affect the use and performance of a Troton product, user is solely responsible for evaluating the Troton product and determining whether it is fit for a particular purpose and suitable for user's method of application.

Limitation of Liability: Except where prohibited by law, Troton will not be liable for any loss or damage arising from the Troton product, whether direct, indirect, special, incidental or consequential, regardless of the legal theory asserted, including warranty, contract, negligence or strict liability. If used as instructed, this product is designed to comply with the European Volatile Organic Compound (VOC) Emission Standard for Automotive Refinish Coatings. Confirm compliance with your country, state and local air quality rules before use. The data on this sheet represent typical values. Since application variables are a major factor in product performance, this information should serve only as a general guide. Troton assumes no obligation or liability for use of this information.

TROTON Sp. z o.o.
Ząbrowo, Poland