

Updated: 28.11.2024

TECHNICAL INFORMATION

FOR PROFESSIONAL USE ONLY

T11

POLISHING COMPOUND

Art. No.

10092 (150 g) 10093 (1 kg bucket) 14711 (1 kg bottle)

11254 (3 kg)

COLOUR: white

DENSITY: 1,22 g/cm³



PRODUCT DESCRIPTION

BRAYT T11 polishing compound contains high quality polishing minerals which guarantees quick elimination of defects and high gloss in one-step polishing process. It removes sanding traces (from P1500 grit). Because of optimized bonding does not burn in during polishing while being easy to clean. It's universal product suitable for each type of gelcoat, PU and PE lacquers in automotive, furniture industry and composite materials.

Cut level: 7/10Gloss level: 8/10

• Processing: manual work, mechanical work (rotary machine)

RECOMMENDED APPLICATORS

- BRAYT POLISHING FOAM HARD yellow
- BRAYT POLISHING FOAM SOFT grey
- BRAYT LAMBSWOOL "D" yellow
- BRAYT LAMBSWOOL "MM" white
- BRAYT ORANGE PEEL REMOVAL PAD "JEANS"

USAGE

- Apply compound on the surface or applicator (polishing foam or lambswool).
- Spread compound on the surface by machine with minimum RPM.
- Slowly increase the speed to max. 1800 RPM and polish surface with light pressure.
- Polish surfaces until the scratches have been removed gradually reducing the speed and pressure.
- When polishing large surfaces, it is recommended to polish smaller sections at a time.

STORAGE

Store the product in tightly closed container at 0 - 45°C. Keep away from heat, fire and direct sunlight. Close the containers immediately after each use. Protect from frost. Keep away from children.

EXPIRY DATE

T11 Polishing compound 24 months from production date.

LIMITATION OF LIABILITY

The information contained in this TDS sheet is up-to-date and correct on the day the information is released

Because TROTON cannot control or predict the conditions under which a product will be used, each user should review the information in the specific context of the intended usage. To the maximum extent permitted by applicable law, TROTON shall not be liable for damages of any kind arising from the use or reliance on information contained in this TDS. Given the variety of factors that can affect the usage and application of the TROTON product, some of which are only within the user's

knowledge and control range, it is essential that the user evaluate the TROTON product to determine if the product is fit for a particular purpose and whether the product is suitable for the user's usage.

Under no circumstances shall TROTON be liable to the user or any third party for any indirect, derivative, incidental, special or punitive damages, including loss of profits resulting from the use of products manufactured by TROTON and / or TROTON's services.

All information is based on meticulous laboratory tests and many years of experience. An established position on the market does not release us from continuous quality control of our products. However, we are not responsible for the final effects of improper storage or use of our products and for work that is not in line with good craftsmanship. .

TROTON Sp. z o.o. Ząbrowo, Poland.