


TECHNICAL INFORMATION

FOR PROFESSIONAL USE ONLY

<h3>T4 PROTECT LIQUID</h3>	
Art. No.	
300005446 (250 ml) 300005447 (500 ml) 300005448 (1000 ml)	
COLOUR: white	
SPECIFIC GRAVITY: 0,97 g/cm ³	

PRODUCT DESCRIPTION

T4 PROTECT LIQUID is a fine – grained polishing paste to refresh the surface which leave an invisible protection film against the contamination. Increase the paint life by 40 – 50% and reduce dirt accumulation by 70 – 80%. Applicable for protection on painted surfaces, gelcoat and polycarbonate. Also has a slightly abrasive properties that allow you to remove minimum size defects and holograms. Is suitable for gelcoat and all automotive paints including Acrylic, two-component, single-component, water-based and OEM. Can also be used for ceramic anti-scratch paints. Increases paint gloss and protect against UV rays, acid rain, tree resins, insects and oxidation. Applied by hand or eccentric polishing machine with polishing sponge. For high glossy finish without haze and holograms use soft polishing sponge.

- Cut level: 2/10
- Gloss level: 9/10
- Processing: manual work, mechanical work (orbital machine)
- Consistency: fluid gel
- Viscosity: > 130 mm²/s

RECOMMENDED APPLICATORS

- BRAYT POLISHING FOAM „FINISH” black

USAGE

- Before application surface must be dry.
- Apply small quantity on the surface to be treated (polish small area at a time).
- Polish the surface with soft polishing sponge applying medium pressure.
- Reduce pressure to achieve the intended effect.
- After polishing leave the product for about 30 – 60 min. to create protection.
- Remove any residue with microfiber cloth or orbital polisher with soft polishing sponge.
- Don't use on unpolymerized surface.

STORAGE

Store the product in tightly closed container at 0 - 45°C. Keep away from heat, fire and direct sunlight. Close the containers immediately after each use. Protect from frost. Keep away from children.

EXPIRY DATE

T4 PROTECT LIQUID	18 months from production date.
-------------------	---------------------------------

LIMITATION OF LIABILITY

The information contained in this TDS sheet is up-to-date and correct on the day the information is released. Because TROTON cannot control or predict the conditions under which a product will be used, each user should review the information in the specific context of the intended usage. To the maximum extent permitted by applicable law, TROTON shall not be liable for damages of any kind arising from the use or reliance on information contained in this TDS. Given the variety of factors that can affect the usage and application of the TROTON product, some of which are only within the user's knowledge and control range, it is essential that the user evaluate the TROTON product to determine if the product is fit for a particular purpose and whether the product is suitable for the user's usage.

Under no circumstances shall TROTON be liable to the user or any third party for any indirect, derivative, incidental, special or punitive damages, including loss of profits resulting from the use of products manufactured by TROTON and / or TROTON's services.

All information is based on meticulous laboratory tests and many years of experience. An established position on the market does not release us from continuous quality control of our products. However, we are not responsible for the final effects of improper storage or use of our products and for work that is not in line with good craftsmanship. .

TROTON Sp. z o.o.
Ząbrowo, Poland.