

TECHNICAL DATA SHEET

FOR PROFESSIONAL USE ONLY

BLENDING REDUCER		
PRODUCT		
BLENDING REDUCER		
PRODUCT DESCRIPTION		
Blending reducer is ideal for spot repairs on 2 component urethane clear coats. Dissolves the dust that settles around the repaired surface, leveling out the optical color difference between the old coating and the newly painted one. Guarantees easy and fast shading, also when using high-solids (HS and UHS) clearcoats. Main characteristics: fast drying, levels out the surface, shades all non-matt surfaces, does not dim the gloss, even when heating at high temperatures (up to 60°C/140°F), practical in use.		
COLOR: transparent		

APPLICATION PROCESS	
	USE AND DOSAGE
	Can be used with TROTON clearcoats. Especially recommended for HS and VHS products. 1. Apply 1-3 thin coat of Blending Reducer where old coats meet with new clearcoat. 2. Apply immediately after applying last coat of clearcoat.
	SPRAYING VISCOSITY
	About 10 seconds, DIN4/20°C (68°F). Product is ready for use.

GENERAL NOTES	
Caution: This technical data sheet presents the procedure for shading by TROTON paint coatings. Product details are listed in the relevant data sheets. To maintain safety, always follow the instructions given in the MSDS of the products.	
STORAGE	
Store the product components between 15 to 25°C (59 to 77°F) in a sealed container, in dry and cool places, away from fire and heat sources, as well as direct sunlight.	
Note: Close the container after use.	

WARRANTY PERIOD	
INTER TROTON BLENDING REDUCER	- 24 months from the date of production
PRODUCT	ART. No.
INTER TROTON BLENDING REDUCER	14793 (1I)

LIMITATION OF LIABILITY	
The information contained in the TDS is up-to-date and correct on the day the information is released. Because TROTON can not control or predict the conditions under which a product will be used, each user should review information in the specific context of the intended usage. To the maximum extent permitted by applicable law, TROTON shall not be liable for damages of any kind arising from the use or reliance on information contained in this TDS. Given the variety of factors that can affect the usage and application of the TROTON product, some of which are only within the user's knowledge and control range, it is essential that the user evaluate the TROTON product to determine if the product is fit for a particular purpose and whether the product is suitable for the user's usage. Under no circumstances shall TROTON be liable to the user or any third party for any indirect, derivative, incidental, special or punitive damages, including loss of profits resulting from the use of products manufactured by TROTON and / or TROTON's services. All information are based upon the precise laboratory studies and many years of experience. The good market position does not release us from the constant supervision of our products quality. However, we are not responsible for the final effects of the improper storage or application of our products, as well as for work inconsistent with the good craft practice.	
TROTON Sp. z o.o. Ząbrowo, Poland.	