



# **TECHNICAL DATA SHEET**

FOR PROFESSIONAL USE ONLY

# FISH EYE ELIMINATOR

ANTISILICONE ADDITIVE

### PRODUCT DESCRIPTION

Agent that prevents the formation of silicone craters (fish eye) caused by the presence of silicone or grease on the repaired surface. Product intended for use with urethane clearcoats and paints. Antisilicone additive should be added in the proportion of 2 to 4% based on the ready to use mixture of clearcoat and hardener.



**COLOR:** transparent

### **APPLICATION PROCESS**



#### **USE AND DOSAGE**

Product dedicated for urethane clearcoats and paints.

The antisilicone additive should be used in an amount of 2 to 4% based on the mixture of clearcoat and hardener.

## **GENERAL NOTES**

**Caution:** To maintain safety, always follow the instructions given in the MSDS of the products.

## **STORAGE**

Store the product between 15 to 25°C (59 to 77°F) in a sealed container, in dry and cool places, away from fire and heat sources, as well as direct sunlight.

Note: After each use the container with product should be immediately closed!

# **WARRANTY PERIOD**

FISH EYE ELIMINATOR Antisilicone Additive

- 12 months from the date of production

PRODUCT	ART. No.
FISH EYE ELIMINATOR Antisilicone Additive	14532 (0,5 l)

### LIMITATION OF LIABILITY

The information contained in the TDS is up-to-date and correct on the day the information is released.

Because TROTON can not control or predict the conditions under which a product will be used, each user should review information in the specific context of the intended usage. To the maximum extent permitted by applicable law, TROTON shall not be liable for damages of any kind arising from the use or reliance on information contained in this TDS.

Given the variety of factors that can affect the usage and application of the TROTON product, some of which are only within the user's knowledge and control range, it is essential that the user evaluate the TROTON product to determine if the product is fit for a particular purpose and whether the product is suitable for the user's usage.

Under no circumstances shall TROTON be liable to the user or any third party for any indirect, derivative, incidental, special or punitive damages, including loss of profits resulting from the use of products manufactured by TROTON and / or TROTON's services.

All information are based upon the precise laboratory studies and many years of experience. The good market position does not release us from the constant supervision of our products quality. However, we are not responsible for the final effects of the improper storage or application of our products, as well as for work inconsistent with the good craft practice.

TROTON Sp. z o.o. Ząbrowo, Poland.