

TECHNICAL INFORMATION

FOR PROFESSIONAL USE ONLY

SPRAY BUMPER PAINT STRUCTURE

STRUCTURE PAINT FOR BUMPERS

PRODUCT DESCRIPTION

The product is based on acrylic and cellulose resins, intended for painting bumpers and other external elements of the car body made of plastic. It allows to obtain a fine-grained structure imitating plastic and concealing minor defects of the substrate. It is characterized by a short drying time and good adhesion. The product can be sprayed directly onto plastic surfaces without the need for a primer. The texture may be recoated (sprayed) with paints commonly used for bumpers.*



PHYSICAL AND CHEMICAL PROPERTIES

Colour:	black, dark grey
Gloss grade:	mat to semigloss (depending on layer thickness)
Capacity:	500 ml
Density:	0,75 g/ml (at 68°F (20°C))
Drying time at 68°F (20°C)**:	dust dry after approx. 15 minutes tack free after approx. 30 minutes

VOLATILE ORGANIC COMPOUNDS

VOC = 622,1 [g/l]

The product fulfils the requirements of the European Directive (2004/42/WE), which defines the volatile components content for that products category (cat. B/5) at the level of 840[g/l] for the ready product.

USAGE

- Surface to be treated should be dry, clean, free of oil and grease.
- Shake before using for 2 minutes and try it on cardboard.
- During lacquering hold aerosol in 25÷30 cm distance from the surface.
- **Clean the spray nozzle after use!** – Hold the can with the valve pointing downward, press the button emptying the content for about 5 seconds.

Caution: For safety reasons always comply with information provided in the Material Safety Data Sheet.

STORAGE

Store the product in sealed container, in dry and cool places, away from heat sources, as well as direct sunlight.

WARRANTY PERIOD

SPRAY BUMPER PAINT STRUCTURE 500 ml	- 3 years from production date.
-------------------------------------	---------------------------------

PRODUCT

SPRAY BUMPER PAINT STRUCTURE 500 ml	ART. No. black 300002299, grey 300006985
-------------------------------------	---

LIMITATION OF LIABILITY

The information contained in the TDS is up-to-date and correct on the day the information is released.

Because TROTON can not control or predict the conditions under which a product will be used, each user should review information in the specific context of the intended usage. To the maximum extent permitted by applicable law, TROTON shall not be liable for damages of any kind arising from the use or reliance on information contained in this TDS.

Given the variety of factors that can affect the usage and application of the TROTON product, some of which are only within the user's knowledge and control range, it is essential that the user evaluate the TROTON product to determine if the product is fit for a particular purpose and whether the product is suitable for the user's usage.

Under no circumstances shall TROTON be liable to the user or any third party for any indirect, derivative, incidental, special or punitive damages, including loss of profits resulting from the use of products manufactured by TROTON and / or TROTON's services.

All information are based upon the precise laboratory studies and many years of experience. The good market position does not release us from the constant supervision of our products quality. However, we are not responsible for the final effects of the improper storage or application of our products, as well as for work inconsistent with the good craft practice.

TROTON Sp. z o.o.
Ząbrowo, Poland.

*Due to the large number of paints and varnishes on the market it's recommended to conduct compatibility test.

**Drying time depends on air temperature, humidity and thickness of the layer.