

TECHNICAL INFORMATION

FOR PROFESSIONAL USE ONLY

SPRAY CLEAR COAT

1K CLEARCOAT

PRODUCT DESCRIPTION

Fast-drying 1K clearcoat with good adhesion to wood, metal, aluminum, glass, stone and various types of plastics. Features anti-corrosion properties, high resistance to scratches and the harmful effects of weather conditions.



PHYSICAL AND CHEMICAL PROPERTIES

Colour:	Colorless
Gloss grade:	gloss
Capacity:	500 ml
Base:	acrylic resin
Temperature resistance:	to 230°F (110°C)
Efficiency:	approx 1,5 – 2 m ²
Density:	0,775 g/cm ³ (at 68°F (20°C))
Drying time at 68°F (20°C) *:	dust dry after approx. 5 – 10 minutes tack free after approx. 10 – 20 minutes completely dry after approx. 2 hours

VOLATILE ORGANIC COMPOUNDS

VOC = 682,4 [g/l]

The product fulfils the requirements of the European Directive (2004/42/WE), which defines the volatile components content for that products category (cat. B/5) at the level of 840[g/l] for the ready product.

USAGE

- The best results are achieved applying at room temperature. The ambient temperature and the temperature of the product should be the same.
- Surface should be dry, degreased, clean from dirt and rust and gently sanded.
- Apply a layer of primer suitable for the surface.
- Shake before using for 2 minutes and try it on cardboard.
- During lacquering hold aerosol in 25÷30 cm distance from the surface.
- Apply one or two layers, depending on the needs.
- **Clean the spray nozzle after use!** – Hold the can with the valve pointing downward, press the button emptying the content for about 5 seconds.

Caution: For safety reasons always comply with information provided in the Material Safety Data Sheet.

STORAGE

Store the product in sealed container, in dry and cool places, away from heat sources, as well as direct sunlight.

WARRANTY PERIOD

SPRAY ACRYLIC PAINT CLEAR COAT 500 ml	- 5 years from production date.
---------------------------------------	---------------------------------

PRODUCT

SPRAY ACRYLIC PAINT CLEAR COAT 500 ml	ART. No. 300003661
---------------------------------------	-----------------------

LIMITATION OF LIABILITY

The information contained in the TDS is up-to-date and correct on the day the information is released.

Because TROTON can not control or predict the conditions under which a product will be used, each user should review information in the specific context of the intended usage. To the maximum extent permitted by applicable law, TROTON shall not be liable for damages of any kind arising from the use or reliance on information contained in this TDS.

Given the variety of factors that can affect the usage and application of the TROTON product, some of which are only within the user's knowledge and control range, it is essential that the user evaluate the TROTON product to determine if the product is fit for a particular purpose and whether the product is suitable for the user's usage.

Under no circumstances shall TROTON be liable to the user or any third party for any indirect, derivative, incidental, special or punitive damages, including loss of profits resulting from the use of products manufactured by TROTON and / or TROTON's services.

All information are based upon the precise laboratory studies and many years of experience. The good market position does not release us from the constant supervision of our products quality. However, we are not responsible for the final effects of the improper storage or application of our products, as well as for work inconsistent with the good craft practice.

TROTON Sp. z o.o.
Ząbrowo, Poland.

*Drying time depends on air temperature, humidity and thickness of the layer.