

NEW



V-PRO EXPRESS 4:1

2K FAST-DRYING DTM PRIMER & SEALER

Fast air-dry urethane primer-sealer for efficient repairs — no baking required.

ULTRA-FAST CURING

READY FOR SANDING IN JUST 60 MINUTES AT 68°F.

AIR DRY TECHNOLOGY

NO BAKE REQUIRED - SAVE TIME AND ENERGY.

VERSATILE APPLICATION

CAN BE USED AS A HIGH-BUILD, SANDABLE PRIMER OR AS A WET-ON-WET SEALER.

DTM APPLICATION

CAN BE APPLIED DIRECTLY TO METAL AND PROVIDES EXCELLENT ADHESION TO A WIDE RANGE OF SUBSTRATES.

C48 UHS 2:1

ULTRA SPEED AIR DRY

Fast air-dry clearcoat for efficient automotive repairs — no baking required.

ULTRA-FAST CURING

READY FOR POLISHING IN JUST 60 MINUTES AT 68°F

AIR DRY TECHNOLOGY

NO BAKING REQUIRED - SAVE TIME AND ENERGY

UHS FORMULA

ULTRA HIGH SOLIDS CONTENT

PREMIUM FINISH

HIGH GLOSS AND EXCELLENT DEPTH OF COLOR

MASTER AIR DRY FAST REPAIR SYSTEM



UP TO **75%** SHORTER
REPAIR TIME*

► PRODUCTS INCLUDED IN THE MASTER AIR DRY SYSTEM:



SUPER-T

Lightweight, fast-curing multifunctional body filler; ready to sand in just 15 minutes at 68°F.



V-PRO EXPRESS 4:1

Fast-drying 2K DTM primer sealer; ready to sand in 60 minutes at 68°F.



C48 UHS 2:1

Fast-drying 2K urethane clearcoat; ready to polish in 60 minutes at 68°F.

MASTER AIR DRY SYSTEM



~2 h 15 min.



BODY FILLER

SUPER-T

ready to sand



PRIMER & SEALER

V-PRO EXPRESS 4:1

ready to sand



CLEARCOAT

C48 UHS 2:1

ready to polish

15 min.

60 min.

60 min.

TRADITIONAL REPAIR PROCESS



~9 h 20 min.



BODY FILLER

ready to sand



FINISHING PUTTY

ready to sand



PRIMER

ready to sand



CLEARCOAT

ready to polish

25 min.

25 min.

2,5 - 3 h

6 - 8 h

The Master Air Dry System reduces repair time by up to 75% while lowering energy consumption. The use of ultra-fast curing products at 68°F eliminates the need for baking in a spray booth, speeding up the process and increasing workshop productivity.

*Comparison based on product curing times at 68°F