

TECHNICAL INFORMATION

FOR PROFESSIONAL USE ONLY

SPRAY STRUCTURE PAINT FOR PLASTIC		
PRODUCT DESCRIPTION		
Structure spray for plastic is designed to restore the structure of damaged external elements (e.g. mirrors, door-frame etc.) and internal elements (e.g. dashboard, door panels etc.). Perfect for spot repairs.		
PHYSICAL AND CHEMICAL PROPERTIES		
Color:	black, grey	
Gloss grade:	mat	
Capacity:	500 ml	
Temperature resistance:	to 176°F (80°C)	
Efficiency:	1,5 m² (depending on the consistency and color of the substrate)	
Density:	0,792 g/cm³ (68°F (20°C))	
Drying time 68°F (20°C) *:	dust dry after approx. 10 minutes	
	tack free after approx. 30 minutes	
VOLATILE ORGANIC COMPOUNDS		
VOC = 675 [g/l]		
The product fulfils the requirements of the European Directive (2004/42/WE), which defines the volatile components content for that products category (cat. B/5) at the level of 840[g/l] for the ready product.		
USAGE		
• Clear the surface carefully, dry and degrease. • Shake before using for 2 – 3 minutes and try it on cardboard. • Structure is dependent on the number of coats and the spraying distance. • Apply several thin coats to get desired texture. • Clean the spray nozzle after use! – Hold the can with the valve pointing downward, press the button emptying the content for about 5 seconds.		
<u>Caution:</u> For safety reasons always comply with information provided in the Material Safety Data Sheet.		
STORAGE		
Store the product in sealed container, in dry and cool places, away from heat sources, as well as direct sunlight.		
WARRANTY PERIOD		
SPRAY STRUCTURE PAINT FOR PLASTIC 500 ml	- 5 years from production date.	
PRODUCT	ART. No.	
SPRAY STRUCTURE PAINT FOR PLASTIC 500 ml	black 300004066, grey 300006210	
LIMITATION OF LIABILITY		
The information contained in the TDS is up-to-date and correct on the day the information is released. Because TROTON can not control or predict the conditions under which a product will be used, each user should review information in the specific context of the intended usage. To the maximum extent permitted by applicable law, TROTON shall not be liable for damages of any kind arising from the use or reliance on information contained in this TDS. Given the variety of factors that can affect the usage and application of the TROTON product, some of which are only within the user's knowledge and control range, it is essential that the user evaluate the TROTON product to determine if the product is fit for a particular purpose and whether the product is suitable for the user's usage. Under no circumstances shall TROTON be liable to the user or any third party for any indirect, derivative, incidental, special or punitive damages, including loss of profits resulting from the use of products manufactured by TROTON and / or TROTON's services. All information are based upon the precise laboratory studies and many years of experience. The good market position does not release us from the constant supervision of our products quality. However, we are not responsible for the final effects of the improper storage or application of our products, as well as for work inconsistent with the good craft practice.		
TROTON Sp. z o.o. Zabrowo, Poland.		

*Drying time depends on air temperature, humidity and thickness of the layer.